

Package Layout Refactor

Branch: [cursor/package-layout-refactor-a435](#)

PR: <https://github.com/berothomas33/esaylinkrefactor/pull/4>

Goal

Arrange packages by responsibility across core, emvflow, emvservice, and emvbase. Behavior unchanged - structure and import cleanup.

``:core` -> `com.emvenhance.core.*``

Package	Contents
<code>`terminal`</code>	<code>`PostTerminal`</code> , <code>`EmvBehavior`</code>
<code>`engine`</code>	<code>`EmvEngine`</code>
<code>`card`</code>	<code>`EntryMethod`</code> , <code>`CardPresence`</code> , <code>`CardSearchListener`</code> , <code>`TransactionConfig`</code>
<code>`event`</code>	<code>`TransactionStep(Event)`</code> , <code>`EmvStep(Event)`</code>
<code>`host`</code>	<code>`CommunicationBehavior`</code> , <code>`PrinterBehavior`</code> , <code>`AuthResult`</code> , <code>`HostDefaults`</code>

``:emvflow` -> `com.emvenhance.emvflow.*``

Package	Contents
<code>`runtime`</code>	<code>`EmvFlowRuntime`</code> (DAL / WMRouter lazy init)
<code>`preprocess`</code>	<code>`EmvPreProcessFacade`</code>
<code>`progress`</code>	<code>`EmvStepProgress`</code>
<code>`device`</code>	<code>`EmvDeviceImpl`</code> , cipher mode
<code>`pin`</code>	<code>`IPinTask`</code>

``:emvservice:export` -> `com.pax.emvservice.export.*``

Package	Contents
<code>`api`</code>	<code>`IEmvBase`</code> , <code>`IEmvCallback`</code> , <code>`IEmvCardInfoService`</code> , ...
<code>`contact`</code> / <code>`contactless`</code>	Contact / CLSS service + result listeners
<code>`mag`</code> / <code>`manual`</code>	Magstripe / manual entry APIs
<code>`pin`</code> / <code>`version`</code> / <code>`constant`</code> / <code>`exceptions`</code>	Supporting APIs

Router keys unchanged (still string keys + interface class).

``:emvservice:emv` -> `com.pax.emvservice.emv.*``

Package	Contents
<code>`init`</code>	<code>`EmvInit`</code>
<code>`contact`</code> / <code>`contactless`</code> / <code>`mag`</code> / <code>`manual`</code> / <code>`pin`</code> / <code>`version`</code>	Concrete Router services

`:emvbase` -> `com.pax.emvbase.\*`

Already structured; documented with package-info:

- constant - tags / constants
 - param - AID / CAPK / terminal params (common / contact / class)
 - process - contact / contactless callbacks and results
 - utils - helpers
-

`:app` vendors

```
vendor.TerminalFactory  
vendor.pax / vendor.fake / vendor.ingenico
```

Verification

:core, :emvflow, :emvservice:*, :emvlib, :app compile OK.