

Electronic Theses and Dissertations at Pitt (a L^AT_EX 2_ε class)

Federico Garcia *

2004/08/17

Contents

1	Introduction	1
2	PDF creation through L^AT_EX	2
2.1	PDFL ^A T _E X	3
2.2	dvipdfm	3
2.3	Other ways to get a PDF file and bookmarks	4
2.4	No hyperref	4
3	Installation	5
3.1	pittetd	5
3.2	Installation of other required packages	6
3.3	PDF _T _E X, dvipdfm	6
4	To keep in mind	7
4.1	Headings and captions	7
4.2	Preliminaries	7
4.3	Use of packages	8
4.3.1	Unsupported packages	9
4.3.2	Supported packages	9
4.4	Related classes	9
4.5	Stage and interaction	10
4.6	Auxiliary files	11
4.7	PDF Document Info	11

*University of Pittsburgh, Electronic Theses and Dissertations (ETD) Working Group.

5	Using <code>pittetd</code>	11
5.1	Loading the class	11
5.2	Font sizes and spacing	12
5.3	Sectioning	13
5.3.1	Sectioning commands	13
5.3.2	Numbering	14
5.4	The preliminaries	14
5.4.1	Title Page	14
5.4.2	Committee membership page	16
5.4.3	Copyright page	18
5.4.4	Abstract	18
5.4.5	Table of Contents, and Lists of Figures and Tables	19
5.4.6	Preface	19
5.4.7	Additional preliminaries	19
5.5	PDF Document Info	20
5.6	Main body	20
5.6.1	Numbering and captions for tables and figures	20
5.6.2	Cross references	21
5.7	Appendices	21
5.8	Bibliography	21
5.8.1	<code>BIBTEX</code> styles	21
5.8.2	Citation packages	23
5.9	The index	23
6	Using the <code>hyperref</code> package	24
6.1	New user's commands	24
6.2	Overriding <code>pittetd</code> 's preferences	25
7	Before submitting	26
	References	27
8	The program	27
8.1	Identification	27
8.2	Declarations	28
8.3	Options	28
8.4	Stage and error handling	30
8.5	Initialization	30
8.6	Counters and numbers	34
8.7	Layout parameters	36
8.8	Font commands	37
8.9	Hyperref	38
8.10	Packages and patches	39
8.11	Preliminaries	39

8.11.1	Commands for the information	39
8.11.2	The order	41
8.11.3	Bookmarking the preliminaries	42
8.11.4	The title	42
8.11.5	The committee page	43
8.11.6	Copyright page	45
8.11.7	The abstract	45
8.11.8	The table of contents	46
8.11.9	Bookmarking tables and figures	47
8.11.10	The list of tables	48
8.11.11	The list of figures	49
8.11.12	The list of listings and list of algorithms	49
8.11.13	The preface	50
8.11.14	Additional preliminaries	50
8.11.15	Support for other Pitt classes	51
8.12	Sectioning	52
8.12.1	Chapters and sections	54
8.12.2	Appendices	55
8.13	Floating objects	56
8.14	Lists	57
8.15	Miscellaneous environments	58
8.16	Footnotes	59
8.17	Bibliography	59
8.17.1	The index	61
8.18	The .etd file	62

Pitt ETD Webpage: <http://www.pitt.edu/~graduate/etd/>

pittetd's Webpage:

<http://www.pitt.edu/~graduate/etd/latextemplate.html/>

T_EX Users Group: <http://www.tug.org/> (with a link to CTAN)

1 Introduction

This is the guide to the `pittetd` L^AT_EX 2_ε document class, designed for the preparation of electronic theses and dissertations (ETD) at the University of Pittsburgh. It is recommended that users read this entire documentation before starting using `pittetd`, so that they will have an idea of the different possibilities and options, some of which are particular to `pittetd` and therefore not usual in standard L^AT_EX classes.

Users will find below a description of `pittetd` usage, extended with an introduction to some of the most relevant features of the `hyperref` package. In addition, when this document has been produced by running L^AT_EX on

the file `pittetd.dtx`, it also contains a commented transcript of the code, so that users can modify things if they need to (and know what they are doing). In the version downloadable from the Pitt ETD webpage, this latter part is omitted. A separate document, *Comments on using L^AT_EX for theses*, also prepared for Pitt ETD authors, describes some standard tools of L^AT_EX that may or may not be known to the reader but can certainly prove useful when writing the thesis or dissertation. Touched upon are topics such as inclusion of graphics and the handling of large, book-length documents [1].

Throughout this text reference is made to the *Format Guidelines for Electronic Thesis and Dissertation Preparation at the University of Pittsburgh*, downloadable from the Pitt ETD webpage. The abbreviation FG is used to refer to it; page numbers are indicated in parenthesis.

Section 2 describes the creation of interactive PDF files through L^AT_EX, introducing the two main tools for that effect, the programs PDFL^AT_EX and dvipdfm. Section 3 explains how to install pittetd and the main L^AT_EX packages needed for its proper working. Also, cursory information for the installation of PDFL^AT_EX and dvipdfm is given.

In section 4 some general considerations are given about the best ways to use pittetd (and to cope with its restrictions). Use of packages and the issues it might bring about (notably incompatibility) is treated in a special subsection.

Detailed information about the options, available commands, and use of pittetd can be found in section 5. Typesetting of the preliminary pages is described in subsection 5.4.

Section 6 describes in an introductory way the basic features of `hyperref`, the package that implements interactivity into L^AT_EX documents.

Finally, section 7 gives some suggestions for a final format review before submitting an ETD written with pittetd. It warns about those problems that are most likely to occur because they lie beyond pittetd's control.

2 PDF creation through L^AT_EX

In principle, pittetd is equipped to fulfill the basic interactivity requirements of the FG, namely the creation of bookmarks from the entries in the Table of Contents, the List of Figures, and the List of Tables, and the implementation of these entries themselves as links to the corresponding page. This is done by means of invoking the formidable `hyperref` package,¹ which offers the basic functions for interactive handling (section 6 below offers an introductory guide to other features from this package that users

¹Written by Sebastian Rahtz.

can take advantage of). Thus, `hyperref` has to be—and it usually is in standard distributions of `LATEX`—installed in the system for `pittetd` to be able to fulfill these tasks (section 3 offers immediate help on the installation of `hyperref` and other tools, including `pittetd` itself).

`pittetd` has been written under the assumption that the user will create the final `.pdf` file through one of two tools, namely `PDFLATEX`, or the program `dvipdfm`. The user indicates which of the two ways is to be used as an option to the `pittetd` class, namely `pdftex` or `dvipdfm` (on the way to load the class and specify options, see section 5.1). The following sections explain the particularities of each way. A third related option, `nohyperref` option, will be discussed in section 2.4. Note that it is possible to switch back and forth between the three ways just by modifying the relevant option; as far as `pittetd` is concerned, nothing else is necessary to effect the change.²

2.1 PDFL^AT_EX

The most direct way to obtain a `.pdf` output file is running `PDFLATEX`³ instead of `LATEX`. Naturally, `PDFLATEX` has to be installed in the system (again, it is usually included in standard distributions of `LATEX`; see section 3). The user has to indicate `pdftex` as an option to `pittetd`, and this latter will pass that option to other packages that need it, including `hyperref` but also `graphicx` and `color` (this latter used by `hyperref`).

Note that if this is the chosen method, a regular `LATEX` (i.e., not `PDFLATEX`) run will result in an error message (‘Why not use pdf(e)T_EX binaries?’). This could affect user’s habits, batch files, etc.

There is one more significant drawback to the use of `PDFLATEX`: the running time is sometimes clearly longer than regular `LATEX`. This depends, to be sure, on one of the configuration options of `PDFLATEX`, namely `\pdfcompresslevel`, and it could be modified. But in that case, the resulting file is incomparably larger.⁴

2.2 dvipdfm

As the name indicates, `dvipdfm`⁵ is one of the programs available to convert `.dvi` files into `.pdf`. The procedure then consists in running `LATEX` as usual

²However, when going to/from `nohyperref`, it is always good to delete any auxiliary files before running. Also, some of the `hyperref` package’s commands discussed in section 6 are of course disabled when `nohyperref` is used.

³Created by Hàn Thé Thàn.

⁴In general, a `.pdf` is much larger—much less efficient in all respects—than the `.dvi`. This tendency is reinforced if `PDFLATEX` is configured to run faster.

⁵Written by Mark A. Wicks.

while the document is in preparation, having loaded `pittetd` with `dvipdfm` option, thus obtaining (more quickly) the usual (and smaller) `.dvi` output. Only optionally, at strategic points in the development of the document (notably at the end), has the user to worry about PDF, and apply `dvipdfm` to the `.dvi` file. This is usually as simple as typing

```
dvipdfm doc.dvi
```

in the command line. The file `dvipdfm.pdf` is the user's manual for the program and explains the switches that can be used in the command line.

In some `.dvi` viewers the bookmarks (and even the links) are lost. But the relevant information is recovered by `dvipdfm` when creating the corresponding `.pdf` file.

Another significant advantage of `dvipdfm` is that it tries to solve inclusion of PostScript graphic files, so it is not always necessary to convert them (see also [1]). To do the job, however, `dvipdfm` uses `GhostScript`, and therefore this program must also be installed in the system.

2.3 Other ways to get a PDF file and bookmarks

There are other ways to obtain a final PDF output file, but they are all discouraged to use alongside with `pittetd`. For example, a common method is to use `dvips` to convert a file to the PostScript format, and then apply Acrobat Distiller on it. This method involves two conversions; links and especially bookmarks tend to have an erratic behavior.

Acrobat PDF Writer, a 'printer emulator' that 'prints' PDF files will, of course, ignore anything that cannot be printed, including bookmarks. And the other `.dvi`→`.pdf` converter in existence, `dvipdf`,⁶ is not as widely available as `dvipdfm`.

On the other hand, `hyperref` is not the only way to create bookmarks with \LaTeX . Older packages and systems exist, like $\text{V}\text{\TeX}$, but since those are much less widely used, `pittetd` does not support them.

2.4 No hyperref

There is a third option concerning the creation of bookmarks and links in `pittetd`. Option `nohyperref` will prevent `pittetd` from taking care of almost all interactivity requirements, and the user is left the freedom (and the burden) to fulfill them by him- or herself.

This option might be more useful than it seems, because it allows users to use the `hyperref` package itself *their way*, not `pittetd`'s. There are in the latter's code a series of minor, but substantial, modifications to `hyperref`,

⁶By Sergey Lesenko.

and some of the options with which the package is loaded are fixed. As a security measure, `pittetd` will not allow the user manually to load the package, unless `nohyperref` is specified. Thus, if a user wants to control `hyperref`'s behavior, this option will be necessary. Section 6.2 gives some directions on how to do this.

Also, if `pittetd` cannot run normally due to some complication in installation or configuration of `hyperref`, the `nohyperref` option provides a way to keep working on the contents of the document and worry about requirements later.

3 Installation

3.1 `pittetd`

The `pittetd` bundle is made of the following files:

<code>pittetd.dtx</code>	Source for the class and this documentation.
<code>pittetd.ins</code>	Batch file for installation.
<code>pittetd.cls</code>	The <code>pittetd</code> class itself.
<code>pit10pt.clo</code>	Definitions for 10pt-size option.
<code>pit11pt.clo</code>	Definitions for 11pt-size option.
<code>pit12pt.clo</code>	Definitions for 12pt-size option.
<code>pitthesis.pit</code>	Patch for <code>pitthesis</code> class
<code>pittdiss.pit</code>	Patch for <code>pittdiss</code> class
<code>achicago.pit</code>	Patch for <code>achicago</code> package
<code>pittetd.dvi</code>	This documentation
<code>pittetd.pdf</code>	

All these files are individually downloadable from `pittetd`'s webpage. It is only the two first files, however, that are necessary, for the rest can be extracted from them. To do this, the file `pittetd.ins` has to be processed with `TeX` (*not* `LATeX`); the documentation results from running `LATeX` (*not* `TeX`) on `pittetd.dtx`.⁷

It is the `.cls` and `.clo` files that conform the class itself, i.e., what `LATeX` needs to have access to. Under a system that, like most `TeX` implementations today, use the standard `TeX` Directory Structure (TDS), `LATeX` files are put in subdirectories of the `.../texmf/tex/latex` directory (for example, the standard classes are in `.../texmf/tex/latex/base`). So the best thing under such a system is to create a subdirectory for `pittetd`:

⁷To get the index right, you have to run `makeindex` with `gind` style, saying, in the command line (and after a `LATeX` run on `pittetd.dtx`), `makeindex -s gind.ist pittetd`. Then a final `latex pittetd.dtx` produces the document with a well-formatted index.

```
.../texmf/tex/latex/pittetd
```

and place there the `.cls` and `.clo` files. Likewise, the documentation (the file you are reading, `pittetd.dvi`) should be placed in

```
.../texmf/doc/latex/pittetd
```

and the source files (`pittetd.dtx` and `pittetd.ins`) in

```
.../texmf/source/latex/pittetd
```

The ‘patches’ should be placed in the same directory as the actual document’s input files.

After placing the files in those directories, you might need to ‘refresh’ the database, i.e., to make \TeX aware that a new class is loaded. This usually appears as a command (or button, or window, etc.) of the implementation.⁸

For non-TDS systems, the suggestion is ‘put the files where \TeX can find them.’ For example, search your disk for the standard classes (e.g., `article.cls`), and put the `pittetd` files where they are. Alternatively, you can simply put the `pittetd` files in the directory that contains the input files of your document.

3.2 Installation of other required packages

In addition, you will need at least the `hyperref` and `color` packages, and $\text{PDF}\text{\TeX}$ if you use `pdftex` option. Most likely, you already have those packages installed. Even so, it is possible that you do not have the file `pdftex.def`, which is part of only relatively recent distributions. This file, available from the `pittetd`’s webpage, should be copied to the same directory where the file `color.sty` is (`.../texmf/tex/latex/graphics` in a TDS system).

`hyperref` is a package used by `pittetd` (unless, of course, the `nohyperref` option is used), so it has to be in the system. In the very unlikely case it is not already installed, you will need to download it from either CTAN (through <http://www.tug.org>) or the `pittetd`’s webpage, and install it by running \TeX (*not* \LaTeX) on the file `hyperref.ins`. This will extract the files and instruct you on where to place them (which, in any case, is analogous to the placement of `pittetd` files).

Likewise, `hyperref` uses other packages from the standard distribution of \LaTeX (notably, `color`). Installation of those packages is analogous.

3.3 $\text{PDF}\text{\TeX}$, `dvipdfm`

Installation of $\text{PDF}\text{\TeX}$ and `dvipdfm` is a more complex matter. Again, several implementations, including \TeX Live, MiKTeX , \TeX , $\text{FP}\text{\TeX}$,

⁸With MiKTeX , for example, you should run the program ‘ MiKTeX Options.’

and CMACT_{EX}, have both tools pre-installed. In case your system does not have either or both of them, you can download the relevant files, and obtain installation directions, at CTAN (through www.tug.org). The PDF_{TE}X manual, file `pdftex-s.pdf`, is available from the `pittetd`'s webpage, and contains information on the installation of the program.

4 To keep in mind

The `pittetd` class has been designed to fully comply with the format guidelines for Pitt ETDs. Due to this, there are some particularities that might create conflict with L_AT_EX users' habits. This section warns and advises about those particularities. Decisions have been made with two priorities: to discourage uses that go against the FG, and to facilitate conversion from standard L_AT_EX classes.

4.1 Headings and captions

`pittetd` will automatically capitalize the title of the document and those of the chapters. However, section titles have to be capitalized by the user.⁹

On the other hand, since both sectional headings and captions for tables and figures must have entries in the bookmarks panel, they are subject to two substantial limitations: they cannot be long, and must consist only of ASCII characters.¹⁰

When building the bookmarks, `hyperref` will convert some simple L_AT_EX commands, but in general will ignore most of them. It also will crop everything that goes beyond the maximum length of a bookmark (that varies among PDF viewers; Acrobat Reader makes it 64 characters). There are two tools to handle these limitations in L_AT_EX: the `hyperref` command `\texorpdfstring` (section 6.1), and the optional argument to `\caption` (section 5.6.1).

4.2 Preliminaries

The series of preliminaries in a Pitt ETD differs substantially from a paper-based thesis/dissertation. The committee page has changed, and dedication and acknowledgements pages have been eliminated (under the assumption and recommendation that these should be part of the preface). The order

⁹This is because modification of the `\section` command in order to capitalize not only the title itself, but also the bookmark, although possible, would highly increase the probability of incompatibilities with other packages.

¹⁰That is why the FG recommend using words (not formulas) in titles and keeping captions "to one line if possible" (p. 9).

was modified accordingly (so that the preface goes immediately before the text of the thesis itself).

Thus, the preliminaries are in principle limited to the following:

- Title page
- Committee Membership page
- Copyright page (optional)
- Abstract
- Table of contents
- List of Tables
- List of Figures
- Preface (optional)

Since all these preliminaries have their own commands in `pittetd` (see section 5.4), there is in principle no need nor place for non-numbered chapters (`\chapter*` commands). In fact, the starred version behaves exactly as the regular one. If there is a need for additional preliminary pages, the (on purpose) cumbersome command `\preliminarychapter` is available (see section 5.4.7).

4.3 Use of packages

Almost certainly authors of Pitt ETD's will need to load a wide and unpredictable variety of packages. Although `pittetd` has been coded with the premise not to 'invite' incompatibilities, it is possible that some of these packages will create clashes, for there is simply no way to claim universal compatibility with the hundreds of packages already available and with those to come.

However, *partial* compatibility can be (and supposedly has been) achieved. A survey carried out in April–May 2003 gave us a list of packages that are of common use in the Pitt community, and those have been taken into account in the writing of `pittetd`.

For the handling of possible incompatibilities arising in the future, the following policy has been designed. The user who suspects he or she has found a clash should contact the Pitt ETD Working Group and explain the problem, ideally e-mailing a copy of the input file(s). Hopefully in a reasonable amount of time, a 'patch' will be created that solves the problem. The patch takes the form of a file with extension `.pit`, downloadable from `pittetd`'s webpage.

After the file has been downloaded and put where \LaTeX can find it (the easiest way is to put it in the same folder as the document itself), it should

`\patch` be accessed. The command `\patch`, that takes the name of the package as its argument, reads any patch that exists for it. For example, there is already a patch for the `achicago` package; to ensure the proper behavior of this package, the user should type, *after* `\usepackage{achicago}`, the command `\patch{achicago}`.

Alternatively, the command `\usepackage` can itself be replaced by `\usewithpatch` `\usewithpatch`. When a package is invoked by means of `\usewithpatch`, `pittetd` will search the system for the corresponding patch; if it exists, it loads it; if not, nothing happens. Options to the package, as usual, are indicated by the optional argument [*options*]. The drawback of this mechanism is that several packages *cannot* be loaded at once (i.e., by comma-separating them, as in `\usepackage{color,graphicx}`); each must receive its own `\usewithpatch`. But using `\usewithpatch` ensures that `pittetd` will always look for a patch when loading a package.

The following paragraphs mention some \LaTeX packages and tell whether they are supported or not by `pittetd`. For information on compatibility with the bibliographical styles and packages, see section 5.8.

4.3.1 Unsupported packages

Many popular \LaTeX packages provide formatting features that either go against the FG or are already incorporated into `pittetd`. Therefore, it is assumed that such packages will *not* be loaded. These include `setspace`, packages for the handling of floating objects (such as `float`, `floatflt`), for variations of layout (`fancyhdr`, `fncychap`, `multicol`), and sectioning (`titlesec`, `tocbibind`). Using any of those packages might result in error messages, anomalies, and unpredictable output. Before reporting or trying to solve these problems, keep in mind that departmental approval is needed to include the features.

4.3.2 Supported packages

Some packages provide features that are legitimate in a Pitt ETD. Font packages, such as those in the PSNFSS collection (`times`, `bookman`, `palatino`, `newcent`, etc.) are perfectly compatible with `pittetd`. In fact, if CM fonts are desired, it is recommendable that the `ae` package is loaded.¹¹

The packages of the American Mathematical Society (`amsmath`, `amsthm`, etc.) are supported. Likewise, all the packages in the standard distribution of \LaTeX (`color`, `graphicx`, `xspace`, `verbatim`, etc.) are supposed to work. `caption2` works miraculously fine. In general, packages that *provide*, as opposed to *override*, features, should work fine.

¹¹The AE fonts emulate CM, but are PostScript, not bitmap, fonts, which gives them a better quality for screen display.

4.4 Related classes

Currently there are two \LaTeX classes that produce theses and dissertations for Pitt, namely `pitthesis` (by Wonkoo Kim, 1999) and `pittdiss` (by Will Slaughter, 2003). The former was designed for paper-based documents, following requirements somewhat different from those of an ETD; the latter, on the contrary, was created with ETD in mind.¹² Many features are shared by those classes and `pittetd`—notably the creation of preliminaries—but the detailed mechanisms (command names and things like that) are different. This release of `pittetd` includes two ‘patch’ files that allow using `pittetd` with conventions from the other two classes, so that the user does not have to change every command (some will require handling, though; `pittetd` will warn or complain).

The patches are called through either

```
\patch{pittdiss}
```

or

```
\patch{pitthesis}
```

(the latter only two t’s.) Having read the corresponding patch, `pittetd` will try to interpret `pittdiss`- or `pitthesis`-commands. Hopefully, most times it will succeed; in any case, it will issue warnings (or error messages in the `final` option) for things that *have* to be changed. For example, if acknowledgements are created with `pitthesis`’s `acknowledgements` environment, `pittetd` will warn that now there is no separate preliminary for that, and that this section should be part of the preface.

As an extra safety measure when going from `pitthesis` or `pittdiss` to `pittetd`, all auxiliary files should be deleted before the first `pittetd` run. Also, it is very much recommendable to change `\bibliography` to `\safebibliography` since the beginning.

4.5 Stage and interaction

In order to facilitate the process of converting files from standard classes into `pittetd`, annoying error messages due to the particularities of `pittetd` have been avoided as much as possible. The ‘stage’ of the document is used to decide whether or not the differences should make stop the \LaTeX run. The idea is that when the `draft` option is used, most problems are reported as ‘Class Warnings’ that do not stop the process. But if `final` is used (and eventually it *should* be used), more prominent error messages appear instead.

However, many packages (including the seminal `hyperref`, `color`, and `graphicx`) themselves operate differently when `draft` is specified. So for

¹²It does not produce links or bookmarks, however.

example, `hyperref` does not create links or bookmarks, and `graphicx` does not import external graphic files. But the user might want to see these features, still not worrying about detailed `pittetd` concerns. That is why an intermediate stage `semifinal` is introduced. The packages will work as usual, but `pittetd` will issue mostly warnings, not error messages. This is the default option.

Both `semifinal` and `draft` issue a final warning at the end of the job, reminding the user to run the document with `final`. As usual, moreover, `draft` makes overfull boxes visible.

The ‘stage’ option also governs `pittetd`’s complaints about the preliminaries when information for the different pages is missing, when the order is wrong, etc.: with `draft` and `semifinal`, there will be a warning, while with `final` there will be an error message.

4.6 Auxiliary files

In addition to the regular auxiliary files (`.aux`, `.toc`, `.lot`, `.lof`, etc.), a run of `pittetd` involving all its features will produce two files: one with extension `.out` (written by `hyperref` for the ‘outlines,’ or bookmarks), and one with extension `.etd`, used by `pittetd` to decide some details. Input or other files created by the user should avoid these extensions. Also, for some implementations of L^AT_EX that provide a quick erasing of auxiliary files, it is advisable to configure this tool to include `.out` and `.etd` files.

4.7 PDF Document Info

`pittetd` offers the possibility of filling in the fields of Acrobat Reader’s ‘Document Info’ dialog box. ‘Title’ and ‘Author’ are filled in with the data of the title page. ‘Subject’ and ‘Keywords’ are handled by additional commands (see section 5.5).

5 Using `pittetd`

5.1 Loading the class

The `pittetd` class is loaded by typing

```
\documentclass[<options>]{pittetd}
```

at the very top of the input file. Table 1 shows all the *<options>* available. Most of the options for conventional classes (i.e., the standard classes `article`, `book`, `report`, and similar ones like `amsart` and `amsbook`) have been disabled

in `pittetd`. The document will always be typeset letter paper (8.5×11 inches), portrait, and one column.¹³

Characteristic	Available Options
Font size	12pt (default) 11pt 10pt
Stage (see section 4.5)	final semifinal (default) draft
Bibliography layout	openbib (‘open’ bibliographies).
Equations	leqno (equation numbers on the left) fleqn (flush-left displays)
Type	phd (dissertation, default) ms (M.S.’s thesis) ma (M.A.’s thesis)
Section numbering (see section 5.3.2)	sectionnumbers (default) sectionletters
PDF production (see section 2)	dvipdfm pdftex nohyperref

Table 1: Available options for `pittetd`

5.2 Font sizes and spacing

`\Small` The usual L^AT_EX commands are defined according to the font size option selected. In addition, the `\Small` and `\SMALL` commands work as in the classes `amsart` and `amsbook`, i.e., are equivalent to `\footnotesize` and `\scriptsize` respectively. See figure 1.

The text of a Pitt ETD has to be at least “one half-spaced, with the exception of long quotations, footnotes, bibliographical references, and the Index (if included), which may be single-spaced” (p. 7). A spacing of little more than one-half for regular text has been built in into `pittetd`; the text in footnotes and quotations has been set to single spacing. The user can always adjust the spacing in the usual way, `\renewcommand`’ing the `\baselinestretch` command `\baselinestretch`, so that

¹³Thus, options to modify these parameters, namely those for *a*) paper size (`letterpaper`, `legalpaper`, etc.); *b*) paper orientation (`portrait`, `landscape`); *c*) number of columns (`onecolumn`, `twocolumn`); and *d*) pagination (`oneside`, `twoside`; `openright`, `openany`; `titlepage`, `notitlepage`), are not implemented.

`\renewcommand\baselinestretch{1.3}`
increases the built-in spacing by a 30%—for *all* the text, footnotes included.

The spacing-scheme is achieved in `pittetd` by building it into the font sizes. Normal-size font (`\normalsize`) is one-half spaced, while all other sizes are single-spaced. The `quote` and `quotation` environments, as well as `\footnote`, all of which set a smaller font, produce thus single-spaced `\singlespace` text. An additional ‘size’ has been implemented, namely `\singlespace`, which produces regular-size, but single-spaced, text.

`\smallskip` The spacing command `\smallskip` is set to an amount of a single space;
`\medskip` `\medskip` is a line (a little more than one and a half space); and `\bigskip`
`\bigskip` a double space.

	<code>\SMALL</code> or	<code>\Small</code> or	
<code>\tiny</code>	<code>\scriptsize</code>	<code>\footnotesize</code>	<code>\small</code>
	<code>\normalsize</code>		
<code>\large</code>	<code>\Large</code>	<code>\LARGE</code>	<code>\huge</code> <code>\Huge</code>

Figure 1: Font sizes

`\acro` Adapted from the `ltugboat` class, `pittetd` implements the command `\acro`, that typesets its argument in a font smaller than the surrounding text. It is useful for all-uppercase acronyms like ETD (`\acro{ETD}`), UNICEF (`\acro{UNICEF}`), etc., which would be too large in regular size (compare ETD, CTAN, UNICEF); it is better than the direct `\small`, which is not good in contexts of font size other than normal.

5.3 Sectioning

5.3.1 Sectioning commands

`\chapter` The sectioning of a `pittetd` document is done through the usual commands `\chapter`, `\section`, `\subsection`, and `\subsubsection`. Note that `\part`, `\paragraph`, and `\subparagraph` are *not* implemented. The `\chapter` command takes care of capitalization of the title *both* in the text and in the bookmarks; however, since `\section` capitalizes in the text but not in the bookmarks, it is always advisable to capitalize manually.

Within preliminaries, the subdivisions `\section`, `\subsection`, and `\subsubsection` will produce neither a number nor a bookmark entry (`\chapter` is reserved for chapters in the body of the text; about additional preliminary ‘chapters’ see section 4.2). The starred variants `\chapter*`,

`\section*`, etc., work exactly as the non-starred counterparts, although producing a warning.

All four sectioning commands have the usual optional argument, that contains the alternate version of the heading that appears in the table of contents. This, however, is implemented only for compatibility reasons, for the FG require that the table of contents lists the headings exactly as it appears in the text. The main reason why the optional argument could be used at all is that it permits to cope with the conversion of the text into ASCII text for the bookmarks, but that is best handled by the command `\texorpdfstring` (section 6.1).

On the other hand, there might be cases in which some letters must appear in lowercase even in headings (chemical elements is such a case). The command `\lowercase` works within the arguments to sectioning commands, and can be used for those cases.

5.3.2 Numbering

The divisions of a Pitt ETD can be numbered in two ways, depicted in Figure 2. The first one is the one used by default (`sectionnumbers`); the user can specify `pittetd`'s option `sectionletters` to use the second one. In this case, in addition, the labels for successive levels of the `enumerate` environment are also changed from their default appearance, to agree with the section numbering: the first level will be an uppercase roman numeral, the second an uppercase letter, and so on. The user has the command `\regularenum` to revert to the usual appearances (namely arabic, letter, roman, Letter).

`\regularenum`

<div> 1.0 FIRST CHAPTER 1.1 FIRST SECTION 1.11 First subsection 1.11.1 First subsubsection </div>	<div> I. FIRST CHAPTER A. FIRST SECTION 1. First subsection a. First subsubsection </div>
<code>sectionnumbers</code> (default)	<code>sectionletters</code>

Figure 2: The two possibilities for section numbering

5.4 The preliminaries

The first part of a Pitt ETD is made of the ‘preliminaries.’ They are created in `pittetd` with special commands that are the subject of the present section.

`pittetd` will keep track of the order in which the user typesets the preliminaries, and will warn or complain according to the ‘stage’ of the document (see section 4.5).

5.4.1 Title Page

`\maketitle` The title page is produced, as usual, by the command `\maketitle`, but involves several pieces of information in addition to `\title`, `\author` and `\date`, so it is only *deceivingly* similar to the same command in standard L^AT_EX classes. All efforts have been taken to prevent the differences to ruin the L^AT_EX run (making easier the conversion from other classes), but the user will eventually have to check it carefully.

`\title` The macro `\title` has an optional argument that sets the title of the document as it will appear in the ‘Document Info’ dialog box of Acrobat Reader. If no optional argument is given, the required argument will be used (however, bear in mind that only a limited portion of it will be visible). In order for this feature to work properly, `\title` must be issued in the preamble of the document. In the text, the title will be typeset uppercase.

Ex.: `\title[An Anatomy of the World]{An Anatomy of %
the World on texts by John Donne, %
for soprano and six instrumentalists}`

`\author` The `\author` command works much the same as in standard L^AT_EX classes. Again, it should be issued in the preamble for the author’s name to appear in the ‘Document Info’ dialog box. On the other hand, `\thanks` and `\and` are disabled. **Ex.:** `\author{Federico Garcia}`

The following macros set other information needed by `pittetd` to build the preliminaries. None of them is required unless `final` option is used. With `semifinal` and `draft`, a warning is issued informing of any missing commands.

These commands are analogous, but not identical, to additional commands in the classes `pitthesis` and `pittdiss`. Patches are available to facilitate conversion from those classes to `pittetd`.

`\setyear` The title page does not include the whole date, but only the year. By default, this is set to the current year; the user can optionally specify it with the command `\setyear`. **Ex.:** `\setyear{2002}`

`\degree` The information of the author’s previous degrees is provided by the `\degree` command, and should contain the degree, institution, and year of the each degree. Several lines or degrees can be separated with `\\`. **Ex.:** `\degree{B.S. in Music (Composition),\\Bogot’a, 2001}`

`\school` The title page includes the text ‘submitted to the graduate faculty of’, followed by the school name. The user sets this name with the command `\school`. By default, the article ‘the’ is appended to the school name, but the user can change it with the optional argument. **Ex.:** `\school{Department of Mathematics}`
Ex.: `\school[]{FAS}`
Ex.: `\school[certain]{Other department}`

`\degreesought` According to the option used (`phd`, `ms`, or `ma`), `pittetd` sets the value of `\degreesought` to either ‘Doctor of Philosophy,’ ‘Master of Sciences,’ or ‘Master of Arts’. If desired, `\renewcommand` can be used to modify it. **Ex.:** `\renewcommand\degreesought{M. A. in Composition and Theory}`

Figure 3 is the title page produced by the examples above.

5.4.2 Committee membership page

`\makecommittee` The `\makecommittee` command builds up the committee membership page. The author is typeset as it was in the Title Page (i.e., as is provided by the `\author` command); the school name comes initially from the `\school` command, although capitalized (see section 5.4.1 for these two commands). In some cases, the name of the school in the committee membership page should be different from the one that appears on the Title Page (for example, when it starts with ‘Faculty’); the user can insert a new `\school` command right before `\makecommittee` (and after `\maketitle`) to control the second appearance.

**AN ANATOMY OF THE WORLD ON TEXTS BY JOHN
DONNE FOR SOPRANO AND SIX INSTRUMENTALISTS**

by

Federico Garcia

B.S. in Music (Composition)

Bogotá, 2001

Submitted to the Graduate Faculty of
Arts and Sciences in partial fulfillment
of the requirements for the degree of
M. A. in Composition and Theory

University of Pittsburgh

2002

Figure 3: Example of title page

In addition to that information, the committee membership page takes also the date and the committee members, which are provided with the next commands.

`\date` The `\date` command is intended for the date of the thesis/dissertation defense, which will appear after the text ‘It was defended on’. The default value is `\today`. It can be omitted with `\date{}` (in whose case there will be no ‘It was defended’), but a warning will be issued.

Ex.: `\date{May 15, 2003}`

`\committeemember` The list of committee members is typeset with information from one or more `\committeemember` commands (one for each member). The argument of `\committeemember` cannot contain more than one line.

Ex.: `\committeemember{N. Chimpsky, Ph.\ D., Professor}`

The *first* name will be treated as the thesis/dissertation advisor. When there are two advisors, the second one should be provided with the `\coadvisor` `\coadvisor` command.

In master’s theses, inclusion of the rest of the committee is optional, but in Ph. D. dissertations it is required. Accordingly, if `pittetd` has been loaded with the `phd` option, it will require at least two `\committeemember` commands, the requirement taking the form of a warning for `draft` and `semifinal` options, an error for `final`.

In any case, if just one member (the advisor) is listed, `pittetd` will omit the text ‘approved by’, only typesetting the advisor’s name at the bottom of the page.

5.4.3 Copyright page

`\copyrightpage` Optionally, a copyright page can be appended immediately after the committee membership page, through the command `\copyrightpage`.

5.4.4 Abstract

`abstract (env.)` An abstract of no more than 350 words is required for every Pitt ETD. It is created as usual with the `abstract` environment:

```
\begin{abstract}
  <text of the abstract>
\end{abstract}
```

The page will start with the title, the author, and the year of the document, followed by the text of the abstract.

Optionally, a list of keywords or descriptors can be appended at the end of the abstract. The keywords themselves have to be set in the preamble by the command `\keywords` (section 5.5). Then, an optional argument to the `abstract` environment sets the title of the list. For example, the command `\begin{abstract}[Keywords:]` produces, after the text of the abstract, the expression ‘**Keywords:**’ followed by the contents of the previous `\keywords` command.

Some schools (including the School of Engineering) recommend that the word ‘ABSTRACT’ appears on the abstract page. `pittetd` provides for that requirement in the form of a starred version for the `abstract` environment:

```
\begin{abstract*}
  <text of the abstract>
\end{abstract*}
```

Keywords can be appended to this kind of `abstract` in the same way.

5.4.5 Table of Contents, and Lists of Figures and Tables

`\tableofcontents` The table of contents and the lists of figures and tables are created with the usual L^AT_EX commands. If `hyperref` is used, the entries in these lists are `\listoffigures` links pointing to the corresponding page, and are included as bookmarks. `\listoftables`

5.4.6 Preface

`\preface` The preface is optional. If one is desired, the user needs only to type `\preface` followed by the text itself. Acknowledgements, dedication, etc., should be included in this preliminary. The preface is the only preliminary that is included in the table of contents.

5.4.7 Additional preliminaries

`\preliminarychapter` As has been said, preliminaries in a Pitt ETD are in principle limited to those described above. Just for the sake of completeness, however, a command for additional preliminaries is implemented (and its use is discouraged) in `pittetd`:

```
\preliminarychapter{<heading>}
```

The `<heading>` will be both typeset and bookmarked, but not included in the table of contents). Sections within the additional preliminary will be unnumbered.

5.5 PDF Document Info

The ‘Document Info’ dialog box of Acrobat Reader includes information for title, author, subject, and keywords. `pittetd` will fill in these fields (if `hyperref` is used) with, respectively: the optional argument to the command `\title`; the `\author`; the `\subject` command; and the `\keywords` command. All four commands must be issued in the preamble for the information to go to the Document Info (although there is no error message if any or all are missing).

`\subject` For example, the commands `\subject{Musical Composition}` and
`\keywords` `\keywords{Music & Text, John Donne, Vocal Music}` define the contents of the ‘subject’ and ‘keywords’ fields. The latter will, optionally, also be typeset at the end of the abstract (see section 5.4.4).

5.6 Main body

The way the main body of the document is typeset by L^AT_EX is very little modified by `pittetd`. As has been said, footnotes and quotations appear in a smaller font, and single-spaced. Within the `table` and `figure` environments, moreover, `\singlespace` is declared, so their contents appears single-spaced. To resort to one-half spacing, the declaration `\normalsize` is enough.

5.6.1 Numbering and captions for tables and figures

`\chapterfloats` By default, figures and tables are numbered consecutively (1, 2, etc.), independently from the chapter. This can be changed with the `\chapterfloats` command, that has to appear before `\begin{document}`. In that case, figures and tables will be numbered within chapters (1.4, 2.5, etc., or I.4, II.5, etc.); `pittetd` reserves enough space for the figure or table number in the list of figures or tables (that might be something long like ‘VIII.14’) , but this requires several runs.

As has been mentioned, captions are subject to the limitations of book-marking: they must be short and contain only ASCII text. In case this poses problems, the optional argument to the `\caption` command is the best tool to deal with them:

`\caption[alternate caption]{caption}`

When present, it is *alternate caption*, instead *caption*, what is actually typeset in the list of tables or figures, and into the corresponding bookmark. So, if a long caption is necessary, it can be handled as in the following example (note the avoidance of `\cite` in the optional argument):

`\caption[A modern ‘wave model’ of the Indo-European`

```
languages according to Raimo~Antilla~(1972).]{A
modern ‘wave model’ of the Indo-European languages
according to \cite{r-a}. The numbers indicate 24
isoglosses (similarities) shared among different
Indo-European languages. Isogloss 1 indicates the
centum:satem split...
}
```

Refer also to section 6.1 for more details on `hyperref` conversion of \TeX into ASCII text.

5.6.2 Cross references

When using `hyperref`, cross references created with the `\ref` and `\pageref` commands are interactive links. The package offers, as an alternative, the command `\nameref`, that is used exactly as `\ref`, but typesets the *name* of the chapter or section, instead of its number.¹⁴ This kind of reference seems to be more consistent with interactivity (for, when a click is enough, the main motivation for an ordered numbering is called into question).

In any case, with `pittetd`, the `\nameref` command is slightly modified when it refers to an appendix: it does not produce the appendix’s title, but its label (‘APPENDIX’, or ‘APPENDIX A’, etc.).

5.7 Appendices

`\appendix` The `\appendix` command tells `pittetd` that the following chapters (i.e., the following `\chapter` commands) are appendices. If there is only one appendix, its heading will be ‘APPENDIX’; if there are more, they will be numbered with capital letters, ‘APPENDIX A’, etc. `pittetd` needs a second run to know which way to follow.

5.8 Bibliography

5.8.1 $\text{Bib}\text{\TeX}$ styles

This section applies only to documents whose bibliography is generated through $\text{Bib}\text{\TeX}$. Manually-created bibliographies (i.e., produced with the `thebibliography` environment) need no special warning to work properly with `pittetd`, which handles spacing after the FG (single space within entries; entries separated by one-half space).

As far as `pittetd` is concerned, there are three kinds of $\text{Bib}\text{\TeX}$ styles (`.bst` files). The first kind includes the styles that limit themselves to

¹⁴`hyperref` achieves this by means of invoking the `nameref` package.

ordering and formatting the different pieces of information within the bibliography entries (without modifying the appearance of the list as a whole). The vast majority of BibTeX styles, including the standard ones (`plain`, `unsrt`, `alpha`, `abbrv`), fall in this category. These styles pose no problem to `pittetd`, and nothing special is needed to fulfill the requirements of the FG.

The second group comprises those styles that, in addition to the individual entries, format the list as well. In general, styles that do not use bracketed labels (`'[1]'` or `'[Cas44]'`) are part of this group, for they need to redefine the `thebibliography` environment to conform to the absence of such labels. They usually come with an associated package (`.sty` file) that takes care of this task. To ensure proper behavior when using these packages, `pittetd` offers the command `\safebibliography`. Its use is identical to that of `\bibliography`, and it tries to make a compromise between the style's conventions and the FG.¹⁵

The last kind of bibliography styles is that of systems that modify aspects of formatting other than the final list of bibliographical references. All these systems have not only `.bst` files, but also substantial packages (`.sty`). `harvard`, `natbib` and `achicago` are common instances. When `pittetd` has a close encounter with packages of the third kind, there can be erratic behavior. It is recommended that `\safebibliography` is used instead of `\bibliography`, but this will probably not be enough. Since there is no general solution, the problems have to be treated individually, with patches, as explained in 4.3 above.

The three mentioned systems have already been tackled: `natbib` is an extremely well-written program, so that conciliating it with `pittetd` is easy and does not merit a separate patch file. No special treatment (other than using `\safebibliography`) will normally be needed.

On the other hand, `harvard` is a more complicated case, for the package creates interactive links. The `hyperref` package has support for `harvard`, but there is no way to foresee potential problems. It is strongly recommended if possible not to use this package, replacing it with `natbib`.

`achicago` poses other kinds of problems. It is an ambitious package that modifies things other than bibliography-related functions. For example, using this package, the effect of `\emph` will not be *italic*, but *slanted* shape; the `quote` and `quotation` environments are also modified, so that `pittetd` cannot set single spacing within them. Again, it is recommended to avoid this package, but in any case there is a patch available at `pittetd`'s webpage, the file `achicago.pit`. It should be loaded saying `\patch{achicago}`.

¹⁵It of course is not guaranteed that it will always succeed in doing so. If it does not, it is possible that the bibliography style is actually of the third kind.

Thus, through the means just explained, a broad range of bibliographical usages is supported by `pittetd`. Bracketed-labels referencing, being what \LaTeX is designed for, can generally be used without restriction; for author-year referencing, `natbib` and `achicago` are supported; and for footnote referencing, the package `opcit` (available from CTAN) works fine if `\safebibliography` is used.

5.8.2 Citation packages

There are some packages that handle the way bibliographical references are handled within the text, rather than the way the entries of the final list are typeset. It is unfortunate that the package `cite`, that sorts the numbers of a multiple `\cite`, creates deep and quite un-traceable conflicts with `hyperref`. The package can be loaded, but it will have no effect. As a result, the `overcite` package will *not* sort the numbers either, although it will typeset them as superscripts (which, in addition, will be interactive links). `achemso` also causes problems, and it is recommended not to use it at all.¹⁶ `chapterbib`, going against FG, is not supposed to be loaded.

On the other hand, support for the `multibib` package, that allows multiple lists of references in the same document, is in progress. For the time being, the recommendation is to plan on writing one general bibliography if possible. In any case, several reference lists can be manually created (i.e., without using \BIBTeX).

5.9 The index

The code of `pittetd` defines the environment `theindex` to suit the FG, but otherwise exactly as standard classes define it. This means that the production of the index, be it manually or through *MakeIndex*, remains the same. `hyperref` offers an option to create a ‘hyper-index,’ whose page numbers are interactive links. However, the option is not very robust, and therefore `pittetd` uses `hyperref` but turns hyper-indexing off.

At the moment there is no support for multiple indexes to be generated automatically by *MakeIndex*, although several indexes can be manually created.

¹⁶In `hyperref`’s documentation, Sebastian Rahtz admits not having been able to make hyper-bibliography robust, “since many styles redefine these things... Any or all of *achemso*, *chapterbib*, and *drftcite* may break.” For the case of `cite`, I tried to make a compromise, sacrificing the interactivity of the bibliographical references to keep the effects of the package. But I got completely lost in the attempt... As Rahtz says, “life is too short,” and I am not going to understand all the workings of `\@cite`, `\@citex`, `\@citen`, ... Sigh.

6 Using the hyperref package

This section is a very brief and incomplete guide to some extra features of the `hyperref` package that have not been explained before. Unfortunately, if something is missing to `hyperref`, it is documentation. Useful information is to be found in [2] and [3], but those documents are not intended for the average user. The present section is a translated adaptation of the relevant section in [4], to my knowledge the most complete (but still not comprehensive) user's guide on the package.

Section 6.2 provides a starting point to use `hyperref` in a way different of `pittetd`'s default.

6.1 New user's commands

Certain character strings (notably the text of the bookmarks) are converted by `hyperref` into ASCII text, ignoring most \LaTeX commands. In general, macros that expand into a piece of text (such as the \LaTeX command itself, the italic correction \swarrow , or things like ‘ and ’) are appropriately handled. But math mode, for example, is completely ignored. The process leads virtually never to an error message; warnings, however, are issued for every ignored token.

`\texorpdfstring` In any case, the user has a way to ‘help’ `hyperref` in the conversion, namely the command

`\texorpdfstring{\langle T\!E\!X text\rangle}{\langle PDF text\rangle}`

that can be used in sectioning commands or captions for figures and tables. For example, a caption with the text ‘An H_2O molecule,’ that would produce a bad bookmark entry, can be fixed by typing

`\caption{\texorpdfstring{An H$_2$O molecule}{A water molecule}}`

After this, the caption for the figure will feature ‘ H_2O ’ (both in the figure and the list of figures), but its bookmark will substitute ‘water’.

To create links other than those produced by the \LaTeX commands `\ref`, `\pageref`, and `\cite`, `hyperref` makes available other commands. Only some of them will be mentioned here. See [2] for the rest.

`\nameref` The `\nameref` command works like `\ref`, but creates a link with the chapter or section *name*. It is only applicable to sectioning commands.

`\url` The command `\url{\langle URL address\rangle}` prints the $\langle URL address\rangle$ as a link that launches the local Internet surfer and leads to the corresponding page.

`\hypertarget` Analogous to `\label`, the command `\hypertarget{\langle key\rangle}{\langle text\rangle}` makes the $\langle text\rangle$ to be the target of a cross reference.

- `\hyperlink` Analogous to `\ref`, the command `\hyperlink{<key>}{<expression>}` sets up an internal link whose target has been previously defined with `\hypertarget`.
- `\Acrobatmenu` Through the command `\Acrobatmenu{<menu function>}{<text>}`, a `<text>` is typeset as a link that activates the `<menu function>` of Acrobat Reader (or Exchange). For a list of the available functions, see section 4 of [2].

6.2 Overriding `pittetd`'s preferences

As has been said, `pittetd` loads `hyperref` with a fixed set of options. In order to access the package keeping control of it, it is needed to specify the `nohyperref` option for `pittetd` and then load `hyperref`:

```
\documentclass[nohyperref]{pittetd}
\usepackage[<personal options>]{hyperref}
```

This procedure is of course recommended only to users experienced with `hyperref`. A comprehensive list of `hyperref`'s options is given in [5]. Here is the list of options that `pittetd` uses by default (when allowed to):

```
hyperindex=true,
pdfencoding=auto,
bookmarks, bookmarksnumbered, bookmarksopen
```

An option not used by `pittetd` that might be relevant is `backref`, that makes the bibliographical entries produce links to the sections in which the corresponding `\cite` appear (there is also the alternative `pagebackref`, with links leading to the *page* of the `\cite`'s).

In any case, it is always good to indicate the driver for `hyperref`, for example `pdftex` or `dvipdfm`, as an option to this package. In fact, when such an option is given to `pittetd`, all that is done by the latter is to pass it on to packages that need it, including `hyperref`, `graphicx` and `color`.

By loading `hyperref` manually, some automatic features of `pittetd` are lost: the bookmarks for the bibliography, the index, and the appendices; and the filling in of the 'Document Info' dialog box of Acrobat Reader. Figures and tables, however, will still create bookmarks. To get those bookmarks created was the thorniest issue in the writing of `pittetd`, and we have decided to keep this working even if the user has chosen to override `pittetd`'s preferences about `hyperref` (see the code for `\listoffigures` and `\listoftables`).

- `\pdfbookmark` To create bookmarks additional to those that come from sections in the table of contents (or from the lists of figures and tables), `hyperref` provides the `\pdfbookmark` command:

```
\pdfbookmark[<level>]{<bookmark text>}{<key>}
```

where $\langle level \rangle$ is 0 for chapters, 1 for sections, and so on. The $\langle key \rangle$ is a unique name chosen by the user. The bookmark will be appended to the panel in the current position, and will point to the page of the text, in which `\pdfbookmark` appears. For more complicated instances (bookmarks that lead to a different location in the document, or that lead to different documents), see sections 5.2.4 and 7.2 of [3].

7 Before submitting

The `pittetd` L^AT_EX class is programmed to follow closely and consistently the FG. In general, the author of a thesis or dissertation needs not to be concerned about most of the formatting requirements (for example, checking the bookmarks and links one by one is unnecessary). However, this creates the danger of implying that nothing can go wrong. There are in fact some things beyond `pittetd`'s control, and those things must be checked by the authors themselves (and will probably be checked closely by format reviewers). This section highlights the most common and likely problems.

Captions of tables and figures. Captions for tables should appear at the top of the table, while those for figures go at the bottom. `pittetd` does not force nor check this requirement.

Captions as bookmarks. Very long captions for tables and figures tend to be truncated when converted to bookmarks. Also, L^AT_EX constructions (like formulas, cite commands, etc.) are lost. Sections 5.6.1 and 6.1 show two ways of dealing with these limitations.

Capitalization of sections. The section titles are capitalized by `pittetd` in the text, but *not* in the bookmarks. The best thing is to provide `\section` with an already-all-capitals argument.

The final option. Before submitting it is always very important to run the document with `final` option (i.e., adding '`final`' to the list of options to `\documentclass`). This will catch and make evident any problems in the preliminary pages. See section 4.5.

Bad line breaks. Sometimes L^AT_EX cannot break a paragraph into lines satisfactorily. The result is one (or more) 'overfull' lines, that stick to the right of the margin. L^AT_EX always gives a warning about each and every overfull, and these can be seen in the `.log` file. This file, a plain-text file, can (and should) be read for overfull and other kinds of warnings. Overfull warnings start with the text '`Overfull \hbox in paragraph`'.

Bad page breaks. Similarly, L^AT_EX issues an ‘underfull’ warning for bad page breaking—when it is able to recognize it. But sometimes L^AT_EX will break a page just after a heading, which is wrong. The best way to check page breaking is to make the pages fit the screen and go scanning quickly page by page (PgDn).

Warnings. There are also warnings about other things, such as incomplete cross references, undefined \cite’s, etc., which are important to fix. The warnings are all collected in the .log file, and usually reveal at least one problem that had not been noticed before. It is not good to neglect reading this file; getting it to report no problems should be the crowning, final step in the thesis/dissertation production.

References

- [1] Federico Garcia, *Comments on using L^AT_EX for theses*, July 2003, file `comments.dvi` or `comments.pdf`, available at pittetd’s webpage.
- [2] Sebastian Rahtz, *Hypertext marks in L^AT_EX: the hyperref package*, June 1998, file `manual.pdf`, part of the `hyperref` package distribution. Available at pittetd’s webpage.
- [3] Heiko Oberdiek, *PDF information and navigation elements with hyperref, pdfT_EX, and thumbpdf*, paper at EuroT_EX’99. File `paper.pdf`, part of the `hyperref` package distribution. Available at pittetd’s webpage.
- [4] Rodrigo De Castro, *El Universo L^AT_EX*, 2nd. edition, Bogotá, Universidad Nacional de Colombia, 2003.
- [5] Sebastian Rahtz, *hyperref package options*, October 1999, file `options.pdf`, part of the `hyperref` package distribution. Available at pittetd’s webpage.

Index

Numbers written in italics refer to the page where the corresponding entry is described. A list of mentioned packages is found under ‘packages mentioned;’ of environments under ‘environments;’ of pittetd options under ‘options to pittetd.’

Symbols	\@@@degree . 58, 61, 66, 71, 567, 590
\@	366 \@@appendix 889

\@chapter	844	\@floatl	23, 172, 654, 933, 934, 942, 943, 955, 956, 964, 965, 1169
\@disable	442, 615, 619	\@fontswitch	337, 338
\@school	416, 420, 509	\@fpbot	323
\@abstractmessage	555, 578	\@fpsep	322
\@advisor	63, 68, 73, 529, 545	\@fptop	321
\@afterheading	569, 592, 720, 734, 853, 917, 1105	\@getadvisor	522, 543
\@afterindentfalse	556, 579, 711, 722, 800, 821, 837, 900	\@getlength	818, 871
\@appendix	889	\@getlengthchapter	846, 871
\@author	374, 477, 512, 550, 567, 590	\@highpenalty	295
\@beginparpenalty	990	\@hyper@creffalse	80, 381
\@biblabel	1072, 1073, 1124	\@hyper@reftrue	12, 380
\@centercr	1034	\@idxitem	1146, 1148, 1149, 1150
\@chapter	842, 844	\@ifpackageloaded	311, 378
\@chapterl	16, 168, 199, 203, 205, 876, 877, 1161	\@itempenalty	992
\@clubpenalty	1082	\@keywords	375, 423, 424, 571, 594
\@coadv	40, 529, 546	\@keywordstrue	554, 577
\@committee	39, 493, 504, 521, 522, 529, 543	\@latex@warning	1085, 1128
\@committeemessage	497	\@linemessage	83, 432, 444, 524, 537, 747, 788
\@commline	493, 543	\@listI	101, 124, 147, 997, 1099
\@copyrightmessage	547	\@listi	101, 124, 147, 993, 997, 1099, 1101
\@currentlabelname	910	\@listii	998
\@currsiz	348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358	\@listiii	1004
\@date	400, 515	\@listiv	1010, 1013, 1016
\@dategivenfalse	399	\@lofmessage	655
\@dategiventrue	15, 398	\@lotmessage	633
\@dblfloat	938, 960	\@lowpenalty	293, 990, 991, 992
\@degree	409, 417, 478, 765, 766, 767, 769, 770, 771	\@mainmatterfalse	890
\@degreesought	62, 67, 72, 421, 483	\@mainmattertrue	11
\@disable	427, 449, 450, 451, 452, 453, 454, 455, 456, 574, 597, 623, 672	\@makecaption	967
\@enable	427, 448, 487, 541, 542, 552, 575, 598, 613, 617, 620, 621, 650, 651, 652, 671, 690, 707, 719	\@makefnmark	1069
\@endparpenalty	991	\@makefntext	1066
\@errorsfalse	194	\@medpenalty	294
\@errorstrue	79	\@minipagefalse	974
\@etdau	6, 1153, 1155, 1158, 1160, 1162, 1164, 1166, 1168, 1170	\@mparswitchfalse	226
\@expandedBOOKMARK	630, 631	\@mpfootins	215
\@expectedprelim	38, 429, 433	\@nolinemessage	89, 409, 412
\@figurestrue	950, 959, 1158	\@onlypreamble	272, 389, 425, 426
		\@openbib@code	49, 224, 1076
		\@outlinefile	467, 501, 560, 583, 603, 637, 659, 678, 695, 726
		\@pdfcreator	370
		\@pdftitle	374, 392, 393
		\@phd	173, 524
		\@pnumwidth	187
		\@prefacemessage	710
		\@prelim	625, 630

\@presubs . . .	21, 198, 199, 200, 207	\@yeargiventrue	408
\@presubsub	22, 200, 201, 209		
\@ptsize 41, 42, 43, 44, 163, 303, 988		Numbers	
\@safebibliography		10pt option	5, 12
.	1071, 1088, 1107, 1114	11pt option	5, 12
\@school	409, 419, 481	12pt option	5, 12
\@seclettersfalse	74		
\@secletterstrue	75	A	
\@secpenalty	806, 827	\abovecaptionskip . . .	25, 328, 968
\@sect	834, 835	\abovedisplayshortskip	98, 121, 144
\@sectionl . .	17, 169, 198, 205, 1163	\abovedisplayskip	
\@setfontsize	96,	. . .	97, 100, 120, 123, 143, 146
102, 103, 104, 105, 106, 107,		abstract	8, 18–19, 20
108, 109, 110, 111, 119, 125,		\abstractname	183
126, 127, 128, 129, 130, 131,		achemso package	23
132, 133, 134, 142, 148, 149,		achicago package	5, 8, 22, 23
150, 151, 152, 153, 154, 155, 157		patch for	5, 22
\@singleline 20, 94, 117, 140, 288,		\achicago@patch	1131
290, 292, 324, 326, 327, 328,		acknowledgements	7, 10, 19
329, 472, 473, 506, 507, 512,		\acro	248, 346
566, 567, 569, 588, 589, 590,		Acrobat PDF Writer	4
592, 718, 733, 853, 857, 858,		Acrobat Reader . .	4, 7, 11, 15, 20, 25
861, 862, 865, 915, 917, 1097,		\addcontentsline	
1100, 1104, 1110, 1122, 1140		714, 854, 918, 1095, 1138
\@ssect	813, 814	\addtocounter	887
\@startbody	815	advisor(s)	18
\@startsection		ae package	9
.	797, 817, 856, 860, 864	AE fonts	9
\@starttoc . .	611, 648, 670, 689, 706	AMS packages	9
\@striptitle	778, 779	amsart class	12
\@subsectionl 18, 170, 201, 207, 1165		amsbook class	12
\@subsubsectionl 19, 171, 209, 1167		amsmath package	9
\@tablemessage	599	amsthm package	9
\@tabletrue	928, 937, 1155	\and	492
\@this	57, 60, 65, 70, 511, 529	appendices	21, 21, 25, 35
\@title	391, 474, 566, 589	\appendix	755, 756, 792, 889
\@titlemessage	457	\appendixname	182, 910
\@tocrmarg	188	\arraycolsep	210
\@topnum	836, 899	\arrayrulewidth	212
\@twocolumnfalse	227	ASCII	7, 13, 20, 21, 24
\@twosidefalse	225	\AtBeginDocument 311, 371, 378, 1109	
\@width	1063	\AtEndDocument	196, 1153
\@withgobble		\AtEndOfClass	368
231, 611, 858, 863, 866, 872, 881		\AtEndOfPackage	48
\@withperiod	229, 611,	author	19, 20
847, 850, 858, 863, 866, 872, 881		\author	491, 764
\@year	406,	author	16
408, 461, 486, 550, 568, 591, 776		author-year	23
\@yeargivenfalse	14	auxiliary files	3, 10, 11

B	
<code>\backmatter</code>	921
<code>\baselinestretch</code>	12
<code>\belowcaptionskip</code>	26, 329, 977
<code>\belowdisplayskip</code>	99, 122, 145
<code>\belowdisplayskip</code>	100, 123, 146
<code>\bf</code>	333
<code>\bibindent</code> 24, 50, 51, 166, 1118, 1119	
bibliography	12, 21–25
BibT _E X styles	9
author-year	23
bracket labels	23
citations	23
footnote	23
packages	9, 21–23
<code>\bibliography</code>	10, 22, 1107
<code>\bibname</code>	177, 1093, 1095, 1096
<code>\bibsep</code>	1110
BibT _E X	21
styles	21–23
<code>\bigskipamount</code>	291
<code>\BOOKMARK</code>	468, 502, 561, 584, 604, 632, 638, 660, 679, 696, 727
bookmarks	2, 4, 7, 10, 11, 13, 19, 20, 25, 26
limitations	7, 20, 24, 26
<code>\bottomfraction</code>	317
C	
<code>\c@addprel</code>	725, 728
<code>\c@chapter</code>	219, 233, 234, 259, 260, 262, 267, 268, 270, 897
<code>\c@enumi</code>	274, 279
<code>\c@enumii</code>	275, 280
<code>\c@enumiii</code>	276, 281
<code>\c@enumiv</code>	277, 282, 1072, 1079
<code>\c@equation</code>	220
<code>\c@figure</code>	252, 263
<code>\c@section</code>	237, 238, 895
<code>\c@subsection</code>	241, 242
<code>\c@subsubsection</code>	245, 246
<code>\c@table</code>	253, 271
<code>\cal</code>	337
capitalization of titles	7, 13, 14, 26
<code>\caption</code>	7
caption2 package	9
captions	7, 20–21, 24, 26
<code>\chapter</code> 21, 815, 899, 905, 906, 1089	
<code>\chapter*</code>	8
chapterbib package	23
<code>\chapterfloats</code>	252
<code>\chaptername</code>	181
chapters	
numbering	14
titles	7
cite package	23
<code>\cite</code>	20, 23
<code>\ClassError</code>	85, 90, 532
classes	
related to pttetd	9–10
related to pttetd	5
standard	1, 7, 10, 14, 16
<code>\ClassInfo</code>	384, 385
<code>\ClassWarning</code>	
87, 362, 394, 809, 830, 839, 904	
<code>\ClassWarningNoLine</code>	
91, 192, 196, 460, 515	
<code>\clubpenalty</code> 296, 1081, 1082, 1126	
CM fonts	9
coadvisor	18
<code>\coadvisor</code>	544, 744
color package	3, 6, 9, 10, 25
<code>\columnsep</code>	1143
<code>\columnseprule</code>	1142
<code>\columnwidth</code>	1063
committee members	18
committee page	7, 16–18
<code>\committeemember</code>	
494, 532, 533, 743, 744, 779, 780, 781, 782, 783, 784	
<code>\committeepage</code>	497, 786
<code>\contentsline</code>	628
<code>\contentsname</code>	174
<code>\convname</code>	184
copyright page	8, 18
<code>\copyrightpage</code>	547
cross referencing	21, 27
CTAN (Comprehensive T _E X Archive Network)	1, 6
D	
date	18
<code>\date</code>	396, 517, 776
<code>\DeclareOldFontCommand</code>	
330, 331, 332, 333, 334, 335, 336	
<code>\DeclareRobustCommand</code> 337, 338, 347	
dedication	7, 19
defense	18

<code>\degree</code>	409, 411, 417, 739, 740, 773	<code>float</code> package	9
<code>\degreesought</code>	421, 740, 773	<code>floatflt</code> package	9
<code>\descriptionlabel</code>	1029, 1031	<code>\floatpagefraction</code>	320
dissertation advisor(s)	18	<code>\floatsep</code>	324
Document Info	11, 15, 16, 20, 25	<code>fncychap</code> package	9
<code>\documentclass</code>	11	<code>\fnum@figure</code>	948
<code>documentclass</code>	26	<code>\fnum@table</code>	926
<code>\doublerulesep</code>	213	fonts	
draft option	10–11, 12, 16, 18	packages	9
DVI		PostScript	9
files	3	size	12
viewers	4	<code>\footins</code>	113, 136, 159, 215
<code>dvipdf</code>	4	<code>\footnoterule</code>	1061
<code>dvipdfm</code>	3–4, 4	footnotes	12, 20
<code>dvipdfm</code> option	3, 3, 12, 25	<code>\footnotesep</code>	112, 135, 158
<code>dvipdfm</code> option	4	<code>\footnotesize</code>	
<code>dvips</code>	4	... 103, 126, 149, 164, 350, 351	
E		<code>\footskip</code>	305
<code>\emph</code>	22, 343	formulas	7
<code>enumerate</code> (environment)	14	<code>\fps@figure</code>	945
environments:		<code>\fps@table</code>	923
<code>thebibliography</code>	21, 22	<code>\frontmatter</code>	920
<code>enumerate</code>	14	<code>\ftype@figure</code>	946
<code>figure</code>	20	<code>\ftype@table</code>	924
<code>quotation</code>	12, 22	G	
<code>quote</code>	12, 22	<code>\Gobble</code>	1124
<code>table</code>	20	<code>\gobble@or@not</code>	
<code>theindex</code>	23	... 228, 236, 240, 244, 250	
error messages	3, 9, 24	graphics	
<code>pittetd's</code>	10–18	inclusion of	10
<code>pittetd's</code>	11	<code>graphicx</code> package	3, 9, 10, 25
<code>\ext@figure</code>	947	H	
<code>\ext@table</code>	925	<code>harvard</code> package	22
F		<code>\hb@xt@</code>	975, 1069
<code>\f@size</code>	506	<code>\headheight</code>	307
<code>fancyhdr</code> package	9	headings	7, 27
<code>\fboxrule</code>	217	<code>\headsep</code>	308
<code>\fboxsep</code>	216	<code>\Huge</code>	110, 133, 156, 358
FG (Format Guidelines)	2,	<code>\huge</code>	109, 132, 155, 156, 357, 358
7, 9, 12, 13, 21–23, 26, 43, 59		<code>\HyOrg@maketitle</code>	379
<code>figure</code> (environment)	20	<code>hyperref</code> package	
<code>\figurename</code>	179	... 2–4, 6, 7, 10, 11, 19–23	
figures	25	use of	24–26
captions	7, 20–21, 26	<code>\hypersetup</code>	372
numbering	20	<code>\hypertarget</code>	466, 500, 559,
spacing in	20	582, 602, 636, 658, 677, 694, 725	
final option	10, 10–11, 12, 16, 18, 26		
<code>fleqn</code> option	12		

I	
\if@dategiven . . .	15, 458, 513, 519
\if@errors	7, 84, 89, 191, 196
\if@figures	10, 616, 650, 1157
\if@hyper@ref	12, 367
\if@keywords	8, 570, 593
\if@mainmatter . .	11, 257, 265, 851
\if@nobreak	803, 824
\if@noskipsec	798, 819
\if@seclatters 13, 232, 235, 239,	243, 258, 266, 278, 851, 855, 874
\if@tables	9, 612, 1154
\if@yeargiven	14, 459
\ignorespaces	249
incompatibility	8–9
index	12, 23, 25
\indexname . .	178, 1136, 1138, 1140
\indexspace	1151
input files	6, 8, 11
\InputIfFileExists	190, 383
installation	
pittetd	5–6
dvipdfm	6
color	6
hyperref	6
PDFTEX	6
\intextsep	327
\it	334
\item 571, 594, 1040, 1052, 1057, 1146	
\itemindent	51, 52, 1028, 1036, 1037, 1049, 1119, 1120
\itemsep	996, 1003, 1009, 1035, 1100, 1104, 1122
\itshape	334
\itswitch	343
J	
\jobname	190, 193, 642, 664, 683, 700, 1153
K	
keywords	19, 20
\keywords	19, 421
L	
\l@algorithm	708
\l@chapter	202
\l@figure	673
\l@section	204
\l@subsection	206
\l@subsubsection	208
\l@table	654, 673, 708
\labelenumi	1019
\labelenumii	1020
\labelenumiii	1021
\labelenumiv	1022
\labelitemi	1023
\labelitemii	1024
\labelitemiii	1025
\labelitemiv	1026
\labelsep	214, 985, 987, 1000, 1006, 1012, 1015, 1018, 1032, 1075, 1117
\labelwidth 986, 987, 999, 1000, 1005, 1006, 1011, 1012, 1014, 1015, 1017, 1018, 1028, 1073, 1074
\LARGE	108, 131, 154, 354, 357
\Large	107, 130, 153, 353, 354
\large	106, 129, 152, 352, 353
\leftmargin . .	50, 979, 994, 998, 1004, 1010, 1013, 1016, 1028, 1038, 1039, 1050, 1056, 1074, 1075, 1102, 1116, 1117, 1118
\leftmargini 978, 979, 986, 994, 1102	
\leftmarginii	980, 998, 999
\leftmarginiii	981, 1004
\leftmarginiv	982, 1010, 1011
\leftmarginv	983, 1013, 1014
\leftmarginvi	984, 1016, 1017
\leftmarginiii	1005
leqno option	12
\lineskip	284
links	2, 4, 10, 19, 21, 23–26
list of figures	8, 19, 20
list of tables	8, 19, 20
\listfigurename	175
\listofalgos	691
\listoffigures	617, 650, 655
\listoflistings	674
\listoftables	613, 633
\listparindent 52, 1037, 1048, 1049, 1120
\listtablename	176
\lowercase	14, 511
M	
ma option	12, 16
\mainmatter	922

\makeatletter		openbib option	12
341, 640, 662, 681, 698, 737, 761		options to pittedd:	
\makeatother	758, 794, 1132	draft	10–11, 12, 16, 18
\makecommittee		dvipdfm	3, 3, 12, 25
487, 497, 534, 536, 538, 751, 786		final ..	10, 10–11, 12, 16, 18, 26
MakeIndex	23	fleqn	12
\makelabel	1029	leqno	12
\maketitle	379, 448, 457, 785	ma	12, 16
\MakeUppercase	859	ms	12, 16
\marginparsep	310, 313	nohyperref	3, 4–5, 6, 12, 25
\marginparwidth	309, 312	openbib	12
\mathbf	333	pdftex	3, 3, 6, 12, 25
\mathcal	337	phd	12, 16, 18
\mathit	334	sectionletters	12, 14
\mathnormal	338	sectionnumbers	12, 14
\mathrm	330	semifinal	11, 12, 16, 18
\mathsf	331	10pt	5, 12
\mathtt	332	11pt	5, 12
\maxdepth	304	12pt	5, 12
\medskip	571, 594	overcite package	23
\medskipamount ...	289, 1047, 1055	overfull lines	26
\MessageBreak	435, 438	\overfullrule	76, 77, 78
MiKTeX	6		
\mit	338	P	
ms option	12, 16	\p@enumiv	1078
multibib package	23	packages	
multicol package	9	bibliography	22
N		fonts	9
nameref package	21	standard	9
\nameref	21, 80	supported	9
natbib package	22, 23	unsupported	9
\newblock	55, 1108	use of	8–9
\newif .	7, 8, 9, 10, 11, 12, 13, 14, 15	packages mentioned:	
\newtoks	38, 39, 40, 422	achemso	23
\newwrite	6	achicago	5, 8, 22, 23
\nobreakspace	926, 948, 971	ae	9
nohyperref option .	3, 4–5, 6, 12, 25	amsmath	9
non-numbered chapters	8	amsthm	9
\normallineskip	285	caption2	9
\normalsfcodes	572, 595	chapterbib	23
\normalsize ...	20, 95, 96, 118,	cite	23
119, 141, 142, 348, 352, 506, 549		color	3, 6, 9, 10, 25
numbering		fancyhdr	9
chapters and sections	14	float	9
figures and tables	20	floatflt	9
O		fncychap	9
\oddsidemargin	300	graphicx	3, 9, 10, 25
opcit package	23	harvard	22
		hyperref	2–4, 6, 7, 10, 11, 19–23

use of	24–26	\pittdiss@patch	793
multibib	23	pittetd	
multicol	9	loading	11
nameref	21	options	
natbib	22, 23	..	3–6, 10–12, 14, 16, 18, 25, 26
opcit	23	webpage	1, 6, 8
overcite	23	pitthesis class	5, 9, 10, 16
setspace	9	patch for	5, 10
titlesec	9	\pittthesis@patch	757
tocbibind	9	PostScript	
verbatim	9	fonts	9
xspace	9	format	4
\pagenumbering	222, 816	preamble	15, 16, 19, 20
\pageref	21	preface	7, 8, 10, 19
\pagestyle	221	\preface	709
paper-based theses/ dissertations	.. 7	preliminaries	.. 7, 8, 10, 13, 14–19, 26
\paperheight	301	\preliminarychapter	721, 746, 787
\paperwidth	298	\prepare@bookmarks	
\paragraph	869	624, 641, 663, 682, 699
\parindent	114,	\previousdegree	411, 417
137, 160, 166, 978, 1067, 1141		\protected@write	
\parsep	53, 995, 1002,	467, 501, 560, 583,
1003, 1008, 1051, 1103, 1121		603, 637, 659, 678, 695, 726, 901	
\parskip	286, 1144	PSNFSS collection	9
\part	868		
\partopsep	988, 989		
\patch	383		
patches	6, 8–10, 22		
PDF			
creation	2		
Document Info	.. 11, 15, 16, 20, 25		
files	3, 4		
viewers	7		
PDFL ^A T _E X	2, 3, 6		
PDF _T E _X	6		
\pdfstringdef	629		
\pdfstringdefPreHook	247		
pdftex option	3, 3, 6, 12, 25		
pdftex.def file	6		
\period@or@not			
... 228, 233, 237, 241, 245, 251			
\phantomsection	.. 713, 1094, 1137		
phd option	12, 16, 18		
Pitt ETD			
format guidelines	7		
webpage	1		
Working Group	8		
pittdiss class	5, 9, 10, 16		
patch for	5, 10		

Q

\quad	851, 874
quotation (environment)	.. 12, 22
quotations	12, 20
quote (environment)	12, 22

R

\ref	21, 80
\regularenun	273
\renewenvironment	1046, 1054, 1113
\reserved@a	631, 632
\rm	330
\rmfamily	330

S

\safebibliography	10, 1107
\sbox	397, 969
\sc	336
\school	16, 412, 414, 419
\scriptsize	
... 104, 127, 150, 165, 351, 355	
\scshape	336
\section	26, 856, 1090
sectionletters option	.. 12, 14
sectionnumbers option	.. 12, 14

sections		captions	7, 20–21, 26
commands	13, 24	numbering	20
numbering	14	spacing in	20
titles	7, 13, 26	TDS	5, 6
semifinal option	11, 12, 16, 18	\texorpdfstring	7, 13, 382
setspace package	9	\textasteriskcentered	1025
\setyear	406, 462	\textbf	62, 67, 72
\sf	331	\textbullet	1023
\sffamily	331	\textcopyright	550
\singlesize	349	\textendash	1024
\singlespace	20, 111, 134, 157, 929, 938, 951, 960, 1098	\textfloatsep	325
\sl	335	\textfraction	319
\SMALL	165	\textheight	302
\Small	164	\textperiodcentered	1026
\small	102, 125, 148, 348, 349, 350, 359, 364, 1052, 1057, 1145	\textSMC	365, 366
\smallskipamount	287, 993	\textwidth	299
\SMC	347, 363, 365	\thanks	394, 395, 488
\SMC@unknown@warning	359, 362	thebibliography (environment)	21, 22
\spacefactor	572, 595	\thechapter	220, 232, 847, 851, 855, 874, 894, 897, 910, 911, 915, 919
spacing	12–13, 20–22	\theenumi	274, 279, 1019
stage	10–11	\theenumii	275, 280, 1020
standard classes	1	\theenumiii	276, 281, 1021
starred commands:		\theenumiv	277, 282, 1022, 1079
\chapter*	8	\theequation	219
\chapter	13	\thefigure	252, 948, 954, 963
\section*	13	theindex (environment)	23
\subsection*	13	\thesection	232, 895
\subsubsection*	13	thesis advisor(s)	18
\stepcounter	495, 882, 902	\thesubsection	232
\subitem	1149	\thesubsubsection	232
subject	20	\thetable	252, 926, 932, 941
\subject	376, 421	\thispagestyle	470, 1141
\subparagraph	870	\tiny	105, 128, 151, 355, 356
\subsection	856	title	7, 19, 20
\subsubitem	1150	\title	390, 490, 763
\subsubsection	856	title page	7, 11, 14–16
		titles	7
T		titlesec package	9
\T	691	tocbibind package	9
\t@or@d	56, 59, 64, 69, 524	\today	401, 405
\tabbingsep	214	\topfraction	315
\tabcolsep	211	\topmargin	306
table (environment)	20	\topsep	993, 1001, 1007, 1009, 1047, 1055, 1101
table of contents	8, 13, 19, 19	\topskip	303, 304
\tablename	180	\tt	332
\tableofcontents	575, 598, 599		
tables	25		

<code>\ttfamily</code>	332	<code>\value</code>	498, 518, 893
<code>\twocolumn</code>	1139	<code>verbatim package</code>	9
U			
<code>underfull boxes</code>	27	W	
<code>\uppercase</code>	420, 474, 565, 589, 848, 852, 912, 916	<code>warnings</code>	10–11, 16, 18, 26, 27
<code>\usepackage</code>	8, 9, 369, 387	<code>\widowpenalty</code>	297, 1083, 1126
<code>\usewithpatch</code>	383	<code>\write</code>	1155, 1158, 1160, 1162, 1164, 1166, 1168
V			
<code>VT_EX</code>	4	X	
		<code>\xdef</code>	766, 769, 771, 910
		<code>xspace package</code>	9

8 The program

DOCSTRIP modules: `class`, `10pt`, `11pt`, `12pt`, `pittdiss`, `pitthesis`, `achicago`

8.1 Identification

```

1 <{*class>
2 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
3 \ProvidesClass{pittetd}[2004/08/17 v1.618
4   University of Pittsburgh ETD
5   (Electronic Thesis & Dissertations) class]
```

8.2 Declarations

```

6 \newwrite\@etdaux
7 \newif\if@errors
8 \newif\if@keywords
9 \newif\if@tables
10 \newif\if@figures
11 \newif\if@mainmatter\@mainmattertrue
12 \newif\if@hyper@ref\@hyper@reftrue
13 \newif\if@seclatters
14 \newif\if@yeargiven\@yeargivenfalse
15 \newif\if@dategiven\@dategivetrue
16 \newlength\@chapterl
17 \newlength\@sectionl
18 \newlength\@subsectionl
19 \newlength\@subsubsectionl
20 \newlength\@singleline
21 \newlength\@presubs
22 \newlength\@presubsub
23 \newlength\@floatl
24 \newdimen\@bibindent
25 \newlength\@abovecaptionskip
```

```

26 \newlength\belowcaptionskip
27 \newcounter{@members}\setcounter{@members}{0}
28 \newcounter{@addprel}\setcounter{@addprel}{8}
29 \newcounter{@appno}\setcounter{@appno}{0}
30 \newcounter{chapter}
31 \newcounter{section}[chapter]
32 \newcounter{subsection}[section]
33 \newcounter{subsubsection}[subsection]
34 \newcounter{paragraph}
35 \newcounter{subparagraph}
36 \newcounter{figure}
37 \newcounter{table}
38 \newtoks\@expectedprelim
39 \newtoks\@committee
40 \newtoks\@coadv

```

8.3 Options

These come pretty unchanged from the standard classes:

```

41 \newcommand\@ptsize{}
42 \DeclareOption{10pt}{\renewcommand\@ptsize{0}}
43 \DeclareOption{11pt}{\renewcommand\@ptsize{1}}
44 \DeclareOption{12pt}{\renewcommand\@ptsize{2}}
45 \DeclareOption{leqno}{\input{leqno.clo}}
46 \DeclareOption{fleqn}{\input{fleqn.clo}}
47 \DeclareOption{openbib}{%
48     \AtEndOfPackage{%
49         \renewcommand\@openbib@code{%
50             \advance\leftmargin\bibindent
51             \itemindent -\bibindent
52             \listparindent \itemindent
53             \parsep \z@
54             }%
55     \renewcommand\newblock{\par}}}

```

Now for pittetd's own options.

```

56 \newcommand\t@or@d{}
57 \newcommand\@this{}
58 \newcommand\@@@degree{}
59 \DeclareOption{phd}{\renewcommand\t@or@d{phd}%
60     \renewcommand\@this{Dissertation}%
61     \renewcommand\@@@degree{PhD}%
62     \def\@degreesought{\textbf{Doctor of Philosophy}}}%
63     \def\@advisor{Director}}
64 \DeclareOption{ma}{\renewcommand\t@or@d{ma}%
65     \renewcommand\@this{Thesis}%
66     \renewcommand\@@@degree{M.A.}%
67     \def\@degreesought{\textbf{Master of Arts}}}%

```

```

68 \def\@advisor{Advisor}}
69 \DeclareOption{ms}{\renewcommand{\t@or@d}{ms}}%
70 \renewcommand\@this{Thesis}%
71 \renewcommand\@@degree{M.S.}%
72 \def\@degreesought{\textbf{Master of Sciences}}%
73 \def\@advisor{Advisor}}
74 \DeclareOption{sectionnumbers}{\@seclettersfalse}
75 \DeclareOption{sectionletters}{\@secletterstrue}

```

The next are the ‘stage’ options. By declaration, `\if@errors` is false, so only `final` is required to mention it explicitly. See section 8.4 for the actual effect of this switch.

```

76 \DeclareOption{draft}{\setlength{\overfullrule}{5pt}}
77 \DeclareOption{semifinal}{\setlength{\overfullrule}{5pt}}
78 \DeclareOption{final}{\setlength{\overfullrule}{0pt}}%
79 \@errorstrue}

```

The following `\let`’ing of `\nameref` to `\ref` provides for the case that a document that has been processed all the time with `hyperref` is suddenly changed to `nohyperref`. If `hyperref` (the package) is to be loaded, it will redefine the command (fortunately it is defined with `\def` in `nameref.sty`; for a not-as-lucky case, see the handling of `\texorpdfstring` below).

```

80 \DeclareOption{nohyperref}{\let\nameref\ref\@hyper@reffalse}

```

Note that the ‘options’ `pdfTeX` and `dvipdfm`, advertised so much in the documentation above, are not actually defined in `pittetd.cls`. Because of L^AT_EX options mechanism, they will be simply passed on to any package that is loaded.

Okay. Default options, and processing of any non-default:

```

81 \ExecuteOptions{12pt,semifinal,hyperref,phd}
82 \ProcessOptions

```

8.4 Stage and error handling

`\@linemessage` Through `\@linemessage` and `\@nolinemessage`, whose actual performance depends on the ‘stage’ option, most problems will only warn, unless the `final` option has turned `\if@errors` true.

```

83 \newcommand\@linemessage[2]{%
84 \if@errors
85 \ClassError{pittetd}{#1}{#2}
86 \else
87 \ClassWarning{pittetd}{#1}
88 \fi}

```


\@nolinemessage

```
89 \newcommand\@nolinemessage[2]{\if@errors
90   \ClassError{pittetd}{#1}{#2}\else
91   \ClassWarningNoLine{pittetd}{#1}\fi}
```

8.5 Initialization

First, let's get the font size done: one file for each of the three available sizes. The length \@singleline is an important one: it is the space between two lines of text, which is exactly 1.5 of the regular spacing in a standard L^AT_EX class (according to size). \normalsize is the only size that really sets everything up, and the only whose spacing is more than single line. The others modify only the font size itself, and are just a little more than single-spaced (as are all sizes in standard classes). Other things that depend on the font size are set in these files.

```
92 </class>
93 <*10pt>
94 \setlength{\@singleline}{18\p@}
95 \renewcommand\normalsize{%
96   \@setfontsize\normalsize\@xpt{18}%
97   \abovedisplayskip 10\p@ \@plus2\p@ \@minus5\p@
98   \abovedisplayshortskip \z@ \@plus3\p@
99   \belowdisplayshortskip 6\p@ \@plus3\p@ \@minus3\p@
100  \belowdisplayskip \abovedisplayskip
101  \let\@listi\@listI}
102 \newcommand\small{\@setfontsize\small\@ixpt{11}}
103 \newcommand\footnotesize{\@setfontsize\footnotesize\@viipt{9.5}}
104 \newcommand\scriptsize{\@setfontsize\scriptsize\@viipt\@viipt}
105 \newcommand\tiny{\@setfontsize\tiny\@vpt\@vpt}
106 \newcommand\large{\@setfontsize\large\@xipt{14}}
107 \newcommand\Large{\@setfontsize\Large\@xivpt{18}}
108 \newcommand\LARGE{\@setfontsize\LARGE\@xvipt{22}}
109 \newcommand\huge{\@setfontsize\huge\@xxpt{25}}
110 \newcommand\Huge{\@setfontsize\Huge\@xxvpt{30}}
111 \newcommand\singlespace{\@setfontsize\singlespace\@xpt\@xipt}
112 \setlength\footnotesep{6.65\p@}
113 \setlength{\skip\footins}{9\p@ \@plus 4\p@ \@minus 2\p@}
114 \setlength\parindent{15\p@}
115 </10pt>

116 <*11pt>
117 \setlength{\@singleline}{20.4\p@}
118 \renewcommand\normalsize{%
119   \@setfontsize\normalsize\@xipt{20.4}%
120   \abovedisplayskip 11\p@ \@plus3\p@ \@minus6\p@
121   \abovedisplayshortskip \z@ \@plus3\p@
122   \belowdisplayshortskip 6.5\p@ \@plus3.5\p@ \@minus3\p@}
```

```

123 \belowdisplayskip \abovedisplayskip
124 \let\@listi\@listI}
125 \newcommand\small{\@setfontsize\small\@xpt\@xipt}
126 \newcommand\footnotesize{\@setfontsize\footnotesize\@ixpt{11}}
127 \newcommand\scriptsize{\@setfontsize\scriptsize\@viipt{9.5}}
128 \newcommand\tiny{\@setfontsize\tiny\@vipt\@viipt}
129 \newcommand\large{\@setfontsize\large\@xipt{14}}
130 \newcommand\Large{\@setfontsize\Large\@xivpt{18}}
131 \newcommand\LARGE{\@setfontsize\LARGE\@xviipt{22}}
132 \newcommand\huge{\@setfontsize\huge\@xxpt{25}}
133 \newcommand\Huge{\@setfontsize\Huge\@xxvpt{30}}
134 \newcommand\singlespace{\@setfontsize\singlespace\@xipt{13.6}}
135 \setlength\footnotesep{7.7\p@}
136 \setlength{\skip\footins}{10\p@ \@plus 4\p@ \@minus 2\p@}
137 \setlength\parindent{17\p@}
138 </11pt>

139 <*12pt>
140 \setlength{\@singleline}{21.75\p@}
141 \renewcommand\normalsize{%
142 \@setfontsize\normalsize\@xipt{21.75}%
143 \abovedisplayskip 12\p@ \@plus32\p@ \@minus7\p@
144 \abovedisplayshortskip \z@ \@plus3\p@
145 \belowdisplayshortskip 6.5\p@ \@plus3.5\p@ \@minus3\p@
146 \belowdisplayskip \abovedisplayskip
147 \let\@listi\@listI}
148 \newcommand\small{\@setfontsize\small\@xipt{13.6}}
149 \newcommand\footnotesize{\@setfontsize\footnotesize\@xpt\@xipt}
150 \newcommand\scriptsize{\@setfontsize\scriptsize\@viipt{9.5}}
151 \newcommand\tiny{\@setfontsize\tiny\@vipt\@viipt}
152 \newcommand\large{\@setfontsize\large\@xivpt{18}}
153 \newcommand\Large{\@setfontsize\Large\@xviipt{22}}
154 \newcommand\LARGE{\@setfontsize\LARGE\@xxpt{25}}
155 \newcommand\huge{\@setfontsize\huge\@xxvpt{30}}
156 \let\Huge\huge
157 \newcommand\singlespace{\@setfontsize\singlespace\@xipt{14.5}}
158 \setlength\footnotesep{8.4\p@}
159 \setlength{\skip\footins}{10.8\p@ \@plus 4\p@ \@minus 2\p@}
160 \setlength{\parindent}{19\p@}
161 </12pt>
162 <*class>

```

The right file is loaded next. For all sizes, the following \let's are true.

```

163 \input{pitetd1\@ptsize.clo}
164 \let\Small\footnotesize
165 \let\SMALL\scriptsize
166 \let\bibindent\parindent

```

Now for some initial values. The first five are needed to format the table

of contents and the lists of tables and figures, and are to be changed by the `\jobname.eto` file below. Oh!, `\normalfont` must come before for `em` to make sense as a length unit.

```

167 \normalfont
168 \setlength\@chapterl{1.5em}
169 \setlength\@sectionl{1.5em}
170 \setlength\@subsectionl{1em}
171 \setlength\@subsubsectionl{1em}
172 \setlength\@floatl{2.3em}

173 \newcommand\@phd{phd}
174 \newcommand\contentsname{CONTENTS}
175 \newcommand\listfigurename{LIST OF FIGURES}
176 \newcommand\listtablename{LIST OF TABLES}
177 \newcommand\bibname{BIBLIOGRAPHY}
178 \newcommand\indexname{INDEX}
179 \newcommand\figurename{Figure}
180 \newcommand\tablename{Table}
181 \newcommand\chaptername{Chapter}
182 \newcommand\appendixname{APPENDIX}
183 \newcommand\abstractname{}
184 \newcommand\convname{CONVENTIONS}

```

For the table of contents and related:

```

185 \setcounter{secnumdepth}{3}
186 \setcounter{tocdepth}{3}
187 \newcommand\@pnumwidth{1.55em}
188 \newcommand\@tocrmarg{2.55em}
189 \newcommand\@dotsep{4.5}

```

And here we go with the `\jobname.eto` file. It will tell `pitteto` whether there are tables and/or figures—switches `\if@figures` and `\if@tables`, both initially false—and the lengths `\@chapterl`, `\@sectionl`, etc., which hold the width of the widest label of each sectioning level and the widest float number (plus some extra space). The indentation of the sections in the table of contents is equal to `\@chapterl`; that of the lesser levels (lengths `\@presubs` and `\@presubsub`) is then calculated as the sum of the widths of higher levels.

These calculations are necessary for potentially long Roman numerals of chapters. For example, in `pittesis`, the number **VIII** collides with the title of the chapter. And once we have to fix this, why not do it with all the levels, in all the cases? Likewise, if figures and tables are numbered within chapters, it is not that unlikely that expressions like ‘VIII.10’ have to appear in the corresponding list. The width has to be kept track of.

```

190 \InputIfFileExists{\jobname.eto}{-}{%
191     \if@errors

```

```

192      \ClassWarningNoLine{pittetd}{%
193          No \jobname.etd file. Entering semifinal mode}%
194      \@errorsfalse
195      \fi}
196 \if@errors\else\AtEndDocument{\ClassWarningNoLine{pittetd}{%
197     Remember to run the document with ‘final’ option}}\fi
198 \setlength\@presubs{1\@sectionl}
199 \addtolength\@presubs{1\@chapterl}
200 \setlength\@presubsub{1\@presubs}
201 \addtolength\@presubsub{1\@subsectionl}
202 \newcommand*\l@chapter{%
203     \@dottedtocline{0}{\z@}{\@chapterl}}
204 \newcommand*\l@section{%
205     \@dottedtocline{1}{\@chapterl}{\@sectionl}}
206 \newcommand*\l@subsection{%
207     \@dottedtocline{2}{\@presubs}{\@subsectionl}}
208 \newcommand*\l@subsubsection{%
209     \@dottedtocline{3}{\@presubsub}{\@subsubsectionl}}

```

Other parameters:

```

210 \setlength\arraycolsep{5\p@}
211 \setlength\tabcolsep{6\p@}
212 \setlength\arrayrulewidth{.4\p@}
213 \setlength\doublerulesep{2\p@}
214 \setlength\tabbingsep{\labelsep}
215 \skip\@mpfootins=\skip\footins
216 \setlength\fbboxsep{3\p@}
217 \setlength\fbboxrule{.4\p@}
218 \@addtoreset{equation}{chapter}
219 \renewcommand\theequation{\ifnum \c@chapter>\z@
220     \thechapter.\fi\@arabic\c@equation}

```

Page style and initialization:

```

221 \pagestyle{plain}
222 \pagenumbering{roman}
223 \setcounter{footnote}{0}
224 \let\@openbib@code\@empty

```

And just in case some L^AT_EX commands need to know this:

```

225 \@twosidefalse
226 \@mparswitchfalse
227 \@twocolumnfalse

```

8.6 Counters and numbers

The issue here is the two kinds of section numbering, 1.1.1.1 or I.A.1.a. In the second case, the headings for each section is *not* to include the ‘number’

of the previous (I. First Chapter; but A. First section). This involves two subtleties concerning cross references in the text: firstly, a reference to ‘section B’ would mean nothing without the chapter ‘number;’ secondly, the ‘number’ bears a final period in headings, but we do not want the period to appear within the text.

`\period@or@not` This is handled with the `\period@or@not` and `\gobble@or@not` mechanisms. In principle, both commands expand to nothing, but when `\@withperiod` or `\@withgobble` are declared (always locally in a group), they expand to period or to gobble.

```
228 \let\period@or@not\relax
229 \def\@withperiod{\def\period@or@not{.}}
230 \let\gobble@or@not\relax
231 \def\@withgobble{\let\gobble@or@not\@gobble}
```

`\thechapter` Now section numbers have to be defined accordingly. A regular call to `\thesection` `\thesubsection`, such as that done by a `\ref` command, for example, will `\thesubsection` not produce a period nor gobble the previous stuff.

```
\thesubsubsection
232 \renewcommand\thechapter{\if@secletters
233     \expandafter\@Roman\c@chapter\period@or@not
234     \else\@arabic\c@chapter\fi}
235 \renewcommand\thesection{\if@secletters
236     \gobble@or@not{\thechapter.}\expandafter\@Alph
237     \c@section\period@or@not
238     \else\thechapter.\@arabic\c@section\fi}
239 \renewcommand\thesubsection{\if@secletters
240     \gobble@or@not{\thesection.}\@arabic
241     \c@subsection\period@or@not
242     \else\thesection.\@arabic\c@subsection\fi}
243 \renewcommand\thesubsubsection{\if@secletters
244     \gobble@or@not{\thesubsection.}\@alph
245     \c@subsubsection\period@or@not
246     \else\thesubsection.\@arabic\c@subsubsection\fi}
```

`\pdfstringdefPreHook` We also have to instruct `hyperref` how to handle these commands when building a PDF string. We take the chance to avoid a series of warnings for `\ignorespace`, and also tell about `\acro`, which is defined below.

```
247 \newcommand\pdfstringdefPreHook{%
248     \let\acro\relax
249     \let\ignorespaces\relax
250     \let\gobble@or@not\@gobble
251     \def\period@or@not{.}}
```

`\thefigure` Next, floating-objects numbering. In principle it is consecutive, but the `\thetable` user might want to make it chapter-dependent. In implementing that `\chapterfloats`

option (as `\chapterfloats`), `\thechapter` cannot be used, since the `\period@or@not` would wrongly expand into a period in the bookmarks, creating double periods. And there is no way around it, so we have to use `\c@chapter` directly.

On the other hand, with `\chapterfloats`, floats in the appendices should be numbered ‘A1,’ not ‘A.1.’ This is achieved by using `\if@mainmatter`, since only `\appendix` sets `\@mainmatterfalse`.

```

252 \renewcommand\thefigure{\@arabic\c@figure}
253 \renewcommand\thetable{\@arabic\c@table}
254 \newcommand\chapterfloats{\@addtoreset{figure}{chapter}%
255   \@addtoreset{table}{chapter}%
256   \renewcommand\thefigure{%
257     \if@mainmatter
258       \if@secletters
259         \expandafter\@Roman\c@chapter
260       \else\@arabic\c@chapter
261       \fi.%
262     \else\expandafter\@Alph\c@chapter\fi
263     \@arabic\c@figure}%
264 \renewcommand\thetable{%
265   \if@mainmatter
266     \if@secletters
267       \expandafter\@Roman\c@chapter
268     \else\@arabic\c@chapter
269     \fi.%
270   \else\expandafter\@Alph\c@chapter\fi
271   \@arabic\c@table}}
272 \@onlypreamble\chapterfloats

```

`\regularenum` Finally, the labels for the four levels of the `enumerate` environment are set. In case the second numbering is used for sections, these labels are set to Roman, Alpha, arabic, alpha.

```

273 \newcommand\regularenum{%
274   \renewcommand\theenumi{\@arabic\c@enumi}%
275   \renewcommand\theenumii{\@alph\c@enumii}%
276   \renewcommand\theenumiii{\@roman\c@enumiii}%
277   \renewcommand\theenumiv{\@Alph\c@enumiv}}
278 \if@secletters
279   \renewcommand\theenumi{\@Roman\c@enumi}
280   \renewcommand\theenumii{\@Alph\c@enumii}
281   \renewcommand\theenumiii{\@arabic\c@enumiii}
282   \renewcommand\theenumiv{\@alph\c@enumiv}
283 \else\regularenum\fi

```

8.7 Layout parameters

This follows closely the standard classes.

```
284 \setlength\lineskip{1\p@}
285 \setlength\normallineskip{1\p@}
286 \setlength\parskip{0\p@ \@plus \p@}
287 \setlength\smallskipamount{%
288   .25\@singleline \@plus 1\p@ \@minus 1\p@}
289 \setlength\medskipamount{%
290   .5\@singleline \@plus 2\p@ \@minus 2\p@}
291 \setlength\bigskipamount{%
292   1\@singleline \@plus 4\p@ \@minus 4\p@}
293 \@lowpenalty 51
294 \@medpenalty 151
295 \@highpenalty 301
296 \clubpenalty 250
297 \widowpenalty 250
```

But page layout, being fixed here, is set directly and not through options.

```
298 \setlength\paperwidth{8.5in}
299 \setlength\textwidth{6.5in}
300 \setlength\oddsidemargin{\z@}
301 \setlength\paperheight{11in}
302 \setlength\textheight{9in}
303 \setlength\topskip{1\@ptsize \p@}
304 \setlength\maxdepth{.5\topskip}
305 \setlength\footskip{.5in}
306 \setlength\topmargin{\z@}
307 \setlength\headheight{\z@}
308 \setlength\headsep{\z@}
309 \setlength\marginparwidth{\z@}
310 \setlength\marginparsep{\z@}
```

By the way, if the `showidx` package is loaded, we should allow room for `\marginpar`'s (lest a forest of overfull messages populates the `.log` file).

```
311 \AtBeginDocument{\@ifpackageloaded{showidx}{%
312   \setlength\marginparwidth{1in}
313   \setlength\marginparsep{2pt}}{}}
```

More layout: this follows the standard classes, with adapted values, and omitting the double-column parameters.

```
314 \setcounter{topnumber}{2}
315 \renewcommand\topfraction{.5}
316 \setcounter{bottomnumber}{1}
317 \renewcommand\bottomfraction{.3}
318 \setcounter{totalnumber}{3}
319 \renewcommand\textfraction{.2}
```

```

320 \renewcommand\floatpagefraction{.5}
321 \setlength{\@fptop}{0\p@ \@plus 1fill}
322 \setlength{\@fpsep}{8\p@ \@plus 1fill}
323 \setlength{\@fpbot}{0\p@ \@plus 1fill}
324 \setlength{\floatsep}{.5\@singleline \@plus \z@ \@minus 10.2\p@}
325 \setlength{\textfloatsep}{%
326     {1.5\@singleline \@plus \z@ \@minus 10.2\p@}
327 \setlength{\intextsep}{.5\@singleline \@plus \z@ \@minus 10.2\p@}
328 \setlength\abovecaptionskip{\@singleline}
329 \setlength\belowcaptionskip{\@singleline}

```

8.8 Font commands

```

330 \DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
331 \DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
332 \DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
333 \DeclareOldFontCommand{\bf}{\normalfont\bfseries}{\mathbf}
334 \DeclareOldFontCommand{\it}{\normalfont\itshape}{\mathit}
335 \DeclareOldFontCommand{\sl}{\normalfont\slshape}{\@nomath\sl}
336 \DeclareOldFontCommand{\sc}{\normalfont\scshape}{\@nomath\sc}
337 \DeclareRobustCommand*\cal{\@fontswitch\relax\mathcal}
338 \DeclareRobustCommand*\mit{\@fontswitch\relax\mathnormal}

```

Here comes the first thing we have to deal with for the `achicago` package, that makes `\emph` behave as `\textsl`, rather than `\textit`. For the use of patches, see section 8.10.

```

339 </class>
340 <*achicago>
341 \makeatletter
342 \@ifundefined{achicago@patch}{\relax\endinput}
343 \renewcommand{\emph}[1]{\@fontswitch #1}%
344 </achicago>
345 <*class>

```

`\acro` The `\acro` command is an adaptation from the one in the `ltugboat` class:

```

346 \@ifundefined{acro}{%
347     \DeclareRobustCommand\SMC{%
348     \ifx\@currsize\normalsize\small\else
349     \ifx\@currsize\singlesize\small\else
350     \ifx\@currsize\small\footnotesize\else
351     \ifx\@currsize\footnotesize\scriptsize\else
352     \ifx\@currsize\large\normalsize\else
353     \ifx\@currsize\Large\large\else
354     \ifx\@currsize\LARGE\Large\else
355     \ifx\@currsize\scriptsize\tiny\else
356     \ifx\@currsize\tiny\tiny\else
357     \ifx\@currsize\huge\LARGE\else
358     \ifx\@currsize\Huge\huge\else

```



```

359             \small\SMC@unknown@warning
360     \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
361   }
362   \newcommand\SMC@unknown@warning{\ClassWarning{pittetd}{%
363     \string\SMC: unrecognized text font size
364     command---using \string\small}}
365   \newcommand\textSMC[1]{\SMC #1}
366   \newcommand\acro[1]{\textSMC{#1}\@}}

```

8.9 Hyperref

We begin by loading `hyperref`; at the end of the preamble, the proper options are set. Here, the user will already have provided the information for the ‘Document Info’ dialog box (`\@pdftitle`, `\@author`, etc.). We take pride on `pittetd` having created the PDF file, too.

```

367 \if@hyper@ref
368   \AtEndOfClass{%
369     \usepackage[bookmarks,hyperindex=true,pdfencoding=auto]{hyperref}%
370     \def\@pdfcreator{LaTeX, pittetd class, hyperref package}
371   \AtBeginDocument{%
372     \hypersetup{%
373       bookmarksnumbered,bookmarksopen,%
374       pdftitle=\@pdftitle,pdfaauthor=\@author,%
375       pdfkeywords=\@keywords,%
376       pdfsubject=\the\subject}}
377 \fi

```

`hyperref` redefines `\maketitle` to implement the special footnotes for `\author` and so on. This is disabled here. Also, the switch `\@hyper@ref` is set to true `\AtBeginDocument`, in case the user has loaded it manually. If `hyperref` is not loaded, `\texorpdfstring` is not defined. Since it could be still used in the document (if it was ever typeset with `hyperref` in mind), we provide a definition it here.

```

378 \AtBeginDocument{\@ifpackageloaded{hyperref}{%
379   \let\maketitle\HyOrg@maketitle
380   \@hyper@reftrue}{%
381   \@hyper@reffalse
382   \let\texorpdfstring\@firstoftwo}}

```

8.10 Packages and patches

`\patch` A difficult decision about the file extension for the patches. For one thing, `\usewithpatch` an automatic search mechanism required the file name to be the same as the package’s. But then extensions like `.clo` or `.def`, already in use by

L^AT_EX, could very well confuse `pittetd`, for it is possible that files called that way, but not designed for the class, are already installed in the system.

```

383 \newcommand*\patch[1]{\InputIfFileExists{#1.pit}{%
384     \ClassInfo{pittetd}{Patch for #1 loaded}}{%
385     \ClassInfo{pittetd}{No patch found for #1}}}
386 \newcommand*\usewithpatch[2][\@empty]{%
387     \ifx\@empty#1\usepackage{#2}\else\usepackage[#1]{#2}\fi%
388     \patch{#2}}
389 \@onlypreamble\patch

```

The patches for the `pittthesis` and `pittdiss` classes are given below (section 8.11.15), and serve as illustration.

8.11 Preliminaries

8.11.1 Commands for the information

`\title` First of all, `\title` has to be redefined for the optional argument, but `\author` remains the same (it `\gdef`'s `\@author` to its argument). However, standard-classes command `\thanks` is disabled here: it gobbles its argument and issues a warning.

```

390 \renewcommand*{\title}[2][\@empty]{%
391     \gdef\@title{#2}\ifx\@empty#1%
392     \gdef\@pdftitle{#2}%
393     \else\gdef\@pdftitle{#1}\fi}
394 \renewcommand{\thanks}[1]{\ClassWarning{pittetd}{%
395     The argument of \string\thanks\space has been ignored.}}

```

`\date` For master's theses the committee may be omitted. I conclude that everything concerning the defense may be omitted too. So, `pittetd` needs a way to know whether it should typeset the text 'It was approved' or not, which means scanning the `\date` to see if it is void. In any case, default value is `\today`.

```

396 \renewcommand*{\date}[1]{%
397     \sbox\@tempboxa{\normalfont #1}
398     \ifnum\wd\@tempboxa>0\global\@dategiventrue
399     \else\global\@dategivenfalse\fi
400     \gdef\@date{\ #1\ }}
401 \edef\today{\ifcase\month\or
402     January\or February\or March\or April\or May\or June\or
403     July\or August\or September\or October\or November\or
404     December\fi\space\number\day, \number\year}
405 \date{\today}

```

`\setyear` The year, on the contrary, must be present. Since it is not a standard L^AT_EX requirement, we provide for the user not having thought of it: it assumes the current year and makes sure to remember that it was not provided.

```
406 \edef\@year{\number\year}
407 \newcommand{\setyear}[1]{%
408     \gdef\@year{#1}\@yeargiventrue}
```

`\@degree` And there are many other commands that regular L^AT_EX never defined.

`\@school` They have to be kept from stopping the run, so we initialize some of values to produce a warning (or error, according to stage).

```
409 \newcommand\@degree{\@nolinemessage{No \string\degree\space
410     command}{It is required to list the author's previous
411     degree(s). Use the \string\degree\space (or \string\previousdegree\space command
412 \newcommand\@school{\@nolinemessage{No \string\school\space
413     command}{It is required to name the school (and
414     optionally the department). Use the \string\school\space
415     command.}}
416 \newcommand\@school{\relax}
```

`\degree` User's commands, if any, will override the previous definitions. `\previousdegree`

`\previousdegree` is useful in case `\degree` is assigned other meaning by a package.

```
417 \newcommand{\degree}[1]{\gdef\@degree{#1}}
418 \let\previousdegree\degree
```

`\school` `\school` defines one thing for the title page, another one for the committee page.

```
419 \newcommand\school[2][the]{\gdef\@school{#1\ #2}%
420     \gdef\@school{\uppercase{#2}}}
```

`\degreesought` Now the only information missing is the degree sought, already initialized, and 'Subject' and 'Keywords' for the Document Info dialog box.

`\keywords` The former is best implemented as a token register (the user fills it in if types `\subject{...}`). Both commands should be in the preamble, before `hyperref` builds up the Document Info.

```
421 \newcommand\degreesought[1]{\def\@degreesought{#1}}
422 \newtoks\subject
423 \def\@keywords{}
424 \newcommand\keywords[1]{\gdef\@keywords{#1}}
425 \@onlypreamble\subject
426 \@onlypreamble\keywords
```

8.11.2 The order

`\@enable` The mechanism by which `pittetd` checks that the preliminaries are in the

`\@disable` right order is the next: each preliminary 'disables' those that cannot be

placed afterwards, and ‘enables’ the one or more than can follow. ‘Disable’ and ‘enable’ mean ‘create the right warning/error:’

```

427 \newcommand\@enable[2]{%
428   \global\expandafter\let\csname @#1message\endcsname\relax
429   \global\@expectedprelim{#2}}
430 \newcommand\@disable[1]{%
431   \global\expandafter\def\csname @#1message\endcsname{%
432     \@linemessage{Something is missing or misplaced.
433       I was expecting \the\@expectedprelim}{%
434       The preliminaries should be placed in the next order:
435       \MessageBreak title, committee, [copyright],
436       abstract, [preface/foreword], tableofcontents,
437       [listoftables], [listoffigures], [listofalgorithms],
438       [listoflistings].\MessageBreak \MessageBreak
439       I think something is either missing or
440       misplaced in your document. I will typeset things in
441       the given order, but you should double-check.}}}

```

When something is ‘enabled,’ the ‘expected preliminary’ (used by `pittetd` when complaining) is changed (it’s the second argument to `\@enable`). Note that the enabled preliminaries and expected ones are not necessarily the same, because there are optional preliminaries.

`\@@disable` A second kind of ‘disable’ (`\@@disable`) is for lists of tables or figures with no tables or figures in it:

```

442 \newcommand\@@disable[2]{%
443   \global\expandafter\def\csname @#1message\endcsname{%
444     \@linemessage{There is no #2}{I have found no #2, so it
445     makes no sense to me to include a list of them.
446     Proceed, but expect an ugly heading followed by
447     nothing...}}}

```

So, each preliminary has (and executes) its own `\@...message` command, which is a complaint or a relaxation, according to the enable-status. To initialize these commands, we need to:

```

448 \@enable{title}{\maketitle}
449 \@disable{committee}
450 \@disable{copyright}
451 \@disable{abstract}
452 \@disable{preface}
453 \@disable{table}
454 \@disable{lof}
455 \@disable{lot}
456 \@disable{conv}

```

8.11.3 Bookmarking the preliminaries

Every preliminary is bookmarked by default. This is done by placing an `\hypertarget` and writing directly into the bookmark file, `\@outlinefile` (the bookmarks of figures and tables are discussed below). Option `nohyperref` turns this off, but in a round-about way: the test is not `\if@hyper@ref`, but `\@ifundefined{@outlinefile}`, because if no driver (`pdftex` or `dvipdfm`) is loaded by the user, `hyperref` will not create bookmarks anyway (it does not know which convention to use).

8.11.4 The title

`\maketitle`

```

457 \newcommand\maketitle{\@titlemessage
458   \if@dategiven
459     \if@yeargiven\else
460       \ClassWarningNoLine{pittetd}{%
461         I assumed '@year' for the year.
462         You can use \string\setyear\space to change it}%
463     \fi
464   \fi
465   \@ifundefined{@outlinefile}{}{%
466     \hypertarget{prelim.0}{}%
467     \protected@write\@outlinefile{}{%
468       \protect\BOOKMARK
469       [0] []{prelim.0}{TITLE PAGE}{}%
470     \thispagestyle{empty}%

```

I chose to ignore the ‘8 spaces’ kind of stuff. That is more suited for typewriters than for T_EX, and far less robust, for multiple-line things could cause the information to overflow the page if the directions are followed at face value. A large font is used, with an interline spacing of around ‘2 spaces,’ which is what the FG ask the most for in the title page. But for the ‘2 spaces’ from the the top, a `\vskip` is needed, and $1.3\@singleline$ is about right ($\@singleline \simeq 3s/2 \Rightarrow 4/3\@singleline \simeq 2s$)!

```

471   {\centering
472     \fontsize\@xviipt{1.5\@singleline}\selectfont
473     \null\vskip 1.3\@singleline
474     {\bfseries\uppercase\expandafter{\@title}}\par
475     \vfill
476     by\par
477     {\bfseries\@author}\par
478     {\let\noexpand\relax\@degree}\par
479     \vfill
480     Submitted to the Graduate Faculty of\par
481     \@school\ in partial fulfillment\par

```

```

482         of the requirements for the degree of\par
483         \@degreesought\par
484         \vfill
485         University of Pittsburgh\par
486         \@year\par}
487     \@enable{committee}{\makecommittee}

```

And, to save memory:

```

488     \global\let\thanks\relax
489     \global\let\maketitle\relax
490     \global\let\title\relax
491     \global\let\author\relax
492     \global\let\and\relax}

```

8.11.5 The committee page

`\@commline` The interesting thing here is the handling of committee members. First of `\@committee` all, the user shouldn't be asked to count the members—that sounds like a task for L^AT_EX—and, second, the advisor could be just the first member mentioned.

```

493 \def\@commline{\ifhmode\\else\relax\fi}
494 \def\committeemember#1{%
495     \stepcounter{@members}
496     \@committee\expandafter{\the\@committee#1\@commline}}

```

Thus the register `\@committee` is a list of members separated by `\@commline`. The latter expands into `\\` only when the list is actually typeset.

`\committeepage` Now for the actual page (which is typeset only if the user provided at least one `\committeemember`).

```

497 \newcommand\makecommittee{\clearpage\@committeemessage
498     \ifnum\value{@members}>0
499         \@ifundefined{@outlinefile}{}{%
500             \hypertarget{prelim.1}{}%
501             \protected@write\@outlinefile{}{%
502                 \protect\BOOKMARK
503                 [0] [] {prelim.1}{COMMITTEE MEMBERSHIP PAGE}{}%
504             \@committee\expandafter{\the\@committee\relax}%
505             {\centering
506             \normalsize\fontsize\fontsize{1.3\@singleline}\selectfont
507             \null\vskip 1.3\@singleline
508             UNIVERSITY OF PITTSBURGH\par
509             \@school\par
510             \vfill
511             This \lowercase\expandafter{\@this} was presented\\

```

```

512      by\\[.67\\@singleline]\\@author\\[.67\\@singleline]
513      \\if@dategiven
514          It was defended on\\
515          \\@date\\ \\else\\ClassWarningNoLine{pittetd}{\\%
516          You really should provide the date of the defense
517          (command \\string\\date)}\\fi
518      \\ifnum\\value{@members}>1
519          \\if@dategiven and \\else It was \\fi
520          approved by\\
521          \\the\\@committee

```

If more than one member is given, the advisor has yet to be found (the trick is done by \\@getadvisor, defined below). If not, and the document is a dissertation, pittetd complains.

```

522      \\expandafter\\@getadvisor\\the\\@committee
523      \\else
524          \\ifx\\t@or@d\\@phd\\@linemessage{Just one committee
525          member}{For Ph. D. dissertations, the whole committee
526          must be included. For the moment, I will typeset only
527          the advisor.}\\fi
528          \\vfill\\fi

```

However, support for two advisors has to be given.

```

529      \\@this\\ \\@advisor: \\the\\@committee\\the\\@coadv
530      \\vfill
531      \\newpage}
532      \\renewcommand\\committeemember[1]{\\ClassError{pittetd}{\\%
533      Command \\string\\committeemember\\space after
534      \\string\\makecommittee}{The new name will just be
535      ignored.}}
536      \\let\\makecommittee\\relax
537      \\else\\@linemessage{No members for the committee}{\\%
538      I will ignore the \\string\\makecommittee\\space command
539      until you give me some names.}
540      \\fi
541      \\@enable{copyright}{\\begin{abstract}}\\%
542      \\@enable{abstract}{\\begin{abstract}}

```

\\@getadvisor When \\@getadvisor is called, it is followed by the whole committee, names separated by \\@commline, and all followed by \\relax. Thus this command can take only the first name. Note that by the moment \\@getadvisor is called, the whole list of the committee has been typeset already, and that is why it can be redefined.

```

543 \\def\\@getadvisor#1\\@commline#2\\relax{\\@committee{#1}}

```

\\coadvisor The \\coadvisor command simply redefines \\@coadv (initially void) and \\@advisor.

```

544 \newcommand\coadvisor[1]{%
545   \renewcommand\@advisor{Advisors}%
546   \@coadv{,\@#1}}

```

8.11.6 Copyright page

\copyrightpage

```

547 \newcommand\copyrightpage{\clearpage\@copyrightmessage
548   \null\vfill
549   {\centering\normalsize Copyright
550     \textcopyright\ by \@author\\\@year\\}%
551   \vfill\newpage
552   \@enable{abstract}{\begin{abstract}}}

```

8.11.7 The abstract

The optional argument is the title for the list of Keywords. The construction has to be done through a switch \@keywordstrue because environment arguments can only be used for the opening part. pittetd appends a period to the list, if it is not already there.

```

553 \newenvironment{abstract}[1][\@empty]
554   {\ifx\@empty#1\else\@keywordstrue\def\@tempcsa{#1}\fi
555   \clearpage\@abstractmessage
556   \@afterindentfalse
557   \typeout{Abstract}%
558   \@ifundefined{@outlinefile}{\{}{\%
559     \hypertarget{prelim.2}{\}%
560     \protected@write\@outlinefile{\}%
561     \protect\BOOKMARK
562     [0][\{prelim.2\}{ABSTRACT}\}}
563   \null\nobreak\vskip 1in
564   {\centering\normalfont
565     {\bfseries\uppercase
566       \expandafter{\@title}}\@.3\@singleline]
567     \@author, \@@@degree\@.3\@singleline]
568     University of Pittsburgh, \@year\par}
569   \par\vspace{1\@singleline}\@afterheading}%
570   {\if@keywords
571     \medskip\begin{description}\item[\@tempcsa]\@keywords
572     {\normalsfcodes\ifnum\spacefactor=\sfcode'\.else.\fi}
573     \end{description}\fi
574   \@disable{copyright}%
575   \newpage\@enable{table}{\tableofcontents}}
576 \newenvironment{abstract*}[1][\@empty]
577   {\ifx\@empty#1\else\@keywordstrue\def\@tempcsa{#1}\fi
578   \clearpage\@abstractmessage

```



```

579 \afterindentfalse
580 \typeout{Abstract}%
581 \@ifundefined{@outlinefile}{}{%
582     \hypertarget{prelim.2}{}%
583     \protected@write\@outlinefile{}{%
584         \protect\BOOKMARK
585         [0] []{prelim.2}{ABSTRACT}{}}
586 \null\nobreak\vskip 1in
587 {\centering\normalfont
588     {\bfseries ABSTRACT}\[.3\@singleline]
589     \uppercase\expandafter{\@title}}\[.3\@singleline]
590     \@author, \@@@degree\[.3\@singleline]
591     University of Pittsburgh, \@year\par}
592 \par\vspace{1\@singleline}\@afterheading}%
593 {\if@keywords
594     \medskip\begin{description}\item[\@tempcsa]\@keywords
595     {\normalsfcodes\ifnum\spacefactor=\sfcode'\.else.\fi}
596     \end{description}\fi
597 \@disable{copyright}%
598 \newpage\@enable{table}{\tableofcontents}}

```

8.11.8 The table of contents

\tableofcontents

```

599 \newcommand\tableofcontents{\clearpage\@tablemessage
600     \typeout{Table of Contents}%
601     \@ifundefined{@outlinefile}{}{%
602         \hypertarget{prelim.4}{}%
603         \protected@write\@outlinefile{}{%
604             \protect\BOOKMARK
605             [0] []{prelim.4}{TABLE OF CONTENTS}{}}
606     }
607 \null\vskip 1in
608 {\normalfont\bfseries\centering
609     TABLE OF CONTENTS\par}
610 \par\vspace{54\p@}%
611 {\@withperiod\@withgobble\@starttoc{toc}}%
612 \if@tables
613     \@enable{lot}{\listoftables}%
614 \else
615     \@@disable{lot}{tables}
616     \if@figures
617         \@enable{lof}{\listoffigures}%
618     \else
619         \@@disable{lof}{figures}%
620         \@enable{preface}{the first chapter}%
621         \@enable{conv}{the first chapter}%
622     \fi

```

8.11.9 **Bookmarking tables and figures**

So far things have been at most challenging. But when it came to bookmarking the tables and figures, research and hard thinking had to be done. The main problem is that the location (within the bookmarks panel) of the bookmarks for tables and figures does not reflect their location in the document. So the immediate approach, modifying the `figure` and `table` environments to make them append a bookmark, does not work (the bookmarks would be appended in the current position of the panel). On the other hand, modifying those environments clearly invites incompatibilities, so it is only the last resource.

`\prepare@bookmarks` `hyperref` builds the bookmarks from information contained in the `.out` file. Each sectioning command, for example, appends a bookmark command to this file. So, the only way to get the bookmarks for floats in the right place is to make the `.out` file call another file where the table or figure bookmarks are compiled. At the beginning I thought that the figures and tables (actually, the `\caption` command) would append lines to these additional files. But that involved changing very basic `LATEX` commands, and also having to deal with different `hyperref` drivers. And, after all, the information would be basically the same as that already compiled in the `.lot` and `.lof` files. So, the point is to redefine the commands there included to interpret those files in terms of bookmarks. That is what `\prepare@bookmarks` does:

```

624 \def\prepare@bookmarks#1{%
625     \def\@prelim{#1}%
626     \def\numberline##1{##1. }
627     \let\\\relax
628     \def\contentsline##1##2##3##4{%
629         \pdfstringdef\@tempcsa{##2}%
630         \@expandedBOOKMARK{##4}{\@tempcsa}{prelim.\@prelim}}
631 \def\@expandedBOOKMARK#1#2{\edef\reserved@a{%
632     \noexpand\BOOKMARK[1][-]{#1}{#2}}\reserved@a}

```

The `\let`’ing of `\\` to `\relax` is a due to a subtlety with strong bug flavor. When `hyperref` is converting `TEX` strings into PDF ones, `\escapechar` is defined to be the `\` character, by means of `\escapechar‘\\`. But then, just before reading the bookmarks, `\escapechar` is `\let` to `\@gobble`. So `\escapechar‘\\` expands into `\@gobble‘\\`, which ultimately renders `\\`. `LATEX` then complains that “there is no line here to end.” On the other hand, `\@expandedBOOKMARK` is needed because otherwise `#2` (`\@tempcsa`) is not expanded.

But, after this tricky preparation (which of course has to take place within a group), the .out line can be instructed to read and interpret the .lot and .lof files.

8.11.10 The list of tables

`\listoftables`

```
633 \newcommand\listoftables{\clearpage\@lotmessage
634   \typeout{List of Tables}%
635   \@ifundefined{outlinefile}{}{%
636     \hypertarget{prelim.5}{}%
637     \protected@write\@outlinefile{}{%
638       \protect\BOOKMARK
639       [0] []{prelim.5}{LIST OF TABLES}{}%
```

Here:

```
640       \protect\beginngroup\protect\makeatletter
641       \protect\prepare@bookmarks5
642       \protect\@input{\jobname.lot}
643       \protect\endgroup}}
644   \null\vskip 1in
645   {\normalfont\bfseries\centering
646     LIST OF TABLES\par}
647   \par\vspace{54\p@}%
648   \@starttoc{lot}%
649   \newpage
650   \if@figures\@enable{lof}{\listoffigures}\else
651     \@enable{preface}{the first chapter}%
652     \@enable{conv}{the first chapter}%
653   \fi}
```

The width for the table numbers in the list depends on the widest float number (`\@float1`), which is calculated at the end of the job, and written in the .etd file. Here it is used:

```
654 \newcommand*\l@table{\@dottedtocline{1}{1.5em}{\@float1}}
```

8.11.11 The list of figures

`\listoffigures` This is analogous.

```
655 \newcommand\listoffigures{\clearpage\@lofmessage
656   \typeout{List of Figures}%
657   \@ifundefined{outlinefile}{}{%
658     \hypertarget{prelim.6}{}%
659     \protected@write\@outlinefile{}{%
660       \protect\BOOKMARK
```

```

661          [0] []{prelim.6}{LIST OF FIGURES}{}%
662          \protect\begin\group\protect\makeatletter
663          \protect\prepare@bookmarks6
664          \protect\@input{\jobname.lof}
665          \protect\end\group}}
666      \null\vskip 1in
667      {\normalfont\bfseries\centering
668       LIST OF FIGURES\par}
669      \par\vspace{54\p@}%
670      \@starttoc{lof}\newpage
671      \@enable{preface}{the first chapter}%
672      \@disable{lot}}
673 \let\l@figure\l@table

```

8.11.12 The list of listings and list of algorithms

`\listoflistings` This is analogous.

```

674 \newcommand\listoflistings{\clearpage
675   \typeout{List of Listings}%
676   \@ifundefined{@outlinefile}{\}%
677   \hypertarget{prelim.8}{\}%
678   \protected@write\@outlinefile{\}%
679   \protect\BOOKMARK
680   [0] []{prelim.8}{LIST OF LISTINGS}{}%
681   \protect\begin\group\protect\makeatletter
682   \protect\prepare@bookmarks8
683   \protect\@input{\jobname.lol}
684   \protect\end\group}}
685 \null\vskip 1in
686 {\normalfont\bfseries\centering
687  LIST OF LISTINGS\par}
688 \par\vspace{54\p@}%
689 \@starttoc{lol}\newpage
690 \@enable{preface}{the first chapter}}

```

`T` his is analogous.

```

691 \newcommand\listofalgorithms{\clearpage
692   \typeout{List of Algorithms}%
693   \@ifundefined{@outlinefile}{\}%
694   \hypertarget{prelim.9}{\}%
695   \protected@write\@outlinefile{\}%
696   \protect\BOOKMARK
697   [0] []{prelim.9}{LIST OF ALGORITHMS}{}%
698   \protect\begin\group\protect\makeatletter
699   \protect\prepare@bookmarks9
700   \protect\@input{\jobname.loa}
701   \protect\end\group}}

```

```

702 \null\vskip 1in
703 {\normalfont\bfseries\centering
704 LIST OF ALGORITHMS\par}
705 \par\vspace{54\p@}%
706 \@starttoc{loa}\newpage
707 \@enable{preface}{the first chapter}}
708 \let\l@algorithm\l@table

```

8.11.13 The preface

`\preface` The only difference with other preliminaries is that this makes it into the table of contents. `\addcontents` creates the bookmark automatically.

```

709 \newcommand\preface{%
710 \clearpage\@prefacemessage
711 \@afterindentfalse
712 \typeout{Preface}%
713 \phantomsection
714 \addcontentsline{toc}{chapter}{\bfseries PREFACE}
715 \null\vskip 1in
716 {\normalfont\bfseries\centering
717 PREFACE\par}
718 \par\vspace{1.5\@singleline}
719 \@enable{conv}{the first chapter}%
720 \@afterheading}

```

8.11.14 Additional preliminaries

`\preliminarychapter`

```

721 \newcommand\preliminarychapter[1]{%
722 \clearpage\@afterindentfalse
723 \typeout{#1}
724 \@ifundefined{@outlinefile}{\{%
725 \hypertarget{prelim.\the\c@addprel}{\}%
726 \protected@write\@outlinefile{\{%
727 \protect\BOOKMARK
728 [0] []{prelim.\the\c@addprel}{#1}{\}}
729 }%
730 \null\vskip 1in
731 {\normalfont\bfseries\centering
732 #1\par}
733 \par\vspace{1.5\@singleline}
734 \@afterheading}

```

8.11.15 Support for other Pitt classes

These two patches serve as an illustration of patches in general. The `\@ifundefined` line makes sure the patch is not loaded twice. Of course, the final `\let` is companion. `\makeatletter` and `\makeatother` are a needed security measure.

For `pittthesis`:

```
735 \</class>
736 \<*pittthesis>
737 \makeatletter
738 \@ifundefined{pittthesis@patch}{\relax}{\endinput}
739 \let\degrees\degree
740 \def\degree#1{\renewcommand\degreesought{#1}}
741 \let\university@gobble
742 \let\proposal@gobble
743 \let\advisor\committeemember
744 \let\coadvisor\committeemember
745 \newenvironment{acknowledgements}{%
746     \preliminarychapter{ACKNOWLEDGEMENTS}%
747     \@linemessage{Acknowledgments should be included in the
748     preface}{I'm complaining because this comes from the
749     'pittthesis' class. You haven't been reading my
750     warnings.}}{\relax}
751 \newenvironment{committeesignature}[1][5]{\relax}{\makecommittee}
752 \let\advisorname@gobble
753 \let\chairpersonname@gobble
754 \let\authortitle@gobble
755 \newenvironment{appendices}{\appendix}{\relax}
756 \newenvironment{singleappendix}{\appendix}{\relax}
757 \let\pittthesis@patch\@empty
758 \makeatother
759 \</pittthesis>
```

For `pittdiss`:

```
760 \<*pittdiss>
761 \makeatletter
762 \@ifundefined{pittdiss@patch}{\relax}\endinput
763 \let\disstitle\title
764 \let\dissauthor\author
765 \newcommand\diplomaone[1]{\gdef\@degree{#1}}
766 \newcommand\diplomatwo[1]{\xdef\@degree{%
767     \@degree\noexpand\noexpand
768     \noexpand\noexpand\noexpand\noexpand\noexpand\\#1}}
769 \newcommand\diplomathree[1]{\xdef\@degree{%
770     \@degree\noexpand\noexpand\noexpand\\#1}}
771 \newcommand\diplomafour[1]{\xdef\@degree{\@degree\noexpand\\#1}}
772 \let\university@gobble
773 \let\degree\degreesought
```

```

774 \let\degreeabr\@gobble
775 \let\disssyear\year
776 \newcommand\disssdate[1]{\date{#1, \@year}}
777 \let\doctype\@gobble
778 \newcommand\chair[1]{\@striptitle#1\relax}
779 \def\@striptitle#1:#2\relax{\committeemember{#2}}
780 \let\committeetwo\committeemember
781 \let\committeethree\committeemember
782 \let\committeefour\committeemember
783 \let\committeefive\committeemember
784 \let\committeesix\committeemember
785 \let\disstitlepage\maketitle
786 \let\committeepage\makecommittee
787 \newenvironment{nomenclature}{\preliminarychapter{NOMENCLATURE}}
788   \@linemessage{Nomenclature is not a recognized
789     preliminary.}{I'm complaining because this comes from the
790     'pittdiss' class. You haven't been reading my
791     warnings.}}{\relax}
792 \let\appendices\appendix
793 \let\pittdiss@patch\@empty
794 \makeatother
795 \</pittdiss>
796 \<*class>

```

8.12 Sectioning

`\@startsection` Section commands in the preliminaries create non-numbered divisions. This initial definition makes it happen:

```

797 \def\@startsection#1#2#3#4#5#6{%
798   \if@noskipsec \leavevmode \fi
799   \par
800   \@afterindentfalse
801   \@tempskipa #4\relax
802   \@tempskipa -\@tempskipa
803   \if@nobreak
804     \everypar{}%
805   \else
806     \addpenalty\@secpenalty\addvspace\@tempskipa
807   \fi
808   \@ifstar
809     {\ClassWarning{pittetd}{Starred
810       \expandafter\string\csname #1\endcsname*\space
811       has been treated as
812       \expandafter\string\csname #1\endcsname}%
813     \@ssect{#3}{#4}{#5}{#6}}%
814     {\@ssect{#3}{#4}{#5}{#6}}}

```

`\@startbody` When the first `\chapter` appears, it acts also as the starting point of the `\chapter`

body of the document: the page numbering is set to arabic, and sectioning commands are redefined.

```

815 \def\@startbody{%
816     \pagenumbering{arabic}%
817     \global\def\@startsection##1##2##3##4##5##6{%
818         \@getlength{##1}%
819         \if@noskipsec \leavevmode \fi
820         \par
821         \@afterindentfalse
822         \@tempskipa ##4\relax
823         \@tempskipa -\@tempskipa
824         \if@nobreak
825             \everypar{}%
826         \else
827             \addpenalty\@secpenalty\addvspace\@tempskipa
828         \fi
829         \ifstar
830             {\ClassWarning{pittetd}{Starred
831                 \expandafter\string\csname ##1\endcsname*\space
832                 has been treated as
833                 \expandafter\string\csname ##1\endcsname}%
834             \@dblarg{\@sect{##1}{##2}{##3}{##4}{##5}{##6}}}%
835             {\@dblarg{\@sect{##1}{##2}{##3}{##4}{##5}{##6}}}%
836     \renewcommand\chapter{\clearpage\global\@topnum\z@
837         \@afterindentfalse
838         \ifstar{%
839             \ClassWarning{pittetd}{Starred
840                 \string\chapter*\space has been treated as
841                 \string\chapter}%
842             \@dblarg{\@chapter}}{\@dblarg{\@chapter}}}%
843 \newcommand\chapter{\clearpage\@startbody\chapter}

```

8.12.1 Chapters and sections

`\@chapter` The actual chapters invoke `\@chapter`. The deferring construction with `\@@chapter` makes sure the chapter's title gets capitalized in the table of contents.

```

844 \def\@chapter[#1]#2{%
845     \refstepcounter{chapter}%
846     \@getlengthchapter
847     {\@withperiod\typeout{Chapter\space\thechapter}}%
848     \uppercase{\@@chapter{#1}}%
849     \null\vskip 1in
850     {\@withperiod\normalfont\bfseries\centering
851         \if@mainmatter\thechapter\if@secletters\else.0\fi\quad\fi
852         \uppercase\expandafter{#2}\par}
853     \par\vspace{2\@singleline}\@afterheading}

```



```

854 \def\@chapter#1{\addcontentsline{toc}{chapter}{\bfseries
855   \protect\numberline{\thechapter\if@secletters\else.0\fi}#1}}

```

\section The rest of sectioning commands invoke \@startsection. Note that all
\subsection \@withperiod's and \@withgobble's will be expanded inside a group.

```

\subsubsection
856 \newcommand\section{\@startsection{section}{1}%
857   {\z@}{-2\@singleline \@plus -1ex \@minus -.2ex}%
858   {1\@singleline \@plus .2ex}{\@withperiod\@withgobble%
859   \centering\normalfont\bfseries\expandafter\MakeUppercase}}
860 \newcommand\subsection{\@startsection{subsection}%
861   {2}{\z@}{-1\@singleline \@plus -1ex \@minus -.2ex}%
862   {.5\@singleline \@plus .2ex}%
863   {\@withperiod\@withgobble\normalfont\expandafter\bfseries}}
864 \newcommand\subsubsection{\@startsection{subsubsection}%
865   {3}{\z@}{-1\@singleline \@plus -1ex \@minus -.2ex}%
866   {-1em}{\@withperiod\@withgobble
867   \normalfont\expandafter\bfseries}}

```

The following are disabled:

```

868 \let\part\@gobble
869 \let\paragraph\@gobble
870 \let\subparagraph\@gobble

```

\@getlengthchapter Now, \chapter's and \...section's keep track of the widest numbers by
\@getlength means of the following commands:

```

871 \newcommand\@getlengthchapter{\begingroup\normalfont
872   \@withgobble\@withperiod
873   \settowidth\@tempskipa{%
874     {\bfseries\thechapter\if@secletters\else0\fi}\quad
875     \mbox{}}}%
876   \ifnum\@tempskipa > \@chapterl
877     \global\@chapterl =\@tempskipa
878   \fi
879 \endgroup}
880 \newcommand\@getlength[1]{\begingroup\normalfont
881   \@withgobble\@withperiod
882   \stepcounter{#1}%
883   \settowidth\@tempskipa{\csname the#1\endcsname.\ \mbox{}}}%
884   \ifnum\@tempskipa > \csname @#1\endcsname
885     \global\csname @#1\endcsname = \@tempskipa
886   \fi
887   \addtocounter{#1}{-1}
888 \endgroup}

```

8.12.2 Appendices

`\appendix` Only important thing: keeping track of the number of appendices, done `\@appendix` through `@appno`. Minor details: redefinition of `\@currentlabel` to make `\@@appendix` `\nameref` refer to ‘APPENDIX’ instead of the title; and redefinition of `\thefigure` and `\thetable` to omit period after the chapter number, in case `\chapterfloats` has been issued.

```

889 \newcommand\appendix{%
890   \@mainmatterfalse
891   \setcounter{chapter}{0}%
892   \setcounter{section}{0}%
893   \ifnum 2>\value{@appno}
894     \gdef\thechapter{%
895       \gdef\thesection{A.\@arabic{c@section}}%
896     \else
897       \gdef\thechapter{ \@Alph{c@chapter}}
898     \fi
899   \renewcommand\chapter{\clearpage\global\@topnum\z@
900     \@afterindentfalse
901     \protected@write\@auxout{%
902       {\string\stepcounter{\string @appno}}%
903     \@ifstar{%
904       \ClassWarning{pittetd}{Starred
905         \string\chapter*\space has been treated as
906         \string\chapter}%
907       \@dblarg{\@appendix}}{\@dblarg{\@appendix}}
908     \let\appendix\relax}
909 \def\@appendix[#1]#2{\refstepcounter{chapter}%
910   \xdef\@currentlabelname{\appendixname\thechapter}%
911   \typeout{Appendix\thechapter}%
912   \uppercase{\@appendix{#1}}%
913   \null\vskip 1in
914   {\normalfont\bfseries\centering
915     APPENDIX\thechapter\[\[2\@singleline]
916     \uppercase\expandafter{#2}\par}
917   \par\vspace{2\@singleline}\@afterheading}
918 \def\@@appendix#1{\addcontentsline{toc}{chapter}{%
919   {\bfseries APPENDIX\thechapter. #1}}}
```

There are no `\...matter` commands in `pittetd`.

```

920 \let\frontmatter\relax
921 \let\backmatter\relax
922 \let\mainmatter\relax
```

8.13 Floating objects

The two-column (starred) versions are implemented just for completeness. They might be used if the document is converted from other classes.

```
923 \def\fps@table{tbp}
924 \def\ftype@table{1}
925 \def\ext@table{lot}
926 \def\fnun@table{Table\nobreakspace\thetable}
927 \newenvironment{table}
928   {\global\@tablestrue
929     \spacespace\@float{table}}{%
```

The following is the main difference with standard classes: the widest label has to be tracked down. This could have been implemented as part of `\@makecaption`, instead of repeated four times here (in addition, there might be figures with no caption, and the test will still run). But I prefer to change here and not there, `\@makecaption` is probably redefined by many packages. `caption2` for one.

```
930   \end@float
931   \settowidth\@tempskipa{%
932     \thetable\ \mbox{}}}%
933   \ifnum\@tempskipa > \@floatl
934     \global\@floatl = \@tempskipa
935   \fi}
936 \newenvironment{table*}
937   {\global\@tablestrue
938     \spacespace\@dblfloat{table}}{%
```

```
939   \end@dblfloat
940   \settowidth\@tempskipa{%
941     \thetable\ \mbox{}}}%
942   \ifnum\@tempskipa > \@floatl
943     \global\@floatl = \@tempskipa
944   \fi}

945 \def\fps@figure{tbp}
946 \def\ftype@figure{1}
947 \def\ext@figure{lof}
948 \def\fnun@figure{Figure\nobreakspace\thefigure}
949 \newenvironment{figure}
950   {\global\@figurestrue
951     \spacespace\@float{figure}}{%
```

```
952   \end@float
953   \settowidth\@tempskipa{%
954     \thefigure\ \mbox{}}}%
955   \ifnum\@tempskipa > \@floatl
956     \global\@floatl = \@tempskipa
957   \fi}
958 \newenvironment{figure*}
```

```

959   {\global\@figurestrue
960     \spacespace\@dblfloat{figure}}{%
961     \end@dblfloat
962     \settowidth\@tempskipa{%
963       \thefigure\ \mbox{}}}%
964     \ifnum\@tempskipa > \@floatl
965       \global\@floatl = \@tempskipa
966     \fi}

```

`\@makecaption` This modified version of `\@makecaption` can be lost if some package redefines it, but it would not hurt much. Only the warning would be lost.

```

967 \def\@makecaption#1#2{%
968   \vskip\abovecaptionskip
969   \sbox\@tempboxa{#1: #2}%
970   \ifdim \wd\@tempboxa > \hsize
971     {\let\nobreakspace\space}%
972     #1: #2\par
973   \else
974     \global\@minipagefalse
975     \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
976   \fi
977   \vskip\belowcaptionskip}

```

8.14 Lists

```

978 \setlength\leftmargini\parindent
979 \leftmargin\leftmargini
980 \setlength\leftmarginii{2.2em}
981 \setlength\leftmarginiii{1.87em}
982 \setlength\leftmarginiv{1.7em}
983 \setlength\leftmarginv{1em}
984 \setlength\leftmarginvi{1em}
985 \setlength\labelsep{.5em}
986 \setlength\labelwidth{\leftmargini}
987 \addtolength\labelwidth{-\labelsep}
988 \setlength\partopsep{\@ptsize\p@ \@plus 1\p@ \@minus 1\p@}
989 \addtolength\partopsep{1.5\p@}
990 \@beginparpenalty -\@lowpenalty
991 \@endparpenalty -\@lowpenalty
992 \@itempenalty -\@lowpenalty

993 \def\@listi{\topsep\smallskipamount
994   \leftmargin\leftmargini
995   \parsep \z@ \@plus 2\p@
996   \itemsep \z@ \@plus 2\p@}
997 \let\@listI\@listi\@listi
998 \def\@listii{\leftmargin\leftmarginii
999   \labelwidth\leftmarginii
1000   \advance\labelwidth-\labelsep

```

```

1001 \topsep \z@ \@plus 2\p@
1002 \parsep \z@ \@plus\p@
1003 \itemsep \parsep}
1004 \def\@listiii{\leftmargin\leftmarginiii
1005 \labelwidth\leftmarginiii
1006 \advance\labelwidth-\labelsep
1007 \topsep \z@ \@plus\p@
1008 \parsep \z@
1009 \itemsep \topsep}
1010 \def\@listiv{\leftmargin\leftmarginiv
1011 \labelwidth\leftmarginiv
1012 \advance\labelwidth-\labelsep}
1013 \def\@listiv{\leftmargin\leftmarginiv
1014 \labelwidth\leftmarginiv
1015 \advance\labelwidth-\labelsep}
1016 \def\@listiv{\leftmargin\leftmarginiv
1017 \labelwidth\leftmarginiv
1018 \advance\labelwidth-\labelsep}

1019 \newcommand\labelenumi{\theenumi.}
1020 \newcommand\labelenumii{\theenumii.}
1021 \newcommand\labelenumiii{\theenumiii.}
1022 \newcommand\labelenumiv{\theenumiv.}

1023 \newcommand\labelitemi{\textbullet}
1024 \newcommand\labelitemii{\normalfont\bfseries\textendash}
1025 \newcommand\labelitemiii{\textasteriskcentered}
1026 \newcommand\labelitemiv{\textperiodcentered}

1027 \newenvironment{description}
1028 {\list{}{\labelwidth\z@ \itemindent-\leftmargin
1029 \let\makelabel\descriptionlabel}}
1030 {\endlist}
1031 \newcommand*\descriptionlabel[1]{%
1032 \hspace\labelsep\normalfont\bfseries #1}

```

8.15 Miscellaneous environments

```

1033 \newenvironment{verse}
1034 {\let\\@centercr
1035 \list{}{\itemsep \z@
1036 \itemindent -1.5em
1037 \listparindent\itemindent
1038 \rightmargin\leftmargin
1039 \advance\leftmargin 1.5em}
1040 \item\relax}
1041 {\endlist}

```

Since `quotation` and `quote` are redefined (against FG) by the `achicago` package, we must include the following definitions in the patch.

```

1042 \newenvironment{quotation}\relax\relax

```

```

1043 \newenvironment{quote}\relax\relax
1044 \end{class}
1045 \class{achicago}
1046 \renewenvironment{quotation}
1047   {\list{}{\topsep\medskipamount
1048     \listparindent 1.5em\relax
1049     \itemindent \listparindent
1050     \rightmargin \leftmargin
1051     \parsep \z@ \@plus\p@}
1052   \item\small\relax}
1053 {\endlist}
1054 \renewenvironment{quote}
1055   {\list{}{\topsep\medskipamount
1056     \rightmargin\leftmargin}%
1057   \item\relax\small}
1058 {\endlist}
1059 \end{class}
1060 \class{achicago}

```

8.16 Footnotes

```

1061 \renewcommand\footnoterule{%
1062   \kern-3\p@
1063   \hrule\@width.3\columnwidth
1064   \kern2.6\p@}
1065 \@addtoreset{footnote}{chapter}
1066 \newcommand\@makefnmark[1]{%
1067   \parindent 1em%
1068   \noindent
1069   \hb@xt@1.8em{\hss\@makefnmark}#1}

```

8.17 Bibliography

The `thebibliography` environment calls for `\@safebibliography`, which takes care of the heading, bookmark, spacing, etc.

```

1070 \newenvironment{thebibliography}[1]{%
1071   \@safebibliography
1072   \list{\@biblabel{\@arabic\c@enumiv}}%
1073   {\settowidth\labelwidth{\@biblabel{#1}}%
1074   \leftmargin\labelwidth
1075   \advance\leftmargin\labelsep
1076   \@openbib@code
1077   \usecounter{enumiv}%
1078   \let\p@enumiv\@empty
1079   \renewcommand\theenumiv{\@arabic\c@enumiv}}%
1080 \sloppy
1081 \clubpenalty4000
1082 \@clubpenalty \clubpenalty
1083 \widowpenalty4000%
1084 \sfcode'\.\@m}

```

```

1085 {\def\@noitemerr{\@latex@warning{Empty
1086 'thebibliography' environment}}}%
1087 \endlist}

```

`\@safebibliography` The spacing within entries is `\singlespacing`. Between entries, `\itemsep` applies.

```

1088 \newcommand\@safebibliography{%
1089   \renewcommand\chapter{\@ifstar{\@gobble}{\@gobble}}%
1090   \renewcommand\section{\@ifstar{\@gobble}{\@gobble}}%
1091   \renewcommand\@mkboth[2]{\relax}%
1092   \clearpage\null\vskip 1in
1093   \typeout{\bibname}%
1094   \@ifundefined{outlinefile}{}{\phantomsection}%
1095   \addcontentsline{toc}{chapter}{\bfseries\protect\bibname}}%
1096   {\normalfont\bfseries\centering\bibname\par}%
1097   \par\vspace{2\@singleline}%
1098   \singlespace
1099   \let\@listi\@listI
1100   \setlength{\itemsep}{.5\@singleline \@plus 4\p@}%
1101   \def\@listi{\topsep\z@
1102     \leftmargin\leftmarginI
1103     \parsep \z@ \@plus 2\p@
1104     \itemsep .5\@singleline \@plus 2\p@}
1105   \@afterheading
1106   \let\@safebibliography\relax}

```

`\safebibliography` `\@safebibliography` is also used by `\safebibliography`.

```

1107 \newcommand\safebibliography{\@safebibliography\bibliography}
1108 \newcommand\newblock{\hskip .11em\@plus.33em\@minus.07em}

```

The `natbib` package handles the spacing not with `\itemsep`, but with the new `\bibsep`. As far as I know, this is the only thing we need to make the package work, so it is done here rather than in a patch.

```

1109 \AtBeginDocument{\@ifundefined{bibsep}{}{%
1110   \setlength{\bibsep}{.5\@singleline \@plus 4\p@}}}

```

Support for the `achicago` package, on the contrary, goes to a patch:

```

1111 </class>
1112 <*achicago>
1113 \renewenvironment*{thebibliography}{%
1114   \@safebibliography
1115   \begin{list}{}{%
1116     \leftmargin\z@
1117     \advance\leftmargin\labelsep
1118     \advance\leftmargin\bibindent
1119     \itemindent -\bibindent

```

```

1120      \listparindent \itemindent
1121      \parsep \z@
1122      \itemsep .5\@singleline \@plus 4\p@}
1123      \sfcode'\.=\@m
1124      \let\@biblabel\Gobble
1125      \sloppy
1126      \clubpenalty4000 \widowpenalty4000
1127      }{%
1128      \def\@noitemerr{\@latex@warning{Empty
1129      'thebibliography' environment}}}%
1130      \relax\end{list}}
1131 \let\achicago@patch\@empty
1132 \makeatother
1133 </achicago>
1134 <*class>

```

8.17.1 The index

```

1135 \newenvironment{theindex}{%
1136   \clearpage\typeout{\indexname}%
1137   \@ifundefined{@outlinefile}{\phantomsection}%
1138   \addcontentsline{toc}{chapter}{\bfseries\protect\indexname}}%
1139   \twocolumn[\null\vskip 1in{\normalfont\bfseries\centering
1140     \indexname\par}\par\vspace{2\@singleline}}%
1141   \thispagestyle{plain}\parindent\z@
1142   \columnseprule \z@
1143   \columnsep 35\p@
1144   \parskip\z@ \@plus .3\p@\relax
1145   \small
1146   \let\item\@idxitem}
1147   {\clearpage}
1148 \newcommand\@idxitem{\par\hangindent 40\p@}
1149 \newcommand\subitem{\@idxitem \hspace*{20\p@}}
1150 \newcommand\subsubitem{\@idxitem \hspace*{30\p@}}
1151 \newcommand\indexspace{\par\vskip10\p@ \@plus5\p@ \@minus3\p@
1152   \relax}

```

8.18 The .etd file

The L^AT_EX run of the document has carefully taken note of certain values for the next run. It is now time to write them down in the .etd file.

```

1153 \AtEndDocument{\immediate\openout\@etdaux=\jobname.etd
1154   \if@tables
1155     \immediate\write\@etdaux{\string\@tablestrue}
1156   \fi
1157   \if@figures
1158     \immediate\write\@etdaux{\string\@figurestrue}
1159   \fi

```



```

1160 \immediate\write\@etdaux{%
1161   \string\setlength{\string\@chapterl}{\the\@chapterl}}
1162 \immediate\write\@etdaux{%
1163   \string\setlength{\string\@sectionl}{\the\@sectionl}}
1164 \immediate\write\@etdaux{%
1165   \string\setlength{\string\@subsectionl}{\the\@subsectionl}}
1166 \immediate\write\@etdaux{%
1167   \string\setlength{\string\@subsubsectionl}{\the\@subsubsectionl}}
1168 \immediate\write\@etdaux{%
1169   \string\setlength{\string\@floatl}{\the\@floatl}}
1170 \immediate\closeout\@etdaux}

```

And that is it.