

BERT GAWIN D

240701075

(CS23331)

Design and Analysis of  
Algorithms



6

N 2**Started on** Friday, 8 August 2025, 1:47 PM**State** Finished**Completed on** Friday, 8 August 2025, 1:51 PM**Time taken** 4 mins 13 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**For example:**

Input	Result
9	12

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int i=1,s=1,c=0;
7     while(s<=n)
8     {
9         c++;
10        i++;
11        c++;
12        s+=i;
13        c++;
14    }
15    printf("%d",c+3);
16 }
```

	Input	Expected	Got	
✓	9	12	12	✓

	Input	Expected	Got	
	4	9	9	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

**Started on** Friday, 8 August 2025, 1:32 PM

**State** Finished

**Completed on** Friday, 8 August 2025, 1:45 PM

**Time taken** 12 mins 42 secs

**Marks** 1.00/1.00

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 void func(int n)
3 {
4     int c=0;
5     if(n==1)
6     {
7         printf("*");
8         c++;
9         printf("*");
10        c++;
11        printf("*");
12        c++;
13    }
14    else
15    {
16        for(int i=1;i<5*n;i++)
17        {
18            c++;
19        }
20        c+=2;
21    }
22    printf("%d\n",c+1);
23 }
24 int main()
25 {
26     int n;
27     scanf("%d\n",&n);
28     func(n);
29 }
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	2	12	12	
	1000	5002	5002	
	143	717	717	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

---

**Started on** Friday, 8 August 2025, 1:45 PM

---

**State** Finished

---

**Completed on** Friday, 8 August 2025, 2:10 PM

---

**Time taken** 24 mins 26 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {  
    {  
        for (i = 1; i <= num; ++i)  
        {  
            if (num % i == 0)  
            {  
                printf("%d ", i);  
            }  
        }  
    }  
}
```

**Note:** No need of counter increment for declarations and scanf() and counter variable printf() statement.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Answer:**

```
1 #include<stdio.h>  
2 int main()  
3 {  
4     int n,c=0,j;  
5     scanf("%d",&n);  
6     for(int i=1;i<=n;i++)  
7     {  
8         if(n%i==0)  
9         {  
10             c++;  
11         }  
12     }  
13     j=(n*2)+c;  
14     printf("%d",j+1);  
15 }
```

	Input	Expected	Got	
	12	31	31	
	25	54	54	
	4	12	12	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

---

**Started on** Friday, 8 August 2025, 2:10 PM

---

**State** Finished

---

**Completed on** Friday, 8 August 2025, 2:25 PM

---

**Time taken** 14 mins 46 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c = 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Answer:**

```
1 #include <stdio.h>
2
3 int main() {
4     int n, i, j, k;
5     int counter = 0;
6
7     scanf("%d", &n);
8
9     for (i = n / 2; i < n; i++) {
10         counter++;
11
12         for (j = 1; j < n; j = 2 * j) {
13             counter++;
14
15             for (k = 1; k < n; k = k * 2) {
16                 counter++;
17                 counter++;
18             }
19
20             counter++;
21         }
22
23         counter++;
24     }
25
26     counter++;
27
28     printf("%d\n", counter+1);
29     return 0;
30 }
31 }
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>
--	--------------	-----------------	------------

Problem 4: Finding Complexity using Counter Method: Attempt review

<http://118.185.187.137/moodle/mod/quiz/review.php?attempt=226765...>

	Input	Expected	Got	
	4	30	30	
	10	212	212	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2****Started on** Friday, 8 August 2025, 2:25 PM**State** Finished**Completed on** Friday, 8 August 2025, 2:31 PM**Time taken** 5 mins 35 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Answer:**

```
1 #include <stdio.h>
2
3 int main() {
4     int n, rev = 0, remainder;
5     int counter = 0;
6
7     scanf("%d", &n);
8
9     while (n != 0) {
10         counter++;
11
12         remainder = n % 10;
13         counter++;
14
15         rev = rev * 10 + remainder;
16         counter++;
17
18         n /= 10;
19         counter++;
20     }
21     counter++;
22
23     printf("%d\n", counter+2);
24     return 0;
25 }
26 }
```

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Friday, 19 September 2025, 1:44 PM

---

**State** Finished

---

**Completed on** Friday, 19 September 2025, 1:46 PM

---

**Time taken** 1 min 56 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00**Problem Statement**

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

**Input Format**

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

**Output Format**

First Line Contains Integer – Number of zeroes present in the given array.

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int countZeroes(int arr[], int left, int right, int n) {
4     if (left > right)
5         return 0;
6
7     int mid = (left + right) / 2;
8
9     if (arr[mid] == 0 && (mid == 0 || arr[mid - 1] == 1)) {
10        return n - mid;
11    }
12
13    if (arr[mid] == 1) {
14        return countZeroes(arr, mid + 1, right, n);
15    } else {
16        return countZeroes(arr, left, mid - 1, n);
17    }
18}
19
20 int main() {
21     int m;
22     scanf("%d", &m);
23
24     int arr[m];
25     for (int i = 0; i < m; i++) {
26         scanf("%d", &arr[i]);
27     }
28
29     int result = countZeroes(arr, 0, m - 1, m);
30     printf("%d\n", result);
31
32     return 0;
33 }
```

	Input	Expected	Got	
✓	5	2	2	✓
	1			
	1			
	1			
	0			
	0			

## 1-Number of Zeros in a Given Array: Attempt review

<http://118.185.187.137/moodle/mod/quiz/review.php?attempt=247386...>

	Input	Expected	Got	
	10 1 1 1 1 1 1 1 1 1	0	0	
	8 0 0 0 0 0 0 0 0 0	8	8	
	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Friday, 19 September 2025, 1:46 PM

---

**State** Finished

---

**Completed on** Friday, 19 September 2025, 1:47 PM

---

**Time taken** 29 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than  $\lfloor n / 2 \rfloor$  times. You may assume that the majority element always exists in the array.

**Example 1:**

**Input:** `nums = [3,2,3]`

**Output:** 3

**Example 2:**

**Input:** `nums = [2,2,1,1,1,2,2]`

**Output:** 2

**Constraints:**

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

**For example:**

Input	Result
3	3
3 2 3	
7	2
2 2 1 1 1 2 2	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int majorityElement(int* nums, int n) {
4     int candidate = nums[0], count = 1;
5     for (int i = 1; i < n; i++) {
6         if (nums[i] == candidate) {
7             count++;
8         } else {
9             count--;
10        if (count == 0) {
11            candidate = nums[i];
12            count = 1;
13        }
14    }
15    return candidate;
16}
17
18
19 int main() {
20     int n;
21     scanf("%d", &n);
22     int nums[n];
23     for (int i = 0; i < n; i++) {
24         scanf("%d", &nums[i]);
25     }
26     int result = majorityElement(nums, n);
27     printf("%d\n", result);
28     return 0;

```

	Input	Expected	Got	
	3	3	3	
	3 2 3			

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Friday, 19 September 2025, 1:47 PM

---

**State** Finished

---

**Completed on** Friday, 19 September 2025, 1:50 PM

---

**Time taken** 2 mins 47 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00**Problem Statement:**

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

**Input Format**

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

**Output Format**

First Line Contains Integer – Floor value for x

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int floorSearch(int arr[], int left, int right, int x) {
4     if (left > right)
5         return -1;
6     if (x >= arr[right])
7         return arr[right];
8     int mid = (left + right) / 2;
9     if (arr[mid] == x)
10        return arr[mid];
11    if (mid > 0 && arr[mid - 1] <= x && x < arr[mid])
12        return arr[mid - 1];
13    if (x < arr[mid])
14        return floorSearch(arr, left, mid - 1, x);
15    return floorSearch(arr, mid + 1, right, x);
16 }
17
18 int main() {
19     int n, x;
20     scanf("%d", &n);
21     int arr[n];
22     for (int i = 0; i < n; i++) {
23         scanf("%d", &arr[i]);
24     }
25     scanf("%d", &x);
26     int result = floorSearch(arr, 0, n - 1, x);
27     printf("%d\n", result);
28     return 0;
29 }
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
✓	6	2	2	✓
	1			
	2			
	8			
	10			
	12			
	19			
	5			

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	5	85	85	
	10			
	22			
	85			
	108			
	129			
	100			
	7	9	9	
	3			
	5			
	7			
	9			
	11			
	13			
	15			
	10			

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

**Started on** Friday, 19 September 2025, 1:50 PM

**State** Finished

**Completed on** Friday, 19 September 2025, 1:51 PM

**Time taken** 29 secs

**Marks** 1.00/1.00

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00**Problem Statement:**

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

**Input Format**

First Line Contains Integer n - Size of array

Next n lines Contains n numbers - Elements of an array

Last Line Contains Integer x - Sum Value

**Output Format**

First Line Contains Integer - Element1

Second Line Contains Integer - Element2 (Element 1 and Elements 2 together sums to value "x")

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int findPair(int arr[], int left, int right, int x, int *a, int *b) {
4     if (left >= right)
5         return 0;
6     int sum = arr[left] + arr[right];
7     if (sum == x) {
8         *a = arr[left];
9         *b = arr[right];
10    return 1;
11 } else if (sum > x) {
12    return findPair(arr, left, right - 1, x, a, b);
13 } else {
14    return findPair(arr, left + 1, right, x, a, b);
15 }
16 }
17
18 int main() {
19     int n, x;
20     scanf("%d", &n);
21     int arr[n];
22     for (int i = 0; i < n; i++)
23         scanf("%d", &arr[i]);
24     scanf("%d", &x);
25     int a, b;
26     if (findPair(arr, 0, n - 1, x, &a, &b)) {
27         printf("%d\n%d\n", a, b);
28     } else {
29         printf("No\n");
30     }
31     return 0;
32 }
33

```

	Input	Expected	Got	
✓	4	4	4	✓
	2	10	10	
	4			
	8			
	10			
	14			

	Input	Expected	Got	
	5	No	No	
	2			
	4			
	6			
	8			
	10			
	100			

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2****Started on** Friday, 19 September 2025, 1:51 PM**State** Finished**Completed on** Friday, 19 September 2025, 1:51 PM**Time taken** 31 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n

The next n lines contain the elements.

Output:

Sorted list of elements

**For example:**

Input	Result
5	12 34 67 78 98
67 34 12 98 78	

**Answer:**

```

1 #include <stdio.h>
2
3 void swap(int *a, int *b) {
4     int t = *a;
5     *a = *b;
6     *b = t;
7 }
8
9 int partition(int arr[], int low, int high) {
10    int pivot = arr[high];
11    int i = low - 1;
12    for (int j = low; j < high; j++) {
13        if (arr[j] <= pivot) {
14            i++;
15            swap(&arr[i], &arr[j]);
16        }
17    }
18    swap(&arr[i + 1], &arr[high]);
19    return i + 1;
20 }
21
22 void quickSort(int arr[], int low, int high) {
23    if (low < high) {
24        int pi = partition(arr, low, high);
25        quickSort(arr, low, pi - 1);
26        quickSort(arr, pi + 1, high);
27    }
28 }
29
30 int main() {
31    int n;
32    scanf("%d", &n);
33    int arr[n];
34    for (int i = 0; i < n; i++)
35        scanf("%d", &arr[i]);
36    quickSort(arr, 0, n - 1);
37    for (int i = 0; i < n; i++)
38        printf("%d ", arr[i]);
39    return 0;
40 }
41

```

Input	Expected	Got	
5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	
10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	
12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 24 August 2025, 6:43 PM**State** Finished

---

**Completed on** Sunday, 24 August 2025, 6:44 PM**Time taken** 1 min 12 secs**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanation:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int main() {
4     int V;
5     scanf("%d", &V);
6
7     int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
8     int n = sizeof(denominations) / sizeof(denominations[0]);
9
10    int count = 0;
11    for (int i = 0; i < n; i++) {
12        if (V >= denominations[i]) {
13            count += V / denominations[i];
14            V = V % denominations[i];
15        }
16    }
17
18    printf("%d\n", count);
19
20    return 0;
21}
22

```

	Input	Expected	Got	
✓	49	5	5	✓

Passed all tests! ✓

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

**Started on** Sunday, 24 August 2025, 6:44 PM

**State** Finished

**Completed on** Sunday, 24 August 2025, 6:46 PM

**Time taken** 1 min 10 secs

**Marks** 1.00/1.00

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child  $i$  has a greed factor  $g[i]$ , which is the minimum size of a cookie that the child will be content with; and each cookie  $j$  has a size  $s[j]$ . If  $s[j] \geq g[i]$ , we can assign the cookie  $j$  to the child  $i$ , and the child  $i$  will be content. Your goal is to maximize the number of your content children and output the maximum number.

**Example 1:****Input:**

```
3
1 2 3
2
1 1
```

**Output:**

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

**Constraints:**

$1 \leq g.length \leq 3 * 10^4$

$0 \leq s.length \leq 3 * 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 // Comparator function for qsort
5 int cmp(const void *a, const void *b) {
6     return (*(int*)a - *(int*)b);
7 }
8
9 int main() {
10     int n, m;
11     scanf("%d", &n);
12
13     int g[n];
14     for (int i = 0; i < n; i++) scanf("%d", &g[i]);
15
16     scanf("%d", &m);
17     int s[m];
18     for (int j = 0; j < m; j++) scanf("%d", &s[j]);
19
20     // Sort both arrays
21     qsort(g, n, sizeof(int), cmp);
22     qsort(s, m, sizeof(int), cmp);
23
24     int i = 0, j = 0, content = 0;
25
26     // Greedy allocation
27     while (i < n && j < m) {
28         if (s[j] >= g[i]) {
29             content++;
30             i++;
31             j++;
32         }
33     }
34 }
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	2	2	2	
	1 2			
	3			
	1 2 3			

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 31 August 2025, 11:23 AM

---

**State** Finished

---

**Completed on** Sunday, 31 August 2025, 11:41 AM

---

**Time taken** 17 mins 48 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten  $i$  burgers with  $c$  calories each, then he has to run at least  $3^i * c$  kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are  $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$ .

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm. Apply greedy approach to solve the problem.

**Input Format**

First Line contains the number of burgers

Second line contains calories of each burger which is  $n$  space-separate integers

**Output Format**

Print: Minimum number of kilometers needed to run to burn out the calories

**Sample Input**

```
3
5 10 7
```

**Sample Output**

```
76
```

**For example:**

Test	Input	Result
Test Case 1	3 1 3 2	18

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int power(int a, int b) {
4     int c = 1;
5     for (int i = 0; i < b; i++)
6         c *= a;
7     return c;
8 }
9
10 int main() {
11     int n, total = 0;
12     scanf("%d", &n);
13     int c[n];
14
15     for (int i = 0; i < n; i++) {
16         scanf("%d", &c[i]);
17     }
18
19     for (int i = 0; i < n; i++) {
20         for (int j = 0; j < n - 1; j++) {
21             if (c[j] < c[j + 1]) {
22                 int t = c[j];

```

	<b>Test</b>	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	Test Case 1	3 1 3 2	18	18	
	Test Case 2	4 7 4 9 6	389	389	
	Test Case 3	3 5 10 7	76	76	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



RAJALAKSHMI  
ENGINEERING  
COLLEGE

6

N 2

**Started on** Sunday, 24 August 2025, 6:48 PM

**State** Finished

**Completed on** Sunday, 24 August 2025, 6:48 PM

**Time taken** 46 secs

**Marks** 1.00/1.00

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of  $\text{arr}[i] * i$ , where  $i$  is the index of the element ( $i = 0, 1, 2, \dots, N$ ). Write an algorithm based on Greedy technique with a Complexity  $O(n\log n)$ .

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3
4
5 int cmp(const void *a, const void *b) {
6     return (*(int*)a - *(int*)b);
7 }
8
9 int main() {
10    int n;
11    scanf("%d", &n);
12
13    int arr[n];
14    for (int i = 0; i < n; i++) {
15        scanf("%d", &arr[i]);
16    }
17
18
19    qsort(arr, n, sizeof(int), cmp);
20
21    long long result = 0;
22    for (int i = 0; i < n; i++) {
23        result += (long long)arr[i] * i;
24    }
25
26    printf("%lld\n", result);
27    return 0;
28 }
```

	Input	Expected	Got	
✓	5	40	40	✓
	2			
	5			
	3			
	4			
	0			

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	10 2 2 2 4 4 3 3 5 5 5	191	191	
	2 45 3	45	45	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 24 August 2025, 6:49 PM

---

**State** Finished

---

**Completed on** Sunday, 24 August 2025, 6:49 PM

---

**Time taken** 46 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given two arrays array\_One[] and array\_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is SUM (A[i] \* B[i]) for all i is minimum.

**For example:**

Input	Result
3	28
1	
2	
3	
4	
5	
6	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3
4
5 int asc(const void *a, const void *b) {
6     return (*(int*)a - *(int*)b);
7 }
8
9
10 int desc(const void *a, const void *b) {
11     return (*(int*)b - *(int*)a);
12 }
13
14 int main() {
15     int n;
16     scanf("%d", &n);
17
18     int arr1[n], arr2[n];
19     for (int i = 0; i < n; i++) scanf("%d", &arr1[i]);
20     for (int i = 0; i < n; i++) scanf("%d", &arr2[i]);
21
22
23     qsort(arr1, n, sizeof(int), asc);
24     qsort(arr2, n, sizeof(int), desc);
25
26     long long sum = 0;
27     for (int i = 0; i < n; i++) {
28         sum += (long long)arr1[i] * arr2[i];
29     }
30
31     printf("%lld\n", sum);
32     return 0;
33 }
34

```

	Input	Expected	Got

Input	Expected	Got	
3 1 2 3 4 5 6	28	28	
4 7 5 1 2 1 3 4 1	22	22	
5 20 10 30 10 40 8 9 4 3 10	590	590	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



RAJALAKSHMI  
ENGINEERING  
COLLEGE

6

N 2

**Started on** Sunday, 12 October 2025, 11:17 AM

**State** Finished

**Completed on** Sunday, 12 October 2025, 11:19 AM

**Time taken** 1 min 36 secs

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 10.00 out of 10.00

### Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3. Write any efficient algorithm to find the possible ways.

#### Example 1:

**Input:** 6

**Output:** 6

**Explanation:** There are 6 ways to represent number with 1 and 3

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

#### Input Format

First Line contains the number n

#### Output Format

**Print:** The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 long long countWays(int n) {
4     if (n < 0)
5         return 0;
6     if (n == 0)
7         return 1;
8
9     long long dp[n + 1];
10    dp[0] = 1; // One way to make 0
11
12    for (int i = 1; i <= n; i++) {
13        dp[i] = dp[i - 1]; // using 1
14        if (i >= 3)
15            dp[i] += dp[i - 3]; // using 3
16    }
17
18    return dp[n];
19 }
20
21 int main() {
22     int n;
23     scanf("%d", &n);
24     printf("%lld\n", countWays(n)); // use %lld for long long
25     return 0;
26 }
27

```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	6	6	6	
	25	8641	8641	
	100	24382819596721629	24382819596721629	

Passed all tests!

**Correct**

Marks for this submission: 10.00/10.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 12 October 2025, 11:19 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:20 AM

---

**Time taken** 53 secs

---

**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 10.00 out of 10.00**Playing with Chessboard:**

Ram is given with an  $n \times n$  chessboard with each cell with a monetary value. Ram stands at the  $(0,0)$ , that the position of the top left white rook. He is been given a task to reach the bottom right black rook position  $(n-1, n-1)$  constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

**Example:****Input**

```
3
1 2 4
2 3 4
8 7 1
```

**Output:**

```
19
```

**Explanation:**

Totally there will be 6 paths among that the optimal is

Optimal path value:  $1+2+8+7+1=19$

**Input Format**

First Line contains the integer  $n$

The next  $n$  lines contain the  $n \times n$  chessboard values

**Output Format**

Print Maximum monetary value of the path

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 #define MAX 100 // maximum board size
4
5 int main() {
6     int n;
7     int board[MAX][MAX];
8     long long dp[MAX][MAX];
9
10    scanf("%d", &n);
11
12    // Input the chessboard values
13    for (int i = 0; i < n; i++) {
14        for (int j = 0; j < n; j++) {
15            scanf("%d", &board[i][j]);
16        }
17    }
18
19    // Base case
20    dp[0][0] = board[0][0];
21
22    // Fill first row
23    for (int j = 1; j < n; j++) {
24        dp[0][j] = dp[0][j - 1] + board[0][j];
25    }
26
27    // Fill first column
28    for (int i = 1; i < n; i++) {
29        dp[i][0] = dp[i - 1][0] + board[i][0];
30    }
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	3 1 2 4 2 3 4 8 7 1	19	19	
	3 1 3 1 1 5 1 4 2 1	12	12	
	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	

Passed all tests!

**Correct**

Marks for this submission: 10.00/10.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 12 October 2025, 11:20 AM**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:21 AM**Time taken** 52 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	<b>g</b>	<b>t</b>	a	<b>b</b>	
s2	<b>g</b>	x	<b>t</b>	x	a	y	<b>b</b>

**The length is 4**

Solving it using Dynamic Programming

For example:

Input	Result
aab	2
azb	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 #include <string.h>
3
4 int max(int a, int b) {
5     return (a > b) ? a : b;
6 }
7
8 int main() {
9     char s1[100], s2[100];
10    scanf("%s %s", s1, s2);
11    int n = strlen(s1), m = strlen(s2);
12    int dp[n + 1][m + 1];
13    for (int i = 0; i <= n; i++) {
14        for (int j = 0; j <= m; j++) {
15            if (i == 0 || j == 0)
16                dp[i][j] = 0;
17            else if (s1[i - 1] == s2[j - 1])
18                dp[i][j] = dp[i - 1][j - 1] + 1;
19            else
20                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
21        }
22    }
23    printf("%d\n", dp[n][m]);
24    return 0;
25 }
26

```

	Input	Expected	Got	
✓	aab	2	2	✓
	azb			

	Input	Expected	Got	
	ABCD	4	4	
	ABCD			

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



---

**Started on** Sunday, 12 October 2025, 11:21 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:23 AM

---

**Time taken** 1 min 13 secs

---

**Marks** 1.00/1.00

---

**Grade** 10.00 out of 10.00 (100%)

1 of 2

4-DP-Longest non-decreasing Subsequence: Attempt review

<http://118.185.187.137/moodle/mod/quiz/review.php?attempt=261274...>

**Question 1** | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int max(int a, int b) {
4     return (a > b) ? a : b;
5 }
6
7 int main() {
8     int n;
9     scanf("%d", &n);
10    int arr[n], dp[n], ans = 1;
11    for (int i = 0; i < n; i++)
12        scanf("%d", &arr[i]);
13    for (int i = 0; i < n; i++) {
14        dp[i] = 1;
15        for (int j = 0; j < i; j++) {
16            if (arr[i] >= arr[j])
17                dp[i] = max(dp[i], dp[j] + 1);
18        }
19        ans = max(ans, dp[i]);
20    }
21    printf("%d\n", ans);
22    return 0;
23 }
```

	Input	Expected	Got	
✓	9 -1 3 4 5 2 2 2 2 3	6	6	✓
✓	7 1 2 2 4 5 7 6	6	6	✓

Passed all tests! ✓

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)





6

N 2

---

**Started on** Sunday, 12 October 2025, 11:23 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:27 AM

---

**Time taken** 4 mins 9 secs

---

**Marks** 1.00/1.00

---

**Grade** 4.00 out of 4.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

**For example:**

Input	Result
5	1
1 1 2 3 4	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int main() {
4     int n;
5     scanf("%d", &n);
6     int arr[n];
7     for (int i = 0; i < n; i++)
8         scanf("%d", &arr[i]);
9     for (int i = 0; i < n; i++) {
10        for (int j = i + 1; j < n; j++) {
11            if (arr[i] == arr[j]) {
12                printf("%d\n", arr[i]);
13                return 0;
14            }
15        }
16    }
17    return 0;
18 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

**N 2**

---

**Started on** Sunday, 12 October 2025, 11:27 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:28 AM

---

**Time taken** 33 secs

---

**Marks** 1.00/1.00

---

**Grade** 4.00 out of 4.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

**For example:**

Input	Result
5	1
1 1 2 3 4	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int main() {
4     int n;
5     scanf("%d", &n);
6     int arr[n];
7     for (int i = 0; i < n; i++)
8         scanf("%d", &arr[i]);
9     for (int i = 0; i < n; i++) {
10        for (int j = i + 1; j < n; j++) {
11            if (arr[i] == arr[j]) {
12                printf("%d\n", arr[i]);
13                return 0;
14            }
15        }
16    }
17    return 0;
18 }
19

```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

**Started on** Sunday, 12 October 2025, 11:28 AM

**State** Finished

**Completed on** Sunday, 12 October 2025, 11:29 AM

**Time taken** 49 secs

**Marks** 1.00/1.00

**Grade** 30.00 out of 30.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

**Input Format**

- The first line contains T, the number of test cases. Following T lines contain:

- Line 1 contains N1, followed by N1 integers of the first array
- Line 2 contains N2, followed by N2 integers of the second array

**Output Format**

The intersection of the arrays in a single line

**Example**

**Input:**

```
1
3 10 17 57
6 2 7 10 15 57 246
```

**Output:**

```
10 57
```

**Input:**

```
1
6 1 2 3 4 5 6
2 1 6
```

**Output:**

```
1 6
```

**For example:**

Input	Result
1	10 57
3 10 17 57	
6	
2 7 10 15 57 246	

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int main() {
4     int T;
5     scanf("%d", &T);
6     while (T--) {
7         int n1, n2;
8         scanf("%d", &n1);
9         int a[n1];
10        for (int i = 0; i < n1; i++)
11            scanf("%d", &a[i]);
12        scanf("%d", &n2);
13        int b[n2];
14        for (int i = 0; i < n2; i++)
15            scanf("%d", &b[i]);
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	
	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

---

**Started on** Sunday, 12 October 2025, 11:29 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:30 AM

---

**Time taken** 37 secs

---

**Marks** 1.00/1.00

---

**Grade** 30.00 out of 30.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

**Input Format**

- The first line contains T, the number of test cases. Following T lines contain:

- Line 1 contains N1, followed by N1 integers of the first array
- Line 2 contains N2, followed by N2 integers of the second array

**Output Format**

The intersection of the arrays in a single line

**Example**

**Input:**

```
1
3 10 17 57
6 2 7 10 15 57 246
```

**Output:**

```
10 57
```

**Input:**

```
1
6 1 2 3 4 5 6
2 1 6
```

**Output:**

```
1 6
```

**For example:**

Input	Result
1	10 57
3 10 17 57	
6	
2 7 10 15 57 246	

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int main() {
4     int T;
5     scanf("%d", &T);
6     while (T--) {
7         int n1, n2;
8         scanf("%d", &n1);
9         int a[n1];
10        for (int i = 0; i < n1; i++)
11            scanf("%d", &a[i]);
12        scanf("%d", &n2);
13        int b[n2];
14        for (int i = 0; i < n2; i++)
15            scanf("%d", &b[i]);
```

	<b>Input</b>	<b>Expected</b>	<b>Got</b>	
	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	
	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

---

**Started on** Sunday, 12 October 2025, 11:30 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:31 AM

---

**Time taken** 38 secs

---

**Marks** 1.00/1.00

---

**Grade** 4.00 out of 4.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that  $A[j] - A[i] = k$ ,  $i \neq j$ .

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as  $5 - 1 = 4$

So Return 1.

**For example:**

Input	Result
3	1
1 3 5	
4	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int main() {
4     int n, k;
5     scanf("%d", &n);
6     int a[n];
7     for (int i = 0; i < n; i++)
8         scanf("%d", &a[i]);
9     scanf("%d", &k);
10
11    int i = 0, j = 1;
12    while (i < n && j < n) {
13        if (i != j && a[j] - a[i] == k) {
14            printf("1\n");
15            return 0;
16        } else if (a[j] - a[i] < k) {
17            j++;
18        } else {
19            i++;
20        }
21    }
22    printf("0\n");
23    return 0;
24 }
25

```

Input	Expected	Got

Input	Expected	Got	
3 1 3 5 4	1	1	
10 1 4 6 8 12 14 15 20 21 25 1	1	1	
10 1 2 3 5 11 14 16 24 28 29 0	0	0	
10 0 2 3 7 13 14 15 20 24 25 10	1	1	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)



6

N 2

---

**Started on** Sunday, 12 October 2025, 11:31 AM

---

**State** Finished

---

**Completed on** Sunday, 12 October 2025, 11:31 AM

---

**Time taken** 26 secs

---

**Marks** 1.00/1.00

---

**Grade** 4.00 out of 4.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that  $A[j] - A[i] = k$ ,  $i \neq j$ .

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as  $5 - 1 = 4$

So Return 1.

**For example:**

Input	Result
3	1
1 3 5	
4	

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 int main() {
4     int n, k;
5     scanf("%d", &n);
6     int a[n];
7     for (int i = 0; i < n; i++)
8         scanf("%d", &a[i]);
9     scanf("%d", &k);
10
11    int i = 0, j = 1;
12    while (i < n && j < n) {
13        if (i != j && a[j] - a[i] == k) {
14            printf("1\n");
15            return 0;
16        } else if (a[j] - a[i] < k) {
17            j++;
18        } else {
19            i++;
20        }
21    }
22    printf("0\n");
23    return 0;
24 }
25

```

Input	Expected	Got

6-Pair with Difference -O(n) Time Complexity,O(1) Space Complexity....

[http://118.185.187.137/moodle/mod/quiz/review.php?attempt=261284...](http://118.185.187.137/moodle/mod/quiz/review.php?attempt=261284)

Input	Expected	Got	
3 1 3 5 4	1	1	
10 1 4 6 8 12 14 15 20 21 25 1	1	1	
10 1 2 3 5 11 14 16 24 28 29 0	0	0	
10 0 2 3 7 13 14 15 20 24 25 10	1	1	

Passed all tests!

**Correct**

Marks for this submission: 1.00/1.00.

[Back to Course](#)