### The Analyst's Guide To:


# Identifying and Fixing Performance Anti-Patterns

















### **Patterns**

### **Anti-Patterns**





FlooringSupplies.co.uk

Chris Maluszynski / MOMENT







### **Bottlenecks**









## **Bert Wagner**

- Developer
- YouTuber and Blogger
- https://BertWagner.com
- bert@bertwagner.com
- Slides: bertwagner.com/anti-patterns















### 5 Performance Anti-Patterns

(and how to fix them)













```
FROM

dbo.Customers

WHERE


Id IN (1,2,3,...)
```


























```
CREATE TABLE ##EligibleCustomers;
-- bulk insert OR use your tool of choice
BULK INSERT ##EligibleCustomers FROM 'C:\EligibleCustomers.csv'
CREATE CLUSTERED INDEX CL Id
    ON ##EligibleCustomers (Id);
CREATE NONCLUSTERED INDEX IX_PurchaseDate
    ON ##EligibleCustomers(PurchaseDate) INCLUDE (FullName);
SELECT
FROM
    dbo.Customers c
    INNER JOIN ##EligibleCustomers ec
        ON c.Td = ec.Td
```










### **SELECT** \*

```
SELECT
FROM
    dbo.Customer
WHERE
    Id = 123
```















## **Converting Data on Read**

```
SELECT
                                                                        Index Scan (NonClustered)
                                                        SELECT
FROM
                                                                       [Customer].[IX_PurchaseDate]
                                                       Cost: 0 %
     dbo.Customer
                                                                              Cost: 100 %
WHERE
     CAST(PurchaseDate AS CHAR(10)) = '2019-01-01'
SELECT
                                                                         Index Seek (NonClustered)
FROM
                                                         SELECT
                                                                       [Customer].[IX_PurchaseDate]
     dbo.Customer
                                                        Cost: 0 %
                                                                              Cost: 100 %
WHERE
     PurchaseDate = CAST('2019-01-01' AS DATETIME2)
```









### **Scalar Functions**

```
SELECT
    FullName, Id
                                                                          Index Scan (NonClustered)
FROM
                                                         SELECT
                                                                        [Customer].[IX_PurchaseDate]
    dbo.Customer
                                                        Cost: 0 %
                                                                               Cost: 100 %
WHERE
    DATEADD(day,30,PurchaseDate) >= GETDATE()
SELECT
                                                           FullName, Id
                                                                          Index Seek (NonClustered)
FROM
                                                          SELECT
                                                                         [Customer].[IX_PurchaseDate]
                                                         Cost: 0 %
     dbo.Customer
                                                                               Cost: 100 %
WHERE
     PurchaseDate >= DATEADD(day, -30,GETDATE())
```










## **Implicit Conversions**

CREATE TABLE dbo.Customer (Id int PRIMARY KEY...

CREATE TABLE dbo.CustomerDetails (Id int PRIMARY KEY... /...

SELECT Clustered Index Scan (Clustered) Nested Loops **SELECT** Compute Scalar [CustomerDetails].[PK\_\_Customer\_\_3214EC... (Inner Join) Cost: 0 % Cost: 0 % FROM Cost: 0 % Cost: 50 % dbo.Customer c (Γ<del>1</del>) INNER JOIN dbo.CustomerDetails d Clustered Index Seek (Clustered) [Customer].[PK\_\_Customer\_\_3214EC073AD... ON c.Id = d.IdCost: 50 %















## **Joining**





#### Join data where it makes sense to do so:

- Do you need to move a lot of data?
- Are indexes available?
- Do you need to convert datatypes?







## **Filtering**

```
FROM

dbo.Orders

WHERE

PurchaseDate = '2019-01-01'

Index Seek (NonClustered)

[Orders].[IX_PurchaseDate_Includes]
```

```
for (int i = 0; i < table.Rows.Count; i++)
{
    if (table.Rows[i]["PurchaseDate"].ToString() == "2019-01-01")
    {
        output.Rows.Add(table.Rows[i]);
    }
}</pre>
```

Rows returned: 5,000
Rows read: 5,000

Rows returned: **5,000** 

Rows read: **10,000,000** 









## Aggregating

```
table = ReadInDataFromDatabase();
var total = table.AsEnumerable()
    .Sum(x => x.Field<int>("Total") );
var average = table.AsEnumerable()
    .Average(x => x.Field<int>("Total") );
```

```
SELECT
    SUM(Total) AS OrderTotal,
    AVG(Total) AS OrderAverage,
    . . .
FROM
    dbo.Orders
```



Columnstore Index Scan (NonClustered) [Orders].[NCC Total]







## **Window and Analytical Functions**

```
SELECT
  CustomerId,
  Total,
  SUM(Total) OVER (
    PARTITION BY CustomerId
    ORDER BY PurchaseDate
    ) AS RunningTotal,
  LEAD(Total) OVER (...) AS NextValue,
  LAST_VALUE(Total) OVER (
    ROWS BETWEEN UNBOUNDED PRECEDING
    AND UNBOUNDED FOLLOWING) AS LastValue
FROM
  dbo.Orders
```

7	CustomerId	Total	RunningTotal	NextValue	LastValue
1	1	5	5	8	6
2	1	8	13	3	6
3	1	3	16	6	6
4	1	6	22	NULL	6
5	2	5	5	5	1
6	2	5	10	1	1
7	2	1	11	NULL	1
8	3	2	2	8	2
9	3	8	10	9	2
10	3	9	19	5	2
11	3	5	24	4	2
12	3	4	28	2	2
13	3	2	30	NULL	2







## Sorting\*

#### **SELECT**

CustomerId, PurchaseDate, Total

#### FROM

dbo.Orders

#### ORDER BY

CustomerId, PurchaseDate

### Might already be sorted if index exists:



#### Might have to sort if no index found:











## **Common Table Expressions (CTEs)**

```
SELECT
FROM
    dbo.Customers c
    LEFT JOIN dbo.Orders o
        ON c.Id = o.CustomerId
    INNER JOIN
    SELECT ...
    FROM dbo.OrderDetails
    WHERE OrderType = 'Online') d
        ON o.Id = d.OrderId
WHERE
    o.PurchaseDate >= DATEADD(month, -1, GETDATE())
    AND c.JoinDate >= DATEADD(day, -365, GETDATE())
```

```
WITH NewCustomers AS (
    SELECT ...
    FROM dbo.Customers
    WHERE c.JoinDate >= DATEADD(day, -365,GETDATE())
), RecentPurchases AS (
   SELECT ...
   FROM dbo.Orders
   WHERE PurchaseDate >= DATEADD(month, -1,GETDATE())
), OnlineOrdersOnly AS (
   SELECT ...
   FROM RecentPurchases o
   INNER JOIN dbo.OrderDetails d
       ON o.Id = d.OrderId
   WHERE d.OrderType = 'Online'
SELECT ...
FROM NewCustomers c
INNER JOIN OnlineOrdersOnly o
    ON c.Id = o.CustomerId
```









### **Cursors and WHILE**

```
DECLARE
             int
DECLARE Ord
               ursor
    FOR SELEC
                 Td FRO
                         ##Orders
OPEN OrderCurs
WHILE @@FETCH S'
                       = 0
BEGIN
                        derCursor INTO @Id;
    FETCH NEXT
                         <code>Petails WHERE OrderId = @Id</code>
    SELECT *
                OM Ort
END
CLOSE Ord
            ursor;
DEALLOC
            OrderCursor;
```

```
SELECT

FROM

dbo.Orders o

INNER JOIN dbo.OrderDetails d

ON o.Id = d.OrderId
```









## **Eager Lazy Loading**

```
DataTable table = retOrders();
for (int i = 0; i < rable.Rows.Count; i++)
{
    var orderId = Co vert.ToInt32(table.Rows[i]["Id"]);
    DataTable dt = GetOrd rDetails(orderId);
}</pre>
```

```
SELECT
...
FROM
    dbo.Orders o
    INNER JOIN dbo.OrderDetails d
    ON o.Id = d.OrderId
```










## **Correlated Subqueries**

```
SELECT
                                                  SELECT
       o.Id,
                                                      o.Id,
                                                      a.AverageTotal
        (SELECT AVG(Total)
                                                  FROM
            FROM ##OrderDetails
                                                      ##Orders o
            WHERE OrderId = o.Id
                                                      INNER JOIN (
             ) AS CombinedTotal
                                                           SELECT AVG(Total) AS AverageTotal,
  FROM
                                                           OrderId
       ##Orders o
                                                           FROM ##OrderDetails
                                                           GROUP BY OrderId) a
Table '##OrderDetails'. Scan count 6, logical reads 12...
                                                               ON o.Id = a.OrderId
Table '##Orders'. Scan count 1, logical reads 1...
                                                  Table '##OrderDetails'. Scan count 1, logical reads 2...
                                                  Table '##Orders'. Scan count 1, logical reads 1...
```









### **DISTINCT vs GROUP BY**

```
Col1,
Col2
FROM
dbo.Table1
```

```
SELECT
Col1,
Col2
FROM
dbo.Table1
GROUP BY
Col1,
Col2
```









### **OR vs UNION ALL**

```
FROM

dbo.Table1

WHERE

Col1 = 'A'

OR Col2 = 'A'
```

```
SELECT
FROM
    dbo.Table1
WHERE
    Col1 = 'A'
UNION ALL
SELECT
FROM
    dbo.Table1
WHERE
    Col2 = 'A'
```







### **NOT IN vs NOT EXISTS**

```
SELECT
    Col1,
    Col2
FROM
    dbo.Table1 t1
WHERE
    Col1 NOT IN (
        SELECT Col1
        FROM dbo.Table2 t2
```

```
SELECT
    Col1,
    Col2
FROM
    dbo.Table1 t1
WHERE
    NOT EXISTS (
        SELECT 1/0
        FROM dbo.Table2 t2
        WHERE t1.Col1 = t2.Col1
```







### JOINS vs JOINS

```
FROM

dbo.Table1 t1

INNER JOIN dbo.Table2 t2

ON t1.Col1 = t2.Col1
```

```
FROM

dbo.Table1 t1

LEFT JOIN dbo.Table2 t2

ON t1.Col1 = t2.Col1

WHERE

t2.Col1 IS NOT NULL
```









## **Correlated Subqueries vs JOINS**

```
SELECT
    Col1,
    (SELECT
        Col2
    FROM
        dbo.Table2 t2
    WHERE
        t1.Col1 = t2.Col1
      AS Col2
FROM
    dbo.Table1 t1
```

```
SELECT
    t1.Col1,
    t2.Col2
FROM
    dbo.Table1 t1
    LEFT JOIN dbo.Table2 t2
    ON t1.Col1 = t2.Col1
```









## **Forcing Join Order**

```
SELECT
FROM
    dbo.Table1 t1
    INNER JOIN dbo.Table2 t2
        ON t1.Col1 = t2.Col1
    INNER JOIN dbo. Table3 t3
        ON t2.Co12 = t3.Co12
```

```
SELECT
FROM
    dbo.Table1 t1
    INNER JOIN (
        -- More rows than your query
        -- will ever return
        SELECT TOP 2147483647
            t2.Col1, ...
        FROM
            dbo.Table2 t2
            INNER JOIN dbo.Table3 t3
                ON t2.Col2 = t3.Col2
    ) t4
```

0N + 1.Col1 = +4.Col1









## Break up giant queries

```
WITH InitialData AS (
), FilteredData AS (
    . . .
SELECT * INTO #FilteredData FROM FilteredData;
CREATE CLUSTERED INDEX ON #FilteredData (Col1, Col2);
WITH JoinedData AS (
    SELECT ... FROM #FilteredData
SELECT ...
FROM JoinedData
```







## More ways to rewrite queries



Presentation: https://bertwagner.com/rewrites

Blog series: <a href="https://bertwagner.com/category/query-rewrites-performance-tuning/">https://bertwagner.com/category/query-rewrites-performance-tuning/</a>







### Review

- 1. Move smaller data to where the larger data exists
- 2. Allow index use
- 3. Use the right tools for the job
- 4. Think in sets instead of looping
- 5. Rewrite your queries







## Thank you!









youtube.com/bertwagner











### **Appendix**

- 19
  - https://docs.microsoft.com/en-us/sql/relational-databases/indexes/columnstore-indexes-guery-performance?view=sqlserver-2017
  - http://www.nikoport.com/columnstore/
- 20
  - https://docs.microsoft.com/en-us/sql/t-sql/queries/select-over-clause-transact-sql?view=sql-server-2017
  - https://docs.microsoft.com/en-us/sql/t-sql/functions/analytic-functions-transact-sql?view=sql-server-2017
- 21
  - https://dba.stackexchange.com/a/158429/168918
- 28
  - https://sqlperformance.com/2017/01/t-sql-queries/surprises-assumptions-group-by-distinct
- 29
  - https://bertwagner.com/2018/02/20/or-vs-union-all-is-one-better-for-performance/
- 30
  - https://sqlperformance.com/2012/12/t-sql-queries/left-anti-semi-join
- 33
  - https://bertwagner.com/2017/11/21/does-the-join-order-of-my-tables-matter/
  - https://sqlbits.com/Sessions/Event14/Query Tuning Mastery Clash of the Row Goals





