## cpnv

# Ecommerce@SC-C236-PC05 Data Dictionary

21.01.2021





# Table of contents

comm	nerce@SC-C236-PC05	6
1. Tab	bles	6
1.1.	Table: carts	6
1.2.	Table: discounts	6
1.3.	Table: events	6
1.4.	Table: orders	7
	Table: orders_apply_discounts	
	Table: orders_contain_products	
1.7.	Table: pages	8
1.8.	Table: products	9
1.9.	Table: products_add_carts	9
1.10.	). Table: roles	10
	. Table: suppliers	
1.12.	. Table: suppliers_supply_products	11
	. Table: users	
	. Table: users_configure_pages	
	. Table: users_create_discounts	
1.16.	5. Table: users_has_roles	13
1.17.	. Table: users_own_carts	13
1.18.	Table: users_participate_events	14
1 10	Table: users, perform orders	1.4

## Legend

- **?** Primary key
- Primary key disabled
- 1 User-defined primary key
- **?** Unique key
- ¶ Unique key disabled
- 1 User-defined unique key
- Active trigger
- Disabled trigger
- → Many to one relation
- $\succ_{\mathbf{i}}$  User-defined many to one relation
- ✓ User-defined one to many relation
- $\succ$  User-defined many to many relation
- One to one relation
- user-defined one to one relation
- •**@** Input
- @ Output
- Input/Output
- Uses dependency
- User-defined uses dependency
- Used by dependency
- 🛅 User-defined used by dependency

# Ecommerce@SC-C236-PC05

# 1. Tables

## 1.1. Table: carts

#### Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
		created_at	datetime	Nullable
		updated_at	datetime	Nullable

#### Linked from

	Table	Join	Title / Name / Description
-	→ products_add_carts	cartsid = products_add_cartscart_id	FK_productscart3A81B327

## Unique keys

			Name / Description
Ŷ	id	PKcarts3213E83F62299660	

## 1.2. Table: discounts

#### Columns

		Name	Data type	Description / Attributes
▤	1	id	int	Identity / Auto increment
▤		rebate	bit	
▤		from_date	datetime	
■		to_date	datetime	
■		created_at	datetime	

## Linked from

	Table	Join	Title / Name / Description
<b>→</b>	orders_apply_discounts	discountsid = orders_apply_discountsdiscount_id	FK_orders_ap_disco_5535A963
<b>→</b>	users_create_discounts	discountsid = users_create_discountsdiscount_id	FK_users_cre_disco_4E88ABD4

## Unique keys

		Name / Description
9	id	PK_discount_3213E83FCDE5D43A

## 1.3. Table: events

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment

	Name	Data type	Description / Attributes
■	name	varchar(50)	
目	description	varchar(250)	
目	address	varchar(65)	
目	start_date	date	
▤	end_date	date	
▤	city	varchar(50)	Nullable
目	zipcode	varchar(50)	Nullable
目	lat	geography	Nullable
目	Ing	geography	Nullable
目	created_at	datetime	Nullable
■	updated_at	datetime	Nullable

	Table	Join	Title / Name / Description
$\rightarrow$	users_own_carts	eventsid = users_own_cartsevent_id	FK_users_own_event_3F466844
$\rightarrow$	users_participate_events	<pre>eventsid = users_participate_eventsevent_id</pre>	FK_users_par_event_4316F928

# Unique keys

		Name / Description
Ŷ	id	PK_events_3213E83FAE73F874

## 1.4. Table: orders

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		total_amount	decimal(18, 0)	
■		tracking_number	varchar(8000)	Nullable
■		created_at	datetime	

## Linked from

	Table	Join	Title / Name / Description
$\rightarrow$	orders_apply_discounts	<pre>ordersid = orders_apply_discountsorder_id</pre>	FK_orders_ap_order_5629CD9C
$\rightarrow$	orders_contain_products	ordersid = orders_contain_productsorder_id	FK_orders_co_order_59063A47
$\rightarrow$	users_perform_orders	ordersid = users_perform_ordersorder_id	FK_users_per_order_52593CB8

# Unique keys

		Name / Description
?	id	PK_orders_3213E83F96CE86E0

# 1.5. Table: orders\_apply\_discounts

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
		discount_id	int	Nullable References: discounts
■		order_id	int	Nullable References: orders

## Links to

	Table	Join	Title / Name / Description
<b>—</b>	discounts	<pre>orders_apply_discountsdiscount_id = discountsid</pre>	FK_orders_ap_disco_5535A963
<b>—</b>	orders	<pre>orders_apply_discountsorder_id = ordersid</pre>	FK_orders_ap_order_5629CD9C

# Unique keys

			Name / Description
Ŷ	id	PK_orders_a_3213E83F5FAB2A1C	

# 1.6. Table: orders\_contain\_products

#### Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
		order_id	int	Nullable References: orders
■		product_id	int	Nullable References: products

#### Links to

	Table	Join	Title / Name / Description
<b>-</b>	orders	<pre>orders_contain_productsorder_id = ordersid</pre>	FK_orders_co_order_59063A47
<b>-</b>	products	orders_contain_productsproduct_id = productsid	FK_orders_co_produ_59FA5E80

## Unique keys

		Name / Description
Ŷ	id	PK_orders_c_3213E83FC2F39C1F

# 1.7. Table: pages

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment

	Name	Data type	Description / Attributes
■	title	varchar(50)	
■	description	varchar(250)	
■	url_page	varchar(8000)	
■	created_at	datetime	Nullable
■	updated_at	datetime	Nullable

	Table	Join	Title / Name / Description
-	users_configure_pages	pagesid = users_configure_pagespage_id	FK_users_con_page4AB81AF0

# Unique keys

		Name / Description
P	id	PKpages3213E83F59C977FC

# 1.8. Table: products

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		name_francais	varchar(50)	
■		description_francais	varchar(50)	
■		name_deutsch	varchar(50)	
■		description_deutsch	varchar(50)	
■		name_english	varchar(50)	
■		description_english	varchar(50)	
		price	int	

## Linked from

	Table	Join	Title / Name / Description
$\rightarrow$	orders_contain_products	<pre>productsid = orders_contain_productsproduct_id</pre>	FK_orders_co_produ_59FA5E80
$\rightarrow$	products_add_carts	<pre>productsid = products_add_cartsproduct_id</pre>	FK_productsprodu_3B75D760
$\rightarrow$	suppliers_supply_products	<pre>productsid = suppliers_supply_productsproduct_id</pre>	FK_suppliers_produ_36B12243

# Unique keys

		Name / Description
9	id	PK_products_3213E83F3E911AAF

# 1.9. Table: products\_add\_carts

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		cart_id	int	Nullable References: carts
■		product_id	int	Nullable References: products

## Links to

	Table	Join	Title / Name / Description
>	- carts	products_add_cartscart_id = cartsid	FK_productscart3A81B327
>	- products	<pre>products_add_cartsproduct_id = productsid</pre>	FK_products_produ_3B75D760

# Unique keys

		Name / Description
Ŷ	id	PK_products_3213E83F75BB352B

## 1.10. Table: roles

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		name	varchar(50)	

## Linked from

	Table	Join			Title / Name / Description
$\rightarrow$	users_has_roles	rolesid = users_has_role	srole_id	FKusers_hasrole	_46E78A0C

## Unique keys

		Name / Description
P	id	PK_roles_3213E83FB5E3F03C

# 1.11. Table: suppliers

		Name	Data type	Description / Attributes
目	1	id	int	Identity / Auto increment
■		name	varchar(50)	
■		email	varchar(50)	
■		address	varchar(50)	
■		phone	varchar(50)	
		country	varchar(50)	

	Table	Join	Title / Name / Description
-	t I sunnuers sunniv nroquets	<pre>suppliersid = suppliers_supply_productssupplier_id</pre>	FK_suppliers_suppl_37A5467C

# Unique keys

		Name / Description
?	id	PK_supplier_3213E83F6147DE21

# 1.12. Table: suppliers\_supply\_products

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		product_id	int	Nullable References: products
■		supplier_id	int	Nullable References: suppliers

## Links to

	Table	Join	Title / Name / Description
<b>&gt;</b>	products	suppliers_supply_productsproduct_id = productsid	FK_suppliers_produ_36B12243
<b>&gt;</b>	suppliers	suppliers_supply_productssupplier_id = suppliersid	FK_suppliers_suppl_37A5467C

# Unique keys

		Name / Description
P	id	PK_supplier_3213E83F08C466EC

## 1.13. Table: users

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		username	varchar(50)	
		firstname	varchar(50)	
■		lastname	varchar(50)	
	1	email	varchar(50)	
■		password	varchar(65)	
		url_profile	varchar(8000)	Nullable
		address	varchar(65)	Nullable
		city	varchar(50)	Nullable
		zip	int	Nullable

	Table	Join	Title / Name / Description
$\rightarrow$	users_configure_pages	usersid = users_configure_pagesuser_id	FK_users_con_user49C3F6B7
$\rightarrow$	users_create_discounts	<pre>usersid = users_create_discountsuser_id</pre>	FK_users_cre_user4D94879B
$\rightarrow$	users_has_roles	usersid = users_has_rolesuser_id	FK_users_has_user45F365D3
$\rightarrow$	users_own_carts	usersid = users_own_cartsuser_id	FK_users_own_user3E52440B
<b>→</b>	users_participate_events	<pre>usersid = users_participate_eventsuser_id</pre>	FK_users_par_user4222D4EF
$\rightarrow$	users_perform_orders	usersid = users_perform_ordersuser_id	FK_users_per_user5165187F

## Unique keys

		Name / Description	
?	id	PK_users_3213E83FC4DA5318	
9	email	UQ_users_AB6E6164D68D97B7	

## 1.14. Table: users\_configure\_pages

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		user_id	int	Nullable References: users
■		page_id	int	Nullable References: pages

#### Links to

	Table	Join	Title / Name / Description
<b>-</b>	pages	<pre>users_configure_pagespage_id = pagesid</pre>	FK_users_con_page4AB81AF0
<b>-</b>	users	<pre>users_configure_pagesuser_id = usersid</pre>	FK_users_con_user49C3F6B7

# Unique keys

		Name / Description
?	id	PK_users_co_3213E83FA8DDD962

# 1.15. Table: users\_create\_discounts

		Name	Data type	Description / Attributes
▤	1	id	int	Identity / Auto increment
■		user_id	int	Nullable References: users

	Name	Data type	Description / Attributes
■	discount_id	int	Nullable References: discounts

## Links to

	Table	Join	Title / Name / Description
<b>&gt;</b>	discounts	<pre>users_create_discountsdiscount_id = discountsid</pre>	FK_users_credisco4E88ABD4
>	users	<pre>users_create_discountsuser_id = usersid</pre>	FK_users_cre_user4D94879B

## Unique keys

		Name / Description
Ŷ	id	PK_users_cr3213E83F4F85DBA7

## 1.16. Table: users\_has\_roles

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
B		user_id	int	Nullable References: users
■		role_id	int	Nullable References: roles

## Links to

	Table	Join		Title / Name / Description
$\rightarrow$	roles	users_has_rolesrole_id = rolesid	FK_users_has_role_	_46E78A0C
$\rightarrow$	users	users_has_rolesuser_id = usersid	FK_users_has_user_	_45F365D3

# Unique keys

			Name / Description
P	id	PK_users_ha_3213E83F70A78483	

# 1.17. Table: users\_own\_carts

## Columns

		Name	Data type	Description / Attributes
	1	id	int	Identity / Auto increment
■		user_id	int	Nullable References: users
		event_id	int	Nullable References: events

## Links to

	Table	Join	Title / Name / Description
$\rightarrow$	events	users_own_cartsevent_id = eventsid	FK_users_own_event_3F466844

	Table	Join	Title / Name / Description
<b>&gt;</b>	users	users_own_cartsuser_id = usersid	FK_users_own_user3E52440B

## Unique keys

		Name / Description
P	id	PK_users_ow3213E83F6AA7491A

# 1.18. Table: users\_participate\_events

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
		user_id	int	Nullable References: users
■		event_id	int	Nullable References: events

#### Links to

		Table	Join	Title / Name / Description
:	<b>—</b>	events	<pre>users_participate_eventsevent_id = eventsid</pre>	FK_users_par_event_4316F928
:	<b>—</b>	users	<pre>users_participate_eventsuser_id = usersid</pre>	FK_users_par_user4222D4EF

# Unique keys

		Name / Description
Ŷ	id	PK_users_pa_3213E83F71D4D552

# 1.19. Table: users\_perform\_orders

## Columns

		Name	Data type	Description / Attributes
■	1	id	int	Identity / Auto increment
■		user_id	int	Nullable References: users
		order_id	int	Nullable References: orders

## Links to

	Table	Join	Title / Name / Description
<b>—</b>	orders	<pre>users_perform_ordersorder_id = ordersid</pre>	FK_users_per_order_52593CB8
<b>—</b>	users	<pre>users_perform_ordersuser_id = usersid</pre>	FK_users_per_user5165187F

## Unique keys

		Name / Description
9	id	PK_users_pe_3213E83FE7472974