Automatic Speech Recognition: Introduction, Current Trends and Open Problems


link to the slides

Laurent Besacier

October 2026



The big picture: 35 years of speech recognition



- From modular pipelines to **one neural network**
- From transcribed speech to **raw audio at web scale**
- From recognizing speech to **holding a conversation**

1. From waves to words
2. Going end-to-end
3. Listening without labels (SSL)
4. Speech as tokens
5. When LLMs learn to listen
6. Talking while listening (full duplex)
7. Is ASR solved?

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens

5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

Speech facts

- Speech generally conveys a (linguistic) message (that can be reduced to a transcript)
- But not only (paralinguistics: speaker identity, speaker mood, speaker health condition, speaker accent, etc.)
- Variability at all levels (intra speaker, inter speaker, microphone, phone line, room acoustics, style)
- Speech is a continuous signal (no explicit word boundaries)
- May be decomposed into elementary units of sound (phonemes) that distinguish one word from another in a particular language (minimal pairs)
  - *kill* vs *kiss* - *pat* vs *bat*
  - phoneme set is language dependent
  - acoustic realization of the phoneme is dependent of its left and right neighbors (co-articulation)

(Main) Speech tasks

- Speech compression (solved, now also with neural codecs)
- Speaker recognition (strong progresses over the last 10 years but still poor compared to other biometric modalities like fingerprint and iris)
- Text-to-speech synthesis (near-human quality and voice cloning from a few seconds of audio)
- **Speech-to-text and Speech-to-Speech (this talk)**
- Speech paralinguistics: detection of gender, age, deception, sincerity, nativeness, emotion, sleepiness, cognitive disorders, (drug or alcohol) intoxication, pathologies, etc.
- Main speech conference: *Interspeech* (core A, every year)

How do we evaluate ASR? Word Error Rate (WER)

ASR = Automatic Speech Recognition. Align the system output with the human transcript (edit distance), then count errors:

$$\text{WER} = \frac{S + D + I}{N}$$

S: substitutions D: deletions I: insertions N: words in reference


REF	the	cat	sat	on	the	–	mat
HYP	–	cat	sit	on	the	big	mat
	D		**S**			**I**	

$$N = 6 \Rightarrow \text{WER} = (1 + 1 + 1)/6 = 50\%$$

- WER can exceed 100% (many insertions)
- No word boundaries (Chinese, Japanese, Thai)? Use the *Character* Error Rate (CER)
- Text normalization (case, punctuation, numbers) matters a lot when comparing systems


Speech-to-text

- Automatic Speech Recognition (ASR): ideally spontaneous, multi-speaker, open vocabulary, any acoustic condition
- But performance differs greatly across contexts (read vs spontaneous ; quiet vs noisy ; native vs non-native)



NIST ASR benchmark tests history (< 2015). Source: NIST

Speech-to-text: the Librispeech era




Librispeech ASR benchmark tests history (> 2016). Source: `https://paperswithcode.com`

ASR as a partial task in a larger system

- ASR for spoken language processing (speech understanding, speech translation, speech summarization, etc.)
- Not just a problem of noisy transcripts
- No sentence boundaries, punctuation, case
- Disfluencies in spontaneous speech: false starts, fillers, repaired utterances
  - btw, should we keep them or remove them ?
  - some speech tasks are ill defined (ex: speech translation)
- Time to work on end-to-end approaches from speech ?


Speech representations

- Handcrafted features (< 2015)
  - 20-30ms sliding windows, 10ms frame rate
  - filterbanks, cepstral coefficients (MFCC), prosody (pitch, energy)
- Spectrograms (< 1990 and > 2015!)
  - time-frequency representation processed as an image
- Raw waveform (> 2015)
  - convolutional front-end learnt with the model
- Self-supervised learnt representations (> 2020, see later!)



Speech signal (top) and spectrogram (bottom)

Progresses over the years




ASR Performance[1] on English Conversational Telephony (Switchboard)

[1] Image from Bhuvana Ramabhadran' s presentation at Interspeech 2018

Classical ASR (1990-2015) in one slide

$$w^* = \arg\max_w p(w|x) = \arg\max_w p(x|w)\, p(w)$$

- Acoustic model $p(x|w)$: HMMs (sequence of states) with GMMs (distribution per state), context-dependent phones (triphones)
- Pronunciation lexicon: words $\rightarrow$ phones (cat /k a t/)
- Language model $p(w)$: n-grams, later RNNs
- Decoding: Viterbi search over the combined graph



ASR Overview

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens


5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

From neural nets to deep learning (1990-2015)

- NNs used in ASR since the 90s, but slow and weaker than HMM/GMMs
- **Hybrid NN-HMM**: the NN estimates the posterior $p(s|x)$ of an HMM state (Renals et al., 1994)
- **NN language models** (Bengio et al., 2003), then RNN LMs (Mikolov et al., 2010)
- **2012 breakthrough**: deep NNs replace GMMs (Hinton et al., 2012), like in vision, thanks to
  - more data (Librispeech 1,000h in 2015 $\rightarrow$ Whisper 680,000h in 2022)
  - GPUs, better optimization, toolkits (Kaldi (Povey et al., 2011), PyTorch)



Hybrid NN-HMM

End-to-end ASR (get rid of HMMs)

One neural network maps speech directly to characters, subwords or words


- Connectionist Temporal Classification (CTC)
  - Solves the problem of unaligned input and output sequences by marginalizing the conditional likelihood of the output sequence given the input over all possible alignments
- Attention Modeling
  - Simultaneously optimize alignment and grapheme (or word) decoding using attention weights (linear combination of hidden states) to influence the generated output
- Transducers (RNN-T) (Graves, 2012)
  - Encoder + prediction network (conditioned on previous outputs, like an LM) + joint network ; like CTC, marginalize over alignments with a blank symbol, but without CTC's independence assumption ; streaming-friendly

CTC overview

- Connectionist Temporal Classification
- Model will learn to align the transcript itself during training (Graves et al., 2006)
- Defined over a label sequence z (of length M)
- *blank or* _ symbol allows M-length target sequence to be mapped to a T-length sequence x[2]
- z can be represented by a set of all possible CTC paths (sequence of labels, at frame level) that are mapped to z
  - ex: M=2 ($z = hi$) and T=3 (3 frames): possible sequences are 'hhi', 'hii', '_hi', 'h_i', 'hi_'
- Probability $p(z/x)$ evaluated as sum of probabilities over all possible CTC paths (using Forward-Backward)
- Generate frame posteriors at decoding time

[2] gives the model the ability to say that a certain audio frame did not produce a character

CTC loss function



CTC Overview (from `https://www.assemblyai.com/blog/end-to-end-speech-recognition-pytorch`)

- There can be a massive number of alignments, so the loss is computed with dynamic programming (forward-backward)

CTC inference

- Greedy decoding


$$Y^* = \underset{Y}{\operatorname{argmax}}\ p(Y \mid X)$$

One heuristic is to take the most likely output at each time-step. This gives us the alignment with the highest probability:

$$A^* = \underset{A}{\operatorname{argmax}} \prod_{t=1}^{T} p_t(a_t \mid X)$$

We can then collapse repeats and remove ϵ tokens to get Y.

- Beam-Search decoding



A standard beam search algorithm with an alphabet of $\{\epsilon, a, b\}$ and a beam size of three.

from `https://www.assemblyai.com/blog/end-to-end-speech-recognition-pytorch`

Attention modeling

Initially proposed for (neural) machine translation (Bahdanau et al., 2014) and introduced for ASR by Chorowski et al. (2015a)

- A speech encoder (CNNs, pyramidal LSTMs Chorowski et al. (2015b), now Transformers)
- A context (attention) model is a function of the encoder codes and of the previous decoded tokens
- While CTC generates frame-level posteriors, attention models generate L predictions until the end-of-sequence symbol (no posterior for a given frame)






Image from Alexandre Berard's thesis

Attention modeling: listen, attend and spell

- **L**isten (encode), **A**ttend, **S**pell (decode, one token at a time)



- Attention weights give a soft alignment between output tokens and input frames, possibly non-monotonic (CTC is monotonic)



Images from `https://lorenlugosch.github.io/posts/2020/11/transducer/`

CTC versus Attention

- CTC provides monotonic alignements while attention allows non-monotonic alignements
  - Attention more suitable for speech translation
- Attention will induce Auto-Regressive decoding (one token at a time) as attention depends on decoder's state
  - slow inference
- CTC does not have this constraint and is much simpler
  - faster inference
- In practice, both are often combined (joint CTC/attention training and decoding)
- Transducers (RNN-T): alignment-free like CTC, but each output also depends on previous outputs through a prediction network ; streaming, on-device, and among the fastest accurate models today (e.g., token-and-duration transducers (Xu et al., 2023))

The Conformer encoder

- Convolution-augmented Transformer (Gulati et al., 2020)
- Attention: *global* context ; convolution: *local* patterns
- Subsampling: 10ms $\rightarrow$ 40ms frames (80ms in FastConformer)
- Default ASR encoder since 2020, for any decoder (CTC, transducer, attention, LLM)




Figure from (Gulati et al., 2020)

Whisper: large-scale weak supervision

- Massively multilingual ASR based on weakly-supervised learning (Radford et al., 2022)
- 680,000 hours of web data (large-v3: 1M hours weakly labeled + 4M hours pseudo-labeled by large-v2) $\rightarrow$ robust to accents, noise and technical language
- One model, many tasks selected by special tokens: transcription (99 languages), translation into English, language ID, timestamps
- Simple encoder-decoder Transformer: the de facto baseline (and encoder) for many systems since 2022





Figure from (Radford et al., 2022)

Open multilingual ASR models


- OWSM: Whisper-style training reproduced with public data and an open toolkit (ESPnet) (Peng et al., 2023)
- MMS: 1,100+ languages (religious recordings, wav2vec 2.0) (Pratap et al., 2023)
- Omnilingual ASR: 1,600+ languages, 500+ never covered before, new languages added from a few examples (in-context) (Omnilingual ASR team et al., 2025)
- mHuBERT-147: compact (95M) multilingual SSL encoder, 147 languages, 90K hours of open data (Zanon Boito et al., 2024)



Labeled hours per language (log): a long tail (Omnilingual ASR team et al., 2025)


Comparing systems: the Open ASR Leaderboard

60+ systems evaluated on 11 English test sets with the same text normalization



RTFx: seconds of audio transcribed per second of compute (1000 = 1h in 3.6s). Dashed: Pareto frontier.
Data from (Srivastav et al., 2025) (arXiv v4, March 2026), open models only.

Building an ASR system in 2026



- **Data**: large-scale weakly labeled and pseudo-labeled speech matters as much as the model
- **Decoder**: depends on the use case (latency, languages, need for context)
- **Evaluation**: normalized WER on diverse test sets, plus speed (RTFx)
- LLM decoders (speech LLMs) are covered later in this course

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens

5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

Self supervised representation learning

- Using huge unlabeled data for training ; targets are computed from the signal itself
  - *"learn representations using objective functions similar to those used for supervised learning, but train networks to perform pretext tasks where both the inputs and labels are derived from an unlabeled dataset"* (from Chen et al. (2020))
- Introduced for vision: see for instance (Chen et al., 2020)
  - learn representations by contrasting positive pairs against negative pairs
- Introduced also in NLP: see for instance (Devlin et al., 2018)
  - learn representations by predicting tokens that were masked in an input sequence

Previous works

- Stacked restricted Boltzman machines (RBM) (Hinton and Salakhutdinov, 2006)
  - hidden layer extracts relevant features from the observations that serve as input to next RBM that is stacked on top of it forming a deterministic feed-forward neural network
- Denoising autoencoders (AE) (Vincent et al., 2008)
  - networks which are tasked with reconstructing outputs from their (noisy) input versions
- Variational autoencoders (VAE) (Kingma and Welling, 2013)
  - VAE is like a traditional AE in which the encoder produces distributions over latent representations (rather than deterministic encodings) while the decoder is trained on samples from this distribution
  - both encoder and decoder are trained jointly
  - VQ-VAE (van den Oord et al., 2017) replaces continuous latent vectors with deterministically quantized versions

Pre-trained language models

- Leverage large amount of freely available unlabeled text to facilitate transfer learning in NLP
- Yield state-of-the-art results on a wide range of NLP tasks + save time and computational resources
- Example of BERT (Devlin et al., 2018) based on the Transformer model (Vaswani et al., 2017)




Figure from (Devlin et al., 2018)

Self supervised representation learning from speech

Three families of pretext tasks

- **Predictive**: predict future frames
  - Autoregressive predictive coding (APC) (Chung et al., 2019; Chung and Glass, 2020)
- **Contrastive**: distinguish the true (future or masked) frame from negatives
  - Contrastive Predictive Coding (CPC) (van den Oord et al., 2018), wav2vec (Schneider et al., 2019), wav2vec 2.0 (Baevski et al., 2020)
- **Masked prediction**: predict (discrete) targets of masked frames, like BERT
  - HuBERT (Hsu et al., 2021), WavLM (Chen et al., 2022), w2v-BERT (Chung et al., 2021), data2vec (Baevski et al., 2022)

Autoregressive predictive coding (APC)

- Predicting the spectrum of a future frame (rather than a wave sample) (Chung et al., 2019)
- Somewhat inspired by language models (LMs) for text, which are typically a probability distribution over sequences of T tokens $(t_1, t_2, ..., t_T)$

$$P(sequence) = \prod_{k=1}^{T} P(t_k | t_1, t_2, ..., t_{k-1}) \tag{1}$$

$$P(sequence) = \prod_{k=1}^{T} P(t_k | h) \tag{2}$$

- Recurrent neural network LM:
  $h = rnn_state(E(t_1), E(t_2), ..., E(t_{k-1}))$
- For speech, each token t_k corresponds to a frame rather than a word or character token

Autoregressive predictive coding (APC)

- No final set of target tokens (softmax layer replaced by a regression layer)
- Learnable parameters in APC are the RNN parameters θ_{rnn} and the regression layer parameters θ_r
- Encourage APC to infer more global structures rather than the local information in the signal
  - ask the model to predict a frame n steps ahead of the current one
- Model is optimized by minimizing the L1 loss between sequence $(x_1, x_2, ..., x_T)$ and the predicted sequence $(y_1, y_2, ..., y_T)$:

$$\sum_{i=1}^{T-n} |t_i - y_i|, t_i = x_{i+n} \tag{3}$$

Differences between speech and text SSL

- Input speech representations (MFCCs for instance) are already in a vector form (no embedding layer)
- More uncertainty
  - text (discrete): finite number of possible outcomes (target tokens)
  - speech and video (continuous): infinite number of frames that can plausibly follow a given audio (or video) clip




Figure from `https://ai.facebook.com/blog/self-supervised-learning-the-dark-matter-of-intelligence`

Contrastive Predictive Coding (CPC)

- Idea proposed by van den Oord et al. (2018): maybe an easier objective (classification instead of regression)
- Contrastive loss: distinguish a true future sample z_{i+k} from distractors drawn from the same utterance
- Example of *wav2vec* (Schneider et al., 2019), fully convolutional
  - encoder $Z = f(X)$: z_i encodes 30ms every 10ms
  - context network $C = g(Z)$: c_i sees 210ms
- Learned representations improve a supervised ASR system




Figure from (Schneider et al., 2019)

Follow-up approaches (2019-2020)

- **Multiple self-supervised tasks**: PASE (Pascual et al., 2019) and PASE+ (Ravanelli et al., 2020)
  - one encoder, several "workers" reconstructing waveform, spectrum, MFCC, prosody + contrastive tasks
- **Masked reconstruction of frames** (BERT-like, regression)
  - Speech-XLNet (Song et al., 2019), Mockingjay (Liu et al., 2020), masking in time and frequency (Wang et al., 2020)
- Lessons learnt
  - bidirectional Transformer encoders + masking work best
  - predicting *discrete* targets works better than regressing frames $\rightarrow$ wav2vec 2.0 and HuBERT

Wav2vec 2.0: masking + contrastive learning

- Encode speech with CNN layers and then mask spans of the resulting latent speech representations (cf masked LM)
- Learn *discrete* speech units as latent representations[3]
- Latent representations fed to a Transformer network to build contextualized representations
- Model trained with a contrastive task (true latent to be distinguished from distractors)




Figure from (Baevski et al., 2020)

[3] Authors found this more effective than non-quantized targets

Wav2vec 2.0: ASR with very few labels

- Pre-train on unlabeled speech (53K hours, Libri-light), then fine-tune with CTC on a small labeled set (Baevski et al., 2020)

Labeled data	test-clean WER	test-other WER
10 minutes	4.8	8.2
960 hours (all Librispeech)	1.8	3.3

Numbers from (Baevski et al., 2020)

- With 1 hour of labels, beats the previous state of the art trained on 100 hours
- Multilingual versions: XLSR, then XLS-R (128 languages, 436K hours) (Babu et al., 2021)
- A game changer for low-resource languages

HuBERT: Hidden-Unit BERT

- Similar Conv+Transformer encoder (Hsu et al., 2021) but
- Cross-entropy loss (same as BERT) instead of contrastive loss
- Discrete targets built through a separate clustering process
- Learnt *discrete* speech units refined at each iteration (3 iterations for large models)
- Matches or improves wav2vec 2.0 on Librispeech (10min to 960h of labels) ; X-Large (1B parameters): up to 13% relative WER reduction on test-other





Figure from (Hsu et al., 2021)

HuBERT: where do the targets come from?



After (Hsu et al., 2021)

- Loss computed on masked frames only: the model must learn an acoustic *and* a language model of the units
- Works because the clustering is *consistent*, not because clusters are good phones
- These cluster indices are **discrete speech units**: the first "speech tokens" (see next section)

After HuBERT

- **WavLM** (Chen et al., 2022)
  - masked prediction (like HuBERT) + denoising: the input is mixed with noise or another speaker
  - good for ASR *and* speaker, diarization, separation tasks ("full stack")
- **w2v-BERT** (Chung et al., 2021)
  - contrastive learning (wav2vec 2.0) + masked prediction (BERT), trained end-to-end, no re-clustering
- **data2vec** (Baevski et al., 2022)
  - predict the teacher's *contextualized* representations of the unmasked input (self-distillation)
  - same method for speech, vision and text
- Multilingual: XLS-R (Babu et al., 2021), mHuBERT-147 (Zanon Boito et al., 2024)
- Today SSL encoders are the front-end of most ASR systems and speech LLMs

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens

5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

Why turn speech into tokens?

- LLMs work on *discrete* tokens ; speech is a continuous signal
- Speech units allow LMs trained on audio only (*textless* NLP, e.g. GSLM (Lakhotia et al., 2021) on HuBERT units)
- But speech is much *longer* than text

Representation	**Tokens per second**
Text (English, subwords)	$\approx$ 3–4
Waveform (16kHz samples)	16,000
HuBERT units (20ms frames)	50
EnCodec, 6kbps (75Hz $\times$ 8 codebooks)	600
Mimi (12.5Hz $\times$ 8 codebooks)	100

Codec rates from (Défossez et al., 2022; Défossez et al., 2024)

- Goal: few tokens/s, keeping *what* is said and *how*

Semantic vs. acoustic tokens

- **Semantic tokens**: k-means on SSL features (HuBERT, w2v-BERT)
  - phonetic content, long-term structure
  - lose speaker and prosody
- **Acoustic tokens**: neural audio codec
  - high-quality waveform reconstruction
  - little linguistic structure
- AudioLM (Borsos et al., 2022): semantic tokens first, then acoustic tokens




Figure from (Borsos et al., 2022)

Neural audio codecs and RVQ

- Convolutional encoder $\rightarrow$ quantizer $\rightarrow$ decoder, trained end-to-end with reconstruction + adversarial losses: SoundStream (Zeghidour et al., 2021), EnCodec (Défossez et al., 2022)
- **Residual vector quantization (RVQ)**: codebook 1 quantizes the encoder output, codebook 2 quantizes what is left (the residual), etc.
  - first codebooks: coarse information ; last ones: fine details
  - bitrate = frame rate $\times$ #codebooks $\times \log_2$(codebook size)
  - fewer codebooks = lower bitrate (SoundStream: 3 to 18 kbps)




Figure from (Zeghidour et al., 2021)

Mimi: semantic and acoustic tokens in one codec

- SpeechTokenizer (Zhang et al., 2023b): the first RVQ level is distilled from HuBERT, so it carries the semantics
- Mimi (Défossez et al., 2024), the codec of Moshi
  - 24kHz audio $\rightarrow$ 12.5 frames/s, 8 codebooks, 1.1 kbps
  - first codebook distilled from WavLM (semantic), 7 others acoustic
  - causal (streaming) encoder and decoder, with Transformers




Figure from (Défossez et al., 2024)

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens

5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

SpeechT5 (Ao et al., 2021)

- Multimodal extension of encoder-decoder models such as T5
- One Transformer backbone for speech *and* text, with modality-specific pre/post-nets
- Shared vector space for acoustic and text information
- Initializes ASR, TTS, voice conversion, speaker id., etc.




Figure from (Ao et al., 2021)

SpeechT5: pre-training and results

- Composite pre-training loss: masked prediction of discrete speech units (*à la* HuBERT), speech reconstruction (filterbanks), text denoising (*à la* BART), cross-modal alignment
- Slightly better than speech-only pre-training on ASR, TTS, voice conversion, speaker id.


Model	LM	dev-clean	dev-other	test-clean	test-other
wav2vec 2.0 BASE (Baevski et al., 2020)	-	6.1	13.5	6.1	13.3
HuBERT BASE (Hsu et al., 2021) †	-	5.5	13.1	5.8	13.3
Baseline (w/o CTC)	-	5.8	12.3	6.2	12.3
Baseline	-	4.9	11.7	5.0	11.9
SpeechT5 (w/o CTC)	-	5.4	10.7	5.8	10.7
SpeechT5	-	**4.3**	**10.3**	**4.4**	**10.4**
DiscreteBERT (Baevski et al., 2019)	4-gram	4.0	10.9	4.5	12.1
wav2vec 2.0 BASE (Baevski et al., 2020)	4-gram	2.7	7.9	3.4	8.0
HuBERT BASE (Hsu et al., 2021)	4-gram	2.7	7.8	3.4	8.1
wav2vec 2.0 BASE (Baevski et al., 2020)	Transf.	2.2	6.3	2.6	6.3
Baseline	Transf.	2.3	6.3	2.5	6.3
SpeechT5	Transf.	**2.1**	**5.5**	**2.4**	**5.8**

Table 1: Results of ASR (speech to text) on the LibriSpeech dev and test sets when training on the 100 hours subset of LibriSpeech. † indicates that results are not reported in the corresponding paper and evaluated by ourselves.

Table from (Ao et al., 2021)


Two ways to connect speech to an LLM

1. Discrete tokens



+ speech in *and* out, same LM loss (SpeechGPT (Zhang et al., 2023a), Moshi)
– long sequences, may lose acoustic detail


2. Continuous embeddings



+ keeps acoustic detail, reuses strong encoders
– speech in, text out (needs a separate speech generator)

The standard recipe: encoder + adapter + LLM

- Pre-trained speech encoder, often frozen (e.g. Whisper)
- Adapter (can be a simple MLP or more complex) reduces the frame rate and maps to the LLM embedding space
- Text LLM, frozen or with LoRA
- Training: alignment (ASR, captioning), then instruction tuning
- SALMONN (Tang et al., 2024), Qwen-Audio (Chu et al., 2023, 2024), Voxtral (Liu et al., 2025)




Voxtral: Whisper encoder, MLP adapter (50Hz $\rightarrow$ 12.5Hz), LLM decoder. Figure from (Liu et al., 2025)

LLM-based ASR

- Audio embeddings prepended to the text of a decoder-only LLM (Speech-LLaMA (Wu et al., 2023))
- In-context learning (Chen et al., 2023): e.g. new languages from a few examples (Omnilingual ASR team et al., 2025)
- Best WERs on the Open ASR Leaderboard (Canary-Qwen, Granite Speech, Qwen3-ASR)

+ prompts and context (names, domain), LLM knowledge

– slower (autoregressive), and **hallucinations**



LLM-ASR in Omnilingual ASR. Figure from (Omnilingual ASR team et al., 2025)

Omni models: speech in, speech out

- GPT-4o (OpenAI, 2024): one network for text, audio, image ; answers in 320ms on average (like humans)
- Qwen2.5-Omni (Xu et al., 2025a): **Thinker** (LLM, generates text) + **Talker** (generates speech tokens, streaming)
- Qwen3-Omni (Xu et al., 2025b): Thinker-Talker with mixture of experts
- Still **turn-based**: waits for the user to finish $\rightarrow$ next section





Figure from (Xu et al., 2025a)

Hallucinations: when WER is not enough

- Whisper (API, 2023): ≈1% of transcriptions contain entire hallucinated phrases, 38% of them harmful (Koenecke et al., 2024)
- More frequent for speakers with aphasia (1.7% vs. 1.2%), linked to longer non-vocal segments
- Autoregressive decoders can *invent* fluent text during pauses or non-speech audio
- WER counts it like any insertion → report hallucinations separately
- Mitigations: voice activity detection, CTC or joint decoding



Types of harm in hallucinated text. Figure from (Koenecke et al., 2024)

1 From waves to words

2 Going end-to-end

3 Listening without labels (SSL)

4 Speech as tokens


5 When LLMs learn to listen

6 Talking while listening (full duplex)

7 Is ASR solved?

From turn-based to full-duplex dialogue

- **Cascaded**: VAD + ASR + LLM + TTS ; seconds of latency, paralinguistics lost
- **Half-duplex** speech LLMs (omni models): one turn at a time
- **Full-duplex**: listen *and* speak at the same time, like humans



- Handle pauses, backchannels, overlaps and interruptions
- Two families (Chen and Yu, 2025): *engineered* synchronization (modules decide when to speak) vs. *learned* synchronization (end-to-end)

First steps: dGSLM, two speakers at once

- dGSLM (Nguyen et al., 2023): the first *textless* model of spoken dialogue
- Each channel (speaker) turned into HuBERT units ; a dual-tower Transformer with cross-attention models both streams in parallel
- Trained on 2,000h of two-channel telephone conversations (Fisher), no text, no labels
- Generates laughter, overlaps and natural turn-taking… but with little meaning




Figure from (Nguyen et al., 2023)

Moshi (Défossez et al., 2024)

- First real-time full-duplex spoken LLM: 160ms theoretical latency, 200ms in practice
- Speech in and out as Mimi tokens at 12.5Hz (see *Speech as tokens*)
- **Multi-stream**: the user's audio and Moshi's own audio are modeled in parallel, no explicit turns
- **Inner monologue**: Moshi also predicts the text of what it says




Figure from (Défossez et al., 2024)

Moshi: what is modeled at each time step

- Every 80ms: 8 user tokens (listened), 8 Moshi tokens + 1 text token (generated)
- Silence is a token too: Moshi can speak, listen, or both
- Text aligned with speech (PAD tokens between words)
- Inner monologue: almost $\times 3$ spoken QA accuracy




Figure from (Défossez et al., 2024)

Moshi: RQ-Transformer and training

- **Temporal Transformer**: Helium, a 7B text LLM (2.1T tokens), over time steps
- Small **Depth Transformer**: the 17 tokens of a step, one after the other
- Training: 7M hours of audio (mostly English, Whisper transcripts) ; Fisher for multi-stream ; 20K+ hours of synthetic dialogues with one voice for Moshi




Figure from (Défossez et al., 2024)

Moshi: performance and limitations

- Outperforms models like SpeechGPT in spoken QA, but loses knowledge compared to Helium (its text LLM)
- The same model does streaming ASR (5.7% WER on Librispeech clean, vs. 3.6% for a streaming FastConformer) and streaming TTS
- Quantization hurts linguistic performance more than audio quality
- Open challenges: safety, toxic audio generation, voice misuse
- Open model: many successors build on it (PersonaPlex, MoshiRAG…)

After Moshi (2024-2026)

- **Frozen or aligned LLMs**: Freeze-Omni (Wang et al., 2024), MinMo (Chen et al., 2025) keep the text LLM's knowledge
- **One sequence for both speakers**: OmniFlatten (Zhang et al., 2024) flattens speech and text streams for a GPT-style model
- **No codec inside the LLM**: SALMONN-omni (Yu et al., 2025) with a "thinking" mechanism to decide when to speak or listen ; +30% relative over open full-duplex models
- **Control**: PersonaPlex (Roy et al., 2026) (NVIDIA, fine-tuned from Moshi): role from a text prompt, voice from a speech sample, trained on synthetic dialogues
- **Controllable behaviour**: F-Actor (Züfle et al., 2026) (next slide)

F-Actor: controllable conversational behaviour

- First open, instruction-following full-duplex model trainable on an academic budget (Züfle et al., 2026)
- Instructions control voice, topic, behaviour (number of backchannels, interruptions) and who starts the dialogue
- Frozen audio encoder, only the LLM is fine-tuned: 2,000 hours of data, single-stage training ; model and code released




Figure from (Züfle et al., 2026)

Evaluating full-duplex models

- **Full-Duplex-Bench** (Lin et al., 2025b): pause handling, backchanneling, turn-taking, interruption management (automatic metrics) ; v2 (Lin et al., 2025a): multi-turn tasks with an automated examiner
- **Talking Turns** (Arora et al., 2025): a judge model trained on human conversations ; systems often do not know when to speak, interrupt too aggressively and rarely backchannel
- **When to take the floor?** (Peng et al., 2026): models speak when addressed or after silence, but rarely to correct a false claim (14–15% of replies) or warn of danger (4–7%)

Full-duplex models sound natural, but *when* and *what* to say still require real understanding of the conversation

1. From waves to words
2. Going end-to-end
3. Listening without labels (SSL)
4. Speech as tokens
5. When LLMs learn to listen
6. Talking while listening (full duplex)
7. Is ASR solved?

Is ASR solved?


Solved as a benchmark, not as a technology for everyone

- ✔ **Yes**: clean, read or broadcast speech in ≈100 well-resourced languages: open models reach ≈5% WER, close to human transcribers, in real time on a laptop
- ✖ **No**: for most of the world's languages, for many speakers (accents, children, atypical speech), in real conversations, and wherever we need to *trust* the output
- ➔ **And the job has changed**: ASR is now the ears of conversational agents, which must listen *while* speaking

Five challenges: languages, speakers, trust, conversations, agents

Challenge 1: the long tail of languages

- 7,000+ languages ; supported: Whisper 99 (Radford et al., 2022), USM 100+ (Zhang et al., 2023c), MMS 1,100+ (Pratap et al., 2023), Omnilingual 1,600+ (Omnilingual ASR team et al., 2025)
- Very uneven quality: Whisper large-v3 from ≈3% to 50%+ error rate
- Still open: dialects, code-switching, unwritten languages



from Laura Welcher - Big Data for Small Languages The Rosetta Project

Challenge 2: not all speakers are equal

- "Human parity" on Switchboard in 2016 (Xiong et al., 2016)… but not for everyone
- Accented speech: much larger gap between humans and machines (table)
- Stuttered and dysarthric speech: WER 2–5× higher than on the leaderboard, up to 24× with hallucination bursts (Dhaka et al., 2026) ; more hallucinations for speakers with aphasia (Koenecke et al., 2024)
- Children, elderly, non-native speakers: under-represented ; report results per group

Accented Speech			
Test set	DS1	DS2	Human
VoxForge American-Canadian	15.01	7.55	4.85
VoxForge Commonwealth	28.46	13.56	8.15
VoxForge European	31.20	17.55	12.76
VoxForge Indian	45.35	22.44	22.15

Accented speech, table from (Amodei et al., 2016)

Challenge 3: trust and evaluation beyond WER


- Standard benchmarks saturate: ≈5% average WER for the best systems
- Hallucinations: fluent, invented text (≈1% of Whisper transcriptions, 38% of them harmful (Koenecke et al., 2024))
- WER treats all errors the same:

REF	do not take this medicine		
HYP A	do not take these medicine	WER 20%	meaning kept
HYP B	do – take this medicine	WER 20%	meaning reversed

- Towards: semantic metrics (e.g. BERTScore), errors on names and keywords, hallucination rates, LLM judges, task success

Challenge 4: real conversations

- Overlapping speech, many speakers, far-field microphones, long recordings
- “Who said what, when”: ASR + diarization, e.g. distant meeting transcription in NOTSOFAR-1 (Vinnikov et al., 2024)
- Long-form audio: the same models make 1.5–2$\times$ more errors ; LLM decoders also get much slower (Canary-Qwen: RTFx 418 $\rightarrow$ 16)



Data from (Srivastav et al., 2025)

Challenge 5: ASR inside conversational agents

- **ASR is the ears of agents**: errors propagate to actions
- **Speed**: humans leave ≈200ms between turns (Stivers et al., 2009) ; voice agents calling tools still need 4–10s (Lin et al., 2026)
- **Full duplex**: listen while speaking (echo, barge-in), know *when* to speak (Peng et al., 2026), keep the LLM's knowledge
- **Streaming, on-device** ASR: privacy, cost
- **Multimodal, multi-party conversation** (embodied AI, robots)
  - who is speaking, and *to whom*? gaze, head pose, body posture (Mazzola et al., 2023)
  - hard for LLMs: GPT-4o barely above chance on three-party addressee recognition (Inoue et al., 2025) ; multimodal LLMs below humans (Fukuda et al., 2026)
  - first audio-visual full-duplex models (Huang et al., 2026)

Resources

- Follow me on Twitter/X: Go to @laurent_besacie
- Blog on Multimodal Speech-Text Models: Read the Blog Post
- Research on Multimodal NLP for Robotics: Read Naver Labs Research Page on Multimodal NLP for Robotics
- Notebook (in French) on ASR and Multimodal Foundation Models: Link
- Open ASR Leaderboard: huggingface.co/spaces/hf-audio/open_asr_leaderboard
- Curated list of full-duplex models and benchmarks: github.com/Ruiqi-Yan/Awesome-Full-Duplex-SDM
- Hugging Face Audio Course (hands-on ASR, Whisper fine-tuning, TTS): huggingface.co/learn/audio-course
- Moshi code and models: github.com/kyutai-labs/moshi

Questions?

Thank you

References I

Amodei, D., Anubhai, R., Battenberg, E., Case, C., Casper, J., Catanzaro, B., Chen, J., Chrzanowski, M., Coates, A., Diamos, G., Elsen, E., Engel, J., Fan, L., Fougner, C., Hannun, A. Y., Jun, B., Han, T., LeGresley, P., Li, X., Lin, L., Narang, S., Ng, A. Y., Ozair, S., Prenger, R., Qian, S., Raiman, J., Satheesh, S., Seetapun, D., Sengupta, S., Wang, C., Wang, Y., Wang, Z., Xiao, B., Xie, Y., Yogatama, D., Zhan, J., and Zhu, Z. (2016). Deep speech 2 : End-to-end speech recognition in english and mandarin. In Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016, pages 173–182.

Ao, J., Wang, R., Zhou, L., Liu, S., Ren, S., Wu, Y., Ko, T., Li, Q., Zhang, Y., Wei, Z., et al. (2021). Speecht5: Unified-modal encoder-decoder pre-training for spoken language processing. arXiv preprint arXiv:2110.07205.

Arora, S., Lu, Z., Chiu, C.-C., Pang, R., and Watanabe, S. (2025). Talking turns: Benchmarking audio foundation models on turn-taking dynamics. arXiv preprint arXiv:2503.01174.

Babu, A., Wang, C., Tjandra, A., Lakhotia, K., Xu, Q., Goyal, N., Singh, K., von Platen, P., Saraf, Y., Pino, J., Baevski, A., Conneau, A., and Auli, M. (2021). Xls-r: Self-supervised cross-lingual speech representation learning at scale. arXiv, abs/2111.09296.

Baevski, A., Hsu, W.-N., Xu, Q., Babu, A., Gu, J., and Auli, M. (2022). data2vec: A general framework for self-supervised learning in speech, vision and language. In Proceedings of ICML.

References II

Baevski, A., Zhou, Y., Mohamed, A., and Auli, M. (2020). wav2vec 2.0: A framework for self-supervised learning of speech representations. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H., editors, Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual.

Bahdanau, D., Cho, K., and Bengio, Y. (2014). Neural machine translation by jointly learning to align and translate. CoRR, abs/1409.0473.

Bengio, Y., Ducharme, R., Vincent, P., and Janvin, C. (2003). A neural probabilistic language model. J. Mach. Learn. Res., 3:1137–1155.

Borsos, Z., Marinier, R., Vincent, D., Kharitonov, E., Pietquin, O., Sharifi, M., Roblek, D., et al. (2022). AudioLM: a language modeling approach to audio generation. arXiv preprint arXiv:2209.03143.

Chen, Q., Chen, Y., Chen, Y., Chen, M., Chen, Y., Deng, C., et al. (2025). MinMo: A multimodal large language model for seamless voice interaction. arXiv preprint arXiv:2501.06282.

Chen, S., Wang, C., Chen, Z., Wu, Y., Liu, S., Chen, Z., et al. (2022). WavLM: Large-scale self-supervised pre-training for full stack speech processing. IEEE Journal of Selected Topics in Signal Processing.

Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. (2020). A simple framework for contrastive learning of visual representations.

References III

Chen, Y. and Yu, H. (2025). From turn-taking to synchronous dialogue: A survey of full-duplex spoken language models. arXiv preprint arXiv:2509.14515.

Chen, Z., Huang, H., Andrusenko, A., Hrinchuk, O., Puvvada, K. C., Li, J., Ghosh, S., Balam, J., and Ginsburg, B. (2023). Salm: Speech-augmented language model with in-context learning for speech recognition and translation.

Chorowski, J., Bahdanau, D., Serdyuk, D., Cho, K., and Bengio, Y. (2015a). Attention-based models for speech recognition. CoRR, abs/1506.07503.

Chorowski, J. K., Bahdanau, D., Serdyuk, D., Cho, K., and Bengio, Y. (2015b). Attention-Based Models for Speech Recognition. In Advances in Neural Information Processing Systems (NIPS 2015).

Chu, Y., Xu, J., Yang, Q., Wei, H., Wei, X., Guo, Z., et al. (2024). Qwen2-Audio technical report. arXiv preprint arXiv:2407.10759.

Chu, Y., Xu, J., Zhou, X., Yang, Q., Zhang, S., Yan, Z., et al. (2023). Qwen-Audio: Advancing universal audio understanding via unified large-scale audio-language models. arXiv preprint arXiv:2311.07919.

Chung, Y., Hsu, W., Tang, H., and Glass, J. R. (2019). An unsupervised autoregressive model for speech representation learning. CoRR, abs/1904.03240.

Chung, Y.-A. and Glass, J. (2020). Improved speech representations with multi-target autoregressive predictive coding.

References IV

Chung, Y.-A., Zhang, Y., Han, W., Chiu, C.-C., Qin, J., Pang, R., and Wu, Y. (2021). W2v-BERT: Combining contrastive learning and masked language modeling for self-supervised speech pre-training. In Proceedings of ASRU.

Défossez, A., Copet, J., Synnaeve, G., and Adi, Y. (2022). High fidelity neural audio compression. arXiv preprint arXiv:2210.13438.

Devlin, J., Chang, M., Lee, K., and Toutanova, K. (2018). BERT: pre-training of deep bidirectional transformers for language understanding. CoRR, abs/1810.04805.

Dhaka, A., Mathur, A., Mujtaba, D., Gerlach-Houck, H., Herring, C., Johnson, C., et al. (2026). WER are we (really): How well do top open ASR leaderboard models generalize to nonstandard speech? In Proceedings of Interspeech.

Défossez, A., Mazaré, L., Orsini, M., Royer, A., Pérez, P., Jégou, H., Grave, E., and Zeghidour, N. (2024). Moshi: a speech-text foundation model for real-time dialogue.

Fukuda, R., Kano, T., Arora, S., Delcroix, M., Tawara, N., Ogawa, A., et al. (2026). Evaluating large language models abilities for addressee, turn-change, and next speaker prediction in meetings. arXiv preprint arXiv:2606.17542.

Graves, A. (2012). Sequence transduction with recurrent neural networks. arXiv preprint arXiv:1211.3711.

References V

Graves, A., Fernández, S., Gomez, F. J., and Schmidhuber, J. (2006). Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks. In ICML, volume 148 of ACM International Conference Proceeding Series, pages 369–376. ACM.

Gulati, A., Qin, J., Chiu, C., Parmar, N., Zhang, Y., Yu, J., Han, W., Wang, S., Zhang, Z., Wu, Y., and Pang, R. (2020). Conformer: Convolution-augmented transformer for speech recognition. In Meng, H., Xu, B., and Zheng, T. F., editors, Interspeech 2020, 21st Annual Conference of the International Speech Communication Association, Virtual Event, Shanghai, China, 25-29 October 2020, pages 5036–5040. ISCA.

Hinton, G., Deng, L., Yu, D., Dahl, G. E., Mohamed, A.-r., Jaitly, N., Senior, A., Vanhoucke, V., Nguyen, P., Sainath, T. N., et al. (2012). Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. Signal Processing Magazine, IEEE, 29(6):82–97.

Hinton, G. and Salakhutdinov, R. (2006). Reducing the dimensionality of data with neural networks. Science, 313(5786):504 – 507.

Hsu, W., Bolte, B., Tsai, Y. H., Lakhotia, K., Salakhutdinov, R., and Mohamed, A. (2021). Hubert: Self-supervised speech representation learning by masked prediction of hidden units. CoRR, abs/2106.07447.

References VI

Huang, M., Zhang, L., Yu, X., Shi, L., Ma, Z., Xu, J., et al. (2026). DuplexOmni: Real-time listening, seeing, thinking, and speaking for full-duplex interaction. arXiv preprint arXiv:2606.09186.

Inoue, K., Lala, D., Elmers, M., Ochi, K., and Kawahara, T. (2025). An LLM benchmark for addressee recognition in multi-modal multi-party dialogue. arXiv preprint arXiv:2501.16643.

Kingma, D. P. and Welling, M. (2013). Auto-encoding variational bayes.

Koenecke, A., Choi, A. S. G., Mei, K. X., Schellmann, H., and Sloane, M. (2024). Careless Whisper: Speech-to-text hallucination harms. In Proceedings of ACM FAccT.

Lakhotia, K., Kharitonov, E., Hsu, W.-N., Adi, Y., Polyak, A., Bolte, B., Nguyen, T.-A., et al. (2021). Generative spoken language modeling from raw audio. Transactions of the Association for Computational Linguistics.

Lin, G.-T., Chen, C., Chen, Z., and yi Lee, H. (2026). Full-Duplex-Bench-v3: Benchmarking tool use for full-duplex voice agents under real-world disfluency. arXiv preprint arXiv:2604.04847.

Lin, G.-T., Kuan, S.-Y. S., Shi, J., Chang, K.-W., Arora, S., Watanabe, S., et al. (2025a). Full-Duplex-Bench-v2: A multi-turn evaluation framework for duplex dialogue systems with an automated examiner. arXiv preprint arXiv:2510.07838.

References VII

Lin, G.-T., Lian, J., Li, T., Wang, Q., Anumanchipalli, G., Liu, A. H., et al. (2025b). Full-Duplex-Bench: A benchmark to evaluate full-duplex spoken dialogue models on turn-taking capabilities. In Proceedings of ASRU.

Liu, A. H., Ehrenberg, A., Lo, A., Denoix, C., Barreau, C., Lample, G., et al. (2025). Voxtral. arXiv preprint arXiv:2507.13264.

Liu, A. T., Yang, S.-w., Chi, P.-H., Hsu, P.-c., and Lee, H.-y. (2020). Mockingjay: Unsupervised speech representation learning with deep bidirectional transformer encoders. ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP).

Mazzola, C., Romeo, M., Rea, F., Sciutti, A., and Cangelosi, A. (2023). To whom are you talking? a deep learning model to endow social robots with addressee estimation skills. arXiv preprint arXiv:2308.10757.

Mikolov, T., Karafiát, M., Burget, L., Černocký, J., and Khudanpur, S. (2010). Recurrent neural network based language model. In Interspeech.

Nguyen, T. A., Kharitonov, E., Copet, J., Adi, Y., Hsu, W.-N., Elkahky, A., et al. (2023). Generative spoken dialogue language modeling. Transactions of the Association for Computational Linguistics.

Omnilingual ASR team, Keren, G., Kozhevnikov, A., Meng, Y., Ropers, C., Setzler, M., et al. (2025). Omnilingual ASR: Open-source multilingual speech recognition for 1600+ languages. arXiv preprint arXiv:2511.09690.

References VIII

OpenAI (2024). GPT-4o system card. arXiv preprint arXiv:2410.21276.

Pascual, S., Ravanelli, M., Serrà, J., Bonafonte, A., and Bengio, Y. (2019). Learning problem-agnostic speech representations from multiple self-supervised tasks. CoRR, abs/1904.03416.

Peng, L., Nuchged, B., Fu, K., and Yao, Y. (2026). Full-duplex speech models take the floor when asked, not when needed. arXiv preprint arXiv:2609.19596.

Peng, Y., Tian, J., Yan, B., Berrebbi, D., Chang, X., Li, X., et al. (2023). Reproducing Whisper-style training using an open-source toolkit and publicly available data. arXiv preprint arXiv:2309.13876.

Povey, D., Ghoshal, A., Boulianne, G., Burget, L., Glembek, O., Goel, N., Hannemann, M., Motlicek, P., Qian, Y., Schwarz, P., Silovsky, J., Stemmer, G., and Vesely, K. (2011). The kaldi speech recognition toolkit. In IEEE 2011 Workshop on Automatic Speech Recognition and Understanding. IEEE Signal Processing Society. IEEE Catalog No.: CFP11SRW-USB.

Pratap, V., Tjandra, A., Shi, B., Tomasello, P., Babu, A., Kundu, S., et al. (2023). Scaling speech technology to 1,000+ languages. arXiv preprint arXiv:2305.13516.

Radford, A., Kim, J. W., Xu, T., Brockman, G., McLeavey, C., and Sutskever, I. (2022). Robust speech recognition via large-scale weak supervision.

Ravanelli, M., Zhong, J., Pascual, S., Swietojanski, P., Monteiro, J., Trmal, J., and Bengio, Y. (2020). Multi-task self-supervised learning for robust speech recognition.

References IX

Renals, S., Morgan, N., Bourlard, H., Cohen, M., and Franco, H. (1994). Connectionist probability estimators in HMM speech recognition. IEEE Trans. Speech and Audio Processing, 2(1):161–174.

Roy, R., Raiman, J., gil Lee, S., Ene, T.-D., Kirby, R., Kim, S., et al. (2026). PersonaPlex: Voice and role control for full duplex conversational speech models. arXiv preprint arXiv:2602.06053.

Schneider, S., Baevski, A., Collobert, R., and Auli, M. (2019). wav2vec: Unsupervised pre-training for speech recognition. CoRR, abs/1904.05862.

Song, X., Wang, G., Wu, Z., Huang, Y., Su, D., Yu, D., and Meng, H. (2019). Speech-xlnet: Unsupervised acoustic model pretraining for self-attention networks.

Srivastav, V., Zheng, S., Bezzam, E., Bihan, E. L., Koluguri, N. R., Żelasko, P., et al. (2025). Open ASR leaderboard: Towards reproducible and transparent multilingual and long-form speech recognition evaluation. arXiv preprint arXiv:2510.06961.

Stivers, T., Enfield, N. J., Brown, P., Englert, C., Hayashi, M., Heinemann, T., Hoymann, G., Rossano, F., de Ruiter, J. P., Yoon, K.-E., and Levinson, S. C. (2009). Universals and cultural variation in turn-taking in conversation. Proceedings of the National Academy of Sciences, 106(26):10587–10592.

Tang, C., Yu, W., Sun, G., Chen, X., Tan, T., Li, W., et al. (2024). SALMONN: Towards generic hearing abilities for large language models. In Proceedings of ICLR.

References X

van den Oord, A., Li, Y., and Vinyals, O. (2018). Representation learning with contrastive predictive coding. CoRR, abs/1807.03748.

van den Oord, A., Vinyals, O., and kavukcuoglu, k. (2017). Neural discrete representation learning. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., and Garnett, R., editors, Advances in Neural Information Processing Systems 30, pages 6306–6315. Curran Associates, Inc.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., and Polosukhin, I. (2017). Attention is all you need. CoRR, abs/1706.03762.

Vincent, P., Larochelle, H., Bengio, Y., and Manzagol, P.-A. (2008). Extracting and composing robust features with denoising autoencoders.

Vinnikov, A., Ivry, A., Hurvitz, A., Abramovski, I., Koubi, S., et al. (2024). NOTSOFAR-1 challenge: New datasets, baseline, and tasks for distant meeting transcription. arXiv preprint arXiv:2401.08887.

Wang, W., Tang, Q., and Livescu, K. (2020). Unsupervised pre-training of bidirectional speech encoders via masked reconstruction.

Wang, X., Li, Y., Fu, C., Shen, Y., Xie, L., Li, K., et al. (2024). Freeze-Omni: A smart and low latency speech-to-speech dialogue model with frozen LLM. arXiv preprint arXiv:2411.00774.

References XI

Wu, J., Gaur, Y., Chen, Z., Zhou, L., Zhu, Y., Wang, T., Li, J., Liu, S., Ren, B., Liu, L., and Wu, Y. (2023). On decoder-only architecture for speech-to-text and large language model integration.

Xiong, W., Droppo, J., Huang, X., Seide, F., Seltzer, M., Stolcke, A., et al. (2016). Achieving human parity in conversational speech recognition. arXiv preprint arXiv:1610.05256.

Xu, H., Jia, F., Majumdar, S., Huang, H., Watanabe, S., and Ginsburg, B. (2023). Efficient sequence transduction by jointly predicting tokens and durations. arXiv preprint arXiv:2304.06795.

Xu, J., Guo, Z., He, J., Hu, H., He, T., Bai, S., et al. (2025a). Qwen2.5-Omni technical report. arXiv preprint arXiv:2503.20215.

Xu, J., Guo, Z., Hu, H., Chu, Y., Wang, X., He, J., et al. (2025b). Qwen3-Omni technical report. arXiv preprint arXiv:2509.17765.

Yu, W., Wang, S., Yang, X., Chen, X., Tian, X., Zhang, J., et al. (2025). SALMONN-omni: A standalone speech LLM without codec injection for full-duplex conversation. arXiv preprint arXiv:2505.17060.

Zanon Boito, M., Iyer, V., Lagos, N., Besacier, L., and Calapodescu, I. (2024). mHuBERT-147: A compact multilingual HuBERT model. In Proceedings of Interspeech.

Zeghidour, N., Luebs, A., Omran, A., Skoglund, J., and Tagliasacchi, M. (2021). SoundStream: An end-to-end neural audio codec. arXiv preprint arXiv:2107.03312.

References XII

Zhang, D., Li, S., Zhang, X., Zhan, J., Wang, P., Zhou, Y., and Qiu, X. (2023a). Speechgpt: Empowering large language models with intrinsic cross-modal conversational abilities.

Zhang, Q., Cheng, L., Deng, C., Chen, Q., Wang, W., Zheng, S., et al. (2024). OmniFlatten: An end-to-end GPT model for seamless voice conversation. arXiv preprint arXiv:2410.17799.

Zhang, X., Zhang, D., Li, S., Zhou, Y., and Qiu, X. (2023b). SpeechTokenizer: Unified speech tokenizer for speech large language models. arXiv preprint arXiv:2308.16692.

Zhang, Y., Han, W., Qin, J., Wang, Y., Bapna, A., Chen, Z., et al. (2023c). Google USM: Scaling automatic speech recognition beyond 100 languages. arXiv preprint arXiv:2303.01037.

Züfle, M., Klejch, O., Sanders, N., Niehues, J., Birch, A., and Lam, T. K. (2026). F-Actor: Controllable conversational behaviour in full-duplex models. arXiv preprint arXiv:2601.11329.