

1027

Code : 15CE53T

Register
Number

--	--	--	--	--	--	--	--	--	--

V Semester Diploma Examination, Oct./Nov.-2019

ESTIMATION & COSTING

Time : 3 Hours]

[Max. Marks : 100

- Note :**
- (i) Answer all Parts.
 - (ii) Missing data may be assumed suitably.
 - (iii) Assume suitable rates.


PART - A

Answer any **one** from the following :

1. (a) What is an estimate ? List the types of estimate. Explain any one of them. 10
(b) Differentiate between preliminary estimate and detailed estimate. 10
2. Write the detailed specification for any **one** of the following [(a) or (b)].
 - (a) (i) Plastering in cement mortar 1 : 6. 5
(ii) Distempering for internal wall two coats. 5
 - (b) (i) Define : 1. General specification. 5
2. Detailed specification 5
(ii) Cement concrete 1 : 2 : 4 for Damp proof course. 5
3. Prepare Rate Analysis for any **one** of the following [(a) or (b)].
 - (a) Cement concrete in foundation 1 : 2 : 4. 10
 - (b) R.C.C. for slab 1 : 15 : 3 including centering and shuttering laid in position with 90 kg/cum steel. complete in all. 10

PART - B

4. Prepare a detailed and abstract estimate for the following items of the plan of building as shown in Fig. 1 by CENTRE LINE METHOD. (any five item).

**Fig. 1**

- (i) CC bed 1 : 4 : 8 for foundation @ ₹ 3,800/m³. 10
- (ii) Burnt Brick Masonry (BBM) in cm 1 : 6 for super structure excluding parapet wall @ ₹ 4,700/m³. 10

- (iii) R.C.C. 1 : 1.5 : 3 for slab, lintex and chejja including centering shuttering laid in position @ ₹ 5,200/m³. 10
- (iv) Plastering with CM 1 : 6 for inside walls excluding ceiling plastering @ ₹ 160/m². 10
- (v) Enamel painting for Doors (fully panelled) windows (partly panelled and partly glazed) and ventilators (fully glazed) @ ₹ 110/m². 10
- (vi) Plastering with CM 1 : 6 for outside walls including Parapet and Chejja @ ₹ 140/m². 10
- (vii) Vitrified floor tiles of size 60 cm × 60 cm laid on 20 mm thick Cement Mortar 1 : 4 @ ₹ 1200/m². 10

PART - C

5. Prepare a detailed estimate for the following items of work for the construction of tar road for state highway 275 km from the following details :

- (i) Two laned with island park.
- (ii) Formation width – 18.00 m.
- (iii) Average height and bank – 1.20 m.
- (iv) Side slope – 2 : 1.
- (v) Metalled width on either side of island for roadway – 4.0 m on each lane.
- (vi) Soling coat for roadway and island - 9.80 m wide 200 mm thick.
- (vii) Intercoat on each lane – 4.0 m wide 15 cm compacted thickness.
- (viii) Top coat on each lane – 4.0 m wide, 15 cm compacted thickness.
- (ix) 15 cm × 60 cm granite side walls for island.
- (x) Filling island with fertilized soil 60 cm thick.
- (xi) Surface is finished with two coats bituminous painting to each lane.

Items of work to be estimated are :

20

- (a) Earth work in banking.
- (b) Soiling coat of boulder.
- (c) Intercoat of stone ballast 60 mm and down size.

[Turn over

(d) Top coat of stone ballast 40 mm and down size.

(e) Painting first coat with road for No. 3.

Note : (1) Take 20 mm gauge stone grit @ $1.35 \text{ m}^3 \text{ \% m}^2$.

(2) Binding tar @ 220 kg \% m^2 .

(f) Painting second coat with asphalt

Note : (1) Take 12 mm gauge stone grit @ $0.75 \text{ m}^3 \text{ \% m}^2$.

(2) Bitumen @ 120 kg \% m^2 .

(g) 15 cm \times 60 cm granite stone side wall (kerb) to island park.

OR

Determine the quantities of earth work for the portion of a road between chainages 0 to 10 from the following data, lengths being measured with standard 20 m chain.

Chainages	0	1	2	3	4	5	6	7	8	9
R.L. of Ground	231.1	231.2	230.9	231.2	230.8	230.7	230.6	230.4	229.1	229.5

The formation level @ 0 chainage is 230.0 and the road is in rising gradient of 1 in 200. The width of formation is 8 m and side slopes 1.5:1 in banking and 1 : 1 in cutting. The lateral slope of ground may be assumed as level.