

~ 1	1000	1121	1 FORES	•
0.0	0		15CE537	
-			LUCIOS.	

Register				
Number	1 8			

V Semester Diploma Examination, Nov./Dec. 2017

ESTIMATING & COSTING

Tin	ie : 3	Ho	urs [Max. Marks : 1	00
Note	e:	(1) (2)	Answer all the parts. Missing data may be assumed suitably.	
		3.0		
200	2000		PART – A	
1.	An		any one from the following (a or b):	
	(a)	(i)	What is an Estimate? List the purpose of Estimate.	5
		(ii)	What are the factors to be considered for deduction in openings in case of plastering?	5
			OR	
	(b)	(i)	State the rules for measurement of works for obtaining the quantities as per IS 1200.	5
		(ii)	Write short notes on lead statement.	5
2.	Wr	ite th	e detailed specification for any one of the following (a or b):	
	(a)	(i)	Pointing in cement Mortar 1:6	5
		(ii)	R.C.C. work of proportion 1:1½:3	5
			OR	
	(b)	(i)	Earthwork in Excavation in foundation.	5
		(ii	Centering and shuttering works. (Form work)	5
3.	Pre	pare	Rate analysis for any one of the following (a or b):	
	(a)	Fir	rst class brickwork in cement mortar 1:4 in superstructure (ground floor).	10
			OR	
	(b)	Vi	trified floor tiles of size 60 cm × 60 cm laid on 20 mm thick cement mortal	r
	16100	1:	4.	10
		**	1 of 4 Turn or	ver

PART - B

 Prepare a detailed and abstract estimate for the following items of the building as shown in Fig. 1 by <u>CENTRELINE METHOD</u>.




Fig. 1 (All dimensions in metres)

External Walla are 30 cm & Internal Walls 20 cm

Foundation Details Same for 20 cm & 30 cm Wall.

- Brick masonry in C.M. 1.: 6 for superstructure excluding parapet wall at ₹ 4,500 per m³.
- (ii) Plastering with C.M. for inside walls excluding ceiling plastering at ₹ 140 per m².
- (iii) Enamel painting for Doors (fully panelled). Windows (partly panelled and partly glazed), and ventilators (fully glazed) at ₹ 75 per m².
- (iv) C.C. bed 1:5:10 for foundation at ₹ 3600/m³.
- (v) S.S. masonry in C.M. 1: 6 for foundation and basement at ₹ 2,250.

PART-C

Answer any one from the following ('a' or 'b'):

(a) Estimate the quantity of earthwork of a road between chainages 10 to 15 measured with standard 50 m chain from the following data:

Chainage	10	11	12	13	14	15
Ground Level (m)	50	50.6	50.30 48.50	47.90	48.20	48.00
Formation Level (m)	49.50	Upward gradient of 1 in 200.				

The formation width is 8 m and side slopes in cutting 1:1 and banking 1.5:1.

OR

- (b) Prepare the detailed and abstract estimate of the following items of work for 800 m long and 4.00 m wide cement concrete road with 15 cm × 15 cm Kerbs and 1.50 m width, 7.5 cm thick stone slab footpath on either side of the road: 20
 - (i) C.C. 1: 4: 8 for depressions taking 0.30 m³ per 100 m² @ ₹ 1300 per cu.m.
 - (ii) C.C. 1:2:4 wearing coat using 12 mm grade granite aggregate of 15 cm thick @ ₹ 2400 per cu. m.
 - (iii) Surface coat of C.C. 1:2:4 of 10 cm thick using 10 mm grade aggregate@ ₹ 2500 per cu. m.
 - (iv) Single line dressed granite stone Kerb 15 cm × 15 cm fixing with C.M.
 1:4 @ ₹ 40 per running metre.
 - (v) 7.5 cm thick granite slab fixing with C.M. 1:3 and pointing @ ₹ 250 per sq. m.