

Experiment 3: Supplementary Analyses

Bethany Gardner

2022-07-07

Contents

Setup	1
Quadratic Name Gender Rating	2
Model	2
Main quadratic effect	4
Quadratic interaction	5
Participant Gender	8
Setup/Data Summary	8
Model	9

Setup

Variable names:

- Experiment: exp3
- Type
 - d = data
 - m = model
 - p = plot
 - est = log odds estimate from model
 - OR = odds ratio converted from est
- Analysis
 - quad = quadratic effect of Name Gender
 - gender = participant gender
- Subset
 - FF = First and Full Name conditions only
 - Last = Last Name condition only

Load data and select columns used in model. See data/exp3_data_about.txt for more details.

```
exp3_d <- read.csv("../data/exp3_data.csv", stringsAsFactors=TRUE) %>%
  rename("Participant"="SubjID", "Item"="Name") %>%
  select(Participant, SubjGender, Condition,
         GenderRating, Item, He, She, Other)

str(exp3_d)
```

```
## 'data.frame': 8904 obs. of 8 variables:
## $ Participant : Factor w/ 1272 levels "R_020U0b05Lb0EtX3",...: 216 216 216 216 216 216 216 41 41 41
## $ SubjGender : Factor w/ 7 levels "agender","asexual",...: 4 4 4 4 4 4 4 3 3 3 ...
## $ Condition : Factor w/ 3 levels "first","full",...: 1 1 1 1 1 1 1 1 1 1 ...
## $ GenderRating: num 5.22 1.24 5.86 3.75 6.78 4.34 2.41 6.24 2.61 6.82 ...
## $ Item : Factor w/ 63 levels "Ashley Cook",...: 6 9 13 43 47 52 62 2 16 20 ...
## $ He : int 0 1 0 0 0 0 1 0 1 0 ...
## $ She : int 0 0 1 0 1 1 0 0 0 1 ...
## $ Other : int 1 0 0 1 0 0 0 1 0 0 ...
```

Center gender rating for names: Original scale from 1 to 7, with 1 as most masculine and 7 as most feminine. Mean-centered with higher still as more feminine.

```
exp3_d %<>% mutate(GenderRatingCentered=
  scale(GenderRating, scale=FALSE))
```

Set contrasts for name conditions. This uses Scott Fraundorf's function for weighted contrasts. (The psycholing package version doesn't support doing 2v1 comparisons, only 1v1.) Condition1 is Last vs First+Full. Condition2 is First vs Full.

```
source("centerfactor.R")
contrasts(exp3_d$Condition) <- centerfactor(
  exp3_d$Condition, c("last", "first"))
contrasts(exp3_d$Condition)
```

```
##           [,1]      [,2]
## first 0.4009434 -0.48113208
## full 0.4009434 0.51886792
## last -0.5990566 0.01886792
```

Quadratic Name Gender Rating

The second supplementary analysis tested the quadratic effect of name gender rating, such that larger values meant names with stronger gender associations (masc or fem), and smaller values meant names with weaker gender associations.

```
exp3_d %<>% mutate(GenderRatingSquared=GenderRatingCentered^2)
```

Model

Quadratic name gender effect on the likelihood of *she* responses, as opposed to *he* and *other* responses. The maximal model includes random intercepts by item, but not by participant.

```

exp3_m_quad <- buildmer(
  She ~ Condition*GenderRatingCentered + Condition*GenderRatingSquared +
    (1|Participant) + (1|Item),
  exp3_d, family="binomial", direction=c("order"), quiet=TRUE)
summary(exp3_m_quad)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) (p-values based on Wald z-scores) [glmerMod]
## Family: binomial ( logit )
## Formula: She ~ 1 + GenderRatingCentered + GenderRatingSquared + Condition +
## GenderRatingCentered:Condition + GenderRatingSquared:Condition +
## (1 | Item)
## Data: exp3_d
##
##      AIC      BIC    logLik deviance df.resid
##  7979.5   8050.4  -3979.7   7959.5     8894
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.1120 -0.5443 -0.1467  0.6532 15.2267
##
## Random effects:
## Groups Name          Variance Std.Dev.
## Item (Intercept) 0.3002  0.5479
## Number of obs: 8904, groups: Item, 63
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|) Pr(>|t|)
## (Intercept)      -1.09643    0.11101 -9.87643  0.000 < 2e-16
## GenderRatingCentered      1.06982    0.05554 19.26236  0.000 < 2e-16
## GenderRatingSquared     -0.11378    0.03102 -3.66732  0.000 0.000245
## Condition1              0.23784    0.07935  2.99748  0.003 0.002722
## Condition2              0.05570    0.09965  0.55893  0.576 0.576208
## GenderRatingCentered:Condition1 0.22179    0.06115  3.62713  0.000 0.000287
## GenderRatingCentered:Condition2 -0.11288    0.08816 -1.28044  0.200 0.200391
## GenderRatingSquared:Condition1 -0.09635    0.02976 -3.23767  0.001 0.001205
## GenderRatingSquared:Condition2  0.03866    0.04184  0.92410  0.355 0.355432
##
## (Intercept)          ***
## GenderRatingCentered  ***
## GenderRatingSquared   ***
## Condition1            **
## Condition2
## GenderRatingCentered:Condition1 ***
## GenderRatingCentered:Condition2
## GenderRatingSquared:Condition1 **
## GenderRatingSquared:Condition2
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) GndrRC GndrRS Cndtn1 Cndtn2 GRC:C1 GRC:C2 GRS:C1
## GndrRtngCnt -0.093

```

```
## GndrRtnoSqr -0.638 -0.252
## Condition1 -0.005 -0.007 0.007
## Condition2 -0.007 0.014 -0.005 0.029
## GndrRtnC:C1 0.021 0.212 -0.189 -0.143 0.018
## GndrRtnC:C2 0.001 -0.099 0.078 0.018 -0.146 -0.090
## GndrRtnS:C1 -0.018 -0.191 0.175 -0.424 -0.032 -0.657 0.078
## GndrRtnS:C2 0.003 0.086 -0.073 -0.031 -0.361 0.081 -0.723 -0.053
```

Main quadratic effect


To make this easier to understand, plot the data converted to log odds. This includes just what the model is testing: *she* responses, no effects of Condition included yet.

```
exp3_d_log <- exp3_d %>%
  group_by(Condition, GenderRating) %>%
  summarise(He.Mean=mean(He),
            She.Mean=mean(She),
            Other.Mean=mean(Other)) %>%
  mutate(He.Log=log(He.Mean),
         She.Log=log(She.Mean),
         Other.Log=log(Other.Mean)) %>%
  mutate(Condition_Model=case_when(
    Condition=="first" ~ "First + Full",
    Condition=="full" ~ "First + Full",
    Condition=="last" ~ "Last"))
```

```
exp3_p_log <- ggplot(exp3_d_log,
  aes(x=GenderRating)) +
  geom_smooth(aes(y=She.Log), fill="red", color="red") +
  geom_point(aes(y=She.Log), fill="red", color="red") +
  geom_vline(xintercept=4) +
  theme_classic() +
  labs(title="Experiment 3: Log Odds of *She* Responses",
       x="Masculine - Feminine",
       y="Log Odds") +
  theme(text=element_text(size=16),
        plot.title=element_markdown())
exp3_p_log
```

```
## 'geom_smooth()' using method = 'loess' and formula 'y ~ x'
```

Experiment 3: Log Odds of *She* Responses



At the masculine end of the scale, *she* responses decrease more linearly. At the feminine end of the scale, *she* responses level off at around 5.5 (mostly feminine), then don't ever reach 0. Fewer *she* responses in 6-7 range than *he* responses in 1-2 range.


Quadratic interaction

Now, plot the comparison for the Last vs First+Full condition interaction.

```
exp3_p_quadCond <- ggplot(exp3_d_log,
  aes(x=GenderRating)) +
  geom_smooth(aes(y=She.Log), fill="red", color="red") +
  geom_point(aes(y=She.Log), fill="red", color="red") +
  geom_vline(xintercept=4) +
  facet_wrap(~Condition_Model) +
  theme_classic() +
  labs(title="Experiment 3: Log Odds of *She* Responses",
    x="Masculine - Feminine",
    y="Log Odds") +
  theme(text=element_text(size=16),
    plot.title=element_markdown())
exp3_p_quadCond
```

```
## 'geom_smooth()' using method = 'loess' and formula 'y ~ x'
```

Experiment 3: Log Odds of *She* Responses



Dummy code to get the quadratic effect just for First and Full Name conditions.

```
exp3_d$FFdummy = as.numeric(exp3_d$Condition)
exp3_d$FFdummy[exp3_d$FFdummy == 1] <- 0
exp3_d$FFdummy[exp3_d$FFdummy == 2] <- 0
exp3_d$FFdummy[exp3_d$FFdummy == 3] <- 1
with(exp3_d, tapply(FFdummy, list(Condition), mean))
```

```
## first  full  last
##      0     0     1
```

```
exp3_m_quadFF <- glmer(
  She ~ 1 + GenderRatingCentered + GenderRatingSquared +
    FFdummy + GenderRatingCentered:FFdummy +
    GenderRatingSquared:FFdummy + (1|Item),
  data=exp3_d, family=binomial)
summary(exp3_m_quadFF)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
##   Family: binomial   ( logit )
##   Formula: She ~ 1 + GenderRatingCentered + GenderRatingSquared + FFdummy +
##             GenderRatingCentered:FFdummy + GenderRatingSquared:FFdummy +
##             (1 | Item)
##   Data: exp3_d
```

```
##
##      AIC      BIC   logLik deviance df.resid
##  7975.4   8025.0 -3980.7   7961.4     8897
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.0991 -0.5411 -0.1463   0.6520 18.1600
##
## Random effects:
##   Groups Name      Variance Std.Dev.
##   Item   (Intercept) 0.3013   0.5489
## Number of obs: 8904, groups: Item, 63
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    -1.00084    0.11549  -8.666 < 2e-16 ***
## GenderRatingCentered    1.15391    0.06491  17.777 < 2e-16 ***
## GenderRatingSquared    -0.15028    0.03505  -4.288 1.8e-05 ***
## FFdummy           -0.23771    0.07930  -2.998 0.002720 **
## GenderRatingCentered:FFdummy -0.21927    0.06089  -3.601 0.000317 ***
## GenderRatingSquared:FFdummy  0.09520    0.02968   3.207 0.001339 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) GndrRC GndrRS FFdmmly GRC:FF
## GndrRtngCnt  -0.084
## GndrRtngSqr  -0.589 -0.385
## FFdummy      -0.270  0.057  0.140
## GndrRtnC:FF   0.018 -0.551  0.386 -0.142
## GndrRtnS:FF   0.136  0.405 -0.492 -0.426 -0.655
```

Dummy code to get the quadratic effect just for First and Full Name conditions.

```
exp3_d$Ldummy = as.numeric(exp3_d$Condition)
exp3_d$Ldummy[exp3_d$Ldummy == 1] <- 1
exp3_d$Ldummy[exp3_d$Ldummy == 2] <- 1
exp3_d$Ldummy[exp3_d$Ldummy == 3] <- 0
with(exp3_d, tapply(Ldummy, list(Condition), mean))
```

```
## first  full  last
##      1      1      0
```

```
exp3_m_quadL <- glmer(
  She ~ 1 + GenderRatingCentered + GenderRatingSquared +
    Ldummy + GenderRatingCentered:Ldummy +
    GenderRatingSquared:Ldummy + (1|Item),
  data=exp3_d, family=binomial)
summary(exp3_m_quadL)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
```

```
## Family: binomial ( logit )
## Formula: She ~ 1 + GenderRatingCentered + GenderRatingSquared + Ldummy +
##      GenderRatingCentered:Ldummy + GenderRatingSquared:Ldummy +      (1 | Item)
## Data: exp3_d
##
##      AIC      BIC   logLik deviance df.resid
##  7975.4   8025.0 -3980.7   7961.4     8897
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.0991 -0.5411 -0.1463   0.6520  18.1601
##
## Random effects:
## Groups Name      Variance Std.Dev.
## Item  (Intercept) 0.3013   0.5489
## Number of obs: 8904, groups: Item, 63
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)      -1.23855    0.12114 -10.224 < 2e-16 ***
## GenderRatingCentered    0.93465    0.05971  15.654 < 2e-16 ***
## GenderRatingSquared   -0.05508    0.03296  -1.671 0.094692 .
## Ldummy              0.23770    0.07930   2.998 0.002720 **
## GenderRatingCentered:Ldummy 0.21927    0.06089   3.601 0.000317 ***
## GenderRatingSquared:Ldummy -0.09520    0.02968  -3.207 0.001339 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) GndrRC GndrRS Ldummy GnRC:L
## GndrRtngCnt -0.124
## GndrRtngSqr -0.635 -0.231
## Ldummy      -0.397  0.083  0.235
## GndrRtngC:L  0.076 -0.421  0.180 -0.142
## GndrRtngS:L  0.150  0.228 -0.378 -0.426 -0.655
```

- Beta for quadratic gender rating in First + Full: -0.15028 ***
- Beta for quadratic gender rating in Last: -0.05508 .

Participant Gender

Setup/Data Summary

The third supplementary analysis looks at participant gender: if male participants show a larger bias towards *he* responses than non-male participants.

Participants entered their gender in a free-response box.

```
exp3_d %>% group_by(SubjGender) %>%
  summarise(total=n_distinct(Participant)) %>% kable()
```


SubjGender	total
agender	1
asexual	1
female	638
male	514
N/A	115
non-binary	2
Prefer not to say	1

For this analysis, we exclude participants who did not respond. Because there are not enough participants to create 3 groups, we compare male to non-male participants.

```
exp3_d_gender <- exp3_d %>%
  filter(SubjGender != "N/A") %>%
  filter(SubjGender != "Prefer not to say") %>%
  mutate(SubjGenderMale=(ifelse(SubjGender=="male", 1, 0)))

exp3_d_gender %>% group_by(SubjGenderMale) %>%
  summarise(total=n_distinct(Participant)) %>% kable()
```

SubjGenderMale	total
0	642
1	514

Summary of responses by condition and participant gender.

```
exp3_d_gender %<>% mutate(ResponseAll=case_when(
  He==1 ~ "He",
  She==1 ~ "She",
  Other==1 ~ "Other"))
```

Participant gender is mean centered effects coded, comparing non-male participants to male participants.

```
exp3_d_gender$SubjGenderMale %<>% as.factor()
contrasts(exp3_d_gender$SubjGenderMale)=cbind("NM_M"=c(-.5,.5))
contrasts(exp3_d_gender$SubjGenderMale)
```

```
##    NM_M
## 0 -0.5
## 1  0.5
```

Model

Effects of Name Condition (first name, full name), the first name's Gender Rating (centered, positive=more feminine), and Participant Gender (non-male vs. male) on the likelihood of a *she* response as opposed to *he* or *other* responses. The maximal model contains random intercepts by item and by participant.

```
exp3_m_gender <- buildmer(
  formula= (She ~ Condition * GenderRatingCentered * SubjGenderMale +
    (1|Participant) + (1|Item)),
  data=exp3_d_gender, family=binomial,
  direction=c("order"), quiet=TRUE)

summary(exp3_m_gender)
```

```

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) (p-values based on Wald z-scores) [glmerMod]
## Family: binomial ( logit )
## Formula: She ~ 1 + GenderRatingCentered + SubjGenderMale + Condition +
## GenderRatingCentered:Condition + SubjGenderMale:Condition +
## GenderRatingCentered:SubjGenderMale + GenderRatingCentered:SubjGenderMale:Condition +
## (1 | Item) + (1 | Participant)
## Data: exp3_d_gender
##
##      AIC      BIC    logLik deviance df.resid
## 7061.6    7159.6   -3516.8   7033.6     8078
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.0837 -0.4716 -0.1392  0.5318  9.8646
##
## Random effects:
## Groups      Name      Variance Std.Dev.
## Participant (Intercept) 0.7527   0.8676
## Item         (Intercept) 0.4478   0.6692
## Number of obs: 8092, groups: Participant, 1156; Item, 63
##
## Fixed effects:
##
##                                     Estimate Std. Error
## (Intercept)                        -1.58004    0.10545
## GenderRatingCentered                 1.14763    0.06289
## SubjGenderMaleNM_M                  -0.33908    0.09599
## Condition1                          0.19527    0.09836
## Condition2                          0.13618    0.12205
## GenderRatingCentered:Condition1      0.11311    0.05254
## GenderRatingCentered:Condition2     -0.07906    0.06655
## SubjGenderMaleNM_M:Condition1        0.12026    0.19714
## SubjGenderMaleNM_M:Condition2        0.04670    0.24325
## GenderRatingCentered:SubjGenderMaleNM_M -0.01729    0.05160
## GenderRatingCentered:SubjGenderMaleNM_M:Condition1 0.09439    0.10525
## GenderRatingCentered:SubjGenderMaleNM_M:Condition2 -0.04577    0.13265
##
##                                     z value Pr(>|z|) Pr(>|t|)
## (Intercept)                    -14.98390    0.000 < 2e-16
## GenderRatingCentered            18.24796    0.000 < 2e-16
## SubjGenderMaleNM_M              -3.53234    0.000 0.000412
## Condition1                      1.98527    0.047 0.047114
## Condition2                      1.11575    0.265 0.264530
## GenderRatingCentered:Condition1  2.15265    0.031 0.031346
## GenderRatingCentered:Condition2 -1.18807    0.235 0.234805
## SubjGenderMaleNM_M:Condition1    0.60999    0.542 0.541870
## SubjGenderMaleNM_M:Condition2    0.19201    0.848 0.847738
## GenderRatingCentered:SubjGenderMaleNM_M -0.33515    0.738 0.737512
## GenderRatingCentered:SubjGenderMaleNM_M:Condition1 0.89678    0.370 0.369837
## GenderRatingCentered:SubjGenderMaleNM_M:Condition2 -0.34504    0.730 0.730061
##
## (Intercept)                    ***
## GenderRatingCentered            ***
## SubjGenderMaleNM_M              ***
## Condition1                      *

```

```

## Condition2
## GenderRatingCentered:Condition1
## GenderRatingCentered:Condition2
## SubjGenderMaleNM_M:Condition1
## SubjGenderMaleNM_M:Condition2
## GenderRatingCentered:SubjGenderMaleNM_M
## GenderRatingCentered:SubjGenderMaleNM_M:Condition1
## GenderRatingCentered:SubjGenderMaleNM_M:Condition2
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) GndrRC SbGMNM_M Cndtn1 Cndtn2 GRC:C1 GRC:C2 SGMNM_M:C1
## GndrRtnGnt -0.300
## SbJGndMNM_M  0.090 -0.063
## Condition1 -0.016  0.005 -0.054
## Condition2 -0.032  0.029  0.012  0.002
## GndrRtnC:C1 -0.001  0.014  0.022 -0.519  0.015
## GndrRtnC:C2  0.030 -0.042  0.001  0.014 -0.507 -0.015
## SbGMNM_M:C1 -0.027  0.012 -0.036  0.191  0.017 -0.125 -0.004
## SbGMNM_M:C2  0.005  0.002 -0.047  0.017  0.133 -0.004 -0.100 -0.001
## GnRC:SGMNM_M -0.062  0.074 -0.517  0.023  0.001 -0.039  0.008  0.019
## GRC:SGMNM_M:C1  0.008 -0.011  0.018 -0.125 -0.003  0.176  0.012 -0.520
## GRC:SGMNM_M:C2  0.003  0.000  0.042 -0.004 -0.100  0.013  0.129  0.015
##      SGMNM_M:C2 GnRC:SGMNM_M GRC:SGMNM_M:C1
## GndrRtnGnt
## SbJGndMNM_M
## Condition1
## Condition2
## GndrRtnC:C1
## GndrRtnC:C2
## SbGMNM_M:C1
## SbGMNM_M:C2
## GnRC:SGMNM_M  0.042
## GRC:SGMNM_M:C1  0.015 -0.001
## GRC:SGMNM_M:C2 -0.506 -0.066 -0.016

```

- Male participants less likely to produce *she* responses overall
- No interactions with participant gender significant