CONFIDENTIAL

PASSIVE FOOTPRINTING & RECONNAISSANCE

INTELLIGENCE REPORT

Open-source intelligence assessment of the Miahnation Financial Group external footprint, collected without touching the target systems.

Client	Miahnation Financial Group
Date	2 October 2026 (reconnaissance performed 1 October 2026)
Analyst	Bethel Onochie, Junior Security Analyst, Miahnation Security Labs
Classification	Confidential
Primary target	miahnationsecurity.site (authorised practice domain)
Secondary target	hackthissite.org (authorised practice target, used for Google dorking)
Reference domain	miahnationfinancial.com (fictional client domain, reference only)

Rules of engagement. Passive techniques only. No packets were sent to the target systems other than ordinary public DNS and WHOIS lookups. All sources used were public.

SECTION 00

Engagement Overview & Method

Miahnation Security Labs asked for an intelligence picture of Miahnation Financial Group, a London-based FinTech, built purely from public information before any active testing begins. The work followed four steps: **Collect** facts from public sources, **Correlate** domains, IPs and services, **Document** commands and screenshots, and **Interpret** what each discovery means for security.

#	Activity	Tool / command	Report section
1	Domain registration lookup	`whois`	1. Domain Information
2	DNS enumeration	`dig A / MX / NS / TXT, dig -x`	2. DNS Configuration
3	IP ownership lookup	`whois -h whois.arin.net`	3. IP Ownership
4	Google dorking (7 queries)	Google search operators	4. Exposed Information
5	Subdomain enumeration	`subfinder, amass enum -passive`	5. Subdomains Discovered
6	Email and host harvesting	`theHarvester -b all`	6. Email Addresses Found

Scope and evidence notes

- All active findings (WHOIS, DNS, ARIN, subdomains, harvesting) relate to **miahnationsecurity.site**, the authorised practice domain standing in for the client. The Google dorks were run against **hackthissite.org** or globally, as the brief specifies.
- Sublist3r could not be run because of dependency problems, so **Subfinder** (also passive) was used instead. OWASP Amass failed with a network error and returned no data.
- The submitted evidence does not include a WHOIS screenshot for hackthissite.org or a `dig ANY` output. These are flagged as gaps and should be added before final submission.
- DNS lookups were answered by a local resolver (192.168.43.x). Several lookups logged a one-off timeout before succeeding on retry; results were not affected.

SECTION 01

Domain Information

WHOIS lookup of `miahnationsecurity.site`.

Registrar	NameCheap, Inc. (IANA ID 1068)
Registration date	28 August 2026
Expiry date	28 August 2027 (one-year registration)
Last updated	2 September 2026
Name servers	dns1.registrar-servers.com, dns2.registrar-servers.com
Registrant details	Not visible. Redacted under ICANN's Temporary Specification for gTLD registration data.
Privacy protection	Yes. Registrant data is redacted by the registry.
Domain status	clientTransferProhibited (registrar transfer lock enabled)
DNSSEC	Unsigned
Registrar abuse contact	abuse@namecheap.com, +1 985 401 4545

Interpretation. The domain is only a few weeks old, the registrant is hidden and a transfer lock is in place. Privacy redaction and the lock are good practice. The absence of DNSSEC means DNS answers for the domain cannot be cryptographically validated.




Figure 1. WHOIS output for miahnationsecurity.site.

Evidence gap: the brief also asks for `whois hackthissite.org`. That output was not included in the submitted evidence.

SECTION 02

DNS Configuration

Queries made with `dig` against `miahnationsecurity.site`.

Record	Result	What it tells us
A	`35.169.115.175`	Single server IP that the main domain resolves to.
MX	eforward1, eforward2, eforward3 (priority 10), eforward4 (15), eforward5 (20) `.registrar-servers.com`	Mail is handled by Namecheap's email-forwarding service, not a dedicated mail platform.
NS	dns1.registrar-servers.com, dns2.registrar-servers.com	DNS is hosted by the registrar (Namecheap).
TXT	`"v=spf1 include:spf.efwd.registrar-servers.com ~all"`	SPF is present with a soft-fail (~all). No DKIM or other verification record appeared at the apex.
PTR	`ec2-35-169-115-175.compute-1.amazonaws.com`	The IP is an Amazon EC2 instance (US East region naming).

Interpretation. The mail setup relies on forwarding, and SPF ends in soft-fail, which tells receivers to accept but flag spoofed mail rather than reject it. The reverse DNS name publicly confirms the web host runs on AWS, which helps an attacker focus on cloud-specific weaknesses.

Supporting evidence



Figure 2.1 A record: server IP address.



Figure 2.2 MX records: mail servers.



```
┌──(bethel001㉿Boc)-[~]
└─$ dig miahnationsecurity.site NS


; <<>> DiG 9.20.27-2-Debian <<>> miahnationsecurity.site NS
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 24878
;; flags: qr rd ra; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1280
;; QUESTION SECTION:
;miahnationsecurity.site.       IN      NS

;; ANSWER SECTION:
miahnationsecurity.site. 904    IN      NS      dns1.registrar-servers.com.
miahnationsecurity.site. 904    IN      NS      dns2.registrar-servers.com.

;; Query time: 219 msec
;; SERVER: 192.168.43.198#53(192.168.43.198) (UDP)
;; WHEN: Thu Oct 01 09:46:43 WAT 2026
;; MSG SIZE  rcvd: 111
```

Figure 2.3 NS records: name servers.



```
┌──(bethel001㉿Boc)-[~]
└─$ dig miahnationsecurity.site TXT
;; communications error to 192.168.43.198#53: timed out
;; communications error to 192.168.43.198#53: timed out

; <<>> DiG 9.20.27-2-Debian <<>> miahnationsecurity.site TXT
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 8918
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 512
;; QUESTION SECTION:
;miahnationsecurity.site.       IN      TXT

;; ANSWER SECTION:
miahnationsecurity.site. 1800   IN      TXT     "v=spf1 include:spf.efwd.registrar-servers.c
om -all"

;; Query time: 415 msec
;; SERVER: 192.168.43.198#53(192.168.43.198) (UDP)
;; WHEN: Thu Oct 01 09:47:37 WAT 2026
;; MSG SIZE  rcvd: 115
```

Figure 2.4 TXT record: SPF policy.



```
┌──(bethel001㉿Boc)-[~]
└─$ dig -x 35.169.115.175
;; communications error to 192.168.43.198#53: timed out
;; communications error to 192.168.43.198#53: timed out

; <<>> DiG 9.20.27-2-Debian <<>> -x 35.169.115.175
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 56005
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1280
;; QUESTION SECTION:
;175.115.169.35.in-addr.arpa.   IN      PTR

;; ANSWER SECTION:
175.115.169.35.in-addr.arpa. 300 IN     PTR     ec2-35-169-115-175.compute-1.amazonaws.com.

;; Query time: 663 msec
;; SERVER: 192.168.43.198#53(192.168.43.198) (UDP)
;; WHEN: Thu Oct 01 09:56:53 WAT 2026
;; MSG SIZE  rcvd: 112
```

Figure 2.5 Reverse DNS (PTR) lookup of 35.169.115.175.

Evidence gap: `dig miahnationsecurity.site ANY` was requested in the brief but no output was submitted. DMARC (`_dmarc`) and DKIM selector records were not queried.

SECTION 03

IP Ownership

ARIN lookup of `35.169.115.175` (the A record from Section 2).

Organisation	Amazon Technologies Inc. (OrgId AT-88-Z), Seattle, WA
Network name / handle	AT-88-Z / NET-35-152-0-0-1 (Direct Allocation, parent NET35)
Network range	35.152.0.0 - 35.183.255.255
CIDR blocks	35.160.0.0/12, 35.176.0.0/13, 35.152.0.0/13
ASN	The OriginAS field was blank in the ARIN output, so no ASN is recorded here. A BGP lookup would confirm it.
Country of registration	United States
Abuse contact	trustandsafety@support.aws.com
Allocation date	9 August 2016

Interpretation. The IP belongs to Amazon's cloud address space, so the client is hosted in AWS rather than on its own network. Abuse reports and takedown requests would go to Amazon, not the client, and the IP offers no direct link to Miahnation as an organisation.




Figure 3.1 ARIN WHOIS result: network block and organisation.




Figure 3.2 ARIN WHOIS result: contact details.

SECTION 04

Exposed Information

Seven Google dorks. Queries 1 to 3 were scoped to hackthissite.org; queries 4 to 7 had no domain filter and are global.

#	Dork	Scope	What it returned	Exposure
1	`site:hackthissite.org filetype:pdf`	Target	0 results. Google reported no matching documents.	None
2	`site:hackthissite.org inurl:admin`	Target	5 public educational articles from /articles/ (e.g. defacement, Google hacking, OSINT, Nmap).	None
3	`site:hackthissite.org intitle:"login"`	Target	1 result: the standard public user login page.	Low
4	`intitle:"Asterisk" login`	Global	Asterisk documentation, project homepage and third-party vendor sites.	None for client
5	`filetype:conf intext:"SIP" intext:"password"`	Global	Sample voipmonitor.conf on GitHub and keepalived.conf man pages.	None for client
6	`intitle:"SSL VPN" inurl:portal`	Global	Study material (e.g. Course Hero) about VPN dorks; no live portals.	None for client
7	`filetype:pcf "enc_GroupPwd"`	Global	Cisco sample.pcf files in GitHub and open-source projects.	None for client

Findings by category

Item	Finding
Sensitive information exposed	None belonging to the target. Global dorks returned public templates, documentation and training material only.
VoIP system identified	Asterisk IP-PBX appears widely across public indices (queries 4 and 5). None tied to the target.
VPN type identified	SSL VPN portals (query 6) and legacy Cisco VPN profiles (query 7) as general technologies. None tied to the target.
Login pages found	One public user login page on hackthissite.org (query 3). Several third-party Asterisk login pages globally (query 4).
Exposed files found	None on the target. Sample voipmonitor.conf, keepalived.conf and sample.pcf files exist in public repositories.

Interpretation. Zero indexed PDFs and no admin panels in the search index are consistent with sound exposure control, but a search engine only shows what it has crawled, so this is not proof that nothing is exposed. The public login page is expected for a community site, yet it is a confirmed target for password attacks in later active testing. The global dorks show how easily an outsider can find VoIP interfaces and credential-bearing configuration files such as Cisco .pcf profiles, whose obfuscated group passwords are widely known to be reversible. If a staff member ever pushed a real file of that type to a public repository, it would give direct access to an internal network.

Evidence: dork results




Figure 4.1 Query 1: site:hackthissite.org filetype:pdf. Google returned no matching documents.




Figure 4.2 Query 2: site:hackthissite.org inurl:admin. Five public articles, no admin interfaces.




Figure 4.3 Query 3: site:hackthissite.org intitle:"login". One public login page.




Figure 4.4 Query 4: intitle:"Asterisk" login (global).




Figure 4.5 Query 5: filetype:conf intext:"SIP" intext:"password" (global).




Figure 4.6 Query 6: intitle:"SSL VPN" inurl:portal (global).




Figure 4.7 Query 7: filetype:pcf "enc_GroupPwd" (global).

SECTION 05

Subdomains Discovered

Passive subdomain enumeration of `miahnationsecurity.site`.

Tool	Command	Result
Subfinder	`subfinder -d miahnationsecurity.site -o subdomains.txt`	**5 subdomains** in 45.7 seconds
OWASP Amass	`amass enum -passive -d miahnationsecurity.site`	**0 results.** Failed with a network protocol error during setup.

Subfinder found more results (5 against 0), although this reflects Amass failing rather than a fair comparison. Sublist3r was not used because of dependency issues.

#	Subdomain	Likely purpose
1	`content.miahnationsecurity.site`	Content delivery or staging endpoint
2	`myaccount.miahnationsecurity.site`	Customer account portal
3	`ssl.miahnationsecurity.site`	Secure gateway or SSL termination node
4	`www.miahnationsecurity.site`	Main public website
5	`accounts.miahnationsecurity.site`	Shared authentication or identity service

Interpretation. **myaccount** and **accounts** indicate interactive login layers, which are natural targets for phishing and credential stuffing. The separate **ssl** host deserves a closer look at certificate and protocol configuration in the active phase.



Figure 5.1 Subfinder output: five subdomains found.



Figure 5.2 Amass run, which did not complete.

SECTION 06

Email Addresses Found

Email and host harvesting with theHarvester, followed by DNS validation of every host found.

Command: `theHarvester -d miahnationsecurity.site -b all -f results.html`

Item	Result
Email addresses	**None found**
Employee names	**None found**
Hosts	31 raw entries, **26 unique hostnames** after de-duplication
IPs	All 26 hosts resolve to one IPv4 address: **35.169.115.175** (AWS)
New subdomains vs Subfinder	21 additional subdomains (Subfinder's 5 are all included in the 26)

All 26 hostnames, grouped by function

Group	Hostnames (all `.miahnationsecurity.site`)	Count
Identity and access	`accounts, admin, login, myaccount, portal, secure`	6
Non-production	`dev, staging, test`	3
Data, transport, operations	`cdn, content, ftp, mail`	4
Application and API	`api, apis, app, mobile`	4
Support and public	`blog, docs, help, play, shop, ssl, status, support, www`	9

Interpretation

- **Shared entry point.** Every hostname, including `admin`, `secure`, `dev` and `test`, points to the same IP. That suggests a shared front end such as a load balancer or reverse proxy, possibly with a wildcard DNS record. A weakness in one low-priority application could expose the same gateway that serves sensitive ones.
- **Wildcard check needed.** Because the results are so uniform, some of these names may be guesses that resolve through a wildcard rather than real services. Querying a random, non-existent name would confirm this.
- **IPv6 results are not evidence of target configuration.** The AAAA answers (`64:ff9b::23a9:73af`) fall in the 64:ff9b::/96 block used by DNS64/NAT64 translators, and the last 32 bits (23a9:73af) simply encode 35.169.115.175. The local resolver on the analyst's network (a private 192.168.x.x address) most likely synthesised them. Re-checking with a public resolver would show whether the domain publishes real AAAA records.
- **Zero emails is not conclusive.** The tool log shows many data sources skipped because of missing API keys, so coverage was limited. Re-running with keys configured may surface addresses and staff names.




Figure 6.1 theHarvester run, showing sources skipped for missing API keys.




Figure 6.2 Hosts extracted from results.xml, de-duplicated to 26.




Figure 6.3 Automated IPv4 and IPv6 resolution of the discovered hosts.

SECTION 07

Summary of Findings

26	1	AWS	0
unique hostnames	IP address behind all of them	hosting provider	emails or staff names found

Using only public sources, the external footprint of `miahnationsecurity.site` was mapped as follows.

- **Ownership and registration.** Registered with Namecheap on 28 August 2026 for one year. Registrant data is redacted, the domain is transfer-locked and DNSSEC is not enabled.
- **Hosting.** The domain resolves to 35.169.115.175, an Amazon EC2 address in Amazon's US allocation. DNS and mail forwarding are provided by the registrar.
- **Email posture.** SPF exists with a soft-fail policy. No DKIM or DMARC evidence was gathered, and mail relies on registrar forwarding servers.
- **Attack surface.** Twenty-six hostnames were found, including identity gateways (accounts, login, myaccount, portal, secure, admin) and non-production hosts (dev, staging, test), all on one IP.
- **Information leakage.** No emails, employee names, exposed files or admin panels were found for the target. The global dorks showed how readily VoIP, VPN and credential files can be found in general.
- **Tool performance.** Subfinder (5 results) and theHarvester (26 hosts) worked. Amass failed, and theHarvester coverage was reduced by missing API keys.

Carry-forward to the active phase

Found today	Next step
26 subdomains	Probe each in depth with Maltego and Recon-ng; confirm or rule out wildcard DNS.
Emails (none yet)	Re-run theHarvester with API keys; extract metadata and build employee profiles.
IP 35.169.115.175 and its AWS range	Use Shodan to see what is running on the address.

SECTION 08

Risks Identified

Risks suggested by the evidence. Ratings are the analyst's judgement from passive data only and must be confirmed by authorised active testing.

ID	Rating	Risk and evidence	Recommended action
R1	HIGH	**Exposed authentication and admin hostnames** admin, login, accounts, myaccount, portal and secure are publicly discoverable (Sections 5, 6).	Prime targets for phishing, credential stuffing and brute force. Enforce MFA, rate limiting and IP restrictions on admin.
R2	MEDIUM	**Single shared entry point** All 26 hostnames resolve to 35.169.115.175 (Section 6).	One compromised or misconfigured application can affect every service behind it. Segment sensitive apps and review proxy rules.
R3	MEDIUM	**Non-production hosts in public DNS** dev, staging and test are resolvable (Section 6).	Test environments are often weakly protected. Restrict them to VPN or allow-lists, or remove the public records.
R4	MEDIUM	**Email spoofing exposure** SPF ends in ~all; no DKIM or DMARC evidence; mail on forwarding servers (Section 2).	Enable DMARC with a reject or quarantine policy, publish DKIM and tighten SPF. Especially important for a financial brand.
R5	LOW	**Cloud and provider fingerprinting** PTR name and ARIN data reveal AWS EC2 hosting (Sections 2, 3).	Lets attackers focus on AWS-specific weaknesses. Use a proxy or CDN in front of origin IPs and harden security groups.
R6	LOW	**DNSSEC not enabled** WHOIS shows DNSSEC unsigned (Section 1).	DNS answers cannot be validated, leaving room for spoofing. Enable DNSSEC where the registrar supports it.
R7	LOW	**Credential-bearing files can be found by dorking** Global dorks located SIP configs and Cisco .pcf samples (Section 4).	No client files found. Educate developers, scan repositories for secrets, and monitor for the organisation's own data in search results.
R8	INFO	**Good practice observed** Registrant data redacted, transfer lock on, no emails or staff names found, no admin panels or PDFs indexed (Sections 1, 4, 6).	Maintain these controls.

Limitations. Passive reconnaissance cannot confirm exploitability. Every item above is a lead for the active phase, to be tested only within authorised scope.