

Force 712, 1418 and 1624 Microcentrifuges

The Force Digital Microcentrifuges were designed for high performance and quiet operation. The line includes 3 models with maximum rcf ranging from 7,200 x g to 16,000 x g. All of the Force Microcentrifuges feature digital set and display of time and rpm/rcf, microprocessor control and are supplied complete with rotor.

- Microprocessor control provides for precise setting of speed and time
- Efficient air flow system keeps samples cool and reduces rotor noise
- Bench saving design



Specifications:

	Force 712	Force 1418	Force 1624
Max capacity	12 x 1.5/2.0mL	18 x 1.5/2.0mL	24 x 1.5/2.0mL
Max speed	10,000 rpm	13,000 rpm	13,000 rpm
Max RCF	7,200 x g	14,000 x g	16,000 x g
Timer	99 minutes	99 minutes	99 minutes
Dims (WxDxH)	19 x 18 x 13 cm/ 7.5 x 7 x 4.5 in	27 x 24 x 18 cm/ 10.5 x 9.3 x 7 in	27 x 24 x 18 cm/ 10.5 x 9.3 x 7 in
Weight	1.5 kg/3.25 lb	5.5 kg/12 lb	5.5 kg/12 lb
Electrical (all models)	120V, 100V or 230V 50/60 Hz		

Ordering Information:

Cat. No.	Description
C9414	Force 712 Microcentrifuge, with 12 place rotor, 120V
C9414-100V	Force 712 Microcentrifuge, with 12 place rotor, 100V
C9414-230V*	Force 712 Microcentrifuge, with 12 place rotor, 230V
C9420	Force 1418 Microcentrifuge, with 18 place rotor, 120V
C9420-100V	Force 1418 Microcentrifuge, with 18 place rotor, 100V
C9420-230V*	Force 1418 Microcentrifuge, with 18 place rotor, 230V
C9424	Force 1624 Microcentrifuge, with 24 place rotor, 120V
C9424-100V	Force 1624 Microcentrifuge, with 24 place rotor, 100V
C9424-230V*	Force 1624 Microcentrifuge, with 24 place rotor, 230V
C1205	Adapters for 0.5/0.6mL tubes, pack of 6
C1206	Adapters for 0.25/0.4mL tubes, pack of 6
C1222	Adapters for 0.2mL tubes, pack of 6

*230V unit includes both EU and UK power cords

