

IncuMix Incubator Shaker

The Select BioProducts IncuMix Incubator Shakers are designed for simultaneous heating and mixing of small samples. The IncuMix is supplied with interchangable platforms for microtubes that can accomodate $56 \times 1.5 \text{mL}$ tubes, or smaller tubes with adapters or microplates that accepts standard and deepweel plates, up to 2.0 mL.





Temperature range ambient +5° to 99°C

Temperature accuracy ±0.5°C

Speed range 120V: 200 - 1200 rpm

230V: 200 - 1500 rpm

Motion/orbit circular, 3 mm

Timer 1 to 99 minutes or continuous

Dimensions $9 \times 12.3 \times 9$ in

23 x 31 x 23 cm

Weight 24.2 lb/11 kg

Electrical 120V or 230V, 50/60 Hz



- Shake and incubate samples simultaneously
- Interchangable platforms
- Broad temperature and speed range
- Intelligent control with digital LED display

Ordering Information:

Cat. No.	Description
SBS256	IncuMix Incubator Shaker with interchangable platforms for tubes and plates, 120V
SBS256-2	IncuMix Incubator Shaker with interchangable platforms for tubes and plates, 230V EU
SBS256-3	IncuMix Incubator Shaker with interchangable platforms for tubes and plates, 230V UK
C1205	Individual adapters for 0.5/0.6 mL tubes, pk of 6
C1206	Individual adapters for 0.4/0.25 mL tubes, pk of 6
C1222	Individual adapters for 0.2mL tubes, pk of 6

