

Curso de Laravel 5.1 - Blog Digital Datos

Resumo do curso feito por Roberto Pinheiro

Trata-se da criação de um blog com painel de administração, utilizando o Laravel.

Aula 1 - Instalando Laravel

Use como servidor o Laragon

Consultar a documentação em:

<https://laravel.com/docs/5.1/installation>

`composer create-project laravel/laravel miblog "5.1.*"`



Banco de dados

Crie um banco de dados com o nome de **miblog**.

Configurando a conexão do banco de dados

.env

```
APP_ENV=local
APP_DEBUG=true
APP_KEY=WkWrUq5Rx2t0edzRvrKfkQLM79Ymmb5h
```

```
DB_CONNECTION=mysql
DB_HOST=localhost
DB_DATABASE=miblog
DB_USERNAME=root
DB_PASSWORD=
```

```
CACHE_DRIVER=file
SESSION_DRIVER=file
QUEUE_DRIVER=sync
```


```
REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379
```

```
MAIL_DRIVER=smtp
MAIL_HOST=mailtrap.io
MAIL_PORT=2525
MAIL_USERNAME=null
MAIL_PASSWORD=null
MAIL_ENCRYPTION=null
```

Preparando as tabelas

Serão criadas três tabelas:

1. users
2. categories
3. articles



Por padrão, o Laravel já vem com o modelo **User.php** e a migration **2014_10_12_000000_create_users_table.php**

Crie os **models** e as **migrations** para construção das tabelas **categories** e **articles**:

php artisan make:model Category -m

php artisan make:model Article -m

```
C:\laragon\www\miblog
λ php artisan make:model Category -m
Model created successfully.
Created Migration: 2019_05_21_030926_create_categories_table

C:\laragon\www\miblog
λ php artisan make:model Article -m
Model created successfully.
Created Migration: 2019_05_21_030945_create_articles_table

C:\laragon\www\miblog
λ |
```

Aula 2 - Migrations

Tabela users

Faça a inclusão do campo **type** na migration:

2014_10_12_000000_create_users_table.php

```
<?php

use Illuminate\Database\Schema\Blueprint;
use Illuminate\Database\Migrations\Migration;

class CreateUsersTable extends Migration
{
    public function up()
    {
        Schema::create('users', function (Blueprint $table) {
            $table->increments('id');
            $table->string('name');
            $table->string('email')->unique();
            $table->string('password', 60);
            $table->enum('type',['member','admin'])->default('member');
            $table->rememberToken();
            $table->timestamps();
        });
    }

    public function down()
    {
        Schema::drop('users');
    }
}
```

E no controller **User.php**, inclua esse campo:

app/User.php

```
<?php
```

```
namespace App;
```

```
use Illuminate\Auth\Authenticatable;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Auth\Passwords\CanResetPassword;
use Illuminate\Foundation\Auth\Access\Authorizable;
use Illuminate\Contracts\Auth\Authenticatable as AuthenticatableContract;
use Illuminate\Contracts\Auth\Access\Authorizable as AuthorizableContract;
use Illuminate\Contracts\Auth\CanResetPassword as CanResetPasswordContract;
```

```
class User extends Model implements AuthenticatableContract,
                                   AuthorizableContract,
                                   CanResetPasswordContract
```

```
{
    use Authenticatable, Authorizable, CanResetPassword;

    protected $table = 'users';

    protected $fillable = ['name', 'email', 'password', 'type'];

    protected $hidden = ['password', 'remember_token'];
}
```

Tabela categories

app/database/2019_05_21_030926_create_categories_table.php

```
<?php
```

```
use Illuminate\Database\Schema\Blueprint;  
use Illuminate\Database\Migrations\Migration;
```

```
class CreateCategoriesTable extends Migration
```

```
{
```

```
    public function up()
```

```
    {
```

```
        Schema::create('categories', function (Blueprint $table) {
```

```
            $table->increments('id');
```

```
            $table->string('name', 60);
```

```
            $table->timestamps();
```

```
        });
```

```
    }
```

```
    public function down()
```

```
    {
```

```
        Schema::drop('categories');
```

```
    }
```

```
}
```

Tabela articles

app/database/2019_05_21_030945_create_articles_table.php

```
<?php
```

```
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Database\Migrations\Migration;
```

```
class CreateArticlesTable extends Migration
{
    public function up()
    {
        Schema::create('articles', function (Blueprint $table) {
            $table->increments('id');
            $table->string('title');
            $table->text('content');
            $table->string('slug')->nullable();
            $table->string('path');
            $table->string('tags');

            $table->integer('user_id')->unsigned();
            $table->integer('category_id')->unsigned();

            $table->foreign('user_id')
                ->references('id')->on('users')
                ->onDelete('cascade');
            $table->foreign('category_id')
                ->references('id')->on('categories')
                ->onDelete('cascade');
            $table->timestamps();
        });
    }

    public function down()
    {
        Schema::drop('articles');
    }
}
```


Criando as tabelas

php artisan migrate

```
C:\laragon\www\miblog
λ php artisan migrate
Migration table created successfully.
Migrated: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_100000_create_password_resets_table
Migrated: 2019_05_21_030926_create_categories_table
Migrated: 2019_05_21_030945_create_articles_table

C:\laragon\www\miblog
λ |
```

Table	Action	Rows	Type	Collation	Size	Overhead
articles	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8_unicode_ci	48 KiB	-
categories	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8_unicode_ci	16 KiB	-
migrations	Browse Structure Search Insert Empty Drop	4	InnoDB	utf8_unicode_ci	16 KiB	-
password_resets	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8_unicode_ci	16 KiB	-
users	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8_unicode_ci	16 KiB	-
5 tables	Sum	4	InnoDB	latin1_swedish_ci	112 KiB	0 B

Aula 3 - Relações entre tabelas

Registrando os tipos de relações nos models

app/User.php

```
<?php

namespace App;

use Illuminate\Auth\Authenticatable;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Auth\Passwords\CanResetPassword;
use Illuminate\Foundation\Auth\Access\Authorizable;
use Illuminate\Contracts\Auth\Authenticatable as AuthenticatableContract;
use Illuminate\Contracts\Auth\Access\Authorizable as AuthorizableContract;
use Illuminate\Contracts\Auth\CanResetPassword as CanResetPasswordContract;

class User extends Model implements AuthenticatableContract,
                                    AuthorizableContract,
                                    CanResetPasswordContract
{
    use Authenticatable, Authorizable, CanResetPassword;

    protected $table = 'users';

    protected $fillable = ['name', 'email', 'password','type'];

    protected $hidden = ['password', 'remember_token'];

    // Relacionamento de 1 para muitos da tabela users com a tabela articles

    public function articles(){
        return $this->hasMany('App\Article');
    }
}
```

app/Category.php

```
<?php

namespace App;
use Illuminate\Database\Eloquent\Model;

class Category extends Model
{
    protected $table = "categories";

    protected $fillable = ['name'];

    // Relacionamento de 1 para muitos da tabela categories com a tabela articles

    public function articles(){
        return $this->hasMany('App\Article');
    }
}
```

app/Article

```
<?php

namespace App;
use Illuminate\Database\Eloquent\Model;

class Article extends Model
{
    protected $table = "articles";

    protected $fillable = ['title','content', 'user_id', 'category_id', 'path', 'tags'];

    // Um artigo pertence a uma categoria

    public function category()
    {
        return $this->belongsTo('App\Category');
    }

    // Um artigo pertence a uma usuário

    public function user()
    {
        return $this->belongsTo('App\User');
    }
}
```

Server: localhost:3306 » Database: miblog » Table: articles

#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action
1	id	int(10)		UNSIGNED	No	None		AUTO_INCREMENT	Change Drop More
2	title	varchar(255)	utf8_unicode_ci		No	None			Change Drop More
3	content	text	utf8_unicode_ci		No	None			Change Drop More
4	slug	varchar(255)	utf8_unicode_ci		Yes	NULL			Change Drop More
5	path	varchar(255)	utf8_unicode_ci		No	None			Change Drop More
6	tags	varchar(255)	utf8_unicode_ci		No	None			Change Drop More
7	user_id	int(10)		UNSIGNED	No	None			Change Drop More
8	category_id	int(10)		UNSIGNED	No	None			Change Drop More
9	created_at	timestamp			No	0000-00-00 00:00:00			Change Drop More
10	updated_at	timestamp			No	0000-00-00 00:00:00			Change Drop More

[Check all](#)
With selected: [Browse](#) [Change](#) [Drop](#) [Primary](#) [Unique](#) [Index](#) [Fulltext](#)

[Print](#)
[Propose table structure](#)
[Move columns](#)
[Normalize](#)

Add 1 column(s) after updated_at [Go](#)

Indexes

Action	Keyname	Type	Unique	Packed	Column	Cardinality	Collation	Null	Comment
Edit Drop	PRIMARY	BTREE	Yes	No	id	0	A	No	
Edit Drop	articles_user_id_foreign	BTREE	No	No	user_id	0	A	No	
Edit Drop	articles_category_id_foreign	BTREE	No	No	category_id	0	A	No	

miblog password_resets

email : varchar(255)
token : varchar(255)
created_at : timestamp

miblog migrations

migration : varchar(255)
batch : int(11)

miblog users


id : int(10) unsigned
name : varchar(255)
email : varchar(255)
password : varchar(60)
type : enum('member','admin')
remember_token : varchar(100)
created_at : timestamp
updated_at : timestamp

miblog articles

id : int(10) unsigned
title : varchar(255)
content : text
slug : varchar(255)
path : varchar(255)
tags : varchar(255)
user_id : int(10) unsigned
category_id : int(10) unsigned
created_at : timestamp
updated_at : timestamp

miblog categories

id : int(10) unsigned
name : varchar(60)
created_at : timestamp
updated_at : timestamp




Aula 4 - Pacote Eloquent Sluggable

O slug permite realizar URL's amigáveis.

Acesse a URL:

<https://packagist.org/>

E procure por **eloquent-sluggable**



The screenshot shows the Packagist website with the search bar containing 'eloquent-sluggable'. The results list several packages, with 'cviebrock/eloquent-sluggable' being the most popular. The right sidebar shows package types and tags.


Package	PHP	Downloads	Stars
cviebrock/eloquent-sluggable	PHP	2 101 190	2 551
spatie/laravel-sluggable	PHP	293 294	491
mr-timofey/eloquent-sluggable	PHP	1 345	3
padosoft/laravel-sluggable	PHP	307	4

Package type

- library 11

Tags

- eloquent 7
- laravel 6
- eloquent-sluggable 4
- slug 4
- laravel-sluggable 3
- spatie 3
- cartrabbit 1
- log 1
- loggable 1
- lumen 1



The screenshot shows the detailed page for the 'cviebrock/eloquent-sluggable' package. It includes the package name, a composer command to install it, and a description.

cviebrock/eloquent-sluggable

`composer require cviebrock/eloquent-sluggable`

Easy creation of slugs for your Eloquent models in Laravel 5.

Instale o pacote com o seguinte comando:

composer require cviebrock/eloquent-sluggable:^3.1.1

```

C:\laragon\www\miblog
λ composer require cviebrock/eloquent-sluggable:^3.1.1
./composer.json has been updated
Loading composer repositories with package information
Updating dependencies (including require-dev)
Package operations: 2 installs, 0 updates, 0 removals
  - Installing cocur/sluggify (v1.1): Downloading (100%)
  - Installing cviebrock/eloquent-sluggable (3.1.1): Downloading (100%)
Package phpunit/phpunit-mock-objects is abandoned, you should avoid using it. No replacement was suggested.
Writing lock file
Generating autoload files
> Illuminate\Foundation\ComposerScripts::postUpdate
> php artisan optimize
Generating optimized class loader
C:\laragon\www\miblog
λ |

```

composer.json

```

{
    "name": "laravel/laravel",
    "description": "The Laravel Framework.",
    "keywords": ["framework", "laravel"],
    "license": "MIT",
    "type": "project",
    "require": {
        "php": ">=5.5.9",
        "laravel/framework": "5.1.*",
        "cviebrock/eloquent-sluggable": "3.1.1"
    },
    "require-dev": {
        "fzaninotto/faker": "~1.4",
        "mockery/mockery": "0.9.*",
        "phpunit/phpunit": "~4.0",
        "phpspec/phpspec": "~2.1"
    },
    "autoload": {
        "classmap": [
            "database"
        ],
        "psr-4": {
            "App\\": "app/"
        }
    },
    "autoload-dev": {
        "classmap": [
            "tests/TestCase.php"
        ]
    },
    "scripts": {
        "post-root-package-install": [
            "php -r \"copy('.env.example', '.env');\""
        ],
        "post-create-project-cmd": [
            "php artisan key:generate"
        ]
    }
}

```

```

    "post-install-cmd": [
        "Illuminate\\Foundation\\ComposerScripts::postInstall",
        "php artisan optimize"
    ],
    "post-update-cmd": [
        "Illuminate\\Foundation\\ComposerScripts::postUpdate",
        "php artisan optimize"
    ]
},
"config": {
    "preferred-install": "dist"
}
}

```

No arquivo **config/app.php**, em **providers** insira a seguinte linha:

```

'providers' => [

    /*
     * Laravel Framework Service Providers...
     */
    Illuminate\Foundation\Providers\ArtisanServiceProvider::class,
    Illuminate\Auth\AuthServiceProvider::class,
    Illuminate\Broadcasting\BroadcastServiceProvider::class,
    Illuminate\Bus\BusServiceProvider::class,
    Illuminate\Cache\CacheServiceProvider::class,
    Illuminate\Foundation\Providers\ConsoleSupportServiceProvider::class,
    Illuminate\Routing\ControllerServiceProvider::class,
    Illuminate\Cookie\CookieServiceProvider::class,
    Illuminate\Database\DatabaseServiceProvider::class,
    Illuminate\Encryption\EncryptionServiceProvider::class,
    Illuminate\Filesystem\FilesystemServiceProvider::class,
    Illuminate\Foundation\Providers\FoundationServiceProvider::class,
    Illuminate\Hashing\HashServiceProvider::class,
    Illuminate\Mail\MailServiceProvider::class,
    Illuminate\Pagination\PaginationServiceProvider::class,
    Illuminate\Pipeline\PipelineServiceProvider::class,
    Illuminate\Queue\QueueServiceProvider::class,
    Illuminate\Redis\RedisServiceProvider::class,
    Illuminate\Auth\Passwords>PasswordResetServiceProvider::class,
    Illuminate\Session\SessionServiceProvider::class,
    Illuminate\Translation\TranslationServiceProvider::class,
    Illuminate\Validation\ValidationServiceProvider::class,
    Illuminate\View\ViewServiceProvider::class,

```

```

/*
 * Application Service Providers...
 */
App\Providers\AppServiceProvider::class,
App\Providers\AuthServiceProvider::class,
App\Providers\EventServiceProvider::class,
App\Providers\RouteServiceProvider::class,

    Cviebrock\EloquentSluggable\SluggableServiceProvider::class,

],

```

app/Article.php

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;
use Cviebrock\EloquentSluggable\SluggableInterface;
use Cviebrock\EloquentSluggable\SluggableTrait;

class Article extends Model implements SluggableInterface
{
    use SluggableTrait;

    protected $sluggable = [
        'build_from' => 'title',
        'save_to'    => 'slug',
    ];

    protected $table = "articles";

    protected $fillable = ['title','content', 'user_id', 'category_id', 'path', 'tags'];

    public function category()
    {
        return $this->belongsTo('App\Category');
    }

    public function user()
    {
        return $this->belongsTo('App\User');
    }
}

```


Aula 5 - ModelFactory e DatabaseSeeder

Preparando Factory e Seeder

database/factories/ModelFactory.php

```
<?php

/*
|-----
| Model Factories
|-----
|
| Here you may define all of your model factories. Model factories give
| you a convenient way to create models for testing and seeding your
| database. Just tell the factory how a default model should look.
|
*/

$factory->defineAs(App\User::class, 'admin', function ($faker) {
    return [
        'name' => $faker->name,
        'email' => $faker->email,
        'password' => bcrypt('123'),
        'type' => 'admin',
        'remember_token' => str_random(10),
    ];
});

$factory->defineAs(App\User::class, 'member', function ($faker) {
    return [
        'name' => $faker->name,
        'email' => $faker->email,
        'password' => bcrypt('123'),
        'type' => 'member',
        'remember_token' => str_random(10),
    ];
});

$factory->define(App\Category::class, function ($faker) {
    return [
        'name' => $faker->word ,
    ];
});
```

```

$factory->define(App\Article::class, function ($faker) {
    return [
        'title'=>$faker->sentence,
        'content'=>$faker->paragraph,
        'tags' => $faker->word,
        'user_id' => App\User::all()->random()->id,
        'category_id' => App\Category::all()->random()->id,
    ];
});

```

database/seeds/DatabaseSeeder.php

```

<?php

use Illuminate\Database\Seeder;
use Illuminate\Database\Eloquent\Model;

class DatabaseSeeder extends Seeder
{
    /**
     * Run the database seeds.
     *
     * @return void
     */
    public function run()
    {
        Model::unguard();

        factory('App\User','admin', 3)->create();
        factory('App\User','member', 50)->create();
        factory('App\Category',5)->create();
        factory('App\Article',20)->create();

        Model::reguard();
    }
}

```

Dessa forma, serão criados:

- 3 usuários admin;
- 50 usuários member;
- 5 categorias;
- 20 artigos;

Populando as tabelas

php artisan db:seed



53 usuários (3 admin, 50 members)

Showing rows 0 - 52 (53 total, Query took 0.0360 seconds.)

SELECT * FROM `users`

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 250 | Filter rows: Search this table | Sort by key: None

	id	name	email	password	type	remember_token	created_at	updated_at
<input type="checkbox"/>	1	Al Murray	tyler97@prohaska.net	\$2y\$10\$0xWNie.bsYVntIWQLH7IDeeOtpEndNB0mE0deytCmH...	admin	ZNHGFCmB6U	2019-05-22 03:54:10	2019-05-22 03:54:10
<input type="checkbox"/>	2	Mafalda Mohr	willms.aniya@howell.biz	\$2y\$10\$kd7T0XP/wr7HAMJUezvUYe2ncJuFJTkGMeDtH52V...	admin	8X43hikVL	2019-05-22 03:54:10	2019-05-22 03:54:10
<input type="checkbox"/>	3	Marjorie Boehm	bergstrom.dorothea@cremin.com	\$2y\$10\$Nn37UAb0Gex5yZDAu5aeknHHSveRZRtVQP4ZGV3kW...	admin	ur7FS3NFnd	2019-05-22 03:54:10	2019-05-22 03:54:10
<input type="checkbox"/>	4	Prof. Tyshawn Treutel	marta09@west.org	\$2y\$10\$4QATVfnJFQ7BPeeC3V9Tiummrc3mVa3spVU6yptqP3R...	member	IBkqTceF3l	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	5	Betsy Kihn	wunsch.ottis@hotmail.com	\$2y\$10\$0aMN9dlLqc2pRohtBn17PuKjhdVTSOGfFVaVM0Yvpg...	member	dKV5Yblht3	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	6	Tina O'Conner	piper.bechtelar@gmail.com	\$2y\$10\$61vElz8nLVajZu1GCn6iOh3QMMh9VxbALPFozysQj...	member	xe7XRYts18	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	7	Kali Thompson	ogoyette@yahoo.com	\$2y\$10\$2nHWFbXfWtyF8d36WoOOSHWW95etHkGg21jVVI2...	member	TJEM1EIdiq	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	8	Ms. Bessie Huels	virginie.weissnat@hotmail.com	\$2y\$10\$S.9tclJhDsUkG\$6JiU8O8/H2LDaP17UN5HaYP77U...	member	1VjVLJmthq	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	9	Wendell Dicki	wabshire@pfeffer.biz	\$2y\$10\$2Z/gYcK3hfxKYPsDIuYO2qX84RmUMqHoGOAwPTZ/...	member	7uKcMLqGZy	2019-05-22 03:54:19	2019-05-22 03:54:19
<input type="checkbox"/>	10	Brooks Bayer	glenda.morar@gmail.com	\$2y\$10\$5iL79IZUpWiKVIBrMEaq/uJv1tRVaemVvXiSpY6ERLs...	member	omxncJqJNK	2019-05-22 03:54:19	2019-05-22 03:54:19

20 artigos

Showing rows 0 - 19 (20 total, Query took 0.0030 seconds.)

SELECT * FROM `articles`

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

	id	title	content	slug	path	tags	user_id	category_id	created_at	updated_at
<input type="checkbox"/>	1	Facere voluptatem quis maxime cum ad aut est.	Dolores in aspernatur ipsum in nobis ut numquam la...	facere-voluptatem-quis-maxime-cum-ad-aut-est	recusandae		20	1	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	2	Ratione molestiae perspiciatis laudantium beatae d...	Eos ea ratione minus sit facilis modi. Quos et ut ...	ratione-molestiae-perspiciatis-laudantium-beatae-d...	vero		6	1	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	3	Tempora id quia quis in.	Quia reiciendis voluptas occaecati odio ipsum volu...	tempora-id-quia-quis-in	possimus		13	2	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	4	Sint aut sit voluptatem nulla qui.	Architecto accusantium velit vel rem. Dolores iust...	sint-aut-sit-voluptatem-nulla-qui	et		30	2	2019-05-22 03:54:22	2019-05-22 03:54:22
<input type="checkbox"/>	5	Esse excepturi ut deserunt molestiae nostrum aperi...	Assumenda porro quia earum. Consectetur laudantium...	esse-excepturi-ut-deserunt-molestiae-nostrum-aperi...	iste		47	3	2019-05-22 03:54:22	2019-05-22 03:54:22
<input type="checkbox"/>	6	Qui et sunt cum reiciendis animi quas officiis asp...	Facere aut aut distinctio nesciunt qui enim ut. Sa...	qui-et-sunt-cum-reiciendis-animi-quas-officiis-asp...	et		7	5	2019-05-22 03:54:22	2019-05-22 03:54:22
<input type="checkbox"/>	7	Sint facilis dolorem iure consequuntur sint	Enim est explicabo aut asperiores explicabo rem no	sint-facilis-dolorem-iure-consequuntur-sint	ratione		21	2	2019-05-22 03:54:22	2019-05-22 03:54:22

5 categorias

✓ Showing rows 0 - 4 (5 total, Query took 0.0000 seconds.)

`SELECT * FROM `categories``
















☐ Show all

Number of rows: 25

Filter rows:

Sort by

+ Options

				id	name	created_at	updated_at
<input type="checkbox"/>	 Edit	 Copy	 Delete	1	et	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	 Edit	 Copy	 Delete	2	sed	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	 Edit	 Copy	 Delete	3	vel	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	 Edit	 Copy	 Delete	4	aliquam	2019-05-22 03:54:21	2019-05-22 03:54:21
<input type="checkbox"/>	 Edit	 Copy	 Delete	5	qui	2019-05-22 03:54:21	2019-05-22 03:54:21

Aula 6 - Routes e Controllers

Criando as rotas

app/http/routes.php

```
<?php

/*
|-----
| Application Routes
|-----
|
| Here is where you can register all of the routes for an application.
| It's a breeze. Simply tell Laravel the URIs it should respond to
| and give it the controller to call when that URI is requested.
|
*/

Route::get('/', function () {
    return view('welcome');
});

Route::group(['prefix' => 'admin'], function () {
    Route::resource('users', 'UsersController');
});
```

Criando o controller

php artisan make:controller UsersController

```
C:\laragon\www\miblog
λ php artisan make:controller UsersController
Controller created successfully.

C:\laragon\www\miblog
λ |
```

app/Http/Controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;

class UsersController extends Controller
{
    public function index()
    {
        return "Hola desde el index del administrador";
    }

    public function create()
    {
        //
    }


    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }

    public function update(Request $request, $id)
    {
        //
    }

    public function destroy($id)
    {
        //
    }
}
```



Aula 7 - Trabalhando com views

app/Http/Controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;

class UsersController extends Controller
{
    public function index()
    {
        return view('admin.users.index');
    }
    public function create()
    {
        //
    }
    public function store(Request $request)
    {
        //
    }
    public function show($id)
    {
        //
    }
    public function edit($id)
    {
        //
    }
    public function update(Request $request, $id)
    {
        //
    }
    public function destroy($id)
    {
        //
    }
}
```


Dentro da pasta **public** criar três subpastas:

- **css**
- **js**
- **fonts**

- Baixe os arquivos do bootstrap e:

- Dentro da subpasta **css** insira os arquivos do bootstrap/css.
- Dentro da subpasta **js** insira os arquivos do bootstrap/js e do jquery.

- Baixe os arquivos do font awesome e:

Insira os arquivos dentro da subpasta **fonts**

Dentro da pasta **resources/views** criar uma pasta chamada **admin** e dentro dela uma pasta chamada **users**. Dentro desta pasta criar um arquivo chamado **index.blade.php**

resources/views/admin/users/index.blade.php

```
@extends('layouts.admin')
```

```
@section('title', 'Listado de usuarios')
```

```
@section('content')
```

```
AQUI VA EL LISTADO DE USUARIOS
```

```
@endsection
```

Dentro da pasta **resources/views** criar uma pasta chamada **layouts** e dentro desta pasta criar um arquivo chamado **admin.blade.php**

resources/views/layouts/admin.blade.php

```
<!DOCTYPE html>
<html lang="pt-br">
<head>
  <meta charset="UTF-8">
  <title>@yield('title', 'Default') | Administração</title>
  <link rel="stylesheet" href="{{ asset('css/bootstrap.css') }}">
  <link rel="stylesheet" href="{{ asset('css/font-awesome.min.css') }}">
</head>
<body>

<nav class="navbar navbar-default">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Brand</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">
        <li class="active"><a href="#">Link <span class="sr-
only">(current)</span></a></li>
        <li><a href="#">Link</a></li>
        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Dropdown <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="#">Action</a></li>
            <li><a href="#">Another action</a></li>
            <li><a href="#">Something else here</a></li>
            <li role="separator" class="divider"></li>
            <li><a href="#">Separated link</a></li>
            <li role="separator" class="divider"></li>
            <li><a href="#">One more separated link</a></li>
          </ul>
        </li>
      </ul>
    </div>
  </div>
</nav>
```

```

    <form class="navbar-form navbar-left" role="search">
      <div class="form-group">
        <input type="text" class="form-control" placeholder="Search">
      </div>
      <button type="submit" class="btn btn-default">Submit</button>
    </form>
    <ul class="nav navbar-nav navbar-right">
      <li><a href="#">Link</a></li>
      <li class="dropdown">
        <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Dropdown <span
class="caret"></span></a>
        <ul class="dropdown-menu">
          <li><a href="#">Action</a></li>
          <li><a href="#">Another action</a></li>
          <li><a href="#">Something else here</a></li>
          <li role="separator" class="divider"></li>
          <li><a href="#">Separated link</a></li>
        </ul>
      </li>
    </ul>
  </div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>


<div class="container">
  <div class="panel panel-default">
    <div class="panel-heading">
      <h3 class="panel-title">@yield('title')</h3>
    </div>
    <div class="panel-body">
      @yield('content')
    </div>
  </div>

</div>

  <script src="{ asset('js/jquery.js') }"></script>
  <script src="{ asset('js/bootstrap.js') }"></script>

</body>
</html>

```



Aula 8 - Listar usuários

Dentro da pasta `resources/views` criar uma pasta chamada `partials` e dentro desta pasta criar um arquivo chamado `navadmin.blade.php`

`resources/views/partials/navadmin.blade.php`

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">
        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="#">Listar</a></li>
            <li><a href="#">Criar</a></li>
          </ul>
        </li>
      </ul>

      <ul class="nav navbar-nav">
        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="#">Listar</a></li>
            <li><a href="#">Criar</a></li>
          </ul>
        </li>
      </ul>
    </div>
  </div>
</nav>
```

```

        <ul class="nav navbar-nav">
            <li class="dropdown">
                <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
                <ul class="dropdown-menu">
                    <li><a href="#">Listar</a></li>
                    <li><a href="#">Criar</a></li>
                </ul>
            </li>
        </ul>

        <ul class="nav navbar-nav navbar-right">
            <li class="dropdown">
                <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Nome do usuário
<span class="caret"></span></a>
                <ul class="dropdown-menu">
                    <li><a href="#">Logout</a></li>
                </ul>
            </li>
        </ul>
    </div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

resources/views/layouts/admin.blade.php

```

<!DOCTYPE html>
<html lang="pt-br">
<head>
    <meta charset="UTF-8">
    <title>@yield('title', 'Default') | Administração</title>
    <link rel="stylesheet" href="{{ asset('css/bootstrap.css') }}">
    <link rel="stylesheet" href="{{ asset('css/font-awesome.min.css') }}">
</head>
<body>

```

@include('partials/navadmin')

```

<div class="container">
    <div class="panel panel-primary">
        <div class="panel-heading">
            <h3 class="panel-title">@yield('title')</h3>
        </div>
        <div class="panel-body">
            @yield('content')
        </div>
    </div>
</div>

```

```
<script src="{{ asset('js/jquery.js') }}"></script>
<script src="{{ asset('js/bootstrap.js') }}"></script>
</body>
</html>
```

app/Http/Controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\User;

class UsersController extends Controller
{
    public function index()
    {
        $users = User::orderBy('id', 'ASC')->paginate(5);
        return view('admin.users.index', compact('users'));
    }
    public function create()
    {
        //
    }
    public function store(Request $request)
    {
        //
    }
    public function show($id)
    {
        //
    }
    public function edit($id)
    {
        //
    }
    public function update(Request $request, $id)
    {
        //
    }
    public function destroy($id)
    {
        //
    }
}
```

resources/views/admin/users/index.blade.php

```
@extends('layouts.admin')
```

```
@section('title', 'Listagem de usuarios')
```

```
@section('content')
```

```
<table class="table table-striped">
```

```
<thead>
```

```
<th>Nome</th>
```

```
<th>Email</th>
```

```
<th>Tipo</th>
```

```
<th>Ações</th>
```

```
</thead>
```

```
<tbody>
```

```
@foreach($users as $user)
```

```
<tr>
```

```
<td>{{ $user['name'] }} </td>
```

```
<td>{{ $user['email'] }} </td>
```

```
<td>{{ $user['type'] }} </td>
```

```
<td></td>
```

```
</tr>
```

```
@endforeach
```

```
</tbody>
```

```
</table>
```

```
{!! $users->render() !!}
```

```
@endsection
```

Nome	Email	Tipo	Ações
Aletha Schowalter	ekassulke@hotmail.com	member	
Abraham Ebert	noe14@oberbrunner.biz	member	
Gunner Ward II	crist.maci@yahoo.com	member	
Dr. Hyman Herman Sr.	pstamm@gmail.com	member	
Barrett Schultz	oblock@renner.biz	member	

« 1 2 3 4 5 6 7 8 9 10 11 »

Aula 9 - Criar usuário

resources/views/admin/users/index.blade.php

```
@extends('layouts.admin')
```

```
@section('title', 'Listagem de usuarios')
```

```
@section('content')
```

```
<table class="table table-striped">
```

```
<thead>
```

```
<th>Nome</th>
```

```
<th>Email</th>
```

```
<th>Tipo</th>
```

```
<th>Ações</th>
```

```
</thead>
```

```
<tbody>
```

```
@foreach($users as $user)
```

```
<tr>
```

```
<td>{{ $user['name'] }} </td>
```

```
<td>{{ $user['email'] }} </td>
```

```
<td>{{ $user['type'] }} </td>
```

```
<td>
```

```
<a class="btn btn-success" href="#" role="button"><i class="fa fa-pencil-square-o"></i></a>
```

```
<a class="btn btn-danger" href="#" role="button"><i class="fa fa-trash-o"></i></a>
```

```
</td>
```

```
</tr>
```


```
@endforeach
```

```
</tbody>
```

```
</table>
```

```
{!! $users->render() !!}
```

```
@endsection
```



Instalação do Laravel Collective

Acesse a URL que contém a documentação do Laravel Collective:

<https://github.com/LaravelCollective/docs/blob/5.1/html.md>

No arquivo **composer.json**, na seção **require**, inserir a seguinte linha:

"laravelcollective/html": "5.1.*"

composer.json

```
{
  "name": "laravel/laravel",
  "description": "The Laravel Framework.",
  "keywords": ["framework", "laravel"],
  "license": "MIT",
  "type": "project",
  "require": {
    "php": ">=5.5.9",
    "laravel/framework": "5.1.*",
    "cviebrock/eloquent-sluggable": "3.1.1",
    "laravelcollective/html": "5.1.*"
  },
}
```

```

"require-dev": {
    "fzaninotto/faker": "~1.4",
    "mockery/mockery": "0.9.*",
    "phpunit/phpunit": "~4.0",
    "phpspec/phpspec": "~2.1"
},
"autoload": {
    "classmap": [
        "database"
    ],
    "psr-4": {
        "App\\": "app/"
    }
},
"autoload-dev": {
    "classmap": [
        "tests/TestCase.php"
    ]
},
"scripts": {
    "post-root-package-install": [
        "php -r \"copy('.env.example', '.env');\""
    ],
    "post-create-project-cmd": [
        "php artisan key:generate"
    ],
    "post-install-cmd": [
        "Illuminate\\Foundation\\ComposerScripts::postInstall",
        "php artisan optimize"
    ],
    "post-update-cmd": [
        "Illuminate\\Foundation\\ComposerScripts::postUpdate",
        "php artisan optimize"
    ]
},
"config": {
    "preferred-install": "dist"
}
}

```

No terminal, entre com o comando:

composer update

```
C:\laragon\www\miblog
λ composer update
Loading composer repositories with package information
Updating dependencies (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
- Installing laravelcollective/html (v5.1.11): Downloading (100%)
Package phpunit/phpunit-mock-objects is abandoned, you should avoid using it. No replacement was suggested.
Writing lock file
Generating autoload files
> Illuminate\Foundation\ComposerScripts::postUpdate
> php artisan optimize
Generating optimized class loader
C:\laragon\www\miblog
λ
```

Next, add your new provider to the providers array of **config/app.php**:

```
'providers' => [
    // ...
    Collective\Html\HtmlServiceProvider::class,
    // ...
],
```

Finally, add two class aliases to the aliases array of **config/app.php**:

```
'aliases' => [
    // ...
    'Form' => Collective\Html\FormFacade::class,
    'Html' => Collective\Html\HtmlFacade::class,
    // ...
],
```

app/Http/Controllers/UsersController.php

```
<?php
```

```
namespace App\Http\Controllers;
```

```
use Illuminate\Http\Request;
```

```
use App\Http\Requests;
```

```
use App\Http\Controllers\Controller;
```

```
use App\User;
```

```
use Session;
```

```
use Redirect;
```

```
class UsersController extends Controller
{
    public function index()
    {
        $users = User::orderBy('id', 'ASC')->paginate(5);
        return view('admin.users.index', compact('users'));
    }

    public function create()
    {
        return view('admin.users.create');
    }

    public function store(Request $request)
    {
        $user = new User($request->all());
        $user->password = bcrypt($request->password);
        $user->save();
        Session::flash('message', 'Usuário cadastrado com sucesso!');
        return redirect::to('admin/users');
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }

    public function update(Request $request, $id)
    {
        //
    }

    public function destroy($id)
    {
        //
    }
}
```

resources/views/admin/users/create.blade.php

```
@extends('layouts.admin')
```

```
@section('title','Criar Usuarios')
```

```
@section('content')
```

```
    {!! Form::open(['route' => 'admin.users.store', 'method' => 'POST']) !!}
    <div class="form-group">
        {!! Form::label('name','Nome') !!}
        {!! Form::text('name',null,['class' => 'form-control', 'placeholder'
=>'Nome Completo','required']) !!}
    </div>
```

```

    <div class="form-group">
        {!! Form::label('email','Email') !!}
        {!! Form::email('email',null,['class' => 'form-control', 'placeholder'
=>'example@gmail.com','required']) !!}
    </div>
```

```

    <div class="form-group">
        {!! Form::label('password','Senha') !!}
        {!! Form::password('password',['class' => 'form-control', 'placeholder'
=>'', 'required']) !!}
    </div>
```


```

    <div class="form-group">
        {!! Form::label('type','Tipo de usuario') !!}
        {!! Form::select('type',['=>'Selecione o tipo de usuário' , 'member'
=> 'Membro','admin'=>'Administrador'], null, ['class'=>'form-control']) !!}
    </div>
```

```

    <div class="form-group">
        {!! Form::submit('Registrar', ['class' => 'btn btn-primary']) !!}
    </div>
```

```
    {!! Form::close() !!}
@endsection
```



resources/views/admin/users/index.blade.php

```
@extends('layouts.admin')
```

```
@section('title', 'Listagem de usuarios')
```

```
@section('content')
```

```
    @if(Session::has('message'))
        <div class="alert alert-warning alert-dismissible" role="alert">
            <button type="button" class="close" data-dismiss="alert" aria-
            label="Close"><span aria-hidden="true">&times;</span></button>
            {{Session::get('message')}}
        </div>
    @endif
```

```
<table class="table table-striped">
    <thead>
        <th>Nome</th>
        <th>Email</th>
        <th>Tipo</th>
        <th>Ações</th>
    </thead>
```

```


<tbody>
  @foreach($users as $user)
    <tr>
      <td>{{ $user['name'] }} </td>
      <td>{{ $user['email'] }} </td>
      <td>{{ $user['type'] }} </td>
      <td>
        <a class="btn btn-success" href="#" role="button"><i class="fa fa-
pencil-square-o"></i></a>
        <a class="btn btn-danger" href="#" role="button"><i class="fa fa-
trash-o"></i></a>
      </td>
    </tr>
  @endforeach
</tbody>
</table>

```

```
{!! $users->render() !!}
```

```
@endsection
```

Senha: 123456













The screenshot shows a web browser window with the address bar displaying 'miblog.test/admin/users/create'. The page has a dark navigation bar with links for 'Admin Blog', 'Usuários', 'Categorias', and 'Artigos', along with a user profile icon. The main content area features a form titled 'Criar Usuarios' with the following fields:

- Nome:** Roberto Pinheiro
- Email:** betopinheiro1005@yahoo.com.br
- Senha:** (masked with dots)
- Tipo de usuario:** Administrador (selected from a dropdown menu)

A blue 'Registrar' button is located at the bottom of the form.

Listagem de usuarios

Usuario criado com sucesso!

Nome	Email	Tipo	Ações
Roberto Pinheiro	betopinheiro1005@yahoo.com.br	admin	 
Aletha Schowalter	ekassulke@hotmail.com	member	 
Abraham Ebert	noe14@oberbrunner.biz	member	 
Gunner Ward II	crist.maci@yahoo.com	member	 
Dr. Hyman Herman Sr.	pstamm@gmail.com	member	 

«

1

2

3

4

5

6

7

8

9

10

11

»

<div>← T →</div>		id	name	email	password	type	remember_token	created_at
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	39	Fanny Heidenreich	lavema.weimann@hotmail.com	\$2y\$10\$VlUrgeWtBcFUb5fSZVMBxu0YzM6Cg9xoZ2y3oN7RK4b...	member	CXDqHJvQg5	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	40	Niko Gerlach	brannon58@hotmail.com	\$2y\$10\$cUymdNLMf7PnIqBxRu8ULOLX.ZX5M9ovKiDwY0fK.8...	member	gUCkiHUCck	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	41	Dean Schroeder	janis19@hotmail.com	\$2y\$10\$QM/Ev5zFhMQKwNpwXq4ieoxBlpYaQ8brb.86pN6oc4...	member	X77QXrjCcr	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	42	Ceasar Witting	gudrun88@yahoo.com	\$2y\$10\$5q2Dg7j0yZnXKWOe8H6DyFG8xnX4vNDVYiZX...	member	Z8psVGMRVD	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	43	Candido Schimmel	zboncak.darion@gmail.com	\$2y\$10\$8myRujqVBtewVJMm2rUjukCicYrf5KJfLowhmQliSa...	member	wOCUOTYnf5	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	44	Olen Kuhn	hauck.marcelino@pouros.org	\$2y\$10\$JdKixGMZLOKP2D6OGsO9OesUOca5St3glamkWhbA1ny...	member	WwVt103vIS	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	45	Triston Gerhold	sonia17@blanda.com	\$2y\$10\$3ZgJol3ISCFd6aZG.q/Mfu.CcQ3plmeULyCILHo48B6...	member	scjKJdJSt	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	46	Mr. Granville Collier	hfunk@yahoo.com	\$2y\$10\$irV/hzKA1foxdc8m2N1Wiu.CftXKcVfRmeGjVj8p...	member	uBBi8mwziR	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	47	Darion Breitenberg II	zwilkinson@gmail.com	\$2y\$10\$AUZsboxdOjkWhuVyomKS8z.rpo1GSTc4aa1u2ZYhmA6R...	member	KeTL9HOSPH	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	48	Cesar Kuhic	lbode@erdman.info	\$2y\$10\$DMDmztY8oOH7mgollz0fzujEOIQZiADSA14IT78P2Yr...	member	TzXugkPujG	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	49	Barrett Schultz	oblock@renner.biz	\$2y\$10\$Horim3aCMxK.NUukiDN0eXZDXLBzFU44JE0kcwKDZg...	member	f1Kti3bslb	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	50	Dr. Hyman Herman Sr.	pstamm@gmail.com	\$2y\$10\$J9gEPRubH7aMnLuDXB5D/ugM7so7B4SX8VFcIN9U0.6...	member	OQPjG0KRkv	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	51	Gunner Ward II	crist.maci@yahoo.com	\$2y\$10\$9FD1qUHCmd4ZjQOW2EotlOnEMzIMhIXatUeH5VZt7IrC...	member	FDmakINs73	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	52	Abraham Ebert	noe14@oberbrunner.biz	\$2y\$10\$UNqy4l2/bg06iZAndf1voeuHFJL34e1wA6lnwnn1Lyr...	member	R19LaLh6wl	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	53	Aletha Schowalter	ekassulke@hotmail.com	\$2y\$10\$KA/qP64AE9iNhV2ryBRVq.95Ceb2N7MWswx2Pij0qXw...	member	o2appfcVr	2019-05-22 12:00:00	
<div><div><div></div><div></div><div></div></div><div><div>Edit</div><div>Copy</div><div>Delete</div></div></div>	54	Roberto Pinheiro	betopinheiro1005@yahoo.com.br	\$2y\$10\$xmIUpj/CbKm2M2D4V4pwO6qV64.Umh2vScPFNnypW...	admin	NULL	2019-05-22 12:00:00	

Aula 10 - Validação de formulários

Criando um request

php artisan make:request UserRequest

```
C:\laragon\www\miblog
λ php artisan make:request UserRequest
Request created successfully.

C:\laragon\www\miblog
λ |
```

app/Http/Requests/UserRequest.php

```
<?php
```

```
namespace App\Http\Requests;
```

```
use App\Http\Requests\Request;
```

```
class UserRequest extends Request
```

```
{
```

```
    public function authorize()
```

```
    {
```

```
        return true;
```

```
    }
```

```
    public function rules()
```

```
    {
```

```
        return [
```

```
            'name' => 'required|min:3|max:80',
```

```
            'email' => 'required|unique:users',
```

```
            'password' => 'required|min:4|max:120',
```

```
        ];
```

```
    }
```

```
}
```

app/Http/Controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\User;
use Session;
use Redirect;
use App\Http\Requests\UserRequest;

class UsersController extends Controller
{
    public function index()
    {
        $users = User::orderBy('id','DESC')->paginate(5);
        return view('admin.users.index', compact('users'));
    }

    public function create()
    {
        return view('admin.users.create');
    }

    public function store(UserRequest $request)
    {
        $user = new User($request->all());
        $user->password = bcrypt($request->password);
        $user->save();
        Session::flash('message','Usuario creado correctamente');
        return redirect::to('admin/users');
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }
}
```

```

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}
}

```

Retire as cláusulas **required** dos campos do formulário:

resources/views/admin/create.blade.php

```

@extends('layouts.admin')

@section('title','Criar Usuarios')

@section('content')

@if(count($errors) > 0)
    <div class="alert alert-danger" role="alert">
        <ul>
            @foreach($errors->all() as $error)
                <li>{{ $error }}</li>
            @endforeach
        </ul>
    </div>
@endif

{!! Form::open(['route' => 'admin.users.store', 'method' => 'POST']) !!}
    <div class="form-group">
        {!! Form::label('name','Nome') !!}
        {!! Form::text('name',null,['class' => 'form-control', 'placeholder' => 'Nome
Completo']) !!}
    </div>

```

```

<div class="form-group">
  {!! Form::label('email','Email') !!}
  {!! Form::email('email',null,['class' =>'form-control', 'placeholder'
=>'example@gmail.com'])!!}
</div>

<div class="form-group">
  {!! Form::label('password','Senha') !!}
  {!! Form::password('password',['class' =>'form-control', 'placeholder'
=>''])!!}
</div>

<div class="form-group">
  {!! Form::label('type','Tipo de usuario') !!}
  {!! Form::select('type',['=>'Selecione o tipo de usuário' , 'member' =>
'Membro','admin'=>'Administrador'], null, ['class'=>'form-control']) !!}
</div>

<div class="form-group">
  {!! Form::submit('Registrar', ['class' =>'btn btn-primary']) !!}

</div>

{!! Form::close() !!}
@endsection

```

Criar Usuarios | Administração

Não seguro | miblog.test/admin/users/create

Admin Blog Usuários ▾ Categorias ▾ Artigos ▾ Nome do usuário ▾

Criar Usuarios

- The name field is required.
- The email field is required.
- The password field is required.

Nome

Email

Senha

Tipo de usuario

Registrar

browser: Criar Usuarios | Administração x +
 browser: Não seguro | miblog.test/admin/users/create
 Admin Blog Usuários ▾ Categorias ▾ Artigos ▾ Nome do usuário ▾

Criar Usuarios

- The email has already been taken.

Nome

Roberto Pinheiro

Email

betopinheiro1005@yahoo.com.br

Senha

Tipo de usuario

Administrador ▾

Registrar

browser: Criar Usuarios | Administração x +
 browser: Não seguro | miblog.test/admin/users/create
 Admin Blog Usuários ▾ Categorias ▾ Artigos ▾ Nome do usuário ▾

Criar Usuarios

- The name must be at least 3 characters.
- The email field is required.
- The password must be at least 4 characters.

Nome

Ro

Email

example@gmail.com

Senha

Tipo de usuario

Membro ▾

Registrar


Alterando as mensagens para o idioma Português

Acesse a URL:

<https://github.com/caouecs/Laravel-lang>

Faça o download.

Na subpasta src, copie a pasta **pt-BR** para **resources/lang**



Abra o arquivo **config/app.php** e altere a linha:

```
'locale' => 'en',
```

Para:

```
'locale' => 'pt-BR',
```

Criar Usuarios | Administração

Não seguro

miblog.test/admin/users/create

Admin Blog

Usuários

Categorias

Artigos

Nome do usuário

Criar Usuarios

- O campo nome é obrigatório.
- O valor informado para o campo e-mail já está em uso.
- O campo senha deve conter no mínimo 4 caracteres.

Nome

Nome Completo

Email

betopinheiro1005@yahoo.com.br

Senha

Tipo de usuario

Administrador

Registrar

Aula 11 - Editar e excluir usuários

app/Http/Controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\User;
use Session;
use Redirect;
use App\Http\Requests\UserRequest;

class UsersController extends Controller
{
    public function index()
    {
        $users = User::orderBy('id','DESC')->paginate(5);
        return view('admin.users.index', compact('users'));
    }

    public function create()
    {
        return view('admin.users.create');
    }

    public function store(UserRequest $request)
    {
        $user = new User($request->all());
        $user->password = bcrypt($request->password);
        $user->save();
        Session::flash('message','Usuario criado com sucesso!');
        return redirect::to('admin/users');
    }

    public function show($id)
    {
        //
    }
}
```

```

public function edit($id)
{
    $user= User::find($id);
    return view('admin.users.edit',compact('user'));
}

public function update(Request $request, $id)
{
    $user= User::find($id);
    $user->fill($request->all());
    $user->save();

    Session::flash('message','Usuário atualizado com sucesso!');
    return redirect::to('admin/users');
}

public function destroy($id)
{
    $user= User::find($id);
    $user->delete();

    Session::flash('message','Usuário eliminado com sucesso!');
    return redirect::to('admin/users');
}
}

```

resources/views/admin/users/index.blade.php

```

@extends('layouts.admin')

@section('title', 'Listagem de usuarios')

@section('content')

    @if(Session::has('message'))
        <div class="alert alert-success alert-dismissible" role="alert">
            <button type="button" class="close" data-dismiss="alert" aria-label="Close"><span aria-hidden="true">&times;</span></button>
            {{Session::get('message')}}
        </div>
    @endif

    <table class="table table-striped">
        <thead>
            <th>Nome</th>
            <th>Email</th>
            <th>Tipo</th>
            <th>Ações</th>
        </thead>

```

```

<tbody>
  @foreach($users as $user)
    <tr>
      <td>{{ $user['name'] }} </td>
      <td>{{ $user['email'] }} </td>
      <td>{{ $user['type'] }} </td>
      <td>
        <a class="btn btn-success" href="{{route('admin.users.edit', $user-
>id)}}}" role="button"><i class="fa fa-pencil-square-o"></i></a>
        <a class="btn btn-danger" href="{{route('admin.users.destroy',
$user->id)}}}" onclick="return confirm('Tem certeza que deseja eliminar o
registro?')" role="button"><i class="fa fa-trash-o"></i></a>
      </td>
    </tr>
  @endforeach
</tbody>
</table>

{!! $users->render() !!}

@endsection

```

resources/views/admin/users/edit.blade.php

```

@extends('layouts.admin')

@section('title', 'Editar Usuario')

@section('content')

  @if(count($errors) > 0)
    <div class="alert alert-danger" role="alert">
      <ul>
        @foreach($errors->all() as $error)
          <li>{{ $error }}</li>
        @endforeach
      </ul>
    </div>
  @endif

  {!! Form::open(['route' => ['admin.users.update', $user], 'method' =>
'PUT']) !!}
  <div class="form-group">
    {!! Form::label('name', 'Nome') !!}
    {!! Form::text('name', $user->name, ['class' => 'form-control',
'placeholder' => 'Nome Completo', 'required']) !!}
  </div>

```

```

        <div class="form-group">
            {!! Form::label('email','Email') !!}
            {!! Form::email('email', $user->email,['class' =>'form-control',
'placeholder' =>'example@gmail.com','required'])!!}
        </div>

        <div class="form-group">
            {!! Form::label('type','Tipo de usuario') !!}
            {!! Form::select('type',['=>'Seleccione o tipo de usuário' , 'member'
=> 'Membro','admin'=>'Administrador'], $user->type, ['class'=>'form-control'])
!!}
        </div>

        <div class="form-group">
            {!! Form::submit('Atualizar', ['class' =>'btn btn-primary']) !!}
        </div>

        {!! Form::close() !!}

    @endsection

```

app/http/routes.php

```

<?php

/*
|-----
| Application Routes
|-----
| Here is where you can register all of the routes for an application.
| It's a breeze. Simply tell Laravel the URIs it should respond to
| and give it the controller to call when that URI is requested.
|
*/

Route::get('/', function () {
    return view('welcome');
});

Route::group(['prefix' => 'admin'], function () {
    Route::resource('users', 'UsersController');
});

Route::get('users/{id}/destroy',[
    'uses' =>'UsersController@destroy',
    'as'   =>'admin.users.destroy'
]);

```

Editando usuário

Editar Usuario | Administração

Não seguro | miblog.test/admin/users/54/edit

Admin Blog Usuários Categorias Artigos Nome do usuário

Editar Usuario

Nome

Roberto Pinheiro - ALTERADO

Email

robertopinheiro@gmail.com

Tipo de usuario

Membro

Atualizar

Listagem de usuarios | Administr

Não seguro | miblog.test/admin/users

Admin Blog Usuários Categorias Artigos Nome do usuário

Listagem de usuarios

Usuário atualizado com sucesso!

Nome	Email	Tipo	Ações
Roberto Pinheiro - ALTERADO	robertopinheiro@gmail.com	member	<div></div>
Aletha Schowalter	ekassulke@hotmail.com	member	<div></div>
Abraham Ebert	noe14@oberbrunner.biz	member	<div></div>
Gunner Ward II	crist.maci@yahoo.com	member	<div></div>
Dr. Hyman Herman Sr.	pstamm@gmail.com	member	<div></div>

«

1

2

3

4

5

6

7

8

9

10

11

»

Excluindo usuário

Excluindo o usuário "Roberto Pinheiro"

Listagem de usuarios | Administrar

← → ↺

Não seguro

miblog.test/admin/users

☆

Admin Blog

Usuários

miblog.test diz











Tem certeza que deseja eliminar o registro?

OK

Cancelar

Nome do usuário

Listagem de usuarios

Nome	Email	Tipo	Ações
Roberto Pinheiro - ALTERADO	robertopinheiro@gmail.com	member	 
Aletha Schowalter	ekassulke@hotmail.com	member	 
Abraham Ebert	noe14@oberbrunner.biz	member	 
Gunner Ward II	crist.maci@yahoo.com	member	 
Dr. Hyman Herman Sr.	pstamm@gmail.com	member	 

«

1

2

3

4

5

6

7

8

9

10

11

»

Listagem de usuarios | Administrar

← → ↺

Não seguro

miblog.test/admin/users

☆

Admin Blog

Usuários











Categorias

Artigos

Nome do usuário

Listagem de usuarios

Usuário eliminado com sucesso!

Nome	Email	Tipo	Ações
Aletha Schowalter	ekassulke@hotmail.com	member	 
Abraham Ebert	noe14@oberbrunner.biz	member	 
Gunner Ward II	crist.maci@yahoo.com	member	 
Dr. Hyman Herman Sr.	pstamm@gmail.com	member	 
Barrett Schultz	oblock@renner.biz	member	 

«

1

2

3

4

5

6

7

8

9

10

11

»

Aula 12 - CRUD Categorias

app/http/routes.php

```
<?php

/*
|-----
| Application Routes
|-----
|
| Here is where you can register all of the routes for an application.
| It's a breeze. Simply tell Laravel the URIs it should respond to
| and give it the controller to call when that URI is requested.
|
*/

Route::get('/', function () {
    return view('welcome');
});

Route::group(['prefix' => 'admin'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
});

Route::get('users/{id}/destroy',[
    'uses' =>'UsersController@destroy',
    'as'   =>'admin.users.destroy'
]);

Route::get('categories/{id}/destroy',[
    'uses' =>'CategoriesController@destroy',
    'as'   =>'admin.categories.destroy'
]);
```

Criando o Controller

php artisan make:controller CategoriesController

```
C:\laragon\www\miblog
λ php artisan make:controller CategoriesController
Controller created successfully.

C:\laragon\www\miblog
λ |
```

app/Http/Controllers/CategoriesController.php

```
<?php
```

```
namespace App\Http\Controllers;
```

```
use Illuminate\Http\Request;
```

```
use App\Http\Requests;
```

```
use App\Http\Controllers\Controller;
```

```
use App\Category;
```

```
use Session;
```

```
use Redirect;
```

```
class CategoriesController extends Controller
```

```
{
```

```
    public function index()
```

```
    {
```

```
        $categories = Category::orderBy('id','DESC')->paginate(5);
```

```
        return view('admin.categories.index', compact('categories'));
```

```
    }
```

```
    public function create()
```

```
    {
```

```
        return view('admin.categories.create');
```

```
    }
```

```
    public function store(Request $request)
```

```
    {
```

```
        $category = new Category($request->all());
```

```
        $category->save();
```

```
        Session::flash('message','Categoria fue creada correctamente');
```

```
        return redirect::to('admin/categories');
```

```
    }
```



```

public function show($id)
{
    //
}

public function edit($id)
{
    $category= Category::find($id);
    return view('admin.categories.edit',compact('category'));
}

public function update(Request $request, $id)
{
    $category= Category::find($id);
    $category->fill($request->all());
    $category->save();

    Session::flash('message','Categoria atualizada corretamente');
    return redirect::to('admin/categories');
}

public function destroy($id)
{
    $category= Category::find($id);
    $category->delete();

    Session::flash('message','Categoria eliminada corretamente');
    return redirect::to('admin/categories');
}
}

```

resources/views/admin/categories/index.blade.php

```

@extends('layouts.admin')

@section('title', 'Listagem de categorias')

@section('content')

@if(Session::has('message'))
    <div class="alert alert-success alert-dismissible" role="alert">
        <button type="button" class="close" data-dismiss="alert" aria-
label="Close"><span aria-hidden="true">&times;</span></button>
        {{Session::get('message')}}
    </div>
@endif

<table class="table table-striped">
    <thead>
        <th>Nome</th>

```

```

        <th>Ações</th>
    </thead>

    <tbody>
        <tr>
            @foreach ($categories as $category)
                <td>{{ $category->name }}</td>

                <td>
                    <a class="btn btn-success" href="{{ route('admin.categories.edit',
                    $category->id) }}" role="button"><i class="fa fa-pencil-square-o"></i></a>
                    <a class="btn btn-danger" href="{{ route('admin.categories.destroy',
                    $category->id) }}" onclick="return confirm('Tem certeza que deseja excluir a
                    categoria?')" role="button"><i class="fa fa-trash-o"></i></a>
                </td>
            </tr>
        @endforeach
    </tbody>
</table>

{!! $categories->render() !!}

@endsection

```

resources/views/admin/categories/create.blade.php

```

@extends('layouts.admin')

@section('title','Criar Categorias')

@section('content')

    @if(count($errors) >0)
        <div class="alert alert-danger" role="alert">
            <ul>
                @foreach($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            </ul>
        </div>
    @endif

    {!! Form::open(['route' => 'admin.categories.store', 'method' =>
'POST']) !!}
    <div class="form-group">
        {!! Form::label('name','Nome') !!}
        {!! Form::text('name',null,['class' => 'form-control', 'placeholder'
=> 'Nome Completo','required']) !!}
    </div>

```

```
<div class="form-group">
    {!! Form::submit('Registrar', ['class' =>'btn btn-primary']) !!}
</div>
```

```
{!! Form::close() !!}
```

```
@endsection
```

resources/views/admin/categories/edit.blade.php

```
@extends('layouts.admin')
```

```
@section('title','Editar Categoria')
```

```
@section('content')
```

```
@if(count($errors) >0)
    <div class="alert alert-danger" role="alert">
        <ul>
            @foreach($errors->all() as $error)
                <li>{{ $error }}</li>
            @endforeach
        </ul>
    </div>
@endif
```

```
    {!! Form::open(['route' => ['admin.categories.update', $category],
'method' => 'PUT']) !!}
    <div class="form-group">
        {!! Form::label('name','Nome') !!}
        {!! Form::text('name', $category->name,['class' =>'form-control',
'placeholder' =>'Nome Completo','required'])!!}
    </div>
```

```
    <div class="form-group">
        {!! Form::submit('Atualizar', ['class' =>'btn btn-primary']) !!}
    </div>
    {!! Form::close() !!}
```

```
@endsection
```

resources/views/partials/navadmin.blade.php

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">
        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="{ { route('admin.users.index') } }">Listar</a></li>
            <li><a href="{ { route('admin.users.create') } }">Criar</a></li>
          </ul>
        </li>

        <ul class="nav navbar-nav">
          <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
            <ul class="dropdown-menu">
              <li><a href="{ { route('admin.categories.index') } }">Listar</a></li>
              <li><a href="{ { route('admin.categories.create') } }">Criar</a></li>
            </ul>
          </li>

          <ul class="nav navbar-nav">
            <li class="dropdown">
              <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
              <ul class="dropdown-menu">
                <li><a href="#">Listar</a></li>
                <li><a href="#">Criar</a></li>
              </ul>
            </li>
          </ul>
        </li>
      </ul>
    </div>
  </div>
</nav>
```

```
</li>
</ul>
```

```
<ul class="nav navbar-nav navbar-right">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Nome do usuário
    <span class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="#">Logout</a></li>
    </ul>
  </li>
</ul>
</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>
```

Aula 13 - Autenticação em Laravel

Rotas

app/http/routes.php

```
<?php

/*
|-----
| Application Routes
|-----
|
| Here is where you can register all of the routes for an application.
| It's a breeze. Simply tell Laravel the URIs it should respond to
| and give it the controller to call when that URI is requested.
|
*/

Route::get('/', function () {
    return view('welcome');
});

Route::group(['prefix' => 'admin'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
});

Route::get('users/{id}/destroy',[
    'uses' => 'UsersController@destroy',
    'as'   => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy',[
    'uses' => 'CategoriesController@destroy',
    'as'   => 'admin.categories.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout',[
    'uses' => 'LoginController@logout',
    'as'   => 'logout'
]);
```

Criando o Controller

php artisan make:controller LoginController

```
C:\laragon\www\miblog
λ php artisan make:controller LoginController
Controller created successfully.

C:\laragon\www\miblog
λ |
```

app/http/Controllers/LoginController.php

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use Auth;

use Session;

use Redirect;

use App\Http\Requests;

use App\Http\Requests\LoginRequest;

use App\Http\Controllers\Controller;

class LoginController extends Controller

{

public function index()

{

return view('admin.login');

}

public function create()

{

//

}

public function store(Request \$request)

{

if (Auth::attempt(['email'=>\$request['email'],
'password'=>\$request['password']])) {

return Redirect::to('admin/users');

}

Session::flash('message','Dados inválidos!');

return redirect::to('login');

}

```
public function show($id)
{
    //
}

public function edit($id)
{
    //
}

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}

public function logout(){
    Auth::logout();
    return Redirect::to('login');
}
}
```

Criando um Request

php artisan make:request LoginRequest

```
C:\laragon\www\miblog
λ php artisan make:request LoginRequest
Request created successfully.

C:\laragon\www\miblog
λ |
```


app/http/Requests/LoginRequest.php

```
<?php

namespace App\Http\Requests;

use App\Http\Requests\Request;

class LoginRequest extends Request
{
    public function authorize()
    {
        return true;
    }

    public function rules()
    {
        return [
            //
        ];
    }
}
```

resources/views/login.blade.php

```
<!DOCTYPE html>
<html lang="pt-br">
<head>
    <meta charset="UTF-8">
    <title>Painel de Administração</title>
    <link rel="stylesheet" href="{{ asset('css/bootstrap.css') }}">
    <link rel="stylesheet" href="{{ asset('css/font-awesome.min.css') }}">
</head>
<body>
<br>
<br>
    <div class="div container">

        @if(Session::has('message'))
            <div class="alert alert-danger alert-dismissible" role="alert">
                <button type="button" class="close" data-dismiss="alert" aria-label="Close"><span aria-hidden="true">&times;</span></button>
                {{Session::get('message')}}
            </div>
        @endif
```

```

<div class="panel panel-primary">
  <div class="panel-heading">
    <h3 class="panel-title">ÁREA DE ACESSO AO SISTEMA</h3>
  </div>
  <div class="panel-body">
    {!! Form::open(['route' => 'login.store', 'method' => 'POST']) !!}

    <div class="form-group">
      {!! Form::label('email','Email') !!}
      {!! Form::email('email',null,['class' => 'form-control', 'placeholder'
=>'Entre com o seu endereço de email'])!!}
    </div>

    <div class="form-group">
      {!! Form::label('password','Senha') !!}
      {!! Form::password('password',['class' => 'form-control', 'placeholder'
=>'Entre com a sua senha'])!!}
    </div>

    <div class="form-group">
      {!! Form::submit('Login', ['class' => 'btn btn-primary']) !!}
      {!! Form::close() !!}
    </div>
  </div>
</div>

<script src="{{ asset('js/jquery.js') }}"></script>
<script src="{{ asset('js/bootstrap.js') }}"></script>
</body>
</html>

```

resources/views/partials/navadmin.blade.php

```

<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

```

```

<!-- Collect the nav links, forms, and other content for toggling -->
<div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
  <ul class="nav navbar-nav">
    <li class="dropdown">
      <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
      <ul class="dropdown-menu">
        <li><a href="{{route('admin.users.index')}}">Listar</a></li>
        <li><a href="{{route('admin.users.create')}}">Criar</a></li>
      </ul>
    </li>
  </ul>

  <ul class="nav navbar-nav">
    <li class="dropdown">
      <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
      <ul class="dropdown-menu">
        <li><a href="{{route('admin.categories.index')}}">Listar</a></li>
        <li><a href="{{route('admin.categories.create')}}">Criar</a></li>
      </ul>
    </li>
  </ul>

  <ul class="nav navbar-nav">
    <li class="dropdown">
      <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
      <ul class="dropdown-menu">
        <li><a href="#">Listar</a></li>
        <li><a href="#">Criar</a></li>
      </ul>
    </li>
  </ul>

  <ul class="nav navbar-nav navbar-right">
    <li class="dropdown">
      <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!! Auth::user()-
>name !!} <span class="caret"></span></a>
      <ul class="dropdown-menu">
        <li><a href="{{ route('logout') }}">Sair</a></li>
      </ul>
    </li>
  </ul>
</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

Senha errada:

Painel de Administração

Não seguro

miblog.test/login

R

ÁREA DE ACESSO AO SISTEMA

Email

janis19@hotmail.com

Senha

.....

Login

Painel de Administração

Não seguro

miblog.test/login

R

Dados inválidos!

ÁREA DE ACESSO AO SISTEMA

Email

Entre com o seu endereço de email

Senha

Entre com a sua senha

Login

Senha correta:

Painel de Administração

Não seguro | miblog.test/login

ÁREA DE ACESSO AO SISTEMA

Email

janis19@hotmail.com

Senha

...

Login

Listagem de usuarios | Administr

Não seguro | miblog.test/admin/users

Admin Blog

Usuários

Categorias

Artigos

Dean Schroeder

Listagem de usuarios

| Nome | Email | Tipo | Ações |
|----------------------|-----------------------|--------|-------------------------|
| Aletha Schowalter | ekassulke@hotmail.com | member | <div></div> <div></div> |
| Abraham Ebert | noe14@oberbrunner.biz | member | <div></div> <div></div> |
| Gunner Ward II | crist.maci@yahoo.com | member | <div></div> <div></div> |
| Dr. Hyman Herman Sr. | pstamm@gmail.com | member | <div></div> <div></div> |
| Barrett Schultz | oblock@renner.biz | member | <div></div> <div></div> |

«

1

2

3

4

5

6

7

8


9

10

11

»

Clicando em sair:



ÁREA DE ACESSO AO SISTEMA

Email

Senha

Login

Aula 14 - Middleware

app/http/routes.php

```
<?php

/*
|-----
| Application Routes
|-----
|
| Here is where you can register all of the routes for an application.
| It's a breeze. Simply tell Laravel the URIs it should respond to
| and give it the controller to call when that URI is requested.
|
*/

Route::get('/', function () {
    return view('welcome');
});

Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
});

Route::get('users/{id}/destroy',[
    'uses' => 'UsersController@destroy',
    'as' => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy',[
    'uses' => 'CategoriesController@destroy',
    'as' => 'admin.categories.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout',[
    'uses' => 'LoginController@logout',
    'as' => 'logout'
]);
```

app/Http/Middleware/Authenticate.php

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Contracts\Auth\Guard;


class Authenticate
{
    protected $auth;

    public function __construct(Guard $auth)
    {
        $this->auth = $auth;
    }

    public function handle($request, Closure $next)
    {
        if ($this->auth->guest()) {
            if ($request->ajax()) {
                return response('Unauthorized.', 401);
            } else {
                return redirect()->guest('login');
            }
        }

        return $next($request);
    }
}
```

Se tentar entrar, pela URL, diretamente com um rota não permitida, o sistema retorna a tela de login



The screenshot shows a web browser window with the title "Painel de Administração" and a single tab. The address bar displays "miblog.test/admin/users". The main content area features a login form with a blue header bar containing the text "ÁREA DE ACESSO AO SISTEMA". Below the header, there are two input fields: "Email" with the placeholder text "Entre com o seu endereço de email" and "Senha" with the placeholder text "Entre com a sua senha". A blue "Login" button is positioned below the password field.

ÁREA DE ACESSO AO SISTEMA

Email

Entre com o seu endereço de email

Senha

Entre com a sua senha

Login

Aula 15 - Trabalhando com o front

Rotas

app/http/routes.php

```
<?php

// Route::get('/', function () {
//     return view('welcome');
// });

Route::get('/', [
    'uses' => 'FrontController@index',
    'as' => 'home'
]);

Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
});

Route::get('users/{id}/destroy', [
    'uses' => 'UsersController@destroy',
    'as' => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy', [
    'uses' => 'CategoriesController@destroy',
    'as' => 'admin.categories.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout', [
    'uses' => 'LoginController@logout',
    'as' => 'logout'
]);
```

Criando o Controller da página principal

php artisan make:controller FrontController

```
C:\laragon\www\miblog
λ php artisan make:controller FrontController
Controller created successfully.

C:\laragon\www\miblog
λ |
```

app/Http/controllers/FrontController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;

class FrontController extends Controller
{
    public function index()
    {
        return view('index');
    }

    public function create()
    {
        //
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }
}
```

```

    public function update(Request $request, $id)
    {
        //
    }

    public function destroy($id)
    {
        //
    }
}

```

resources/views/index.blade.php

```

@extends('layouts.front')

@section('title', 'Mi Blog')

@section('content')
    <div class="container">
        <h1>Últimas Noticias</h1>
    </div>
@endsection

```

resources/views/layouts/front.blade.php

```

<!DOCTYPE html>
<html lang="pt-br">
<head>
    <meta charset="UTF-8">
    <title>@yield('title')</title>
    <link rel="stylesheet" href="{{ asset('css/bootstrap.css') }}">
    <link rel="stylesheet" href="{{ asset('css/font-awesome.min.css') }}">

</head>
<body>

    @include('partials.navfront')
    @yield('content')

    <script src="{{ asset('js/jquery.js') }}"></script>
    <script src="{{ asset('js/bootstrap.js') }}"></script>

</body>
</html>

```

resources/views/partials/navfront.blade.php


```
<nav class="navbar navbar-default">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="{{route('home')}}">Mi Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{{route('home')}}">Início</a></li>
        <li><a href="#">Contato</a></li>
        <li><a href="#">Categorias</a></li>
        <li><a href="#">Administrador</a></li>

      </ul>

    </div><!-- /.navbar-collapse -->
  </div><!-- /.container-fluid -->
</nav>
```



Aula 16 - Navegando entre o blog e administrador

app/http/routes.php

```
<?php

// Route::get('/', function () {
//     return view('welcome');
// });

Route::get('/', [
    'uses' => 'FrontController@index',
    'as' => 'home'
]);

Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
    Route::get('index', [
        'uses' => 'FrontController@admin',
        'as' => 'administrador'
    ]);
});

Route::get('users/{id}/destroy', [
    'uses' => 'UsersController@destroy',
    'as' => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy', [
    'uses' => 'CategoriesController@destroy',
    'as' => 'admin.categories.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout', [
    'uses' => 'LoginController@logout',
    'as' => 'logout'
]);
```

app/Http/controllers/LoginController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use Auth;
use Session;
use Redirect;
use App\Http\Requests;
use App\Http\Requests\LoginRequest;
use App\Http\Controllers\Controller;

class LoginController extends Controller
{
    public function index()
    {
        return view('admin.login');
    }

    public function create()
    {
        //
    }

    public function store(Request $request)
    {
        if (Auth::attempt(['email'=>$request['email'],
'password'=>$request['password']])) {
            return Redirect::to('admin/index');
        }

        Session::flash('message','Datos inválidos!');
        return redirect::to('login');
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }

    public function update(Request $request, $id)
    {
        //
    }
}
```

```

public function destroy($id)
{
    //
}

public function logout(){
    Auth::logout();
    return Redirect::to('login');
}
}

```

resources/views/partials/navadmin.blade.php

```

<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{{route('administrador')}}">Inicio</a></li>
        <li><a href="{{route('home')}}">Blog</a></li>

        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="{{route('admin.users.index')}}">Listar</a></li>
            <li><a href="{{route('admin.users.create')}}">Criar</a></li>
          </ul>
        </li>
      </ul>
    </div>
  </div>
</nav>

```



```

<ul class="nav navbar-nav">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{ { route('admin.categories.index') } }">Listar</a></li>
      <li><a href="{ { route('admin.categories.create') } }">Criar</a></li>
    </ul>
  </li>
</ul>

<ul class="nav navbar-nav">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="#">Listar</a></li>
      <li><a href="#">Criar</a></li>
    </ul>
  </li>
</ul>

<ul class="nav navbar-nav navbar-right">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!!
Auth::user()->name !!}<span class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{ { route('logout') } }">Sair</a></li>
    </ul>
  </li>
</ul>
</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

resources/views/partials/navfront.blade.php

```
<nav class="navbar navbar-default">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="{{route('home')}}">Mi Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{{route('home')}}">Início</a></li>
        <li><a href="#">Contato</a></li>
        <li><a href="#">Categorias</a></li>
        <li><a href="{{ route('administrador') }}">Administrador</a></li>

      </ul>

    </div><!-- /.navbar-collapse -->
  </div><!-- /.container-fluid -->
</nav>
```

resources/views/index.blade.php

```
@extends('layouts.admin')

@section('title', 'Início')

@section('content')
  <h2>Bem-vindo a área administrativa!</h2>
@endsection
```

app/Http/controllers/FrontController.php

```
<?php

namespace App\Http\Controllers;


use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;

class FrontController extends Controller
{
    public function index()
    {
        return view('index');
    }


    public function admin()
    {
        return view('admin.index');
    }

    public function create()
    {
        //
    }
    public function store(Request $request)
    {
        //
    }
    public function show($id)
    {
        //
    }
    public function edit($id)
    {
        //
    }
    public function update(Request $request, $id)
    {
        //
    }
    public function destroy($id)
    {
        //
    }
}
```





Últimas Notícias

Clicando em Administrador:




Fazendo o login:





Clicando em Blog:



Últimas Notícias

Aula 17 - Listando os artigos

app/http/routes.php

```
<?php

// Route::get('/', function () {
//     return view('welcome');
// });

Route::get('/', [
    'uses' => 'FrontController@index',
    'as'   => 'home'
]);

Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
    Route::resource('articles', 'ArticlesController');
    Route::get('index', [
        'uses' => 'FrontController@admin',
        'as'   => 'administrador'
    ]);
});

Route::get('users/{id}/destroy', [
    'uses' => 'UsersController@destroy',
    'as'   => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy', [
    'uses' => 'CategoriesController@destroy',
    'as'   => 'admin.categories.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout', [
    'uses' => 'LoginController@logout',
    'as'   => 'logout'
]);
```

app/Http/controllers/LoginController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use Auth;
use Session;
use Redirect;
use App\Http\Requests;
use App\Http\Requests\LoginRequest;
use App\Http\Controllers\Controller;

class LoginController extends Controller
{
    public function index()
    {
        return view('admin.login');
    }

    public function create()
    {
        //
    }

    public function store(Request $request)
    {
        if (Auth::attempt(['email'=>$request['email'],
'password'=>$request['password']])) {
            return Redirect::to('admin/index');
        }

        Session::flash('message','Datos inválidos!');
        return redirect::to('login');
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }

    public function update(Request $request, $id)
    {
        //
    }
}
```

```

    public function destroy($id)
    {
        //
    }

    public function logout(){
        Auth::logout();
        return Redirect::to('/');
    }
}

```

Criando um controlador para artigos

php artisan make:controller ArticlesController

```

C:\laragon\www\miblog
λ php artisan make:controller ArticlesController
Controller created successfully.

C:\laragon\www\miblog
λ |

```

app/Http/controllers/ArticlesController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Article;
use App\User;
use App\Category;

class ArticlesController extends Controller
{
    public function index()
    {
        $articles = Article::orderBy('id','DESC')->paginate(5);
        return view('admin.articles.index', compact('articles'));
    }
}

```



```

    public function create()
    {
        //
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }

    public function edit($id)
    {
        //
    }

    public function update(Request $request, $id)
    {
        //
    }

    public function destroy($id)
    {
        //
    }
}

```

resources/views/admin/articles/index.blade.php

```

@extends('layouts.admin')

@section('title', 'Listagen de artigos')

@section('content')

    @if(Session::has('message'))
        <div class="alert alert-success alert-dismissible" role="alert">
            <button type="button" class="close" data-dismiss="alert" aria-
label="Close"><span aria-hidden="true">&times;</span></button>
            {{Session::get('message')}}
        </div>
    @endif

```

```

<table class="table table-striped">
  <thead>
    <th>Título</th>
    <th>Conteúdo</th>
    <th>Autor</th>
    <th>Categoria</th>
    <th>Imagem</th>
    <th width="100px">Ações</th>
  </thead>

  <tbody>
    <tr>
      @foreach ($articles as $article)
        <td>{{ $article->title }}</td>
        <td>{{ substr($article->content, 0,300) }}...</td>
        <td>{{ $article->user->name }}</td>
        <td>{{ $article->category->name }}</td>
        @if(empty($article->path))
          <td></td>
        @else
          <td></td>
        @endif

        <td>
          <a class="btn btn-success" href="{{ route('admin.articles.edit', $article-
>id) }}" role="button"><i class="fa fa-pencil-square-o"></i></a>
          <a class="btn btn-danger" href="{{ route('admin.articles.destroy',
$article->id) }}" onclick="return confirm('Tem certeza que deseja excluir o
registro?')" role="button"><i class="fa fa-trash-o"></i></a>
        </td>
      </tr>
    @endforeach
  </tbody>
</table>

{!! $articles->render() !!}

@endsection

```

resources/views/partials/navadmin.php

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{{route('administrador')}}">Inicio</a></li>
        <li><a href="{{route('home')}}">Blog</a></li>

        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="{{route('admin.users.index')}}">Listar</a></li>
            <li><a href="{{route('admin.users.create')}}">Criar</a></li>
          </ul>
        </li>


        <ul class="nav navbar-nav">
          <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
            <ul class="dropdown-menu">
              <li><a href="{{route('admin.categories.index')}}">Listar</a></li>
              <li><a href="{{route('admin.categories.create')}}">Criar</a></li>
            </ul>
          </li>
        </ul>
      </ul>
    </div>
  </div>
</nav>
```

```

<ul class="nav navbar-nav">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{{route('admin.articles.index')}}">Listar</a></li>
      <li><a href="#">Criar</a></li>
    </ul>
  </li>
</ul>

<ul class="nav navbar-nav navbar-right">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!! Auth::user()-
>name !!}<span class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{{ route('logout') }}">Sair</a></li>
    </ul>
  </li>
</ul>
</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```



| Listagem de artigos | | | | | |
|---|--|-----------------------|-----------|--------|---|
| Título | Conteúdo | Autor | Categoria | Imagem | Ações |
| Voluptatem ullam ut asperiores facere numquam deleniti. | Eligendi nam eveniet voluptatem ipsum. Doloribus libero sunt labore et fugit. Est magnam ea illo iusto. Ea id et ad non quod ratione. | Wendell Dicki | aliquam | |   |
| Voluptatem aliquam iure vel veritatis dolor delectus. | Cum qui et recusandae sint. Corrupti officia quia quas perspiciatis placeat dolor. Libero illo et unde illo amet velit. | Tina O'Conner | aliquam | |   |
| Impedit ducimus ut ut doloribus. | Dolores sed nulla est. Sit et ut incidunt hic voluptatem sunt. Animi est quod sequi necessitatibus placeat reprehenderit aspernatur. Quos et voluptas unde reiciendis aliquid optio molestiae magni. | Mr. Granville Collier | sed | |   |
| Ut architecto voluptas voluptatum et ad non corrupti. | Reprehenderit eveniet mollitia provident in praesentium. Sint in commodi reiciendis unde totam. Qui aut aperiam assumenda est. | Oran Aufderhar | aliquam | |   |

Aula 18 - Criando os artigos

resources/views/partials/navadmin.php

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{route('administrador')}">Inicio</a></li>
        <li><a href="{route('home')}">Blog</a></li>

        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="{route('admin.users.index')}">Listar</a></li>
            <li><a href="{route('admin.users.create')}">Criar</a></li>
          </ul>
        </li>

        <ul class="nav navbar-nav">
          <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
            <ul class="dropdown-menu">
              <li><a href="{route('admin.categories.index')}">Listar</a></li>
              <li><a href="{route('admin.categories.create')}">Criar</a></li>
            </ul>
          </li>
        </ul>
      </ul>
    </div>
  </div>
</nav>
```

```

        <ul class="nav navbar-nav">
            <li class="dropdown">
                <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
                <ul class="dropdown-menu">
                    <li><a href="{{route('admin.articles.index')}}">Listar</a></li>
                    <li><a href="{{route('admin.articles.create')}}">Criar</a></li>
                </ul>
            </li>
        </ul>

        <ul class="nav navbar-nav navbar-right">
            <li class="dropdown">
                <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!! Auth::user()-
>name !!}<span class="caret"></span></a>
                <ul class="dropdown-menu">
                    <li><a href="{{ route('logout') }}">Sair</a></li>
                </ul>
            </li>
        </ul>
    </div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

app/Http/controllers/ArticlesController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Article;
use App\User;
use App\Category;
use Session;
use Redirect;

class ArticlesController extends Controller
{
    public function index()
    {
        $articles = Article::orderBy('id','DESC')->paginate(5);
        return view('admin.articles.index', compact('articles'));
    }
}

```

```
public function create()
{
    $categories = Category::lists('name','id');
    return view('admin.articles.create',compact('categories'));
}

public function store(Request $request)
{
    $article = new Article($request->all());

    $article->save();
    Session::flash('message','Artigo criado com sucesso!');
    return redirect::to('admin/articles');
}

public function show($id)
{
    //
}

public function edit($id)
{
    //
}

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}
}
```

resources/views/admin/articles/create.blade.php

```
@extends('layouts.admin')

@section('title','Criar Artigos')

@section('content')

    {!! Form::open(['route' => 'admin.articles.store', 'method' =>
'POST','files'=>true]) !!}

        <div class="form-group">
            {!! Form::label('title','Título') !!}
            {!! Form::text('title',null,['class' =>'form-control', 'placeholder'
=>'Título do artigo','required']) !!}
        </div>

        <div class="form-group">
            {!! Form::label('content','Conteúdo') !!}
            {!! Form::textarea('content',null,['class' =>'form-control', 'placeholder'
=>'Conteúdo do artigo','required']) !!}
        </div>

        <div class="form-group">
            {!! Form::label('categoria','Categoria') !!}
            {!! Form::select('category_id',$categories, null,['class' =>'form-
control']) !!}
        </div>

        <div class="form-group">

            {!! Form::hidden('user_id', Auth::user()->id, null,['class' =>'form-
control']) !!}
        </div>

        <div class="form-group">
            {!! Form::label('imagem','Imagem') !!}
            {!! Form::file('path') !!}
        </div>

        <div class="form-group">
            {!! Form::submit('Registrar', ['class' =>'btn btn-primary']) !!}
        </div>

    {!! Form::close() !!}
@endsection
```


resources/views/partials/navadmin.php

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">

        <li><a href="{{route('administrador')}}">Inicio</a></li>
        <li><a href="{{route('home')}}">Blog</a></li>

        <li class="dropdown">
          <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
          <ul class="dropdown-menu">
            <li><a href="{{route('admin.users.index')}}">Listar</a></li>
            <li><a href="{{route('admin.users.create')}}">Criar</a></li>
          </ul>
        </li>

        <ul class="nav navbar-nav">
          <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
            <ul class="dropdown-menu">
              <li><a href="{{route('admin.categories.index')}}">Listar</a></li>
              <li><a href="{{route('admin.categories.create')}}">Criar</a></li>
            </ul>
          </li>
        </ul>
      </ul>
    </div>
  </div>
</nav>
```

```

<ul class="nav navbar-nav">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{{route('admin.articles.index')}}">Listar</a></li>
      <li><a href="{{route('admin.articles.create')}}">Criar</a></li>
    </ul>
  </li>
</ul>

<ul class="nav navbar-nav navbar-right">
  <li class="dropdown">
    <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!! Auth::user()-
>name !!}<span class="caret"></span></a>
    <ul class="dropdown-menu">
      <li><a href="{{ route('logout') }}">Sair</a></li>
    </ul>
  </li>
</ul>
</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

Configurando o upload de imagem

config/filesystems.php

```

<?php

return [

    'default' => 'local',

    'cloud' => 's3',

    'disks' => [

        'local' => [
            'driver' => 'local',
            'root' => public_path('images'),
        ],
    ],

```

```

'ftp' => [
  'driver' => 'ftp',
  'host' => 'ftp.example.com',
  'username' => 'your-username',
  'password' => 'your-password',

  // Optional FTP Settings...
  // 'port' => 21,
  // 'root' => '',
  // 'passive' => true,
  // 'ssl' => true,
  // 'timeout' => 30,
],

's3' => [
  'driver' => 's3',
  'key' => 'your-key',
  'secret' => 'your-secret',
  'region' => 'your-region',
  'bucket' => 'your-bucket',
],

'rackspace' => [
  'driver' => 'rackspace',
  'username' => 'your-username',
  'key' => 'your-key',
  'container' => 'your-container',
  'endpoint' => 'https://identity.api.rackspacecloud.com/v2.0/',
  'region' => 'IAD',
  'url_type' => 'publicURL',
],

],

];

```

App/Articles.php

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;
use Cviebrock\EloquentSluggable\SluggableInterface;
use Cviebrock\EloquentSluggable\SluggableTrait;

class Article extends Model implements SluggableInterface
{
    use SluggableTrait;

    protected $sluggable = [
        'build_from' => 'title',
        'save_to'    => 'slug',
    ];

    protected $table = "articles";

    protected $fillable = ['title','content', 'user_id', 'category_id', 'path', 'tags'];

    public function setPathAttribute($path){
        if(!empty($path)){
            $nome = $path->getClientOriginalName();
            $this->attributes['path'] = $nome;
            \Storage::disk('local')->put($nome, \File::get($path));
        }
    }

    public function category()
    {
        return $this->belongsTo('App\Category');
    }

    public function user()
    {
        return $this->belongsTo('App\User');
    }
}
```

Criando um novo artigo

Listagen de artigos | Administraç

Não seguro | miblog.test/admin/articles

Admin BlogInícioBlogUsuáriosCategoriasArtigosDean Schroeder

Listagen de artigos

Artigo criado com sucesso!

| Título | Conteúdo | Autor | Categoria | Imagem | Ações |
|---|---|----------------|-----------|--------|-------|
| Arco íris - Uma linda paisagem | Lorem ipsum dolor sit amet, consectetur adipiscing elit. Phasellus sed mi neque. Integer quis tincidunt elit. Quisque congue at quam ut ornare. Aliquam posuere pretium dolor et congue. Nam ac mattis mi. Integer tristique arcu rhoncus purus sollicitudin tincidunt. Fusce porttitor nunc sed nunc tristique molestie. | Dean Schroeder | aliquam | | |
| Voluptatem ullam ut asperiores facere numquam deleniti. | Eligendi nam eveniet voluptatem ipsum. Doloribus libero sunt labore et fugit. Est magnam ea illo iusto. Ea id et ad non quod ratione. | Wendell Dicki | aliquam | | |
| Voluptatem aliquam iure vel veritatis dolor delectus. | Cum qui et recusandae sint. Corrupti officia quia quas perspiciatis placeat dolor. Libero illo et unde illo amet velit. | Tina O'Conner | aliquam | | |

public

css

fonts

images

no-imagem.jpg

paisagens-com-arco-iris.jpg

Showing rows 0 - 20 (21 total, Query took 0.0010 seconds.) [id: 23... - 1...]

SELECT * FROM `articles` ORDER BY `id` DESC

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all

Number of rows: 25

Filter rows: Search this table

Sort by key: PRIMARY (DESC)

+ Options

| | | id | title | content | slug | path | tags | user_id | category_id | created_at | updated_at | |
|--------------------------|--|----|-------|---------|---|---|---|-----------------------------|-------------|------------|---------------------|---------------------|
| <input type="checkbox"/> | | | | 23 | Arco íris - Uma linda paisagem | Lorem ipsum dolor sit amet, consectetur adipiscing... | arco-iris-uma-linda-paisagem | paisagens-com-arco-iris.jpg | 41 | 4 | 2019-05-23 03:18:41 | 2019-05-23 03:18:41 |
| <input type="checkbox"/> | | | | 20 | Voluptatem ullam ut asperiores facere numquam dele... | Eligendi nam eveniet voluptatem ipsum. Doloribus l... | voluptatem-ullam-ut-asperiores-facere-numquam-dele... | similique | 9 | 4 | 2019-05-22 03:54:22 | 2019-05-22 03:54:22 |
| <input type="checkbox"/> | | | | 19 | Voluptatem aliquam iure vel veritatis dolor delect... | Cum qui et recusandae sint. Corrupti officia quia ... | voluptatem-aliquam-iure-vel-veritatis-dolor-delect... | dolor | 6 | 4 | 2019-05-22 03:54:22 | 2019-05-22 03:54:22 |
| <input type="checkbox"/> | | | | 18 | Impedit ducimus ut ut doloribus. | Dolores sed nulla est. Sit et ut incidunt hic volu... | impedit-ducimus-ut-ut-doloribus | non | 46 | 2 | 2019-05-22 03:54:22 | 2019-05-22 03:54:22 |

Aula 19 - Atualizando e excluindo artigos

app/http/routes.php

```
<?php
```

```
Route::get('/', [  
    'uses' => 'FrontController@index',  
    'as'   => 'home'  
]);
```

```
Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {  
    Route::resource('users', 'UsersController');  
    Route::resource('categories', 'CategoriesController');  
    Route::resource('articles', 'ArticlesController');  
    Route::get('index', [  
        'uses' => 'FrontController@admin',  
        'as'   => 'administrador'  
    ]);  
});
```

```
Route::get('users/{id}/destroy', [  
    'uses' => 'UsersController@destroy',  
    'as'   => 'admin.users.destroy'  
]);
```

```
Route::get('categories/{id}/destroy', [  
    'uses' => 'CategoriesController@destroy',  
    'as'   => 'admin.categories.destroy'  
]);
```

```
Route::get('articles/{id}/destroy', [  
    'uses' => 'ArticlesController@destroy',  
    'as'   => 'admin.articles.destroy'  
]);
```

```
Route::resource('login', 'LoginController');
```

```
Route::get('logout', [  
    'uses' => 'LoginController@logout',  
    'as'   => 'logout'  
]);
```

app/Http/controllers/ArticlesController.php

```
<?php
```

```
namespace App\Http\Controllers;
```

```
use Illuminate\Http\Request;
```

```
use App\Http\Requests;
```

```
use App\Http\Controllers\Controller;
```

```
use App\Article;
```

```
use App\User;
```

```
use App\Category;
```

```
use Session;
```

```
use Redirect;
```

```
class ArticlesController extends Controller
```

```
{
```

```
    public function index()
```

```
    {
```

```
        $articles = Article::orderBy('id','DESC')->paginate(5);
```

```
        return view('admin.articles.index', compact('articles'));
```

```
    }
```

```
    public function create()
```

```
    {
```

```
        $categories = Category::lists('name','id');
```

```
        return view('admin.articles.create',compact('categories'));
```

```
    }
```

```
    public function store(Request $request)
```

```
    {
```

```
        $article = new Article($request->all());
```

```
        $article->save();
```

```
        Session::flash('message','Artigo criado com sucesso!');
```

```
        return redirect::to('admin/articles');
```

```
    }
```

```
    public function show($id)
```

```
    {
```

```
        //
```

```
    }
```

```
public function edit($id)
{
    $users = User::lists('name', 'id');
    $categories = Category::lists('name', 'id');

    $article = Article::find($id);
    return view('admin.articles.edit', compact('users', 'categories', 'article'));
}

public function update(Request $request, $id)
{
    $article = Article::find($id);
    $article->fill($request->all());

    $article->save();
    Session::flash('message', 'Artigo editado com sucesso!');
    return redirect::to('admin/articles') ;
}

public function destroy($id)
{
    Article::destroy($id);
    Session::flash('message', 'Artigo eliminado com sucesso!');
    return redirect::to('admin/articles') ;
}
}
```


resources/views/admin/articles/edit.blade.php

```
@extends('layouts.admin')
```

```
@section('title','Editar artigo: '. $article->title)
```

```
@section('content')
```

```
{!!Form::model($article,['route'=>['admin.articles.update',$article],'method'=>'PUT','files' => true])!!}
```

```
    <div class="form-group">
        {!!Form::label('title','Título')!!}
        {!!Form::text('title',null,['class'=>'form-control','placeholder'=>'Entre com o título'])!!}
    </div>
```

```
    <div class="form-group">
        {!! Form::label('content','Conteúdo') !!}
        {!! Form::textarea('content',null,['class' =>'form-control', 'placeholder' =>'Conteúdo'])!!}
    </div>
```

```
    <div class="form-group">
        {!! Form::label('usuario','Usuário') !!}
        {!! Form::select('user_id',$users, null,['class'=>'form-control']) !!}
    </div>
```

```
    <div class="form-group">
        {!! Form::label('categoria','Categoria') !!}
        {!! Form::select('category_id',$categories, null,['class'=>'form-control']) !!}
    </div>
```

```
    @if(empty($article->path))
        
    @else
        
    @endif
```

```
    <div class="form-group">
        {!!Form::label('imagem','Imagem')!!}
        {!!Form::file('path')!!}
    </div>
```

```
{!!Form::submit('Atualizar',['class'=>'btn btn-primary'])!!}
{!!Form::close()!!}<br>
```

```
@endsection
```

Editando artigos

Admin Blog

Inicio

Blog

Usuários

Categorias

Artigos

AI Murray

Listagen de artigos

| Título | Conteúdo | Autor | Categoria | Imagem | Ações |
|---|--|-----------------------|------------|--------|-------|
| Arco Íris - Uma linda paisagem | A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após u... | Dean Schroeder | Paisagens | | |
| Paisagens naturais | O termo Paisagem é um conceito chave na ciência geográfica. Essa expressão, em resumo, faz referência a tudo aquilo que o indivíduo abstrai do espaço a partir dos seus sentidos (visão, audição, tato, olfato e paladar), o que torna esse termo uma relação entre o ser humano e a sua formaç... | Tina O'Conner | Paisagens | | |
| Planetas do sistema solar | O Sistema Solar compreende o conjunto constituído pelo Sol e todos os corpos celestes que estão sob seu domínio gravitacional. A estrela central, maior componente do sistema, respondendo por mais de 99,85% da massa total,[5] gera sua energia através da fusão de hidrogênio em hélio, dois de se... | Mr. Granville Collier | Astronomia | | |
| Ut architecto voluptas voluptatum et ad non corrupti. | Reprehenderit eveniet mollitia provident in praesentium. Sint in commodi reiciendis unde totam. Qui aut aperiam assumenda est.... | Oran Aufderhar | Paisagens | | |

Excluindo um artigo

Admin Blog

Inicio

Blog

Usuários

miblog.test diz

Tem certeza que deseja excluir o artigo?

OK













Cancelar

AI Murray

Listagen de artigos

| Título | Conteúdo | Autor | Categoria | Imagem | Ações |
|---|--|-----------------------|------------|--------|-------|
| Arco Íris - Uma linda paisagem | A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após u... | Dean Schroeder | Paisagens | | |
| Paisagens naturais | O termo Paisagem é um conceito chave na ciência geográfica. Essa expressão, em resumo, faz referência a tudo aquilo que o indivíduo abstrai do espaço a partir dos seus sentidos (visão, audição, tato, olfato e paladar), o que torna esse termo uma relação entre o ser humano e a sua formaç... | Tina O'Conner | Paisagens | | |
| Planetas do sistema solar | O Sistema Solar compreende o conjunto constituído pelo Sol e todos os corpos celestes que estão sob seu domínio gravitacional. A estrela central, maior componente do sistema, respondendo por mais de 99,85% da massa total,[5] gera sua energia através da fusão de hidrogênio em hélio, dois de se... | Mr. Granville Collier | Astronomia | | |
| Ut architecto voluptas voluptatum et ad non corrupti. | Reprehenderit eveniet mollitia provident in praesentium. Sint in commodi reiciendis unde totam. Qui aut aperiam assumenda est.... | Oran Aufderhar | Paisagens | | |

Artigo eliminado com sucesso!

| Título | Conteúdo | Autor | Categoria | Imagem | Ações |
|--|--|-----------------------|------------|---|---|
| Arco íris - Uma linda paisagem | A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após u... | Dean Schroeder | Paisagens |  |   |
| Paisagens naturais | O termo Paisagem é um conceito chave na ciência geográfica. Essa expressão, em resumo, faz referência a tudo aquilo que o indivíduo abstrai do espaço a partir dos seus sentidos (visão, audição, tato, olfato e paladar), o que torna esse termo uma relação entre o ser humano e a sua formaç... | Tina O'Conner | Paisagens |  |   |
| Planetas do sistema solar | O Sistema Solar compreende o conjunto constituído pelo Sol e todos os corpos celestes que estão sob seu domínio gravitacional. A estrela central, maior componente do sistema, respondendo por mais de 99,85% da massa total,[5] gera sua energia através da fusão de hidrogênio em hélio, dois de se... | Mr. Granville Collier | Astronomia |  |   |
| Quas recusandae ad cum pariatur pariatur illo. | Vel ducimus molestiae veritatis dolore. Consequatur aperiam voluptates in sed iste. Consequatur totam ducimus quisquam ea in iusto.... | Mr. Granville Collier | vel |  |   |

Painel para administradores e membros

resources/views/partials/navadmin.blade.php

```
<nav class="navbar navbar-inverse">
  <div class="container-fluid">
    <!-- Brand and toggle get grouped for better mobile display -->
    <div class="navbar-header">
      <button type="button" class="navbar-toggle collapsed" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1" aria-
expanded="false">
        <span class="sr-only">Toggle navigation</span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
        <span class="icon-bar"></span>
      </button>
      <a class="navbar-brand" href="#">Admin Blog</a>
    </div>

    <!-- Collect the nav links, forms, and other content for toggling -->
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
      <ul class="nav navbar-nav">
        <li><a href="{route('administrador')}">Inicio</a></li>
        <li><a href="{route('home')}">Blog</a></li>
```

```

@if(Auth::user()->type == 'admin')
    <li class="dropdown">
        <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Usuários <span
class="caret"></span></a>
        <ul class="dropdown-menu">
            <li><a href="{{route('admin.users.index')}}">Listar</a></li>
            <li><a href="{{route('admin.users.create')}}">Criar</a></li>
        </ul>
    </li>
</ul>

    <ul class="nav navbar-nav">
        <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Categorias <span
class="caret"></span></a>
            <ul class="dropdown-menu">
                <li><a href="{{route('admin.categories.index')}}">Listar</a></li>
                <li><a href="{{route('admin.categories.create')}}">Criar</a></li>
            </ul>
        </li>
    </ul>


    <ul class="nav navbar-nav">
        <li class="dropdown">
            <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">Artigos <span
class="caret"></span></a>
            <ul class="dropdown-menu">
                <li><a href="{{route('admin.articles.index')}}">Listar</a></li>
                <li><a href="{{route('admin.articles.create')}}">Criar</a></li>
            </ul>
        </li>
    </ul>
@endif

<ul class="nav navbar-nav navbar-right">
    <li class="dropdown">
        <a href="#" class="dropdown-toggle" data-toggle="dropdown"
role="button" aria-haspopup="true" aria-expanded="false">{!! Auth::user()-
>name !!} <span class="caret"></span></a>
        <ul class="dropdown-menu">
            <li><a href="{{ route('logout') }}">Sair</a></li>
        </ul>
    </li>
</ul>


</div><!-- /.navbar-collapse -->
</div><!-- /.container-fluid -->
</nav>

```

Painel para administradores



Painel para membros



Aula 20 - Protegendo a área administrativa

Criando um Middleware

php artisan make:middleware Admin

```
C:\laragon\www\miblog
λ php artisan make:middleware Admin
Middleware created successfully.

C:\laragon\www\miblog
λ |
```

app/http/Middleware/Admin.php

```
<?php
```

```
namespace App\Http\Middleware;
```

```
use Illuminate\Contracts\Auth\Guard;
```

```
use Session;
```

```
use Closure;
```

```
class Admin
```

```
{
```

```
    protected $auth;
```

```
    public function __construct(Guard $auth){
```

```
        $this->auth = $auth;
```

```
    }
```

```
    public function handle($request, Closure $next)
```

```
    {
```

```
        if ($this->auth->user()->type != 'admin') {
```

```
            Session::flash('message-error', 'Sem privilégios para realizar esta  
operação!');
```

```
            return redirect()->to('admin/index');
```

```
        }
```

```
        return $next($request);
```

```
    }
```

```
}
```

app/http/kernel.php

```
<?php
```

```
namespace App\Http;
```

```
use Illuminate\Foundation\Http\Kernel as HttpKernel;
```

```
class Kernel extends HttpKernel
```

```
{
```

```
    /**
```

```
     * The application's global HTTP middleware stack.
```

```
     *
```

```
     * @var array
```

```
     */
```

```
    protected $middleware = [
```

```
        \Illuminate\Foundation\Http\Middleware\CheckForMaintenanceMode::class,
```

```
        \App\Http\Middleware\EncryptCookies::class,
```

```
        \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::class,
```

```
        \Illuminate\Session\Middleware\StartSession::class,
```

```
        \Illuminate\View\Middleware\ShareErrorsFromSession::class,
```

```
        \App\Http\Middleware\VerifyCsrfToken::class,
```

```
    ];
```

```
    /**
```

```
     * The application's route middleware.
```

```
     *
```

```
     * @var array
```

```
     */
```

```
    protected $routeMiddleware = [
```

```
        'auth' => \App\Http\Middleware\Authenticate::class,
```

```
        'auth.basic' =>
```

```
\Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
```

```
        'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
```

```
        'admin' => \App\Http\Middleware\Admin::class
```

```
    ];
```

```
}
```

app/Http/controllers/ArticlesController.php

```
<?php
```

```
namespace App\Http\Controllers;
```

```
use Illuminate\Http\Request;
use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Article;
use App\User;
use App\Category;
use Session;
use Redirect;
```

```
class ArticlesController extends Controller
{
```

```
    public function __construct(){
        $this->middleware('auth');
        $this->middleware('admin', ['only' => ['edit','update','destroy','create']]);
    }
```

```
    public function index()
    {
        $articles = Article::orderBy('id','DESC')->paginate(5);
        return view('admin.articles.index', compact('articles'));
    }
```

```
    public function create()
    {
        $categories = Category::lists('name','id');
        return view('admin.articles.create',compact('categories'));
    }
```

```
    public function store(Request $request)
    {
        $article = new Article($request->all());

        $article->save();
        Session::flash('message','Artigo criado com sucesso!');
        return redirect::to('admin/articles');
    }
```

```
    public function show($id)
    {
        //
    }
```



```

public function edit($id)
{
    $users = User::lists('name', 'id');
    $categories = Category::lists('name', 'id');
    $article = Article::find($id);
    return view('admin.articles.edit',compact('users','categories','article'));
}

public function update(Request $request, $id)
{
    $article = Article::find($id);
    $article-> fill($request->all());
    $article->save();
    Session::flash('message','Artigo editado com sucesso!');
    return redirect::to('admin/articles') ;
}

public function destroy($id)
{
    Article::destroy($id);
    Session::flash('message','Artigo eliminado com sucesso!');
    return redirect::to('admin/articles') ;
}
}

```

app/Http/controllers/CategoriesController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Category;
use Session;
use Redirect;

class CategoriesController extends Controller
{
    public function __construct(){
        $this->middleware('auth');
        $this->middleware('admin', ['only' => ['edit','update','destroy','create']]);
    }
}

```

```

public function index()
{
    $categories = Category::orderBy('id','DESC')->paginate(5);
    return view('admin.categories.index', compact('categories'));
}

public function create()
{
    return view('admin.categories.create');
}

public function store(Request $request)
{
    $category = new Category($request->all());

    $category->save();
    Session::flash('message','Categoria criada com sucesso!');
    return redirect::to('admin/categories');
}

public function show($id)
{
    //
}

public function edit($id)
{
    $category= Category::find($id);
    return view('admin.categories.edit',compact('category'));
}

public function update(Request $request, $id)
{
    $category= Category::find($id);
    $category->fill($request->all());
    $category->save();

    Session::flash('message','Categoria atualizada com sucesso!');
    return redirect::to('admin/categories');
}

public function destroy($id)
{
    $category= Category::find($id);
    $category->delete();

    Session::flash('message','Categoria eliminada com sucesso!');
    return redirect::to('admin/categories');
}
}

```

app/Http/controllers/UsersController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\User;
use Session;
use Redirect;
use App\Http\Requests\UserRequest;

class UsersController extends Controller
{

    public function __construct(){
        $this->middleware('auth');
        $this->middleware('admin', ['only' => ['edit','update','destroy','create']]);
    }

    public function index()
    {
        $users = User::orderBy('id','DESC')->paginate(5);
        return view('admin.users.index', compact('users'));
    }

    public function create()
    {
        return view('admin.users.create');
    }

    public function store(UserRequest $request)
    {
        $user = new User($request->all());
        $user->password = bcrypt($request->password);
        $user->save();
        Session::flash('message','Usuario criado com sucesso!');
        return redirect::to('admin/users');
    }

    public function show($id)
    {
        //
    }
}
```

```

public function edit($id)
{
    $user= User::find($id);
    return view('admin.users.edit',compact('user'));
}




public function update(Request $request, $id)
{
    $user= User::find($id);
    $user->fill($request->all());
    $user->save();

    Session::flash('message','Usuário atualizado com sucesso!');
    return redirect::to('admin/users');
}

public function destroy($id)
{
    $user= User::find($id);
    $user->delete();
    Session::flash('message','Usuário eliminado com sucesso!');
    return redirect::to('admin/users');
}
}

```

Membro tentando acessar rotas de admin pela URL



Aula 21 - Desenho de template básico

resources/views/index.blade.php

```
@extends('layouts.front')

@section('title', 'Mi blog')

@section('content')

<div class="container">

    <div class="row">
        <div class="col-md-8">
            <h1>Últimas Noticias</h1>
            <article>
                <h2> Titulo da noticia</h2>
                <div class="row">
                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-folder-open"></span> Nome
da Categoria
                        <span class="glyphicon glyphicon-user"></span> Nome do
usuário
                    </div>
                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-calendar"></span> Data
                    </div>
                </div>
                <br>
                
                <br>
                <p> Lorem ipsum dolor sit amet, consectetur adipisicing elit.
Consequatur ducimus maxime, inventore veritatis, sit dolor. Harum iure unde
voluptates voluptatum aut cupiditate impedit magnam asperiores alias tenetur,
nobis eligendi nesciunt!</p>
                <a class="btn btn-primary" href="#" role="button">Ler mais...</a>
            </article>
        </div>
    </div>
</div>
```

```

<div class="col-md-4">
  <div class="panel panel-primary">
    <!-- Default panel contents -->
    <div class="panel-heading">Últimas Notícias</div>
    <div class="panel-body"></div>

    <!-- List group -->
    <ul class="list-group">
      <li class="list-group-item">Cras justo odio</li>
      <li class="list-group-item">Dapibus ac facilisis in</li>
      <li class="list-group-item">Morbi leo risus</li>
      <li class="list-group-item">Porta ac consectetur ac</li>
      <li class="list-group-item">Vestibulum at eros</li>
    </ul>
  </div>

  <div class="panel panel-primary">
    <!-- Default panel contents -->
    <div class="panel-heading">Recursos</div>
    <div class="panel-body"></div>

    <!-- List group -->
    <ul class="list-group">
      <li class="list-group-item">Cras justo odio</li>
      <li class="list-group-item">Dapibus ac facilisis in</li>
      <li class="list-group-item">Morbi leo risus</li>
      <li class="list-group-item">Porta ac consectetur ac</li>
      <li class="list-group-item">Vestibulum at eros</li>
    </ul>
  </div>
</div> <!-- fin row -->

<footer>
  <div class="container">
    <hr/>
    <p class="text-center">Copyright &copy; Digital Datos.Todos os direitos reservados</p>
  </div>
</footer>


</div>

@endsection

```

Últimas Notícias

Titulo da noticia

 Nome da Categoria

 Nome do usuário

 Data



Lorem ipsum dolor sit amet, consectetur adipisicing elit. Consequatur ducimus maxime, inventore veritatis, sit dolor. Harum iure unde voluptates voluptatum aut cupiditate impedit magnam asperiores alias tenetur, nobis eligendi nesciunt!

Ler mais...

Últimas Notícias

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Recursos

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Aula 22 - Dados no template

app/http/routes.php

```
<?php

Route::get('/', [
    'uses' => 'FrontController@index',
    'as' => 'home'
]);

Route::get('article/{slug}', [
    'uses' => 'FrontController@article',
    'as' => 'article'
]);

Route::group(['prefix' => 'admin', 'middleware' => 'auth'], function () {
    Route::resource('users', 'UsersController');
    Route::resource('categories', 'CategoriesController');
    Route::resource('articles', 'ArticlesController');
    Route::get('index', [
        'uses' => 'FrontController@admin',
        'as' => 'administrador'
    ]);
});

Route::get('users/{id}/destroy', [
    'uses' => 'UsersController@destroy',
    'as' => 'admin.users.destroy'
]);

Route::get('categories/{id}/destroy', [
    'uses' => 'CategoriesController@destroy',
    'as' => 'admin.categories.destroy'
]);

Route::get('articles/{id}/destroy', [
    'uses' => 'ArticlesController@destroy',
    'as' => 'admin.articles.destroy'
]);

Route::resource('login', 'LoginController');

Route::get('logout', [
    'uses' => 'LoginController@logout',
    'as' => 'logout'
]);
```


resources/views/index.blade.php

```
@extends('layouts.front')
```

```
@section('title', 'Mi blog')
```

```
@section('content')
```

```
<div class="container">
```

```
<div class="row">
```

```
<div class="col-md-8">
```

```
<h1>Últimas Notícias</h1>
```

```
@foreach($articles as $article)
```

```
<article>
```

```
<h2>{{ $article->title }} </h2>
```

```
<div class="row">
```

```
<div class="col-md-6">
```

```
<span class="glyphicon glyphicon-folder-open"></span>
```

```
{{ $article->category->name }}
```

```
<span class="glyphicon glyphicon-user"></span> {{ $article->
```

```
user->name }}
```

```
</div>
```

```
<div class="col-md-6">
```

```
<span class="glyphicon glyphicon-calendar"></span>{{ $article->created_at }}
```

```
</div>
```

```
</div>
```

```
<br>
```

```
@if(empty($article->path))
```

```
@else
```

```

```

```
@endif
```

```
<br>
```

```
<p> {{ substr($article->content, 0,300) }}...</p>
```

```
<a class="btn btn-primary" href="{{ 'article' }}/{{ $article->slug }}"
role="button">Ler mais</a>
```

```
</article>
```

```
@endforeach()
```

```
{!! $articles->render()!!}
```

```
</div>
```

```

<div class="col-md-4">
  <div class="panel panel-primary">
<!-- Default panel contents -->
    <div class="panel-heading">Últimas Notícias</div>
    <div class="panel-body"> </div>

    <!-- List group -->
    <ul class="list-group">
      <li class="list-group-item">Cras justo odio</li>
      <li class="list-group-item">Dapibus ac facilisis in</li>
      <li class="list-group-item">Morbi leo risus</li>
      <li class="list-group-item">Porta ac consectetur ac</li>
      <li class="list-group-item">Vestibulum at eros</li>
    </ul>
  </div>

  <div class="panel panel-primary">
<!-- Default panel contents -->
    <div class="panel-heading">Recursos</div>
    <div class="panel-body">

    </div>

    <!-- List group -->
    <ul class="list-group">
      <li class="list-group-item">Cras justo odio</li>
      <li class="list-group-item">Dapibus ac facilisis in</li>
      <li class="list-group-item">Morbi leo risus</li>
      <li class="list-group-item">Porta ac consectetur ac</li>
      <li class="list-group-item">Vestibulum at eros</li>
    </ul>
  </div>

</div>

</div>

</div> <!-- fin row -->

<footer>
  <div class="container">
    <hr/>
    <p class="text-center">Copyright &copy; Digital Datos.Todos os direitos
reservados</p>
  </div>
</footer>

</div>

@endsection

```

app/Http/controllers/FrontController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Article;

class FrontController extends Controller
{
    public function index()
    {
        $articles = Article::OrderBy('id', 'DESC')->paginate(3);
        return view('index',compact('articles'));
    }

    public function admin()
    {
        return view('admin.index');
    }

    public function article($slug)
    {
        $articles = Article::findBySlug($slug);
        /* $articles->paginate();*/

        return view('article',compact('articles'));
    }

    public function create()
    {
        //
    }

    public function store(Request $request)
    {
        //
    }

    public function show($id)
    {
        //
    }
}
```

```

public function edit($id)
{
    //
}

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}
}

```

resources/views/article.blade.php

```

@extends('layouts.front')

@section('title', 'Mi blog')

@section('content')

<div class="container">
    <div class="row">

        <div class="col-md-8">
            <h1>Últimas Noticias</h1>

            <article>
                <h2>{{ $articles->title }} </h2>

                <div class="row">

                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-folder-open"></span>
                        {{ $articles->category->name }}
                        <span class="glyphicon glyphicon-user"></span> {{ $articles->user->name }}
                    </div>

                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-calendar"></span> {{ $articles->created_at }}
                    </div>
                </div>
            </article>
        </div>
    </div>
</div>

```

```

        <br>
        @if(empty($articles->path))
        @else
        
        @endif
        <br>

        <p> {{($articles->content)}} </p>

    </article>
    <button class="btn btn-primary" onclick="history.go(-1)">« Retornar
</button>

</div>

```

```

<div class="col-md-4">
    <div class="panel panel-primary">
<!-- Default panel contents -->
        <div class="panel-heading">Últimas Notícias</div>
        <div class="panel-body">

    </div>

    <!-- List group -->
    <ul class="list-group">
        <li class="list-group-item">Cras justo odio</li>
        <li class="list-group-item">Dapibus ac facilisis in</li>
        <li class="list-group-item">Morbi leo risus</li>
        <li class="list-group-item">Porta ac consectetur ac</li>
        <li class="list-group-item">Vestibulum at eros</li>
    </ul>
</div>

    <div class="panel panel-primary">
<!-- Default panel contents -->
        <div class="panel-heading">Recursos</div>
        <div class="panel-body">

    </div>

    <!-- List group -->
    <ul class="list-group">
        <li class="list-group-item">Cras justo odio</li>
        <li class="list-group-item">Dapibus ac facilisis in</li>
        <li class="list-group-item">Morbi leo risus</li>
        <li class="list-group-item">Porta ac consectetur ac</li>
        <li class="list-group-item">Vestibulum at eros</li>
    </ul>
</div>

```

</div>

</div>

</div> <!-- fin row -->

<footer>

<div class="container">

<hr/>

<p class="text-center">Copyright © Digital Datos.Todos os direitos reservados</p>

</div>

</footer>

</div>

@endsection

Últimas Notícias

Arco íris - Uma linda paisagem

 Paisagens  Dean Schroeder

 2019-05-23 03:18:41



A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após u...

[Ler mais](#)

Paisagens naturais

 Paisagens  Tina O'Conner

 2019-05-22 03:54:22




O termo Paisagem é um conceito chave na ciência geográfica. Essa expressão, em resumo, faz referência a tudo aquilo que o indivíduo abstrai do espaço a partir dos seus sentidos (visão, audição, tato, olfato e paladar), o que torna esse termo uma relação entre o ser humano e a sua formaç...

[Ler mais](#)

Planetas do sistema solar

 Astronomia  Mr. Granville Collier

 2019-05-22 03:54:22



O Sistema Solar compreende o conjunto constituído pelo Sol e todos os corpos celestes que estão sob seu domínio gravitacional. A estrela central, maior componente do sistema, respondendo por mais de 99,85% da massa total,[5] gera sua energia através da fusão de hidrogênio em hélio, dois de se...

[Ler mais](#)

Últimas Notícias

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Recursos

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Últimas Notícias

Arco íris - Uma linda paisagem

 Paisagens  Dean Schroeder

 2019-05-23 03:18:41



A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após uma chuvaram, por exemplo. Quando um raio bate na borda de uma gotinha de água ou de vapor, a luz branca do Sol é desviada e se decompõe nas sete cores que compõem seu espectro: vermelho, laranja, amarelo, verde, azul, anil e violeta. É o mesmo efeito do prisma, que aprendemos na escola: cada cor é refletida em um ângulo diferente e muda de direção ao retornar para a atmosfera. A cor vermelha é a que se propaga mais rápido, formando a faixa superior do arco-íris. A violeta, a mais lenta, aparece na parte inferior. O fenômeno é tão comum que os cientistas acumulam alguns recordes coloridos. "Em laboratório, foram observados mais de 12 arco-íris a partir de uma única gota d'água", afirma o físico José Pedro Rino, da Universidade Federal de São Carlos (UFSCAR).

[« Retornar](#)

Últimas Notícias

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Recursos

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Aula 23 - Solucionando problema de atualização de slug

app/Http/controllers/ArticlesController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Http\Requests;
use App\Http\Controllers\Controller;
use App\Article;
use App\User;
use App\Category;
use Session;
use Redirect;

class ArticlesController extends Controller
{
    public function __construct(){
        $this->middleware('auth');
        $this->middleware('admin', ['only' => ['edit','update','destroy','create']]);
    }

    public function index()
    {
        $articles = Article::orderBy('id','DESC')->paginate(5);
        return view('admin.articles.index', compact('articles'));
    }

    public function create()
    {
        $categories = Category::lists('name','id');
        return view('admin.articles.create',compact('categories'));
    }

    public function store(Request $request)
    {
        $article = new Article($request->all());

        $article->save();
        Session::flash('message','Artigo criado com sucesso!');
        return redirect::to('admin/articles');
    }
}
```

```

public function show($id)
{
    //
}

public function edit($id)
{
    $users = User::lists('name', 'id');
    $categories = Category::lists('name', 'id');

    $article = Article::find($id);
    return view('admin.articles.edit', compact('users', 'categories', 'article'));
}

public function update(Request $request, $id)
{
    $article = Article::find($id);
    $article-> fill($request->all());

    $article->resluggify();

    $article->save();
    Session::flash('message', 'Artigo editado com sucesso!');
    return redirect::to('admin/articles') ;
}

public function destroy($id)
{
    Article::destroy($id);
    Session::flash('message', 'Artigo eliminado com sucesso!');
    return redirect::to('admin/articles') ;
}
}


```

Aula 24 - Datas e comentários

Manipulação de datas

Acesse a URL:

<https://carbon.nesbot.com/docs/>



The screenshot shows the Carbon documentation website. The browser's address bar displays <https://carbon.nesbot.com/docs/>. The website's header includes the Carbon logo and navigation links: Getting Started, Docs, Reference, History, Contribute, and GitHub. The main content area is titled "Introduction" and explains that the Carbon class is inherited from the PHP `DateTime` class. It includes a code snippet for the Carbon class declaration in PHP. A sidebar on the right lists various topics covered in the documentation, such as Introduction, Instantiation, Localization, Testing Aids, Getters, Setters, Weeks, Fluent Setters, IsSet, String Formatting, Common Formats, Conversion, Comparison, Addition and Subtraction, Difference, Difference for Humans, Modifiers, Constants, and Serialization. The main text also mentions the `CarbonImmutable` class extending `DateTimeImmutable`.

carbon Getting Started Docs Reference History Contribute GitHub

Introduction

The Carbon class is [inherited](#) from the PHP [DateTime](#) class.

```
<?php
namespace Carbon;

class Carbon extends \DateTime
{
    // code here
}
```

You can see from the code snippet above that the Carbon class is declared in the Carbon namespace. You need to import the namespace to use Carbon without having to provide its fully qualified name each time.

```
use Carbon\Carbon;
```

Examples in this documentation will assume you imported classes of the Carbon namespace this way.


We also provide `CarbonImmutable` class extending [DateTimeImmutable](#). The same methods are available on

- Introduction
- Instantiation
- Localization
- Testing Aids
- Getters
- Setters
- Weeks
- Fluent Setters
- IsSet
- String Formatting
- Common Formats
- Conversion
- Comparison
- Addition and Subtraction
- Difference
- Difference for Humans
- Modifiers
- Constants
- Serialization

Instalação do pacote jenssegers/date

Acesse a URL:


<https://packalyst.com/>



Procure pelo pacote **jenssegers/date**

Para instalar entre com o seguinte comando no terminal:

composer require jenssegers/date



No arquivo **app/config/app.php**, na seção **providers**, incluir a seguinte linha:

```
// Jenssegers/date  
Jenssegers\Date\DateServiceProvider::class
```

E na seção **aliases**, incluir a seguinte linha:

```
'Date' => Jenssegers\Date\Date::class,
```

app/Http/controllers/FrontController.php

```
<?php  
  
namespace App\Http\Controllers;  
  
use Illuminate\Http\Request;  
  
use App\Http\Requests;  
use App\Http\Controllers\Controller;  
use App\Article;  
use Jenssegers\Date\Date;  
  
class FrontController extends Controller  
{  
  
    public function __construct(){  
        Date::setLocale('pt-br');  
    }  
  
    public function index()  
    {  
        $articles = Article::OrderBy('id', 'DESC')->paginate(3);  
        return view('index',compact('articles'));  
    }  
  
    public function admin()  
    {  
        return view('admin.index');  
    }  
  
    public function article($slug)  
    {  
        $articles = Article::findBySlug($slug);  
        /* $articles->paginate();*/  
  
        return view('article',compact('articles'));  
    }  
}
```

```
public function create()
{
    //
}

public function store(Request $request)
{
    //
}

public function show($id)
{
    //
}

public function edit($id)
{
    //
}

public function update(Request $request, $id)
{
    //
}

public function destroy($id)
{
    //
}
}
```

resources/views/index.blade.php

```
@extends('layouts.front')

@section('title', 'Mi blog')

@section('content')

<div class="container">
    <div class="row">

        <div class="col-md-8">
            <h1>Últimas Notícias</h1>
            @foreach($articles as $article)
                <article>
                    <h2>{{ $article->title }} </h2>

                    <div class="row">

                        <div class="col-md-6">
                            <span class="glyphicon glyphicon-folder-open"></span>
                            {{ $article->category->name }}
                            <span class="glyphicon glyphicon-user"></span> {{ $article->user->name }}
                        </div>

                        <div class="col-md-6">
                            <span class="glyphicon glyphicon-calendar"></span>
                            {{ Date::parse($article->created_at)->format('j \d\e F \d\e Y')}}
                        </div>

                    </div>

                    <br>
                    @if(empty($article->path))
                    @else
                        
                    @endif
                    <br>

                    <p> {{ substr($article->content, 0,300) }}...</p>

                    <a class="btn btn-primary" href="{{ '{'article' } } / {{ $article->slug }}"
                    role="button">Ler mais</a>
                </article>
            @endforeach()

            {!! $articles->render() !!}

        </div>
    </div>
</div>
```

```

<div class="col-md-4">
  <div class="panel panel-primary">
<!-- Default panel contents -->
    <div class="panel-heading">Últimas Notícias</div>
    <div class="panel-body">

</div>

<!-- List group -->
<ul class="list-group">
  <li class="list-group-item">Cras justo odio</li>
  <li class="list-group-item">Dapibus ac facilisis in</li>
  <li class="list-group-item">Morbi leo risus</li>
  <li class="list-group-item">Porta ac consectetur ac</li>
  <li class="list-group-item">Vestibulum at eros</li>
</ul>
</div>

<div class="panel panel-primary">
<!-- Default panel contents -->
  <div class="panel-heading">Recursos</div>
  <div class="panel-body">

</div>

<!-- List group -->
<ul class="list-group">
  <li class="list-group-item">Cras justo odio</li>
  <li class="list-group-item">Dapibus ac facilisis in</li>
  <li class="list-group-item">Morbi leo risus</li>
  <li class="list-group-item">Porta ac consectetur ac</li>
  <li class="list-group-item">Vestibulum at eros</li>
</ul>
</div>

</div>
</div>

</div> <!-- fin row -->

<footer>
  <div class="container">
    <hr/>
    <p class="text-center">Copyright &copy; Digital Datos.Todos os direitos
reservados</p>
  </div>
</footer>
</div>

@endsection

```


resources/views/article.blade.php

```
@extends('layouts.front')

@section('title', 'Mi blog')

@section('content')

<div class="container">
    <div class="row">

        <div class="col-md-8">
            <h1>Últimas Noticias</h1>

            <article>
                <h2>{{ $articles->title }} </h2>

                <div class="row">

                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-folder-open"></span>
                        {{ $articles->category->name }}
                        <span class="glyphicon glyphicon-user"></span> {{ $articles->user->name }}
                    </div>

                    <div class="col-md-6">
                        <span class="glyphicon glyphicon-calendar"></span>
                        {{ Date::parse($articles->created_at)->format('j \d\e F \d\e Y')}}
                    </div>

                </div>

                <br>
                @if(empty($articles->path))
                @else
                
                @endif
                <br>

                <p class="text-justify">{{ ($articles->content) }}</p>

            </article>
            <button class="btn btn-primary" onclick="history.go(-1)">« Retornar
        </button>

    </div>

</div>
```

```

<div class="col-md-4">
  <div class="panel panel-primary">
<!-- Default panel contents -->
    <div class="panel-heading">Últimas Notícias</div>
    <div class="panel-body">

</div>

<!-- List group -->
<ul class="list-group">
  <li class="list-group-item">Cras justo odio</li>
  <li class="list-group-item">Dapibus ac facilisis in</li>
  <li class="list-group-item">Morbi leo risus</li>
  <li class="list-group-item">Porta ac consectetur ac</li>
  <li class="list-group-item">Vestibulum at eros</li>
</ul>
</div>

<div class="panel panel-primary">
<!-- Default panel contents -->
  <div class="panel-heading">Recursos</div>
  <div class="panel-body">

</div>

<!-- List group -->
<ul class="list-group">
  <li class="list-group-item">Cras justo odio</li>
  <li class="list-group-item">Dapibus ac facilisis in</li>
  <li class="list-group-item">Morbi leo risus</li>
  <li class="list-group-item">Porta ac consectetur ac</li>
  <li class="list-group-item">Vestibulum at eros</li>
</ul>
</div>

</div>

</div>

</div> <!-- fin row -->

<footer>
  <div class="container">
    <hr/>
    <p class="text-center">Copyright &copy; Digital Datos.Todos os direitos
reservados</p>
  </div>
</footer>
</div>

```

@endsection

Últimas Notícias

Arco íris - Uma linda paisagem

 Paisagens  Dean Schroeder

 23 de maio de 2019



A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após u...

[Ler mais](#)

Últimas Notícias

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Recursos

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus


Porta ac consectetur ac

Vestibulum at eros

Últimas Notícias

Arco íris - Uma linda paisagem

 Paisagens  Dean Schroeder

 23 de maio de 2019



A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após uma chuvarada, por exemplo. Quando um raio bate na borda de uma gotinha de água ou de vapor, a luz branca do Sol é desviada e se decompõe nas sete cores que compõem seu espectro: vermelho, laranja, amarelo, verde, azul, anil e violeta. É o mesmo efeito do prisma, que aprendemos na escola: cada cor é refletida em um ângulo diferente e muda de direção ao retornar

Últimas Notícias

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac

Vestibulum at eros

Recursos

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus


Porta ac consectetur ac

Vestibulum at eros

Sistema de comentários

Acesse a URL
<https://disqus.com/>

E cadastre-se.



resources/views/article.blade.php

```
@extends('layouts.front')
```

```
@section('title', 'Mi blog')
```

```
@section('content')
```

```
<div class="container">
```

```
<div class="row">
```

```
<div class="col-md-8">
```

```
<h1>Últimas Notícias</h1>
```

```
<article>
```

```
<h2>{{ $articles->title }} </h2>
```

```

<div class="row">

    <div class="col-md-6">
        <span class="glyphicon glyphicon-folder-open"></span>
        {{ $articles->category->name }}
        <span class="glyphicon glyphicon-user"></span> {{ $articles-
>user->name }}
    </div>

    <div class="col-md-6">
        <span class="glyphicon glyphicon-calendar"></span>
        {{ Date::parse($articles->created_at)->format('j \d\e F \d\e Y')}}
    </div>

</div>

<br>
@if(empty($articles->path))
@else

@endif
<br>

<p class="text-justify">{{ ($articles->content) }}</p>

</article>
<button class="btn btn-primary" onclick="history.go(-1)">« Retornar
</button>

<div id="disqus_thread"></div>
<script>

/**
 * RECOMMENDED CONFIGURATION VARIABLES: EDIT AND
UNCOMMENT THE SECTION BELOW TO INSERT DYNAMIC VALUES FROM YOUR
PLATFORM OR CMS.
 * LEARN WHY DEFINING THESE VARIABLES IS IMPORTANT:
https://disqus.com/admin/universalcode/#configuration-variables*/
/*
var disqus_config = function () {
this.page.url = PAGE_URL; // Replace PAGE_URL with your page's
canonical URL variable
this.page.identifier = PAGE_IDENTIFIER; // Replace PAGE_IDENTIFIER
with your page's unique identifier variable
};
*/
(function() { // DON'T EDIT BELOW THIS LINE
var d = document, s = d.createElement('script');
s.src = 'https://oriontecinfo-1.disqus.com/embed.js';
s.setAttribute('data-timestamp', +new Date());
(d.head || d.body).appendChild(s);

```

```
})();  
</script>  
<noscript>Please enable JavaScript to view the <a  
href="https://disqus.com/?ref_noscript">comments powered by  
Disqus.</a></noscript>
```

```
</div>
```

```
<div class="col-md-4">  
  <div class="panel panel-primary">  
    <!-- Default panel contents -->  
    <div class="panel-heading">Últimas Notícias</div>  
    <div class="panel-body">  
  
    </div>  
  
    <!-- List group -->  
    <ul class="list-group">  
      <li class="list-group-item">Cras justo odio</li>  
      <li class="list-group-item">Dapibus ac facilisis in</li>  
      <li class="list-group-item">Morbi leo risus</li>  
      <li class="list-group-item">Porta ac consectetur ac</li>  
      <li class="list-group-item">Vestibulum at eros</li>  
    </ul>  
  </div>  
  
  <div class="panel panel-primary">  
    <!-- Default panel contents -->  
    <div class="panel-heading">Recursos</div>  
    <div class="panel-body">  
  
    </div>  
  
    <!-- List group -->  
    <ul class="list-group">  
      <li class="list-group-item">Cras justo odio</li>  
      <li class="list-group-item">Dapibus ac facilisis in</li>  
      <li class="list-group-item">Morbi leo risus</li>  
      <li class="list-group-item">Porta ac consectetur ac</li>  
      <li class="list-group-item">Vestibulum at eros</li>  
    </ul>  
  </div>  
  
</div>  
  
</div>  
  
</div> <!-- fin row -->
```

```

<footer>
  <div class="container">
    <hr/>
    <p class="text-center">Copyright &copy; Digital Datos.Todos os direitos
reservados</p>
  </div>
</footer>

</div>

@endsection

```

Mi Blog
Início
Contato
Categorias
Administrador

Últimas Notícias

Arco íris - Uma linda paisagem

 Dean Schroeder  23 de maio de 2019



A mitologia grega diria que ele aparece sempre que a deusa Íris deixa um rastro colorido no céu, para transmitir aos homens as mensagens de Zeus, o todo-poderoso do Olimpo. A explicação científica é bem menos romântica. O arco-íris surge quando o Sol ilumina a umidade suspensa no ar, após uma chuvareda, por exemplo. Quando um raio bate na borda de uma gotinha de água ou de vapor, a luz branca do Sol é desviada e se decompõe nas sete cores que compõem seu espectro: vermelho, laranja, amarelo, verde, azul, anil e violeta. É o mesmo efeito do prisma, que aprendemos na escola: cada cor é refletida em um ângulo diferente e muda de direção ao retornar para a atmosfera. A cor vermelha é a que se propaga mais rápido, formando a faixa superior do arco-íris. A violeta, a mais lenta, aparece na parte inferior. O fenômeno é tão comum que os cientistas acumulam alguns recordes coloridos. "Em laboratório, foram observados mais de 12 arco-íris a partir de uma única gota d'água", afirma o físico José Pedro Rino, da Universidade Federal de São Carlos (UFSCAR).

Retornar

0 Comments
OrionTecInfo
betopinheiro1005

Recommend
Tweet
Share
Sort by Best



Be the first to comment.

Subscribe
Add Disqus to your site
Disqus' Privacy Policy
DISQUS

Copyright © Digital Datos.Todos os direitos reservados

| Últimas Notícias |
|-------------------------|
| |
| Cras justo odio |
| Dapibus ac facilisis in |
| Morbi leo risus |
| Porta ac consectetur ac |
| Vestibulum at eros |

| Recursos |
|-------------------------|
| |
| Cras justo odio |
| Dapibus ac facilisis in |
| Morbi leo risus |
| Porta ac consectetur ac |
| Vestibulum at eros |