Curso Laravel - Roles y Permisos Italo Morales (Rimorsoft)

https://www.youtube.com/watch?v=EwqZgypiKYk&list=PLhCiuvlix-rSgQNLIl7Qg2KbQni3fz-ea

Resumo do curso feito por Roberto Pinheiro

Aula 2 - Instalação de pacotes

Instalando o Laravel Collective

Acesse a URL:

https://github.com/LaravelCollective/docs/blob/5.6/html.md

No terminal, na pasta do projeto, entre com o seguinte comando: composer require "laravelcollective/html":"^5.4.0"

```
C:\laragon\www\laravel-roles
\lambda composer require "laravelcollective/html":"^5.4.0"
./composer.json has been updated
Loading composer repositories with package information
Updating dependencies (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
- Installing laravelcollective/html (v5.6.10): Loading from cache
Writing lock file
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover
Discovered Package: laravel/tinker
Discovered Package: laravel/tinker
Discovered Package: laravelcollective/html
Discovered Package: nunomaduro/collision
Package manifest generated successfully.

C:\laragon\www\laravel-roles
\lambda
```

Abra o arquivo config/app.php e insira as seguintes linhas:

```
'providers' => [
    // ...
    Collective\Html\HtmlServiceProvider::class,
    // ...
],
'aliases' => [
    // ...
    'Form' => Collective\Html\FormFacade::class,
    'Html' => Collective\Html\HtmlFacade::class,
    // ...
],
```

Instalando shinobi

Trata-se de um pacote para administrar as permissões.

Acesse a URL:

https://github.com/caffeinated/shinobi

No terminal, na pasta do projeto, entre com o seguinte comando:

composer require caffeinated/shinobi

```
C:\laragon\www\laravel-roles
λ composer require caffeinated/shinobi
Using version ^3.3 for caffeinated/shinobi
./composer.json has been updated
Loading composer repositories with package information
Updating dependencies (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
  - Installing caffeinated/shinobi (v3.3): Loading from cache
Writing lock file
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover
Discovered Package: caffeinated/shinobi
Discovered Package: fideloper/proxy
Discovered Package: laravel/tinker
Discovered Package: laravelcollective/html
Discovered Package: nunomaduro/collision
Package manifest generated successfully.
C:\laragon\www\laravel-roles
λ
```

Abra o arquivo config/app.php e, em providers, insira a seguinte linha:

Caffeinated\Shinobi\ShinobiServiceProvider::class,

Aula 3 - Estrutura base de um sistema com regras e permissões

Alterando tamanho padrão de campo string

app/Providers/AppServiceProvider.php

```
<?php
namespace App\Providers;
use Illuminate\Support\ServiceProvider;
use Illuminate\Support\Facades\Schema;
class AppServiceProvider extends ServiceProvider
{
   public function boot()
   {
      Schema::defaultStringLength(120);
   }
   public function register()
   {
      //
   }
}</pre>
```

Criando as tabelas

php artisan migrate

```
C:\laragon\www\laravel-roles

λ php artisan migrate

Migration table created successfully.

Migrating: 2014_10_12_000000_create_users_table

Migrated: 2014_10_12_100000_create_users_table

Migrating: 2014_10_12_100000_create_password_resets_table

Migrated: 2014_10_12_100000_create_password_resets_table

Migrating: 2015_01_20_084450_create_roles_table

Migrating: 2015_01_20_084450_create_roles_table

Migrating: 2015_01_20_084525_create_role_user_table

Migrating: 2015_01_20_084525_create_role_user_table

Migrating: 2015_01_24_080208_create_permissions_table

Migrated: 2015_01_24_080208_create_permissions_table

Migrating: 2015_01_24_080433_create_permission_role_table

Migrating: 2015_01_24_080433_create_permission_role_table

Migrating: 2015_01_24_080433_create_permission_role_table

Migrated: 2015_01_24_080433_create_permission_role_table


Migrating: 2015_12_04_003040_add_special_role_column

Migrated: 2015_12_04_003040_add_special_role_column

Migrated: 2017_10_17_170735_create_permission_user_table


C:\laragon\www\laravel-roles

λ
```




As migrações de Shinobi localizam-se na pasta:

vendor/caffeinate/shinobi/migrations



Relações entre as tabelas

Acesse o phpmyadmin e clique na aba More→Design



Criando um seed de Permissões

php artisan make:seeder PermissionsTableSeeder

```
C:\laragon\www\laravel-roles
λ php artisan make:seeder PermissionsTableSeeder
Seeder created successfully.
C:\laragon\www\laravel-roles
λ |
```

database/seeds/PermissionsTableSeeder

```
<?php
use Illuminate\Database\Seeder;

class PermissionsTableSeeder extends Seeder
{
   public function run()
   {
      //
   }
}</pre>
```

Aula 4 - Definição de permissões do sistema

database/seeds/PermissionsTableSeeder

```
<?php
use Illuminate\Database\Seeder;
use Caffeinated\Shinobi\Models\Permission;
class PermissionsTableSeeder extends Seeder
  public function run()
  {
    // users
     Permission::create([
       'name' => 'Exibir usuários',
       'slug' => 'users.index',
       'description' => 'Lista e exibe todos os usuários do sistema',
     ]);
     Permission::create([
       'name' => 'Ver detalhes de usuário',
       'slug' => 'users.show',
       'description' => 'Ver em detalhes cada usuário do sistema',
     1);
     Permission::create([
       'name' => 'Edição de usuários',
       'slug' => 'users.edit',
       'description' => 'Editar qualquer dado de um usuário do sistema',
     ]);
     Permission::create([
       'name' => 'Eliminar usuário',
       'slug' => 'users.destroy',
       'description' => 'Eliminar qualquer usuário do sistema',
     ]);
     // Roles
     Permission::create([
       'name' => 'Exibir roles',
       'slug' => 'roles.index',
       'description' => 'Lista e exibe todos os roles do sistema',
     ]);
     Permission::create([
       'name' => 'Ver detalhes de rol',
       'slug' => 'roles.show',
       'description' => 'Ver em detalhes cada role do sistema',
     ]);
```

```
Permission::create([
       'name' => 'Criação de rol',
       'slug' => 'roles.create',
       'description' => 'Criar role do sistema',
     1);
     Permission::create([
       'name' => 'Edição de rol',
       'slug' => 'roles.edit',
       'description' => 'Editar qualquer dado de um role do sistema',
     1);
     Permission::create([
       'name' => 'Eliminar rol',
       'slug' => 'roles.destroy',
       'description' => 'Eliminar qualquer role do sistema',
     ]);
     // Products
     Permission::create([
       'name' => 'Exibir produtos',
       'slug' => 'products.index',
       'description' => 'Lista e exibe todos os produtos do sistema',
     Permission::create([
       'name' => 'Ver detalhes de produto',
       'slug' => 'products.show',
       'description' => 'Ver em detalhes cada produto do sistema',
     1);
     Permission::create([
       'name' => 'Criação de produto',
       'slug' => 'products.create',
       'description' => 'Criar produto do sistema',
     1);
     Permission::create([
       'name' => 'Edição de produto',
       'slug' => 'products.edit',
       'description' => 'Editar qualquer dado de um produto do sistema',
     1);
     Permission::create([
       'name' => 'Eliminar produto',
       'slug' => 'products.destroy',
       'description' => 'Eliminar qualquer produto do sistema',
     ]);
  }
}
```


database/seeds/DatabaseTableSeeder

```
<?php
use Illuminate\Database\Seeder;
class DatabaseSeeder extends Seeder
{
   public function run()
   {
      $this->call(PermissionsTableSeeder::class);
   }
}
```

Criando os registros de permissões

php artisan migrate:refresh --seed

```
C:\laragon\www\laravel-roles
 \ php artisan migrate:refresh --seed
Rolling back: 2017_10_17_170735_create_permission_user_table
Rolled back: 2017_10_17_170735_create_permission_user_table
Rolling back: 2015_12_04_003040_add_special_role_column
Rolled back: 2015_12_04_003040_add_special_role_column
Rolling back: 2015_01_24_080433_create_permission_role_table
Rolled back: 2015_01_24_080433_create_permission_role_table
Rolling back: 2015_01_24_080208_create_permissions_table
Rolled back: 2015_01_24_080208_create_permissions_table Rolling back: 2015_01_20_084525_create_role_user_table
Rolled back: 2015_01_20_084525_create_role_user_table
Rolling back: 2015_01_20_084450_create_roles_table
Rolled back: 2015_01_20_084450_create_roles_table
Rolling back: 2014_10_12_100000_create_password_resets_table
Rolled back: 2014 10 12 100000 create password resets table
Rolling back: 2014_10_12_000000_create_users_table
Rolled back: 2014 10 12 000000 create users table
Migrating: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_0000000_create_users_table
Migrating: 2014_10_12_1000000_create_password_resets_table
Migrated: 2014_10_12_1000000_create_password_resets_table
Migrating: 2015_01_20_084450_create_roles_table
Migrated: 2015_01_20_084450_create_roles_table
Migrating: 2015_01_20_084525_create_role_user_table
Migrated: 2015_01_20_084525_create_role_user_table
Migrating: 2015_01_24_080208_create_permissions_table
Migrated: 2015_01_24_080208_create_permissions_table
Migrating: 2015_01_24_080433_create_permission_role table
Migrated: 2015_01_24_080433_create_permission_role_table
Migrating: 2015_12_04_003040_add_special_role_column
Migrated: 2015_12_04_003040_add_special_role_column
Migrating: 2017_10_17_170735_create_permission_user_table Migrated: 2017_10_17_170735_create_permission_user_table Seeding: PermissionsTableSeeder
C:\laragon\www\laravel-roles
```



Aula 5 - Factory, migrations, models, controllers

model, factory, migration e controller de Produtos

php artisan make:model Product -a

```
C:\laragon\www\laravel-roles

\( \) php artisan make:model Product -a

Model created successfully.
Factory created successfully.
Created Migration: 2019_04_17_210019_create_products_table
Controller created successfully.

C:\laragon\www\laravel-roles
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \|
\( \) \
```

criando seeders para usuários e produtos

php artisan make:seeder ProductsTableSeeder

```
C:\laragon\www\laravel-roles
λ php artisan make:seeder ProductsTableSeeder
Seeder created successfully.
C:\laragon\www\laravel-roles
λ |
```

php artisan make:seeder UsersTableSeeder

```
C:\laragon\www\laravel-roles
λ php artisan make:seeder UsersTableSeeder
Seeder created successfully.
C:\laragon\www\laravel-roles
λ |
```

Aula 6 - Seeders

```
database/migrations/ 2019_04_17_210019_create_products_table.php
<?php
use Illuminate\Support\Facades\Schema;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Database\Migrations\Migration;
class CreateProductsTable extends Migration
  public function up()
     Schema::create('products', function (Blueprint $table) {
        $table->increments('id');
        $table->string('name');
        $table->string('description');
        $table->timestamps();
     });
  }
  public function down()
     Schema::dropIfExists('products');
  }
}
database/factories/ProductFactory.php
<?php
use Faker\Generator as Faker;
$factory->define(App\Product::class, function (Faker $faker) {
  return [
    'name' => $faker -> sentence,
    'description' => $faker -> sentence
  ];
});
```

database/factories/UserFactory.php

```
<?php
use Faker\Generator as Faker;
| Model Factories
| This directory should contain each of the model factory definitions for
 your application. Factories provide a convenient way to generate new
| model instances for testing / seeding your application's database.
*/
$factory->define(App\User::class, function (Faker $faker) {
  return [
     'name' => $faker->name,
     'email' => $faker->unique()->safeEmail,
     'password' =>
'$2y$10$TKh8H1.PfQx37YgCzwiKb.KjNyWgaHb9cbcoQgdIVFlYg7B77UdFm', // secret
     'remember_token' => str_random(10),
  ];
});
database/seeds/UsersTableSeeder.php
<?php
use Illuminate\Database\Seeder;
use Caffeinated\Shinobi\Models\Role;
class UsersTableSeeder extends Seeder
  public function run()
     factory(App\User::class, 20)->create();
     Role::create([
      'name' => 'Admin',
      'slug' => 'admin',
      'special' => 'all-access'
     ]);
  }
}
```

database/seeds/ProductsTableSeeder.php

```
<?php
use Illuminate\Database\Seeder;
class ProductsTableSeeder extends Seeder
  public function run()
     factory(App\Product::class, 80) -> create();
}
database/seeds/DatabaseTableSeeder
<?php
use Illuminate\Database\Seeder;
class DatabaseSeeder extends Seeder
  public function run()
     $this->call(PermissionsTableSeeder::class);
     $this->call(ProductsTableSeeder::class);
     $this->call(UsersTableSeeder::class);
  }
}
```

Populando as tabelas de produtos e usuários

php artisan migrate:refresh --seed

```
λ php artisan migrate:refresh --seed
Rolling back: 2019 04 17 210019 create products table
Rolled back: 2019_04_17_210019_create_products_table
Rolling back: 2017_10_17_170735_create_permission_user_table
Rolled back: 2017_10_17_170735_create_permission_user_table
Rolling back: 2015_12_04_003040_add_special_role_column
Rolled back: 2015_12_04_003040_add_special_role_column
Rolling back: 2015_01_24_080433_create_permission_role_table
Rolled back: 2015_01_24_080433_create_permission_role_table
Rolling back: 2015_01_24_080208_create_permissions_table
Rolled back: 2015_01_24_080208_create_permissions_table
Rolling back: 2015_01_20_084525_create_role_user_table
Rolled back: 2015_01_20_084525_create_role_user_table
Rolling back: 2015_01_20_084450_create_roles_table
Rolled back: 2015_01_20_084450_create_roles_table
Rolling back: 2014_10_12_100000_create_password_resets_table
Rolled back: 2014_10_12_100000_create_password_resets_table Rolling back: 2014_10_12_000000_create_users_table
Rolled back: 2014_10_12_000000_create_users_table
Migrating: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_000000_create_users_table
Migrating: 2014_10_12_100000_create_password_resets_table
Migrated: 2014_10_12_100000_create_password_resets_table
Migrating: 2015_01_20_084450_create_roles_table
Migrated: 2015_01_20_084450_create_roles_table
Migrating: 2015_01_20_084525_create_role_user_table
Migrated: 2015_01_20_084525_create_role_user_table Migrating: 2015_01_24_080208_create_permissions_table
Migrated: 2015_01_24_080208_create_permissions_table
Migrating: 2015_01_24_080433_create_permission_role_table
Migrated: 2015_01_24_080433_create_permission_role_table
Migrating: 2015_12_04_003040_add_special_role_column
Migrated: 2015_12_04_003040_add_special_role_column
Migrating: 2017_10_17_170735_create_permission_user_table
Migrated: 2017_10_17_170735_create_permission_user_table
Migrating: 2019_04_17_210019_create_products_table
Migrated: 2019_04_17_210019_create_products_table
Seeding: PermissionsTableSeeder
Seeding: ProductsTableSeeder
Seeding: UsersTableSeeder
```




Tabela de Usuários




Tabela de produtos





Tabela de roles:



Aula 7 - Middleware de Papéis e Permissões

Autenticação

php artisan make:auth

```
C:\laragon\www\laravel-roles
λ php artisan make:auth
Authentication scaffolding generated successfully.
C:\laragon\www\laravel-roles
λ |
```

routes/web.php

Configurando Middleware

app/Http/kernel.php

```
<?php
namespace App\Http;
use Illuminate\Foundation\Http\Kernel as HttpKernel;
class Kernel extends HttpKernel
{
   * The application's global HTTP middleware stack.
   * These middleware are run during every request to your application.
   * @var array
   */
  protected $middleware = [
     \Illuminate\Foundation\Http\Middleware\CheckForMaintenanceMode::class,
     \Illuminate\Foundation\Http\Middleware\ValidatePostSize::class,
     \App\Http\Middleware\TrimStrings::class,
     \Illuminate\Foundation\Http\Middleware\ConvertEmptyStringsToNull::class,
     \App\Http\Middleware\TrustProxies::class,
  ];
   * The application's route middleware groups.
   * @var array
  protected $middlewareGroups = [
     'web' => [
       \App\Http\Middleware\EncryptCookies::class,
       \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::class,
       \Illuminate\Session\Middleware\StartSession::class,
        // \Illuminate\Session\Middleware\AuthenticateSession::class,
       \Illuminate\View\Middleware\ShareErrorsFromSession::class,
       \App\Http\Middleware\VerifyCsrfToken::class,
       \Illuminate\Routing\Middleware\SubstituteBindings::class,
     ],
     'api' => [
        'throttle:60,1',
        'bindings',
     ],
  ];
```

```
* The application's route middleware.
   * These middleware may be assigned to groups or used individually.
   * @var array
   */
  protected $routeMiddleware = [
     'auth' => \Illuminate\Auth\Middleware\Authenticate::class,
     'auth.basic' => \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
     'bindings' => \Illuminate\Routing\Middleware\SubstituteBindings::class,
     'cache.headers' => \Illuminate\Http\Middleware\SetCacheHeaders::class,
     'can' => \Illuminate\Auth\Middleware\Authorize::class,
     'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
     'signed' => \Illuminate\Routing\Middleware\ValidateSignature::class,
     'throttle' => \Illuminate\Routing\Middleware\ThrottleRequests::class,
     'role' => \Caffeinated\Shinobi\Middleware\UserHasRole::class,
     'permission' => \Caffeinated\Shinobi\Middleware\UserHasPermission::class,
  ];
}
```

Aula 8 - Rotas e atribuição de permissões


```
routes/web.php
<?php
| Web Routes
 .....
Here is where you can register web routes for your application. These
| routes are loaded by the RouteServiceProvider within a group which
| contains the "web" middleware group. Now create something great!
*/
Route::get('/', function () {
  return view('welcome');
});
Auth::routes();
Route::get('/home', 'HomeController@index')->name('home');
Route::middleware(['auth'])->group(function(){
  // Roles
  Route::post('roles/store', 'RoleController@store')->name('roles.store')
  ->middleware('permission:roles.create');
  Route::get('roles', 'RoleController@index')->name('roles.index')
  ->middleware('permission:roles.index');
  Route::get('roles/create', 'RoleController@create')->name('roles.create')
  ->middleware('permission:roles.create');
  Route::put('roles/{role}', 'RoleController@update')->name('roles.update')
  ->middleware('permission:roles.edit');
  Route::get('roles/{role}', 'RoleController@show')->name('roles.show')
  ->middleware('permission:roles.show');
  Route::delete('roles/{role}', 'RoleController@destroy')->name('roles.destroy')
  ->middleware('permission:roles.destroy');
  Route::get('roles/{role}/edit', 'RoleController@edit')->name('roles.edit')
  ->middleware('permission:roles.edit');
```

```
// Products
  Route::post('products/store', 'ProductController@store')->name('products.store')
  ->middleware('permission:products.create');
  Route::get('products', 'ProductController@index')->name('products.index')
  ->middleware('permission:products.index');
  Route::get('products/create', 'ProductController@create')->name('products.create')
  ->middleware('permission:products.create');
  Route::put('products/{product}', 'ProductController@update')->name('products.update')
  ->middleware('permission:products.edit');
  Route::get('products/{product}', 'ProductController@show')->name('products.show')
  ->middleware('permission:products.show');
  Route::delete('products/{product}', 'ProductController@destroy')-
>name('products.destroy')
  ->middleware('permission:products.destroy');
  Route::get('products/{product}/edit', 'ProductController@edit')->name('products.edit')
  ->middleware('permission:products.edit');
  // Users
  Route::get('users', 'UserController@index')->name('users.index')
  ->middleware('permission:users.index');
  Route::put('users/{user}', 'UserController@update')->name('users.update')
  ->middleware('permission:users.edit');
  Route::get('users/{user}', 'UserController@show')->name('users.show')
  ->middleware('permission:users.show');
  Route::delete('users/{user}', 'UserController@destroy')->name('users.destroy')
  ->middleware('permission:users.destroy');
  Route::get('users/{user}/edit', 'UserController@edit')->name('users.edit')
  ->middleware('permission:users.edit');
});
```

Aula 9 - Ocultar botões se não há permissões

Inserindo um usuário

Senha: 123456



Criando controllers para usuários e funções

php artisan make:controller UserController --resource

```
C:\laragon\www\laravel-roles
λ php artisan make:controller UserController --resource
Controller created successfully.
C:\laragon\www\laravel-roles
λ |
```

php artisan make:controller RoleController --resource


```
C:\laragon\www\laravel-roles
λ php artisan make:controller RoleController --resource
Controller created successfully.

C:\laragon\www\laravel-roles
λ |
```

resources/views/welcome.php

```
<!doctype html>
<html lang="{{ app()->getLocale() }}">
  <head>
     <meta charset="utf-8">
     <meta http-equiv="X-UA-Compatible" content="IE=edge">
     <meta name="viewport" content="width=device-width, initial-scale=1">
     <title>Roles e Permissions</title>
     <!-- Fonts -->
     k href="https://fonts.googleapis.com/css?family=Raleway:100,600"
rel="stylesheet" type="text/css">
     <!-- Styles -->
     <style>
        html, body {
          background-color: #fff;
          color: #636b6f;
          font-family: 'Raleway', sans-serif;
          font-weight: 100;
          height: 100vh;
          margin: 0;
        }
        .full-height {
          height: 100vh;
        }
        .flex-center {
          align-items: center;
          display: flex;
          justify-content: center;
        .position-ref {
          position: relative;
        .top-right {
          position: absolute;
          right: 10px;
          top: 18px;
        }
        .content {
          text-align: center;
        .title {
          font-size: 84px;
```

```
.links > a {
          color: #636b6f;
          padding: 0 25px;
          font-size: 12px;
          font-weight: 600;
          letter-spacing: .1rem;
          text-decoration: none;
          text-transform: uppercase;
       }
        .m-b-md {
          margin-bottom: 30px;
     </style>
  </head>
  <body>
     <div class="flex-center position-ref full-height">
        @if (Route::has('login'))
          <div class="top-right links">
             @auth
                <a href="{{ url('/home') }}">Home</a>
             @else
                <a href="{{ route('login') }}">Login</a>
                <a href="{{ route('register') }}">Registro</a>
             @endauth
          </div>
        @endif
        <div class="content">
          <div class="title m-b-md">
             Roles e Permissions
          </div>
          <div class="links">
             <a href="http://oriontecinfo.com.br/">OrionTecInfo</a>
          </div>
        </div>
     </div>
  </body>
</html>
```



Roles e Permissions

ORIONTECINFO

resources/views/layouts/app.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
<head>
  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <!-- CSRF Token -->
  <meta name="csrf-token" content="{{ csrf_token() }}">
  <title>{{ config('app.name', 'Laravel') }}</title>
  <!-- Scripts -->
  <script src="{{ asset('js/app.js') }}" defer></script>
  <!-- Fonts -->
  <link rel="dns-prefetch" href="https://fonts.gstatic.com">
  <link href="https://fonts.googleapis.com/css?family=Nunito" rel="stylesheet" type="text/css">
  <!-- Styles -->
  k href="{{ asset('css/app.css') }}" rel="stylesheet">
</head>
<body>
  <div id="app">
     <nav class="navbar navbar-expand-md navbar-light navbar-laravel">
        <div class="container">
          <a class="navbar-brand" href="{{ url('/') }}">
             {{ config('app.name', 'Laravel') }}
          </a>
          <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-expanded="false"
aria-label="{{ __('Toggle navigation') }}">
             <span class="navbar-toggler-icon"></span>
          </button>
          <div class="collapse navbar-collapse" id="navbarSupportedContent">
             <!-- Left Side Of Navbar -->
             ul class="navbar-nav mr-auto">
                @can('products.index')
                cli class="nav-item">
                  <a class="nav-link" href="{{ route('products.index') }}">Produtos</a>
                @endcan
                @can('users.index')
                class="nav-item">
                  <a class="nav-link" href="{{ route('users.index') }}">Usuários</a>
                @endcan
                @can('roles.index')
                class="nav-item">
                  <a class="nav-link" href="{{ route('roles.index') }}">Funções</a>
                @endcan
             <!-- Right Side Of Navbar -->
             ul class="navbar-nav ml-auto">
```

```
<!-- Authentication Links -->
               @guest
                  class="nav-item">
                     <a class="nav-link" href="{{ route('login') }}">{{ __('Login') }}</a>
                  class="nav-item">
                     <a class="nav-link" href="{{ route('register') }}">{{ __('Register') }}</a>
                  @else
                  class="nav-item dropdown">
                     <a id="navbarDropdown" class="nav-link dropdown-toggle" href="#"
role="button" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false" v-pre>
                       {{ Auth::user()->name }} <span class="caret"></span>
                     <div class="dropdown-menu dropdown-menu-right" aria-
labelledby="navbarDropdown">
                       <a class="dropdown-item" href="{{ route('logout') }}"</pre>
                         onclick="event.preventDefault();
                                  document.getElementById('logout-form').submit();">
                          {{ __('Logout') }}
                       <form id="logout-form" action="{{ route('logout') }}" method="POST"
style="display: none;">
                          @csrf
                       </form>
                     </div>
                  @endguest
             </div>
        </div>
     </nav>
     <main class="py-4">
        @yield('content')
     </main>
  </div>
</body>
</html>
```

Aula 10 - Aplicando roles e permissions


```
app/User.php
<?php
namespace App;
use Caffeinated\Shinobi\Traits\ShinobiTrait;
use Illuminate\Notifications\Notifiable;
use Illuminate\Foundation\Auth\User as Authenticatable;
class User extends Authenticatable
  use Notifiable, ShinobiTrait;
  protected $fillable = [
    'name', 'email', 'password',
  ];
  protected $hidden = [
    'password', 'remember_token',
  ];
}
roles
+ Options

▼ id name slug description created_at updated_at


\leftarrow T \rightarrow
 Check all
             With selected: get Edit : Copy   Delete  Export
role_user
+ Options
\leftarrow T \rightarrow
                 1
                                  21 2019-04-17 23:37:34 2019-04-17 23:37:34
 Check all
                With selected: Ø Edit 3 Copy
                                           Delete
                                                   Export
```



roles



permission_role





Aula 11 - Ocultar ou mostrar botões segundo a permissão atribuída

Volte a deixar o usuário 21 com todos os acessos:



Na tabela permission_role, apague os dois acessos personalizados

http/Controllers/ProductController.php

```
<?php
namespace App\Http\Controllers;
use App\Product;
use Illuminate\Http\Request;
class ProductController extends Controller
  public function index()
  {
     $products = Product::paginate();
     return view('products.index', compact('products'));
  public function create()
     //
  }
  public function store(Request $request)
  {
     //
  }
  public function show(Product $product)
     //
  }
```

```
public function edit(Product $product)
{
     //
}


public function update(Request $request, Product $product)
{
     //
}

public function destroy(Product $product)
{
     //
}
```

resources/views/products/index.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
    <div class="col-md-1"></div>
    <div class="col-md-10">
      <div class="card">
        <div class="card-header">
          Produtos
          @can('products.create')
            <a href="{{ route('products.create') }}"
            class="btn btn-sm btn-primary float-right">
               Criar
             </a>
          @endcan
        </div>
        <div class="card-body">
          <thead>
              ID
                Nome
                 
              </thead>
```

```
@foreach($products as $product)
                 {{ $product->id }}
                   {{ $product->name }}
                   @can('products.show')
                        <a href="{{ route('products.show', $product->id) }}"
                          class="btn btn-sm btn-success">Ver</a>
                      @endcan
                   @can('products.edit')
                        <a href="{{ route('products.edit', $product->id) }}"
                          class="btn btn-sm btn-warning">Editar</a>
                      @endcan
                   @can('products.destroy')
                        {!! Form::open(['route' => ['products.destroy', $product->id],
                        'method' => 'DELETE']) !!}
                          <button class="btn btn-sm btn-danger">Eliminar</button>
                        {!! Form::close() !!}
                      @endcan
                   @endforeach
             {{ $products->render() }}
        </div>
      </div>
    </div>
    <div class="col-md-1"></div>
  </div>
</div>
@endsection
```



Aula 12 - Métodos de um controlador - Injeção de método

http/Controllers/ProductController.php

```
<?php
namespace App\Http\Controllers;
use App\Product;
use Illuminate\Http\Request;
class ProductController extends Controller
  public function index()
     $products = Product::paginate();
     return view('products.index', compact('products'));
  public function create()
     return view('products.create');
  public function store(Request $request)
     $product = Product::create($request->all());
     return redirect()->route('products.edit', $product->id)
     ->with('info', 'Produto gravado com sucesso!');
  }
  public function show(Product $product)
     return view('products.show', compact('product'));
  public function edit(Product $product)
     return view('products.edit', compact('product'));
  public function update(Request $request, Product $product)
     $product->update($request->all());
     return redirect()->route('products.edit', $product->id)
     ->with('info', 'Produto atualizado com sucesso!');
  }
  public function destroy(Product $product)
     $product->delete();
     return back()->with('info', 'Produto eliminado com sucesso!');
}
```

app/Product.php

```
<?php
namespace App;
use Illuminate\Database\Eloquent\Model;
class Product extends Model
{
   protected $fillable = [
     'name', 'description'
   ];
}</pre>
```

Aula 13 - Vista form e show | Debug de erros

resources/views/products/partials/form.blade.php

```
<div class="form-group">
    {{ Form::label('name', 'Nome do produto') }}
    {{ Form::text('name', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
    {{ Form::label('description', 'Descrição do produto') }}
    {{ Form::text('description', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
    {{ Form::submit('Gravar', ['class' => 'btn btn-sm btn-primary']) }}
</div>
```

resources/views/products/show.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
       <div class="card">
          <div class="card-header">Produto</div>
          <div class="card-body">
            <strong>Produto: </strong> {{ $product->name }}
            <strong>Descrição: </strong> {{ $product->description }}
          </div>
       </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
```



Aula 14 - Formulário criar e editar do módulo de produtos

resources/views/products/edit.blade.php

@endsection

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
        <div class="card">
          <div class="card-header">Produto</div>
          <div class="card-body">
             {!! Form::model($product, ['route' => ['products.update', $product->id],
'method' => 'PUT']) !!}
                @include('products.partials.form')
             {!! Form::close() !!}
          </div>
        </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
resources/views/products/create.blade.php
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
        <div class="card">
          <div class="card-header">Produto</div>
          <div class="card-body">
             {!! Form::open(['route' => 'products.store']) !!}
                @include('products.partials.form')
             {!! Form::close() !!}
          </div>
        </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
```


resources/views/layouts/app.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
<head>
  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <!-- CSRF Token -->
  <meta name="csrf-token" content="{{ csrf_token() }}">
  <title>{{ config('app.name', 'Laravel') }}</title>
  <!-- Scripts -->
  <script src="{{ asset('js/app.js') }}" defer></script>
  <!-- Fonts -->
  <link rel="dns-prefetch" href="https://fonts.gstatic.com">
  <link href="https://fonts.googleapis.com/css?family=Nunito" rel="stylesheet"</pre>
type="text/css">
  <!-- Styles -->
  <link href="{{ asset('css/app.css') }}" rel="stylesheet">
</head>
<body>
  <div id="app">
     <nav class="navbar navbar-expand-md navbar-light navbar-laravel">
       <div class="container">
          <a class="navbar-brand" href="{{ url('/') }}">
             {{ config('app.name', 'Laravel') }}
          </a>
          <button class="navbar-toggler" type="button" data-toggle="collapse" data-
target="#navbarSupportedContent" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="{{ ___('Toggle navigation') }}">
             <span class="navbar-toggler-icon"></span>
          </button>
          <div class="collapse navbar-collapse" id="navbarSupportedContent">
             <!-- Left Side Of Navbar -->
             ul class="navbar-nav mr-auto">
               @can('products.index')
                class="nav-item">
                  <a class="nav-link" href="{{ route('products.index') }}">Produtos</a>
                @endcan
               @can('users.index')
               class="nav-item">
                  <a class="nav-link" href="{{ route('users.index') }}">Usuários</a>
               @endcan
               @can('roles.index')
               class="nav-item">
                  <a class="nav-link" href="{{ route('roles.index') }}">Funções</a>
               @endcan
```


```
<!-- Right Side Of Navbar -->
             ul class="navbar-nav ml-auto">
               <!-- Authentication Links -->
               @guest
                  class="nav-item">
                     <a class="nav-link" href="{{ route('login') }}">{{ __('Login') }}</a>
                  cli class="nav-item">
                     <a class="nav-link" href="{{ route('register') }}">{{ __('Register') }}</a>
                  @else
                  class="nav-item dropdown">
                     <a id="navbarDropdown" class="nav-link dropdown-toggle" href="#"
role="button" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false" v-pre>
                       {{ Auth::user()->name }} <span class="caret"></span>
                     </a>
                     <div class="dropdown-menu dropdown-menu-right" aria-
labelledby="navbarDropdown">
                       <a class="dropdown-item" href="{{ route('logout') }}"</pre>
                         onclick="event.preventDefault();
                                   document.getElementById('logout-form').submit();">
                          {{ __('Logout') }}
                       <form id="logout-form" action="{{ route('logout') }}" method="POST"
style="display: none;">
                          @csrf
                       </form>
                     </div>
                  @endguest
             </div>
        </div>
     </nav>
```

```
<br/>br>
     @if(session('info'))
        <div class="container">
           <div class="row">
              <div class="col-md-1"></div>
<div class="col-md-10">
                  <div class="alert alert-success">
                    {{ session('info') }}
                  </div>
              </div>
              <div class="col-md-1"></div>
           </div>
        </div>
     @endif
     @yield('content')
  </div>
</body>
</html>
```


Editando um produto:




Criando um produto:



Eliminando um produto (id 81)





Aula 15 - Módulo de usuário - index

http/Controllers/UserController.php

```
<?php
namespace App\Http\Controllers;
use App\User;
use Illuminate\Http\Request;
class UserController extends Controller
     public function index()
  {
     $users = User::paginate();
     return view('users.index', compact('users'));
  }
  public function show(User $user)
     return view('users.show', compact('user'));
  public function edit(User $user)
     return view('users.edit', compact('user'));
  public function update(Request $request, User $user)
     $user->update($request->all());
     return redirect()->route('users.index', $user->id)
     ->with('info', 'Usuário atualizado com sucesso!');
  }
  public function destroy(User $user)
     $user->delete();
     return back()->with('info', 'Usuário eliminado com sucesso!');
}
```


Duplique (copie) a pasta views/resources/products como views/resources/users

Elimine o arquivo create.blade.php

Nesta primeira etapa, altere apenas o arquivo abaixo

resources/views/users/index.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
 <div class="row justify-content-center">
    <div class="col-md-1"></div>
    <div class="col-md-10">
      <div class="card">
        <div class="card-header">
          Usuários
        </div>
        <div class="card-body">
          <thead>
              ID
                Nome
                 
              </thead>
            @foreach($users as $user)
                {{ $user->id }}
                  {{ $user->name }}
                  @can('users.show')
                      <a href="{{ route('users.show', $user->id) }}"
                        class="btn btn-sm btn-success">Ver</a>
                    @endcan
                  @can('users.edit')
                      <a href="{{ route('users.edit', $user->id) }}"
                        class="btn btn-sm btn-warning">Editar</a>
                    @endcan
                  @can('users.destroy')
                      {!! Form::open(['route' => ['users.destroy', $user->id],
                       'method' => 'DELETE']) !!}
                         <button class="btn btn-sm btn-danger">Eliminar</button>
                      {!! Form::close() !!}
                    @endcan
                  @endforeach
```



Aula 16 - Módulo de usuário - show, destroy, edit

resources/views/users/show.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
       <div class="card">
          <div class="card-header">Usuário</div>
          <div class="card-body">
             <strong>Nome: </strong> {{ $user->name }}
             <strong>Email: </strong> {{ $user->email }}
          </div>
       </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
```


resources/views/users/edit.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
        <div class="card">
           <div class="card-header">Usuário</div>
           <div class="card-body">
             {!! Form::model($user, ['route' => ['users.update', $user->id], 'method' =>
'PUT']) !!}
                @include('users.partials.form')
             {!! Form::close() !!}
           </div>
        </div>
     </div>
     <div class="col-md-1"></div>
   </div>
</div>
@endsection
```


resources/views/users/partials/form.blade.php


```
<div class="form-group">
    {{ Form::label('name', 'Nome do usuário') }}
    {{ Form::text('name', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
    {{ Form::label('email', 'Email') }}
    {{ Form::text('email', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
    {{ Form::submit('Gravar', ['class' => 'btn btn-sm btn-primary']) }}
</div>
```

Exibindo informações de usuário:




Editando informações de usuário:





Eliminando usuário de id 2:




Aula 17 - Desenho de edição de usuários (Listagem de roles)

resources/views/users/partials/form.blade.php

```
<div class="form-group">
  {{ Form::label('name', 'Nome') }}
 {{ Form::text('name', null, ['class' => 'form-control']) }}
</div>
<hr>
<h3>Lista de roles</h3>
<div class="form-group">
  ul class="list-unstyled">
    @foreach($roles as $role)
      <label>
           {{ Form::checkbox('roles[]', $role->id, null) }}
           {{ $role->name }}
           <em>({{ $role->description ? : 'Sem descrição' }})</em>
         </label>
      @endforeach
  </div>
<div class="form-group">
  {{ Form::submit('Gravar', ['class' => 'btn btn-sm btn-primary']) }}
</div>
```


http/Controllers/UserController.php

```
<?php
namespace App\Http\Controllers;
use App\User;
use Caffeinated\Shinobi\Models\Role;
use Illuminate\Http\Request;
class UserController extends Controller
     public function index()
  {
     $users = User::paginate();
     return view('users.index', compact('users'));
  }
  public function show(User $user)
     return view('users.show', compact('user'));
  }
  public function edit(User $user)
     $roles = Role::get();
     return view('users.edit', compact('user', 'roles'));
  public function update(Request $request, User $user)
  {
     $user->update($request->all());
     return redirect()->route('users.index', $user->id)
     ->with('info', 'Usuário atualizado com sucesso!');
  }
  public function destroy(User $user)
  {
     $user->delete();
     return back()->with('info', 'Usuário eliminado com sucesso!');
  }
}
```




Aula 18 - Atribuição de roles a usuários

Na tabela roles, altere description de "null" para "Role Administrador"




Crie um novo role: Suspenso



```
<?php
namespace App\Http\Controllers;
use App\User;
use Caffeinated\Shinobi\Models\Role;
use Illuminate\Http\Request;
class UserController extends Controller
     public function index()
  {
     $users = User::paginate();
     return view('users.index', compact('users'));
  }
  public function show(User $user)
     return view('users.show', compact('user'));
  }
  public function edit(User $user)
     $roles = Role::get();
     return view('users.edit', compact('user', 'roles'));
  }
  public function update(Request $request, User $user)
     // Atualizar usuário
     $user->update($request->all());
     // Atualizar roles
     $user->roles()->sync($request->get('roles'));
     return redirect()->route('users.index', $user->id)
     ->with('info', 'Usuário atualizado com sucesso!');
  }
  public function destroy(User $user)
     $user->delete();
     return back()->with('info', 'Usuário eliminado com sucesso!');
  }
}
```

Editando roles do usuário de id 1:



Marque a opção "Suspenso" e clique no botão "Gravar".





tabela role_user



Aula 19 - Desenho do módulo Roles

http/Controllers/RoleController.php

```
<?php
namespace App\Http\Controllers;
use Caffeinated\Shinobi\Models\Role;
use Caffeinated\Shinobi\Models\Permission;
use Illuminate\Http\Request;
class RoleController extends Controller
     public function index()
  {
     $roles = Role::paginate();
     return view('roles.index', compact('roles'));
  }
  public function create()
     return view('roles.create');
  }
  public function store(Request $request)
     $role = Role::create($request->all());
     return redirect()->route('roles.edit', $role->id)
     ->with('info', 'Role gravado com sucesso!');
  }
  public function show(Role $role)
     return view('roles.show', compact('role'));
  }
  public function edit(Role $role)
     $roles = Role::get();
     return view('roles.edit', compact('role', 'roles'));
  public function update(Request $request, Role $role)
     // Atualizar usuário
     $role->update($request->all());
```

```
// Atualizar roles
$role->roles()->sync($request->get('roles'));


return redirect()->route('roles.edit', $role->id)
    ->with('info', 'Role atualizado com sucesso!');
}

public function destroy(Role $role)
{
    $role->delete();
    return back()->with('info', 'Role eliminado com sucesso!');
}
```

resources/views/roles/index.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
    <div class="col-md-1"></div>
    <div class="col-md-10">
      <div class="card">
        <div class="card-header">
          Roles
          @can('roles.create')
            <a href="{{ route('roles.create') }}"
            class="btn btn-sm btn-primary float-right">
               Criar
             </a>
          @endcan
        </div>
        <div class="card-body">
          <thead>
              ID
                Role
                 
              </thead>
            @foreach($roles as $role)
                   {{ $role->id }}
                   {{ $role->name }}
                  @can('roles.show')
                       <a href="{{ route('roles.show', $role->id) }}"
                         class="btn btn-sm btn-success">Ver</a>
                    @endcan
```

```
@can('roles.edit')
                         <a href="{{ route('roles.edit', $role->id) }}"
                           class="btn btn-sm btn-warning">Editar</a>
                      @endcan
                    @can('roles.destroy')
                         {!! Form::open(['route' => ['roles.destroy', $role->id],
                         'method' => 'DELETE']) !!}
                           <button class="btn btn-sm btn-danger">Eliminar</button>
                         {!! Form::close() !!}
                      @endcan
                    @endforeach
             {{ $roles->render() }}
         </div>
      </div>
    </div>
    <div class="col-md-1"></div>
  </div>
</div>
@endsection
```



resources/views/roles/create.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
        <div class="card">
           <div class="card-header">Role</div>
           <div class="card-body">
             {!! Form::open(['route' => 'roles.store']) !!}
                @include('roles.partials.form')
             {!! Form::close() !!}
           </div>
        </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
```

resources/views/roles/edit.blade.php


```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
        <div class="card">
           <div class="card-header">Role</div>
           <div class="card-body">
             {!! Form::model($role, ['route' => ['roles.update', $role->id], 'method'
=> 'PUT']) !!}
                @include('roles.partials.form')
             {!! Form::close() !!}
           </div>
        </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
```


resources/views/roles/show.blade.php

```
@extends('layouts.app')
@section('content')
<div class="container">
  <div class="row justify-content-center">
     <div class="col-md-1"></div>
     <div class="col-md-10">
       <div class="card">
          <div class="card-header">Role</div>
          <div class="card-body">
            <strong>Role: </strong> {{ $role->name }}
            <strong>Slug: </strong> {{ $role->slug }}
            <strong>Descrição: </strong> {{ $role->description }}
          </div>
       </div>
     </div>
     <div class="col-md-1"></div>
  </div>
</div>
@endsection
```

Eliminando um role

Elimine o role de id 2





Aula 20 - Gravar e editar roles e permissions

resources/views/roles/partials/form.blade.php

```
<div class="form-group">
  {{ Form::label('name', 'Nome') }}
  {{ Form::text('name', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
  {{ Form::label('slug', 'URL amigável') }}
  {{ Form::text('slug', null, ['class' => 'form-control']) }}
</div>
<div class="form-group">
  {{ Form::label('description', 'Descrição') }}
  {{ Form::textarea('description', null, ['class' => 'form-control']) }}
</div>
<hr>
<h3>Permissão especial</h3>
<div class="form-group">
  <label>{{ Form::radio('special', 'all-access') }} Acesso Total</label>
  <label>{{ Form::radio('special', 'no-access') }} Nenhum Acesso</label>
</div>
<h3>Lista de permissions</h3>
<div class="form-group">
  ul class="list-unstyled">
    @foreach($permissions as $permission)
       <label>
           {{ Form::checkbox('permissions[]', $permission->id, null) }}
           {{ $permission->name }}
           <em>({{ $permission->description ? : 'Sem descrição' }})</em>
         </label>
       @endforeach
  </div>
<div class="form-group">
  {{ Form::submit('Gravar', ['class' => 'btn btn-sm btn-primary']) }}
</div>
```

http/Controllers/RoleController.php


```
<?php
namespace App\Http\Controllers;
use Caffeinated\Shinobi\Models\Role;
use Caffeinated\Shinobi\Models\Permission;
use Illuminate\Http\Request;
class RoleController extends Controller
     public function index()
  {
     $roles = Role::paginate();
     return view('roles.index', compact('roles'));
  }
  public function create()
     $permissions = Permission::get();
     return view('roles.create', compact('permissions'));
  }
  public function store(Request $request)
     $role = Role::create($request->all());
     // Atualizar permissions
     $role->permissions()->sync($request->get('permissions'));
     return redirect()->route('roles.edit', $role->id)
     ->with('info', 'Role gravado com sucesso!');
  }
  public function show(Role $role)
     return view('roles.show', compact('role'));
  }
  public function edit(Role $role)
     $permissions = Permission::get();
     return view('roles.edit', compact('role', 'permissions'));
  }
  public function update(Request $request, Role $role)
  {
     // Atualizar role
     $role->update($request->all());
```


```
// Atualizar permissions
$role->permissions()->sync($request->get('permissions'));

return redirect()->route('roles.edit', $role->id)
    ->with('info', 'Role atualizado com sucesso!');
}

public function destroy(Role $role)
{
    $role->delete();
    return back()->with('info', 'Role eliminado com sucesso!');
}
```

Criando role e permissions











Registrando um novo usuário

Senha: 123456




Administrador atribuindo role de supervisor ao usuário registrado




Usuário criado (Italo Morales) acessando o sistema

Descrição: Voluptas non recusandae et neque sit nihil et sed.

Produtos:



Usuários:



Roles:





Aula 21 - Atribuindo permissões a partir das rotas e do controlador

```
routes/web.php
<?php
| Web Routes
 .....
Here is where you can register web routes for your application. These
| routes are loaded by the RouteServiceProvider within a group which
| contains the "web" middleware group. Now create something great!
*/
Route::get('/', function () {
  return view('welcome');
});
Auth::routes();
Route::get('/home', 'HomeController@index')->name('home');
Route::middleware(['auth'])->group(function(){
  Route::resource('roles', 'RoleController');
  // Products
  Route::post('products/store', 'ProductController@store')->name('products.store')
  ->middleware('permission:products.create');
  Route::get('products', 'ProductController@index')->name('products.index')
  ->middleware('permission:products.index');
  Route::get('products/create', 'ProductController@create')->name('products.create')
  ->middleware('permission:products.create');
  Route::put('products/{product}', 'ProductController@update')->name('products.update')
  ->middleware('permission:products.edit');
  Route::get('products/{product}', 'ProductController@show')->name('products.show')
  ->middleware('permission:products.show');
  Route::delete('products/{product}', 'ProductController@destroy')-
>name('products.destroy')
  ->middleware('permission:products.destroy');
  Route::get('products/{product}/edit', 'ProductController@edit')->name('products.edit')
  ->middleware('permission:products.edit');
  // Users
  Route::get('users', 'UserController@index')->name('users.index')
  ->middleware('permission:users.index');
  Route::put('users/{user}', 'UserController@update')->name('users.update')
  ->middleware('permission:users.edit');
```

```
Route::get('users/{user}', 'UserController@show')->name('users.show')
->middleware('permission:users.show');
Route::delete('users/{user}', 'UserController@destroy')->name('users.destroy')
->middleware('permission:users.destroy');
Route::get('users/{user}/edit', 'UserController@edit')->name('users.edit')
->middleware('permission:users.edit');
});
```

http/Controllers/RoleController.php

```
<?php
namespace App\Http\Controllers;
use Caffeinated\Shinobi\Models\Role;
use Caffeinated\Shinobi\Models\Permission;
use Illuminate\Http\Request;
class RoleController extends Controller
  public function __construct()
     $this->middleware('permission:roles.create')->only(['create', 'store']);
     $this->middleware('permission:roles.index')->only(['index']);
     $this->middleware('permission:roles.edit')->only(['edit', 'update']);
     $this->middleware('permission:roles.show')->only(['show']);
     $this->middleware('permission:roles.destroy')->only(['destroy']);
  }
  public function index()
  {
     $roles = Role::paginate();
     return view('roles.index', compact('roles'));
  }
  public function create()
     $permissions = Permission::get();
     return view('roles.create', compact('permissions'));
  }
  public function store(Request $request)
     $role = Role::create($request->all());
     // Atualizar permissions
     $role->permissions()->sync($request->get('permissions'));
     return redirect()->route('roles.edit', $role->id)
     ->with('info', 'Role gravado com sucesso!');
  }
  public function show(Role $role)
     return view('roles.show', compact('role'));
  }
```

```
public function edit(Role $role)
     $permissions = Permission::get();
     return view('roles.edit', compact('role', 'permissions'));
  }
  public function update(Request $request, Role $role)
     // Atualizar role
     $role->update($request->all());
     // Atualizar permissions
     $role->permissions()->sync($request->get('permissions'));
     return redirect()->route('roles.edit', $role->id)
     ->with('info', 'Role atualizado com sucesso!');
  }
  public function destroy(Role $role)
     $role->delete();
     return back()->with('info', 'Role eliminado com sucesso!');
  }
}
```

resources/views/errors/403.blade.php

```
<!doctype html>
<html lang="{{ app()->getLocale() }}">
  <head>
     <meta charset="utf-8">
     <meta http-equiv="X-UA-Compatible" content="IE=edge">
     <meta name="viewport" content="width=device-width, initial-scale=1">
     <title>Erro 403</title>
     <!-- Fonts -->
     k href="https://fonts.googleapis.com/css?family=Raleway:100,600"
rel="stylesheet" type="text/css">
     <!-- Styles -->
     <style>
        html, body {
          background-color: #fff;
          color: #636b6f;
          font-family: 'Raleway', sans-serif;
          font-weight: 100;
          height: 100vh;
          margin: 0;
       }
        .full-height {
          height: 100vh;
        }
        .flex-center {
          align-items: center;
          display: flex;
          justify-content: center;
        .position-ref {
          position: relative;
        .top-right {
          position: absolute;
          right: 10px;
          top: 18px;
        }
        .content {
          text-align: center;
```


```
.title {
          font-size: 84px;
        .links > a {
          color: #636b6f;
          padding: 0 25px;
          font-size: 12px;
          font-weight: 600;
          letter-spacing: .1rem;
          text-decoration: none;
          text-transform: uppercase;
       }
        .m-b-md {
          margin-bottom: 30px;
     </style>
  </head>
     <div class="flex-center position-ref full-height">
        <div class="content">
          <div class="title m-b-md">
             403 - Ação não autorizada!
          </div>
          <div class="links">
             <a href={{ route('home') }}>Ir para Home</a>
          </div>
        </div>
     </div>
  </body>
</html>
```

resources/views/errors/403.blade.php

```
<!doctype html>
<html lang="{{ app()->getLocale() }}">
  <head>
     <meta charset="utf-8">
     <meta http-equiv="X-UA-Compatible" content="IE=edge">
     <meta name="viewport" content="width=device-width, initial-scale=1">
     <title>Erro 404</title>
     <!-- Fonts -->
     k href="https://fonts.googleapis.com/css?family=Raleway:100,600"
rel="stylesheet" type="text/css">
     <!-- Styles -->
     <style>
        html, body {
          background-color: #fff;
          color: #636b6f;
          font-family: 'Raleway', sans-serif;
          font-weight: 100;
          height: 100vh;
          margin: 0;
       }
        .full-height {
          height: 100vh;
        }
        .flex-center {
          align-items: center;
          display: flex;
          justify-content: center;
        .position-ref {
          position: relative;
        .top-right {
          position: absolute;
          right: 10px;
          top: 18px;
        }
        .content {
          text-align: center;
```

```
.title {
          font-size: 84px;
        .links > a {
          color: #636b6f;
          padding: 0 25px;
          font-size: 12px;
          font-weight: 600;
          letter-spacing: .1rem;
          text-decoration: none;
          text-transform: uppercase;
       }
        .m-b-md {
          margin-bottom: 30px;
     </style>
  </head>
     <div class="flex-center position-ref full-height">
        <div class="content">
          <div class="title m-b-md">
             404 - Esta rota não existe!
          </div>
          <div class="links">
             <a href={{ route('home') }}>Ir para Home</a>
          </div>
       </div>
     </div>
  </body>
</html>
```

Alterar a lista de permissões para supervisor para:



E gravar.

Entrar como usuário supervisor (Italo Morales):



Entre com a URL:

http://laravel-roles.test/roles



Entre com a URL:

http://laravel-roles.test/roles/1/edit



Entre com a URL:

http://laravel-roles.test/roles/11/edit



404 - Esta rota não existe!

IR PARA HOME