

---

Beginner's Essential

# CSS CHEAT SHEET

What makes a website unique is its styling. A must-have skill for every web developer.



## TABLE OF CONTENTS

Backgrounds	3
Border	3
Box Model	5
Font	8
Text	9
Column	11
Colors	12
Table	12
Speech	12
List & Markers	14
Animations	15
transitions	16
UI	16
Pseudo-Class	17
Pseudo-Element	18
Absolute Measurement	19

Relative Measurement	19
Angles	19
Time	20
Frequency	20
Colors	20
Selector Types	21
Outline	22
3D / 2D Transform	23
Generated Content	23
Line Box	25
Hyperlink	27
Positioning	28
Ruby	29
Paged Media	29

## BACKGROUNDS

### BACKGROUND

background-image background-position background-size background-repeat background-attachment background-origin background-clip background-color

### BACKGROUND-IMAGE

url gradients none

### BACKGROUND-POSITION

top left | top center | top right | center left | center center | center right | bottom left | bottom center | bottom right x-% y-% x-pos y-pos

### BACKGROUND-SIZE

length %

auto | cover | contain **background-repeat**

repeat | repeat-x | repeat-y | no-repeat

**background-attachment** scroll | fixed | local

**background-origin**

border-box | padding-box | content-box

**background-clip**

border-box | padding-box | content-box

### BACKGROUND-COLOR

color transparent

## BORDER

### BORDER

border-width border-style border-color

## border-width

thin | medium | thick | length

---

### BORDER-STYLE

none | hidden | dotted | dashed | solid | double

| groove | ridge | inset | outset

---

### BORDER-COLOR COLOR

#### BORDER-BOTTOM

border-bottom-width border-style

border-color

---

### BORDER-LEFT

border-left-width

border-style border-color

border-left-style border-style border-right-  
color border-color border-right-width

thin | medium | thick | length

## border-top-width

thin | medium | thick | length

---

### BORDER-BREAK

border-width

border-style color

close

border-bottom-color border-color border-  
bottom-style border-style border-left-color

border-color border-left-width

thin | medium | thick length

---

### BORDER-RIGHT-STYLE BORDER-

STYLE BORDER-TOP

border-top-width border-style border-color

---

**BORDER-TOP-COLOR** **BORDER-COLOR**  
**BORDER-TOP-STYLE** **BORDER-STYLE** **BOX-SHADOW**

inset || [ length, length, length, length || <color> ] none

**border-collapse** collapse | separate

---

**BORDER-IMAGE**

image

[ number / % border-width stretch | repeat | round ] none

---

**BORDER-RIGHT**

border-right-width border-style border-color

---

**BORDER-RADIUS**

border-radius border-top-right-radius border-bottom-right-radius border-bottom-left-radius border-top-left-radius

**border-top-right-radius**

length

**border-bottom-right-radius**

length

**border-bottom-left-radius**

length

## BOX MODEL

**float**

left | right | none

---

**HEIGHT**

auto length

%

## max-height

none length

%

---

## MAX-WIDTH

none length%

---

## MIN-HEIGHT

none length

%

---

## WIDTH

auto %

length

---

## MARGIN

margin-top margin-right margin-

bottom margin-left

---

## MARGIN-BOTTOM

auto length

%

---

## MARGIN-LEFT

auto height

%

---

## MARGIN-RIGHT

auto height

%

---

## MARGIN-TOP

auto length

%

---

## PADDING

padding-top padding-right padding-

bottom padding-left

---

## PADDING-BOTTOM

length

%

---

## PADDING-LEFT

length

%

---

## PADDING-RIGHT

length %

---

## PADDING-TOP

length

%

---

## DISPLAY

none | inline | block | inline-block | flex | inline-flex | grid | inline-grid | contents | list-item | run-in | compact |

table | inline-table | table-row-group | table-header-group |

table-footer-group | table-row | table-column-group | table-column | table-cell | table-caption | ruby | ruby-base |

ruby-text | ruby-base-group | ruby-text-group

---

## OVERFLOW

visible | hidden | scroll | auto | no-display | no-

content overflow-x overflow-y

## overflow-style

auto | marquee-line | marqueeblock



---

## OVERFLOW-X

visible | hidden | scroll | auto | no-display | no-content

## visibility

visible | hidden | collapse

## clear

left | right | both | none

## FONT

---

### FONT

font-style font-variant font-weight

font-size/line-height

font-family

caption | icon | menu | messagebox | small-caption | status-bar

---

#### FONT-SIZE-ADJUST

none | inherit number

### font-family

serif | sans-serif | Font Name

### font-style

normal | italic | oblique | inherit

### font-variant

normal | small-caps | inherit

---

#### FONT-SIZE

xx-small | x-small | small | medium | large | x-large | xxlarge | smaller | larger | inherit length

%

---

#### FONT-WEIGHT

normal | bold | bolder | lighter | 100 | 200 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | inherit

## TEXT

### direction

ltr | rtl | inherit

### hanging-punctuation

none | [ start | end | endedge ]

### letter-spacing

normal

length

%

---

#### TEXT-OUTLINE

none color

length

## unicode-bidi

normal | embed | bidi-override

## white-space

normal | pre | nowrap | pre-wrap | pre-line

## white-space-collapse

preserve | collapse | pre-servebreaks | discard

## punctuation-trim

none | [ start | end | adjacent ]

## text-align

start | end | left | right | center | justify

## text-align-last

start | end | left | right | center | justify

## text-decoration

none | underline | overline | line-through | blink

---

## TEXT-SHADOW

none color

length

## word-break

normal | keep-all | loose | break-strict | break-all

---

## WORD-WRAP

normal nowrap

## text-emphasis

none | [ [ accent | dot | circle | disc | [ before | after ]? ]

---

## TEXT-INDENT

length

%

---

#### TEXT-JUSTIFY

auto | inter-word | interideograph | inter-cluster | distribute | kashida | tibetan

#### text-transform

none | capitalize | uppercase | lowercase

#### text-wrap

normal | unrestricted | none | suppress

---

#### WORD-SPACING

normal length

%

### COLUMN

---

#### COLUMN-COUNT

auto number

#### column-fill

auto | balance

---

#### COLUMN-GAP

normal length

---

#### COLUMN-RULE

column-rule-width column-rule-style column-rule-color

#### column-rule-style

border-style

---

#### COLUMNS

column-width column-count

---

## COLUMN-RULE-WIDTH

thin | medium | thick length

## column-span

1 | all

---

## COLUMN-WIDTH

auto length

## COLORS

color inherit color

---

## OPACITY

inherit number

## TABLE

border-collapse collapse | separate

empty-cells show | hide

border-spacing length length

table-layout

auto | fixed

caption-side

top | bottom | left | right

## SPEECH

---

### CUE

cue-before cue-after

---

### CUE-BEFORE

url [ silent | x-soft | soft | medium | loud | x-loud | none | inherit  
] number

%

---

## MARK

mark-before mark-after

---

## MARK-BEFORE STRING

## MARK-AFTER STRING VOICE- PITCH-RANGE

x-low | low | medium | high | xhigh | inherit number

## voice-stress

strong | moderate | none | reduced | inherit

---

## VOICE-VOLUME

silent | x-soft | soft | medium | loud | x-loud | inherit number

%

---

## CUE-AFTER

url [ silent | x-soft | soft | medium | loud | x-loud | none | inherit  
] number

%

---

## PAUSE

pause-before pause-after

---

## PAUSE-BEFORE

none | x-weak | weak | medium | strong | x-strong | inherit time

phonemes string

voice-duration time

voice-family

inherit | [ <specific-voice, age, generic-voice, number> ]

---

#### VOICE-RATE

x-slow | slow | medium | fast | x-fast | inherit

%

---

#### VOICE-PITCH

x-low | low | medium | high | xhigh | inherit number

%

### caption-side

top | bottom | left | right

---

#### REST

rest-before rest-after

---

#### REST-BEFORE

none | x-weak | weak | medium | strong | x-strong | inherit time

---

#### REST-AFTER

none | x-weak | weak | medium | strong | x-strong | inherit time

---

#### SPEAK

none | normal | spell-out | digits | literal-punctuation | no-punctuation | inherit-number

## LIST & MARKERS

---

#### LIST-STYLE

list-style-type list-style-position list-style-image

---

#### LIST-STYLE-IMAGE

none url

---

#### LIST-STYLE-TYPE

none | asterisks | box | check | circle | diamond | disc | hyphen | square | decimal | decimal-leading-zero | lower-roman | upper-roman | lower-alpha | upper-alpha | lower-greek | lower-latin | upper-latin | hebrew | armenian | georgian | cjk-ideographic | hiragana | katakana | hiragana-iroha | katakana-iroha | footnotes

---

## MARKER-OFFSET

auto length

## ANIMATIONS

---

### ANIMATIONS

animation-name animation-duration animation-timing-function animation-delay animation-iteration-count animation-direction

**animation-name** none | IDENT

**animation-duration**

time

---

### ANIMATION-TIMING-FUNCTION

ease | linear | ease-in | easeout | ease-in-out | cubic-Bezier  
(number, number, number, number)

**animation-delay**

time

---

### ANIMATION-ITERATION-COUNT

inherit number

---

**ANIMATION-DIRECTION** NORMAL |  
ALTERNATE **ANIMATION-PLAY-STATE**  
RUNNING | PAUSED

**rotation** angle

rotation-point



position (paired value off-set)

## Transitions

### TRANSITIONS

transitions-property transitions-duration transitions-timing-

function transitions-delay

#### transitions-delay

time

#### transitions-duration

time

#### transitions-property

none | all

---

### TRANSITION-TIMING-FUNCTION

ease | linear | ease-in | ease-out | ease-in-out | cubicBezier( number, number, number, number)

### UI

#### appearance

normal | inherit | [icon | window | desktop | work-space | document | tooltip | dialog | button | push-button | hyperlink | radio-button | checkbox | menu-item | tab | menu | menubar | pull-down-menu | pop-up-menu | list-menu | radio-group | checkbox-group | outline-tree | range | field | combo-box | signature | password]

---

### CURSOR

auto | crosshair | default | pointer | move | e-resize | neresize | nw-resize | n-resize | se-resize | sw-resize | swresize | s-resize | w-resize | text | wait | help url

---

### ICON

auto | inherit url

---

## NAV-INDEX

auto | inherit number

### nav-up

auto | inherit <id> [current | root | <target-name>

### nav-right

auto | inherit <id> [current | root | <target-name>

### nav-down

auto | inherit <id> [current | root | <target-name>

---

## NAV-LEFT

auto | inherit <id> [current | root | <target-name>

---

## RESIZE

none | both | horizontal | vertical | inherit

## PSEUDO-CLASS

:active	an activated element
:focus	an element while the element has focus
:hover	an element when you mouse over it
:link	an unvisited link
:disabled	an element while the element is disabled
:enabled	an element while the element is enabled
:checked	an element that is checked
:selection	an element that is currently selected or highlighted by the user

:lang	allows the author to specify a language to use in a specified element
:nth-child(n)	an element that is the n-th sibling
:nth-last-child(n)	an element that is the n-th sibling counting from the last sibling
:first-child	an element that is the first sibling
:last-child	an element that is the last sibling
:only-child	an element that is the only child
:nth-of-type(n)	an element that is the n-th sibling of its type
:nth-last-of-type(n)	an element that is the n-th sibling of its type counting from the last sibling
:last-of-type	an element that is the last sibling of its type
:first-of-type	an element that is the first sibling of its type
:only-of-type	an element that is the only child of its type
:empty	an element that has no children
:root	root element within the document
:not(x)	an element not represented by the argument 'x'
:target	a target element as specified by a target in a UR

## PSEUDO-ELEMENT

::first-letter	Adds special style to the first letter of a text
::first-line	Adds special style to the first line of a text

::before	Inserts some content before the content of an element
::after	Inserts some content after the content of an element

## ABSOLUTE MEASUREMENT

%	percentage
cm	centimeter
in	inch
mm	millimeter
pc	pica (1p = 12 points)
pt	point (1pt = 1/72 inch)
px	pixel (1px = 1/96 inch)

## RELATIVE MEASUREMENT

ch	width of the “0” glyph found in the font for the font size used to render
em	1em = current font size of current element
ex	x-height of the element’s font
gd	the grid defined by ‘layout-grid’
rem	the font size of the root element
vh	the viewport’s height
vw	the viewport’s width
vm	viewport’s height or width, whichever is smaller of the two

## ANGLES

deg	degrees
grad	grads
rad	radians
turn	turns

## TIME

ms	mili-seconds
s	seconds

## FREQUENCY

Hz	hertz
kHz	kilo-hertz

## COLORS

color name	red, blue, green, dark green
rgb(x,y,z)	red = rgb(255,0,0)
rgb(x%,y%,z%)	red = rgb(100%,0,0)

rgba(x,y,z,alpha)	red = rgba(255,0,0,0)
#rrggbb	red = #ff0000 (or shorthand - #f00)
hsl(hue, saturation, lightness)	red = hsl (0, 100%, 50%)
flavor	An accent color (typically chosen by the user) to customize the user interface of the user agent itself.
currentColor	computer value of the 'currentColor' keyword is the computed value of the 'color' property

## SELECTOR TYPES

Name	Info	Example
Universal	Any element	* { font: 10px Arial; }
Type	Any element of that type	h1 { text-decoration: underline; }
Grouping	Multiple elements of different types	h1, h2, h3 { font-family: Verdana; }
Class	Multiple elements of different types when you don't want to affect all instances of that type	.sampleClass { text-decoration: underline; }
Id	A single element type when you don't want to affect all instances of that type	#sampleID { text-decoration: underline; }
Descendant	An element that is below (in the document tree) another element - no matter how many levels	#gallery h1 { text-decoration: underline; }
	below	

Child	An element that is directly below (in the document tree) another element	#title > p { font-weight: bold; }
Adjacent Sibling	All elements that share the same parent and elements are in the same immediate sequence	h1 + p { font-style: italic; }
General Sibling	All elements that share the same parent and elements are in the same sequence (not necessarily immediate)	h1 ~ p { font-style: italic; }
Attribute	An element that matches the attribute listed	E[selected] - att whatever the value E[att="val"] - att with a specific value E[rel~="next"] - att with a value is a whitespace separated list *[lang = "en"] - att value either being exactly "val" or beginning with "val" immediately followed by "-" E[att^="val"] - att value that begins with the prefix "val"

## OUTLINE

### OUTLINE

outline-color outline-style outline-width

### OUTLINE-OFFSET

inherit length

### OUTLINE-STYLE

none | dotted | dashed | solid | double | groove | ridge | inset | outset

### OUTLINE-WIDTH

thin | medium | thick length

## 3D / 2D TRANSFORM

BACKFACE-VISIBILITY **VISIBLE** | **HIDDEN**

PERSPECTIVE

none number

PERSPECTIVE-ORIGIN

[ [ <percentage> | <length> | left | center | right ] [ <percentage> | <length> | top | center | bottom ]? ] <length>  
] | [ [ left | center  
| right ] | [ top | center | bottom ] ] <length> ]

TRANSFORM

none | matrix | matrix3d | translate3d | translateX | translateY | translateZ | scale | scale3d | scaleX | scaleY |  
scaleZ | rotate | rotate3d | rotateX | rotateY | rotateZ | skewX | skewY | skew | perspective

TRANSFORM-ORIGIN

[ [ [ <percentage> | <length> | left | center | right ] [ <percentage> | <length> | top | center | bottom ]? ]  
<length> ] | [ [ [ left | center | right ] | [ top | center | bottom ] ] <length> ]

transform-style flat | preserve-  
3d

## GENERATED CONTENT

BOOKMARK-LABEL

content attr

string

BOOKMARK-LEVEL

none integer

BOOKMARK-TARGET

self url attr

BORDER-LENGTH



self url attr

---

## CONTENT

normal | none | inhibit url

**counter-reset** none

identifier number

---

## CROP

auto shape

---

## DISPLAY

normal | none | list-item

**float-offset** length length

---

## HYPHENATE-AFTER

auto integer

---

## COUNTER-INCREMENT

none identifier number

---

## HYPHENATE-LINES

no-limit integer

---

## HYPHENATE-RESOURCE

none url

---

## HYPHENS

none | manual | auto **image-resolution**

normal | auto dpi

---

## HYPHENATE-BEFORE

auto integer

---

#### HYPHENATE-CHARACTER

auto string

#### marks

[crop || cross ] | none

---

#### MOVE-TO

normal | here identifier

#### page-policy

start | first | last

---

#### QUOTES

none

string string string string

---

#### STRING-SET

identifier content-list

---

#### TEXT-REPLACE

none

[<string> <string>]+

### LINE BOX

---

#### ALIGNMENT-ADJUST

auto | baseline | before-edge | text-before-edge | middle | central | after-edge | textafter-edge | ideographic  
| alphabetic | hanging | mathematical length

%

---

#### ALIGNMENT-BASELINE

baseline | is-script | beforeedge | text-before-edge | afteredge | text-after-edge | central | middle | ideographic | alphabetic | hanging | mathematical

---

#### BASELINE-SHIFT

baseline | sub | super

length

%

---

#### DOMINANT-BASELINE

auto | use-script | no-change | reset-size | alphabetic | hanging | ideographic | mathematical | central | middle | text-after-edge | text-beforeedge

---

#### DROP-INITIAL-AFTER-ALIGN ALIGNMENT-BASELINE DROP-INITIAL-AFTER-ALIGN

central | middle | after-edge | text-after-edge | ideographic | alphabetic | mathematical

%

---

#### DROP-INITIAL-BEFORE-ALIGN

caps-height alignment-baseline

---

#### DROP-INITIAL-BEFORE-ADJUST

before-edge | text-before-edge | central | middle | hanging | mathematical length

%

---

#### DROP-INITIAL-VALUE

initial integer

---

#### DROP-INITIAL-SIZE

auto

integer %

line

---

#### INLINE-BOX-ALIGN

initial | last

integer

---

## LINE-HEIGHT

normal number

length

%

---

## LINE-STACKING

line-stacking-strategy line-stacking-ruby line-stacking-shift

### line-stacking-strategy

inline-line-height | block-lineheight | max-height | gridheight

### line-stacking-ruby

exclude-ruby | include-ruby

### line-stacking-shift

consider-shifts | disregardshifts

---

## LINE-STACKING

line-stacking-strategy line-stacking-ruby line-stacking-shift

---

## TEXT-HEIGHT

auto | font-size | text-size | max-size

---

## VERTICAL-ALIGN

Baseline | sub | super | top | text-top | middle | bottom | text-bottom length %

---

## HYPERLINK

---

### TARGET

target-name target-new target-

position

---

### TARGET-NAME

current | root | parent | new | modal string

---

## TARGET-NEW

window | tab | none **target-position**

above | behind | front | back

## POSITIONING

---

### BOTTOM

auto %

length

**right**

auto %

length

---

### CLIP

shape auto

**top** auto

% length

---

### LEFT

auto %

length

---

### Z-INDEX

auto

Number

**position**

static | relative | absolute | fixed

## RUBY

### RUBY-ALIGN

auto | start | left | center | end | right | distribute-letter | distribute-space | line-edge

### ruby-overhang

auto | start | end | none

### ruby-position

before | after | right | inline

### ruby-span

attr(x) | none

## PAGED MEDIA

### fit

fill | hidden | meet | slice

### FIT-POSITION

[top | center | bottom] || [left | center | right] length

%

### orphans integer

### IMAGE-ORIENTATION

auto angle

### page

auto identifier

### page-break-after

auto | always | avoid | left | right

### page-break-before

auto | always | avoid | left | right

---

PAGE-BREAK-INSIDE AUTO | AVOID  
SIZE

auto | landscape | portrait length

windows integer