

VCC: 3 V .. 12 V
Signal levels: 3.3 V

Alternative header: JLC# C9136

Use IDC ribbon-cable to get a
1:1 connection to a PMOD2A host

When plugging the display directly
into a PMOD port, be aware the the
columns (even and odd pin numbers)
will be swapped compared to the PMOD
standard

For a matching cable, search for:
FC-FD DC4 IDC 2.54mm pitch Male
to Female connector



SSD1322 OLED panel

Switches and LEDs

File: switches.kicad_sch



3.3 V LDO VOUT = 1.235V * (1 + R1/R2) = 3.34 V



12 V Step-up for panel V_OUT = 1.233 V (1 + R1 / R2) = 13.6 V



Betz Engineering

H16 D2.7 H17 D2.7 H21 D2.7 H22 D2.7
H1 D2.7 H12 D2.7 H32 D2.7 H40 D2.7

Sheet: /
File: ui_board_1u.kicad_sch

Title: ui_board_1u – User interface board

Size: A4	Date: 2025-12-17	Rev: –
KiCad E.D.A. 9.0.0-rc3-dirty		Id: 1/2



RS-3535MWAR	R	G	B
Lum @ 20 mA [mcd]	950	2200	500
Lum target [mcd]	400	400	400
I target [mA]	8.0	1.8	13.0
V_FWD [V]	2.0	2.3	3.0
R [Ohm]	162.5	555.6	25.4
R chosen [Ohm]	150	560	22







Betz Engineering

Sheet: /Switches and LEDs/
File: switches.kicad_sch

Title: *ui_board_1u – User interface board*

Size: A4	Date: 2025-12-17	**Rev: –**
KiCad E.D.A. 9.0.0-rc3-dirty		Id: 2/2