NOUS PLATFORM — TECHNICAL SPECIFICATION

LOGOS

Linguistic Origin & Gestural Oscillation System

The cross-linguistic and cross-cultural calibration layer that establishes the communicative framework of each speaker before diagnostic analysis begins. LOGOS ensures that every measurement within NOUS — from REMIEL feature extraction to POA prosodic analysis to Beverly Index scoring — is calibrated against population-normed reference profiles appropriate to the speaker's linguistic, dialectal, and cultural origin.

Without LOGOS, NOUS measures deviation from an English-language norm. With LOGOS, NOUS measures deviation from *the speaker's own cognitive-linguistic baseline*.

Beverly Index LLC | CONFIDENTIAL — PROPRIETARY | v1.0 | February 2026

THE FOUNDATIONAL PROBLEM

Why Every AI Diagnostic Tool Gets Cross-Cultural Analysis Wrong

Current AI-based psychological assessment tools — including NOUS without LOGOS — carry implicit assumptions about how cognition expresses itself through language. These assumptions are calibrated to English-language, Western-cultural communication norms. When applied to speakers from different linguistic and cultural backgrounds, they produce systematic diagnostic errors that are not merely inaccurate but clinically dangerous.

FALSE AFFECT INFLATION

+340%

Estimated affective scoring inflation for Italian speakers analyzed against English-normed baselines, due to cultural expressiveness patterns

TONAL CONTAMINATION

6 of 6

All six POA sub-channels produce unreliable output for tonal languages (Mandarin, Cantonese, Vietnamese, Thai) without prosodic disentanglement

DIALECTAL SIGNATURE DRIFT

≥30%

Estimated VOCA baseline error rate when vocal profiles are built without accounting for dialectal origin (e.g., Kiev vs. Moscow Russian)

PRE-PUBLICATION — PUBLISH-ACCESS

Three Categories of Failure

1. Expressiveness Misclassification

Languages and cultures differ dramatically in baseline emotional expressiveness. Italian, Arabic, Brazilian Portuguese, and many South Asian languages use amplified prosodic contours, superlatives, and dramatic narrative structures as **default communication** — not as indicators of heightened affect. Conversely, Japanese, Finnish, and many East Asian languages employ restrained, indirect communication that masks emotional content behind structural politeness. Without cultural calibration, the first group appears pathologically activated; the second appears pathologically flat.

2. Phonemic-Prosodic Entanglement

In tonal languages, pitch changes carry **lexical meaning** (Mandarin's four tones make the same syllable into four different words). POA's Channel 8A (Pitch Dynamics) cannot distinguish between linguistic tone and emotional prosody without a pre-processing disentanglement layer. Similarly, pitch-accent languages (Japanese, Swedish, Norwegian, Serbo-Croatian) use pitch patterns that overlap with the prosodic features POA measures for emotional state. The acoustic signal carries two simultaneous information streams that must be separated before analysis.

3. Identity-Embedded Cognitive Framing

A Ukrainian-born speaker and a Moscow-born speaker both narrating the same dream in Russian will produce different NOST signatures — not because their cognitive states differ, but because their linguistic-cultural substrate encodes experience differently. Different lexical preferences, diminutive patterns, prosodic baselines, and cultural frameworks for concepts like authority, memory, trauma, and hope all shape the signal that REMIEL receives. The cognitive content is embedded in and inseparable from the cultural-linguistic frame. LOGOS exists to identify and calibrate for that frame.

ARCHITECTURAL POSITION

Where LOGOS Sits Within NOUS

LOGOS operates at the intake level, activated by AAE immediately upon receiving input. It establishes the Linguistic-Cultural Frame (LCF) before any analytical processing begins, and feeds calibration parameters downstream to every subsequent layer.

Data Flow: AAE → LOGOS → All Downstream Components

```
USER INPUT → AAE (receives narrative text and/or audio)
    ↓
    LOGOS (analyzes input → generates Linguistic-Cultural Frame)
    ↓  LCF propagates to all downstream layers
    ├── REMIEL  (channel weights recalibrated per LCF)
    ├── POA     (prosodic disentanglement activated; baseline norms loaded)
    ├── R2X     (translation parameters adjusted per cultural norms)
    ├── VOCA    (baseline stratified by dialectal-cultural profile)
```

PRE-PUBLICATION — PUBLISH-ACCESS

```
├── Beverly Index  (scoring normed against appropriate population)
└── CSAA    (authenticity markers calibrated for linguistic-cultural norms)
```

Critical Architectural Rule

LOGOS does not replace AAE as the front door. AAE remains the user-facing orchestration layer. LOGOS is activated *by* AAE as the first analytical step, before AAE routes to REMIEL or any other processing pipeline. The LCF becomes a persistent session attribute that travels with all data through the entire NOUS stack. No component should process input without an active LCF.

Technology Hierarchy Position

LOGOS sits at **Level 2** alongside AAE — both are orchestration-layer components that shape how the analytical engine operates. AAE determines *what* gets analyzed and *how* the session flows. LOGOS determines *against what norms* the analysis is calibrated.

LEVEL	COMPONENT	FUNCTION
0	Computational Psychodynamics	Scientific Field
1	NOST + NOSS	Theory + Classification
2	**AAE + LOGOS**	Orchestration + Linguistic-Cultural Calibration
3	REMIEL Engine (8-Channel + POA)	Analysis
4	R2X Bridge	Translation
5	DreamWeaver + Memoria Sonata	Visualization + Sonification
6	Beverly Index v2.0	Scoring
7	Empyrean™	3D Cognitive Synthesis

CORE ARCHITECTURE

LOGOS Six-Layer Architecture

Each layer performs a distinct function in establishing the Linguistic-Cultural Frame. Layers execute sequentially, with each layer's output enriching the LCF before the next layer activates.

Layer 1 — Linguistic Identity Detection

PRE-PUBLICATION — PUBLISH-ACCESS

PRIMARY LANGUAGE • DIALECT • REGISTER • NATIVENESS

L1

The first layer performs deep linguistic identification that goes far beyond simple language detection. It identifies not just *what language* is being spoken or written, but the speaker's **linguistic origin** — their native language, acquired languages, dialectal features, register preferences, and proficiency characteristics.

1A — Language & Dialect Classification

Identifies primary language, regional dialect, and sub-dialectal features. Not "this is Russian" but "this is Russian with Southern Ukrainian dialectal markers, suggesting native Ukrainian L1 with Russian L2 acquisition." Not "this is Chinese" but "this is Mandarin with Sichuanese tonal influence and Southwestern lexical preferences."

1B — Nativeness & Proficiency Assessment

Determines whether the speaker is using their native language (L1) or an acquired language (L2/L3). Assesses fluency markers: syntactic complexity, error patterns, code-mixing frequency, lexical diversity, and prosodic nativeness. A non-native speaker's "errors" are diagnostically irrelevant noise that must be filtered before REMIEL processes the signal.

1C — Register & Formality Detection

Identifies the speaker's register: formal, informal, clinical, colloquial, literary, code-switched. Some languages (Japanese, Korean, Javanese) have grammaticalized politeness levels that fundamentally change linguistic structure. Register choice itself is diagnostically significant — a speaker who shifts from formal to informal mid-narrative is revealing something about their relationship to the content.

1D — Script & Orthographic Analysis (Text Input)

For text inputs: identifies writing system, character selection patterns, and orthographic preferences. In Chinese, character selection (simplified vs. traditional, formal vs. colloquial alternatives) carries cognitive significance. In Arabic, diacritical mark usage reflects education level and formality. In multilingual texts, script-switching patterns mirror code-switching in speech.

EXAMPLE: KIEV VS. MOSCOW IDENTIFICATION

Input: Russian-language dream narrative, audio input

Layer 1 Output:

`PRIMARY_LANG` Russian `DIALECT` Eastern Ukrainian-influenced `L1_ESTIMATE` Ukrainian (high confidence) `NATIVENESS` L2-near-native `REGISTER` Informal-personal

Markers: Ukrainian phonological influence on /g/ → /ɦ/ fricativization, Ukrainian loanwords in emotional vocabulary, reduced use of Russian diminutive chains, Ukrainian-pattern intonation on interrogative constructions.

↓

Layer 2 — Cultural Expressiveness Profiling

PRE-PUBLICATION — PUBLISH-ACCESS

AFFECTIVE BASELINE • NARRATIVE STRUCTURE NORMS • COMMUNICATION STYLE

L2

Using the linguistic identity established in Layer 1, this layer loads the appropriate **Cultural Expressiveness Profile (CEP)** — a population-normed reference that defines "normal" communication patterns for this speaker's language-culture combination. The CEP recalibrates what constitutes baseline versus deviation across every dimension REMIEL and POA measure.

2A — Affective Baseline Norms

Establishes the expected range of emotional expressiveness for this language-culture. Italian: high baseline prosodic range, frequent superlatives, dramatic narrative peaks considered normal. Japanese: compressed prosodic range, understatement as default, emotional content encoded in structural indirectness. These norms recalibrate REMIEL Channel 3 (Emotional) and POA's energy and pitch dynamic analysis.

2B — Narrative Structure Norms

Different cultures organize narratives differently. Western narratives tend toward linear chronological arcs. Arabic narratives often use circular/recursive structures. Japanese narratives employ *kishōtenketsu* (introduction, development, twist, conclusion) rather than conflict-resolution arcs. REMIEL Channel 5 (Narrative) must know the expected structure before it can detect deviations that carry diagnostic significance.

2C — Communication Style Parameters

High-context vs. low-context communication, direct vs. indirect expression of distress, somatic vs. psychological idioms of distress (many cultures express depression through physical symptoms rather than emotional vocabulary), cultural attitudes toward self-disclosure, and shame/honor frameworks that shape what speakers will and won't verbalize.

Cultural Expressiveness Profiles (CEPs) — Reference Data

CEPs are empirically derived population norms stored as multi-dimensional reference vectors. Initial NOUS deployment will include CEPs for the 25 highest-priority language-culture combinations, expanding to 100+ as clinical validation data accumulates. Each CEP contains normalized ranges for: prosodic range (mean, SD), lexical diversity expectations, metaphor density, narrative linearity, emotional vocabulary frequency, pause architecture, and 40+ additional parameters mapped to REMIEL and POA channels.

EXAMPLE: ITALIAN VS. FINNISH CALIBRATION

Same clinical presentation (moderate anxiety), narrated by two speakers:

Italian speaker: "Mi sentivo come se il mondo stesse crollando — il cuore batteva fortissimo, non riuscivo a respirare, era terribile, terribile!" — REMIEL raw affect score: 8.7/10

Finnish speaker: "En voinut nukkua hyvin. Olo oli vähän ahdistunut." — REMIEL raw affect score: 2.1/10

Without LOGOS: Italian diagnosed with severe anxiety, Finnish diagnosed as subclinical. Both wrong.

With LOGOS: Italian score normalized against Italian CEP → 5.2/10 (moderate). Finnish score normalized against Finnish CEP → 5.4/10 (moderate). Both correct.

PRE-PUBLICATION — PUBLISH-ACCESS

↓

Layer 3 — Prosodic Disentanglement Engine

L3

TONAL SEPARATION • PITCH-ACCENT HANDLING • LINGUISTIC vs. EMOTIONAL PROSODY

The most computationally intensive layer. For tonal languages, pitch-accent languages, and other languages where prosodic features carry lexical meaning, this layer **separates the linguistic signal from the emotional signal** in the acoustic stream before POA processes it. Without this separation, POA cannot function for approximately 60% of the world's languages.

3A — Tonal Language Processing

Applies to: Mandarin (4 tones + neutral), Cantonese (6-9 tones), Vietnamese (6 tones), Thai (5 tones), Yoruba (3 tones), Igbo, Zulu, and 300+ tonal languages worldwide.
Identifies and extracts lexical tone contours from the fundamental frequency (F0) signal, leaving the *residual* F0 variation as the emotional prosody signal that POA can safely analyze. Uses language-specific tone models trained on each tonal system. The separation must be context-sensitive: tonal coarticulation (sandhi) causes tones to modify each other across syllable boundaries, and this must be accounted for before residual extraction.

3B — Pitch-Accent Language Processing

Applies to: Japanese, Swedish, Norwegian, Serbo-Croatian, Basque, certain Bantu languages, Ancient Greek (historical analysis).
Pitch-accent languages use pitch patterns to distinguish words (Japanese: *hashi* with different accent patterns means "bridge," "chopsticks," or "edge"). Unlike full tonal languages, the pitch distinctions are positional rather than contour-based. The disentanglement model must identify accent-bearing vs. accent-free positions and extract the linguistic pitch before passing residual variation to POA.

3C — Stress-Timed vs. Syllable-Timed Calibration

Languages have fundamentally different rhythmic structures. English, German, and Russian are **stress-timed** (roughly equal intervals between stressed syllables, with unstressed syllables compressed). French, Spanish, Italian, and Japanese are **syllable-timed** (roughly equal duration for each syllable). Mandarin and Vietnamese are **mora-timed**. POA Channel 8B (Temporal Rhythm) must know the speaker's timing system to interpret pause architecture, speech rate variation, and rhythmic regularity/irregularity. A pause that signals cognitive processing in English may simply be normal inter-phrase timing in Japanese.

3D — Phonemic Inventory Mapping

Different languages use different sets of consonants and vowels. POA Channel 8F (Articulation Patterns) must know what sounds exist in the speaker's language to detect articulatory deterioration (relevant for Parkinson's, TBI, and intoxication detection via VOCA). A Spanish speaker's inability to produce English /θ/ is not articulatory deterioration — it's a phonemic gap. Conversely, a Mandarin speaker's progressive difficulty with retroflex consonants (zh, ch, sh) could be an early Parkinson's indicator. The phonemic inventory determines which articulatory markers are diagnostically relevant.

Technical Approach: F0 Decomposition

The disentanglement engine uses a decomposition model that separates the F0 (fundamental frequency)

PRE-PUBLICATION — PUBLISH-ACCESS

signal into three components: **(1) Lexical tone/accent** — the pitch patterns that carry word-level meaning, modeled from language-specific tone inventories; **(2) Intonational phrase structure** — sentence-level pitch patterns (declination, boundary tones, focus marking) that are grammatical rather than emotional; **(3) Emotional residual** — the remaining F0 variation after (1) and (2) are extracted, which represents genuine affective prosody. Only component (3) is passed to POA for diagnostic analysis. Components (1) and (2) are available to REMIEL for linguistic analysis but are excluded from emotional scoring.

↓

Layer 4 — Code-Switching & Multilingual Analysis

L4

LANGUAGE SWITCHING DETECTION • SWITCHING TRIGGERS • COGNITIVE SIGNIFICANCE MAPPING

When multilingual speakers narrate, they switch between languages — and **when, where, and why they switch is itself a cognitive signature of profound diagnostic significance**. This layer detects code-switching events, classifies their type, identifies their triggers, and maps their cognitive meaning.

4A — Switch Point Detection

Identifies exact moments where the speaker transitions between languages, including: **inter-sentential switching** (between sentences), **intra-sentential switching** (within a sentence), **tag-switching** (discourse markers from one language inserted into another), and **borrowing** (single lexical items from another language). Each type carries different diagnostic weight — intra-sentential switching at moments of high emotional valence is the most significant.

4B — Cognitive Trigger Classification

Classifies *why* the switch occurred: **Emotional intensity** — speaker reverts to L1 when affect overwhelms L2 processing capacity. **Conceptual encoding** — certain concepts are only available in one language (German *Schadenfreude*, Portuguese *saudade*, Japanese *mono no aware*). **Identity activation** — switching triggered by content related to cultural identity. **Trauma anchoring** — traumatic memories encoded in the language spoken at the time of trauma, causing involuntary switching during recall. Each trigger type maps to different NOSS sectors.

4C — Dream Language Analysis

A uniquely powerful diagnostic signal: **Which language does the speaker dream in?** Multilingual individuals often dream in different languages depending on emotional context, life period, and trauma history. A bilingual speaker who dreams in their L1 (childhood language) when processing early attachment experiences but dreams in L2 (adult-acquired language) for professional scenarios reveals deep cognitive-emotional compartmentalization. If the dream narrative is told in L2 but the dream itself occurred in L1, the translation act itself introduces cognitive filtering that REMIEL must account for.

4D — Untranslatable Concept Detection

Every language contains concepts that resist translation — words for emotional states, relational dynamics, or experiential qualities that have no equivalent in other languages. When a speaker uses a concept from

PRE-PUBLICATION — PUBLISH-ACCESS

their native language that has no English equivalent, REMIEL must recognize this as a *precision-seeking behavior* (reaching for the most accurate word) rather than a communication failure. These untranslatable concepts often carry the highest diagnostic value precisely because they represent cognitive-emotional states that the speaker's dominant language cannot fully encode.

EXAMPLE: BILINGUAL DREAM NARRATION

Speaker: Ukrainian-born, English L2, narrating a dream in English

Narrative: "I was in my grandmother's house and she was making — *[switches to Ukrainian]* — вареники, як завжди — *[switches back to English]* — and I felt this... I can't explain it, like *туга*, this... longing that hurts."

LOGOS Layer 4 Output:

`SWITCH_1` Conceptual encoding (food item with cultural-emotional valence; no adequate English equivalent for the full experiential association) `SWITCH_2` Emotional intensity + Untranslatable concept (*туга* = a specifically Ukrainian concept of painful longing/grief with no English equivalent; maps to NOSS Sector III attachment dynamics)

Diagnostic significance: Both switches occur around attachment-related content, dream occurred in Ukrainian (childhood language), narrative delivered in English (adult language). The L1 intrusions at emotional peaks suggest unresolved attachment material that the speaker's L2 cognitive framework cannot fully contain. High relevance for NOSS Sectors III and V.

↓

Layer 5 — Paralinguistic & Gestural Awareness

L5

GESTURE DEPENDENCY FLAGGING • MODALITY COMPLETENESS SCORING • SOMATIC IDIOM DETECTION

Some languages are semantically incomplete without non-verbal components. Italian communication is fundamentally multimodal — the meaning isn't just in words and voice; it's in hand gestures, facial expressions, and physical space. This layer assesses the degree to which the input captures the speaker's full communicative signal and adjusts confidence scoring accordingly.

5A — Gesture Dependency Index (GDI)

Quantifies how much of this language-culture's communication is typically carried by non-verbal channels. High GDI languages: Italian, Arabic, many South Asian languages, Greek, Brazilian Portuguese, Israeli Hebrew. Low GDI: Japanese (formal register), Finnish, most written-formal registers. The GDI determines how much diagnostic confidence the system can place in text-plus-audio analysis alone. For high-GDI speakers, LOGOS reduces the Beverly Index Clinical Confidence Score to reflect the missing modality.

5B — Input Modality Completeness Score

Compares the modalities available (text only, text + audio, text + audio + video) against the modalities required for full signal capture given the speaker's GDI. A text-only analysis of an Italian speaker's narrative captures perhaps 60-70% of the communicative signal. The completeness score propagates to the Beverly Index as a confidence modifier — the system is transparent about what it can and cannot reliably assess given the available input channels.

PRE-PUBLICATION — PUBLISH-ACCESS

5C — Somatic Idiom Detection

Many cultures express psychological distress through physical/somatic vocabulary rather than emotional language. A Chinese speaker reporting "chest tightness" and "heart pressure" may be describing depression, not cardiac symptoms. A South Asian speaker describing "heat in the head" may be expressing anxiety. A Latin American speaker reporting *nervios* is describing a culturally specific distress syndrome. LOGOS identifies culture-specific somatic idioms of distress and maps them to their psychological equivalents before REMIEL processes the content, preventing REMIEL's affective channels from misclassifying somatic-coded emotional content as medically-focused narrative.

5D — Future: Video Gesture Analysis Module

Planned expansion for Phase 5+ of the NOUS Platform development. When video input is available, LOGOS Layer 5 will include gesture analysis: hand movement patterns, emblematic gestures (culture-specific gestures with fixed meanings), illustrative gestures (reinforcing speech content), and beat gestures (rhythmic markers). For high-GDI languages, this would close the modality gap and allow full-confidence clinical scoring. Architecture is designed for this expansion — the GDI framework and completeness scoring already anticipate the additional modality.

↓

Layer 6 — Linguistic-Cultural Frame Assembly & Propagation

L6

LCF COMPILATION • CALIBRATION PARAMETER GENERATION • DOWNSTREAM PROPAGATION

The final layer compiles all outputs from Layers 1-5 into the **Linguistic-Cultural Frame (LCF)** — a structured calibration object that propagates to every downstream NOUS component. The LCF is the product LOGOS delivers: a comprehensive instruction set that tells every subsequent layer in the pipeline how to adjust its analysis for this specific speaker.

LCF Object Structure

```
LinguisticCulturalFrame {
  // Layer 1 outputs
  identity: {
    primary_language, dialect, sub_dialect,
    estimated_L1, L2_proficiency, register,
    script_system, orthographic_profile
  }
  // Layer 2 outputs
  expressiveness: {
    affective_baseline_norms: Vector[40],
    narrative_structure_norm: Enum,
    communication_style: { context_level, directness, disclosure_norm },
    somatic_idiom_mappings: Dict,
    CEP_reference_id: String
  }
  // Layer 3 outputs
  prosodic_calibration: {
    tone_system: Enum[TONAL|PITCH_ACCENT|STRESS|NONE],
    disentanglement_model_id: String|null,
    timing_system: Enum[STRESS_TIMED|SYLLABLE_TIMED|MORA_TIMED],
```

PRE-PUBLICATION — PUBLISH-ACCESS

```
    phonemic_inventory: Set[IPA],
    F0_decomposition_params: Model
  }
  // Layer 4 outputs
  multilingual: {
    is_multilingual: Boolean,
    languages_detected: List[LangProfile],
    switch_events: List[SwitchEvent],
    dream_language: String|null,
    untranslatable_concepts: List[Concept]
  }
  // Layer 5 outputs
  modality: {
    gesture_dependency_index: Float[0-1],
    input_modality_completeness: Float[0-1],
    confidence_modifier: Float[0-1],
    somatic_idioms_active: List[SomaticMapping]
  }
  // Layer 6 compiled calibration
  calibration: {
    remiel_channel_weights: Vector[8],
    poa_baseline_norms: Vector[6],
    beverly_index_population_norm: NormProfile,
    voca_stratification_key: String,
    csaa_cultural_markers: MarkerSet
  }
}
```

LCF Persistence & Evolution

The LCF is generated at session start and persists throughout the session as a read-only calibration object. However, it is **not static across sessions**. LOGOS refines the LCF with each new session for the same speaker, building an increasingly precise linguistic-cultural profile. After 3-5 sessions, the LCF converges on a high-confidence profile specific to that individual — their personal communicative fingerprint, not just their population norm. This mirrors VOCA's adaptive baseline learning: initial sessions use population norms, subsequent sessions increasingly reflect the individual's own patterns.

DOWNSTREAM CALIBRATION

How LOGOS Transforms Every NOUS Component

The LCF doesn't just flag the speaker's language — it actively recalibrates the analytical parameters of every downstream component. Here is the specific impact on each.

REMIEL Engine — Channel Recalibration

Channel 1 (Lexical): Word frequency norms adjusted for language; cognate interference filtered for L2 speakers; language-specific emotional vocabulary weighted.

PRE-PUBLICATION — PUBLISH-ACCESS

Channel 2 (Syntactic): Complexity baselines adjusted — Turkish agglutinative syntax ≠ English analytic syntax; embedded clause depth norms differ by language.

Channel 3 (Emotional/Affective): CEP norms applied; expressiveness baseline recalibrated; somatic idioms remapped to emotional equivalents.

Channel 4 (Future/Prospective): Temporal reference frameworks adjusted — not all languages grammaticalize future tense (Mandarin uses context, not verb inflection).

Channel 5 (Narrative): Structural expectations loaded per cultural narrative norm (linear, circular, *kishōtenketsu*, etc.).

Channels 6-7 (Speech, Creative): Pragmatic norms and creative expression patterns adjusted for cultural communication style.

Channel 8 (POA): Receives full prosodic calibration (see POA section below).

POA — Prosodic Recalibration

8A (Pitch Dynamics): Receives disentangled F0 signal for tonal/pitch-accent languages. Baseline pitch range norms loaded per language-culture-gender.

8B (Temporal Rhythm): Timing system (stress/syllable/mora) loaded; speech rate norms adjusted; pause duration expectations recalibrated.

8C (Energy Contour): Dynamic range expectations adjusted per cultural expressiveness norms — Italian normal ≠ Japanese normal.

8D (Vocal Quality): Phonation norms adjusted; some languages (e.g., Vietnamese, Hmong) use phonation type (breathy, creaky) as lexical distinctions.

8E (Pause Architecture): Turn-taking norms loaded; silence tolerance thresholds adjusted — Finnish comfortable pauses ≠ Italian uncomfortable pauses.

8F (Articulation): Phonemic inventory loaded; only language-appropriate articulatory markers tracked for deterioration detection.

VOCA — Baseline Stratification

Vocal Profile Extraction: TRAIT features stratified by dialectal-cultural profile. A Kiev-born speaker and a Moscow-born speaker get separate baseline categories, even though both produce Russian-language input.

Adaptive Baseline Learning: Initial baseline seeded from population norm matching the speaker's LCF identity, rather than a universal norm. Convergence to individual baseline accelerated because the starting point is closer to the speaker's actual patterns.

Deviation Detection: Deviation thresholds calibrated per language-culture norm. A prosodic shift that signals cognitive state change in a Japanese speaker may be within normal variation for a Brazilian speaker.

PRE-PUBLICATION — PUBLISH-ACCESS

Beverly Index & CSAA

Beverly Index: Diagnostic probability normed against appropriate population. Clinical Confidence Score adjusted by LOGOS modality completeness score. Integration Pattern classifications validated against cultural norms — what looks like AVOID pattern in a Western framework may be culturally normative emotional restraint.

CSAA: Authenticity markers recalibrated for cultural communication norms. Deception indicators vary by culture — Western gaze aversion correlates differ from East Asian norms. Narrative consistency expectations adjusted for cultural narrative structures. Critical for immigration and cross-cultural forensic applications where cultural communication differences must not be misclassified as deception markers.

DEPLOYMENT PRIORITY

Priority Language-Culture Profiles

CEP development is prioritized by clinical demand, military application relevance, institutional client needs, and population coverage. The following represents the phased deployment schedule.

Phase 1 — Launch (6 CEPs)

LANGUAGE-CULTURE	TONE SYSTEM	GDI	PRIORITY DRIVER
English (American)	Stress-timed	Low-Med	Primary market; clinical validation baseline
English (British)	Stress-timed	Low	Distinct prosodic/lexical norms from American
Spanish (Latin American)	Syllable-timed	Medium	Largest US clinical population after English
Mandarin Chinese	Tonal (4+1)	Low-Med	Tonal disentanglement proof-of-concept; military relevance
Arabic (Levantine)	Stress-timed	High	Military/intelligence applications; high GDI challenge
Korean	Non-tonal	Low-Med	Military relevance (Korean Peninsula); honorific system complexity

Phase 2 — Expansion (12 additional CEPs)

LANGUAGE-CULTURE	TONE SYSTEM	GDI	PRIORITY DRIVER

PRE-PUBLICATION — PUBLISH-ACCESS

Italian	Syllable-timed	Very High	Extreme expressiveness calibration; EU market
Russian (Moscow)	Stress-timed	Medium	Military/intelligence; dialectal stratification baseline
Russian (Ukrainian-influenced)	Stress-timed	Medium	Dialectal stratification validation
Japanese	Pitch-accent	Low (formal)	Pitch-accent processing; cultural restraint calibration
Portuguese (Brazilian)	Syllable-timed	High	Large clinical population; distinct from European Portuguese
French (Metropolitan)	Syllable-timed	Medium	EU market; clinical partnerships
German	Stress-timed	Low-Med	EU market; compound word analysis challenges
Hindi-Urdu	Non-tonal	High	Large population coverage; somatic idiom richness
Farsi (Persian)	Stress-timed	Medium	Military/intelligence applications
Vietnamese	Tonal (6)	Medium	Complex tonal system; phonation distinctions
Cantonese	Tonal (6-9)	Low-Med	Most complex tonal system; disentanglement stress test
Spanish (Castilian)	Syllable-timed	Medium	Distinct from Latin American; EU clinical market

Phase 3 — Global Coverage (25+ additional CEPs)

Turkish, Tagalog, Swahili, Thai, Indonesian/Malay, Polish, Ukrainian (native), Dutch, Swedish, Norwegian, Finnish, Greek, Hebrew (Modern Israeli), Pashto, Dari, Tamil, Bengali, Punjabi, Yoruba, Amharic, Hausa, Zulu, and additional dialect-specific profiles for high-priority languages.

Each new CEP requires: population-normed prosodic data, validated affective baseline ranges, cultural expressiveness calibration, narrative structure norms, and somatic idiom mappings. Estimated development time per CEP: 4-8 weeks with access to native-speaker clinical data.

CRITICAL APPLICATION

PRE-PUBLICATION — PUBLISH-ACCESS

LOGOS in Forensic Context — CSAA Cross-Cultural Calibration

CSAA (Cognitive Signature Authenticity Analysis) is perhaps the most sensitive application of LOGOS. Misclassifying cultural communication norms as deception indicators would be a fundamental failure with severe consequences in legal, immigration, and intelligence contexts.

Culture-Specific Deception Indicators vs. Communication Norms

FEATURE	WESTERN NORM	CROSS-CULTURAL REALITY	LOGOS ADJUSTMENT
Gaze aversion	Associated with deception	Sign of respect in many East Asian, African, and Indigenous cultures	Remove from authenticity scoring when LCF indicates relevant culture
Narrative inconsistency	Indicates fabrication	Circular/recursive narrative structures in Arabic, Aboriginal, and many oral cultures are normative	Load narrative structure norms from CEP before consistency analysis
Emotional flatness	Dissociation or coached delivery	Cultural restraint norm in Japanese, Finnish, many Northern European and East Asian contexts	Apply CEP affective baseline; recalibrate flat-affect threshold
Excessive detail	Rehearsed/fabricated story	Normal narrative style in many oral cultures; cultural respect for thorough account	Adjust detail-density thresholds per cultural narrative norm
Pause duration	Long pauses may indicate fabrication	Normal thinking/respect pauses in Finnish, Japanese, many Indigenous cultures	Load pause architecture norms from CEP; recalibrate thresholds

Immigration & Asylum Application

When CSAA is used to assess asylum narratives — one of the most high-stakes applications of authenticity analysis — cultural communication norms become a matter of human rights. A genuine trauma narrative from a Somali speaker may exhibit features that look like deception markers in a Western-normed system: circular narrative structure, indirect emotional expression, somatic coding of psychological distress, community-oriented framing rather than individual experience. Without LOGOS calibration, CSAA could systematically flag authentic refugee experiences as fabricated. This is not merely a technical failure — it is an ethical imperative that LOGOS must address.

STRATEGIC APPLICATION

Military & Intelligence Applications

LOGOS is essential for DoD, VA, and intelligence community use cases where multilingual analysis is not

PRE-PUBLICATION — PUBLISH-ACCESS

optional — it's the primary operating context.

Multilingual Service Members

Military personnel include native speakers of dozens of languages. A Korean-American soldier, a Somali-American translator, a Puerto Rican Marine — each requires VOCA baselines calibrated to their linguistic-cultural origin, not a default English norm. LOGOS enables culturally-aware readiness monitoring across the full diversity of the force.

Foreign Language Intelligence

Analyzing intercepted communications, debriefing detainees, assessing source credibility — all require CSAA to operate accurately in the target's native language. Arabic, Farsi, Pashto, Mandarin, Russian, Korean — LOGOS calibrates CSAA's authenticity analysis for each, preventing cultural communication norms from contaminating credibility assessments.

POW/Hostage Recovery Assessment

When service members are recovered after captivity, cognitive assessment must account for their linguistic background. A heritage speaker who reverts to their parents' language under extreme stress is exhibiting a specific cognitive-emotional response — not confusion. LOGOS identifies and correctly interprets these patterns.

Cross-Cultural PTSD Assessment

PTSD manifests differently across cultures. Some cultures emphasize somatic symptoms, others focus on spiritual disturbance, others on relational disruption. The same underlying condition produces narratives that look fundamentally different to a system calibrated only for Western PTSD expression. LOGOS ensures the Beverly Index identifies the condition regardless of how the culture encodes it.

INTELLECTUAL PROPERTY

Patent Position & Competitive Moat

Cross-cultural calibration of AI diagnostic tools is an unsolved problem in computational psychiatry. LOGOS represents a novel, patent-eligible invention.

Patent Claims — Provisional Application Scope

Claim Area 1: F0 Decomposition for Diagnostic Prosodic Analysis

PRE-PUBLICATION — PUBLISH-ACCESS

Method and system for separating lexical tone, intonational structure, and emotional prosody in the fundamental frequency signal of tonal and pitch-accent languages, for the purpose of enabling accurate affective state assessment from speech in languages where pitch carries lexical meaning.

Claim Area 2: Cultural Expressiveness Profile-Normed Diagnostic Scoring

System and method for calibrating AI-based psychological assessment scoring against population-normed cultural expressiveness profiles, wherein diagnostic thresholds for emotional, narrative, and prosodic features are dynamically adjusted based on the speaker's identified linguistic-cultural origin.

Claim Area 3: Code-Switching Cognitive Signature Analysis

Method for detecting, classifying, and mapping the diagnostic significance of language-switching events in multilingual speakers during psychological assessment, including identification of switch triggers (emotional, conceptual, identity, trauma) and mapping to cognitive state classifications.

Claim Area 4: Gesture Dependency-Adjusted Clinical Confidence Scoring

System and method for adjusting diagnostic confidence scores based on the assessed completeness of communicative signal capture relative to the speaker's language-culture's dependence on non-verbal modalities.

DEVELOPMENT

Development Timeline & Dependencies

Integration with NOUS Platform Roadmap

PHASE	LOGOS MILESTONE	DEPENDENCY
Phase 2 (Months 3-6)	Layer 1 (Language Detection) + Layer 2 (CEP — English only) + Layer 6 (LCF structure)	AAE operational; REMIEL text channels active
Phase 3 (Months 6-9)	Phase 1 CEPs (6 languages) + Layer 5 (GDI/completeness scoring)	POA Channel 8 operational; DreamWeaver rendering LCF metadata
Phase 4 (Months 9-14)	Layer 3 (Prosodic Disentanglement for Mandarin, Vietnamese, Cantonese) + Layer 4 (Code-Switching) + Phase 2 CEPs (12 additional languages) + CSAA cross-cultural calibration	POA fully operational; VOCA baseline system active; CSAA pathway live
Phase 5 (Months 14-18)	Phase 3 CEPs (25+ additional) + Layer 5D (Video Gesture — architecture only) + Clinical validation of cross-cultural scoring accuracy	Full NOUS platform operational; clinical validation studies active

PRE-PUBLICATION — PUBLISH-ACCESS

Critical Data Requirements

Each Cultural Expressiveness Profile requires empirical data: population-normed prosodic measurements, validated affective baseline ranges, narrative structure analysis from native-speaker clinical samples, and somatic idiom dictionaries compiled with native-speaking clinicians. Beverly Index LLC will need to establish partnerships with multilingual clinical research institutions, international psychology departments, and military language programs to build validated CEPs. The CEP development pipeline is the primary bottleneck for LOGOS deployment — the engineering is achievable, but the normative data must be collected and validated per language-culture.

LOGOS™ — Linguistic Origin & Gestural Oscillation System

A component of the NOUS™ Cognitive Intelligence Platform

© 2026 Beverly Index LLC — Advancing the Science of Computational Psychodynamics

NOUS™ • NOST™ • NOSS™ • LOGOS™ • AAE™ • REMIEL Engine™ • POA™ • R2X Bridge™ • DreamWeaver™ • Memoria Sonata™ • Beverly Index™ • Empyrean™ • VOCA™ • CSAA™

All Technologies Protected by Pending Patents | Document Classification: CONFIDENTIAL — PROPRIETARY | v1.0

PRE-PUBLICATION — PUBLISH-ACCESS