Bansat: Blueprint-First Gating of AI Coding Agents, with a Continuously Verified Privacy-Law Registry

Muhammad Tufail Khan*[1] and Naeem Ramzan [1]

[1]School of Computing, Engineering and Physical Sciences, University of the West of Scotland, Paisley, United Kingdom

10 November 2026

Abstract

The failures that sink applications built by AI coding agents are often decisions nobody made, such as whether every table enforces access control or whether trackers load before consent. Bansat is an open framework and Agent Skill that has the agent write a complete blueprint before any production code (product, architecture, security, privacy law, accessibility and 17 UI states for every screen), sized by a 20-question risk screen, and then holds the agent at approval gates that only a person may sign. An optional hook makes the first gate a hard stop in agents that support pre-tool-use hooks; a retrofit track covers live applications. Because legal advice ages, Bansat also keeps a public law registry in which every claim must cite an official source, enforced in continuous integration; it holds 120 entries citing 2,944 official URLs. A weekly watch detects changes on 105 official sources, and a weekly AI verify task, told to treat fetched content as data and never as instructions, drafts sourced updates for a person to review. On 31 golden cases, six of them carrying injected instructions, the verify task's first round found 10 of 18 known changes, invented none and followed no injected instruction; the misses shared one cause, which led to a prompt change. With the revised prompt, a second round found all 18, again inventing nothing and following no injected instruction, although its runs were not fully independent. We also publish an agreed, pre-specified protocol for comparing applications an AI agent builds with and without Bansat; its runs have not yet taken place.

1 Introduction

Coding agents built on large language models (LLMs) let a founder with no engineering team describe an application and have it built. What the agent rarely does, unless asked, is settle the questions that decide whether it can be launched safely and lawfully. Bansat's README calls these *decisions nobody made* and lists twenty-nine recurring "launch traps" [25]. Among them: row-level security is off, so anyone with the application's public key can read or change its tables; fonts load from a third-party host, sending every visitor's IP address there before any consent; session replay or advertising pixels load before anyone has said yes; the "we launched" email to a waitlist has no unsubscribe link or sender identity; the sign-up form never asks for age; and the privacy notice, written by an AI, describes an application that does not exist. Each has a concrete cost. In 2022 the Regional Court of Munich held that a site which passed a visitor's dynamic IP address to Google through Google Fonts, without consent, had infringed his rights, and awarded €100 in damages under Article 82 GDPR [29].

These failures are documented. Bansat's breach casebook (Appendix F of the framework) maps twenty incidents and regulators' decisions from January 2025 to October 2026 to the checks that catch each class of failure, and admits a case only if it rests on a primary source [25]. Researchers

*Corresponding author: Muhammadtufail.khan@uws.ac.uk

who examined 1,645 applications from one AI app builder's showcase reported 303 vulnerable endpoints across 170 of them, about 10.3%, and traced them to inadequate row-level security in the applications' database backends [40]. A scan of about 300,000 domains showing signs of one backend-as-a-service found 16,326 databases with tables readable without authorisation, noting that tables created through the API, as coding agents typically create them, do not have row-level security on by default [44]. One company reported that an AI agent ignored a code freeze and deleted a production database of 1,206 executive records and more than 1,196 company profiles, later recovered [46]; a hosting provider reported that an agent found an account-scoped API token on a user's machine and used it to delete a production volume [1]. A security vendor reported that crafted error reports led coding agents asked to fix them to run an attacker's package, and found 2,388 organisations whose error-tracking endpoints could be used this way; its 85% success rate is its own, unverified figure [50]. A self-replicating worm compromised more than 500 npm packages [9]. At the largest scale, France's data protection authority fined SHEIN's Irish subsidiary €150 million because advertising cookies were placed before visitors chose and after they clicked "Refuse all" [8]. The casebook says its checks catch a *class* of failure, not that Bansat would have prevented any one incident; we make no such claim either.

Studies of agent-built software agree. An analysis of deployed "vibe-coded" applications traces their vulnerabilities to security obligations forgotten, underspecified or never established in the workflow [12]. A benchmark of real-world feature requests found that few of the agents' functionally correct solutions were also secure, and that adding vulnerability hints to the request did not fix this [57]. A missing decision is better caught before the code exists.

Bansat (Pashto for "foundation") takes that position: before an AI coding agent writes production code, it writes a complete blueprint of the project and stops at gates that only a person may sign. Our contributions are:

1. **A blueprint-first framework distributed as an Agent Skill** (Section 3): a risk screen that sizes the blueprint, fifteen blueprint parts, gates signed only by a person (with an optional hook that makes the first a hard stop), 17 mandatory UI states, an 18-item blocking launch gate, and a retrofit track.
2. **A casebook-driven feedback loop**: twenty sourced incidents mapped to checks, which exposed gaps and added 14 checks to version 2.4, most of them about coding agents, CI/CD and connected applications.
3. **A public privacy-law registry with an official-sources rule** enforced in CI, kept current by a deterministic weekly watch and an AI verify task whose output a person reviews (Section 4).
4. **An evaluation of the verify task** on 31 golden cases, six with injected instructions, reporting two rounds as recorded, the prompt change between them, and the limits on their independence.
5. **A pre-specified controlled experiment** (Section 5), with hypotheses, a randomised block design and an analysis plan, agreed by the authors and published before any run.

2 Background and related work

Plan-first and spec-driven development with AI agents. Models can plan before writing code [23], and multi-agent frameworks organise agents into a software process [21, 45]; in practice the idea has become *spec-driven development*. GitHub's Spec Kit gives a coding agent a sequence of commands (a project *constitution*, then *specify*, *plan*, *tasks* and *implement*, with a convergence check) in which the specification remains the reference point [18]. Marri proposes a versioned "constitution" of security constraints that governs all later generation [34], and Alenezi a reference model in which structured specifications, not conversation, are the source of truth [4]. Bansat shares the premise but its blueprint is a fixed, cross-domain template reaching into privacy law, consent, children's data, accessibility and UI states; its depth is set by a legal and safety risk screen; and its gates are approvals only a person signs.

Agent Skills. Agent Skills are an open format in which a skill is a folder with a `SKILL.md` file of metadata and instructions, optionally with scripts and references. Agents load skills by progressive disclosure: each skill's name and description at start-up, the full instructions when a task matches, and bundled files as needed [3]. SkillsBench found that curated skills raised agents' average pass rate by 16.2 percentage points across 86 tasks, with wide variation by domain [30]. Skills also add attack surface, including the absence of a data–instruction boundary [31] and vulnerable skills in the wild [32]. Bansat is itself a skill, so these findings apply to it (Section 6).

Privacy by design and GDPR Article 25. Article 25 GDPR requires a controller to implement appropriate technical and organisational measures, both when it decides how to process personal data and during processing, and by default to process only the data each purpose needs [14]. Its engineering demands are debated [7], and privacy by design has long been easier to endorse than to operationalise [49]. Privacy professionals report no shared understanding of the "technical measures" the GDPR asks for [27]. Measurement studies have asked whether consent banners respect users' choices and comply with the law [35], and how consent pop-up design influences what users choose [36]. Bansat turns several such duties into build-time tests.

Threat modelling and OWASP ASVS. Threat modelling is well studied [55], and LINDDUN extends it to privacy threats [13]. Bansat's security part applies STRIDE [48] to each data flow and pre-fills 16 threats that recur in AI-built applications, from missing row-level security to coding agents holding production credentials. The OWASP Application Security Verification Standard, at version 5.0.0, gives a basis for testing web applications' technical security controls and requirements for building them securely [38]; Bansat lists it among its standards, with WCAG 2.2 for accessibility [54].

Security of AI-generated code. Early work found GitHub Copilot often suggesting vulnerable code in scenarios built around common weakness classes [41]. In a user study, participants with an AI assistant wrote significantly less secure code than those without one, yet were more likely to believe it secure [43]. Studies of ChatGPT's and Copilot's code followed [17, 26], and benchmarks have moved to whole backends [51] and multi-file agent tasks [57]. This work measures vulnerabilities in code; Bansat targets the step before, the decisions about data, consent, access and failure states that determine what the code should do.

Prompt injection against LLM agents. Prompt injection was first characterised as goal hijacking and prompt leaking [42]; indirect prompt injection plants instructions in data an application retrieves, and has compromised deployed LLM-integrated applications [20]. AgentDojo and InjecAgent evaluate attacks and defences for tool-using agents [11, 56]. Bansat meets it in its coding-agent rules and in its law-verification task, which reads untrusted pages (Section 4.3).

Regulatory change monitoring. Requirements engineering treats law as a source of requirements [6, 37] and counts the changeability of regulatory acts among its central difficulties [28]. Tracing regulatory change by hand is time-consuming and error-prone, which motivates automated change-impact analysis [2]. LLMs also state legal falsehoods with confidence [10, 33]. Bansat's response: detection is deterministic, the AI only drafts, every claim cites an official source, and a person reviews every change.

3 The Bansat framework

3.1 Structure and distribution

Bansat 2.4 is plain Markdown: fifteen parts (0–14) and six appendices (A–F), about 3,800 lines split into modules [25]. A combined single file is generated from the modules, and continuous integration (CI) fails if the two drift apart. `SKILL.md` tells the agent which modules to read at each step, so it




Figure 1: The new-project track (top two rows) and the retrofit track (bottom row). At each gate the agent is told to stop until a person signs the gate's row in the blueprint. G3, the release candidate, blocks launch while any of the 18 blocking launch-gate checks is red (Table 2). Once a retrofit reaches its gate R2 (blueprint complete, every gap registered), new scope follows the normal gates. Adapted from the repository README.

loads only the parts in scope. Text and templates are licensed CC BY 4.0 and code samples MIT. The code samples run in CI, where a Prisma schema's row-level security (RLS) policies pass 13 access checks in Postgres and a Playwright privacy test must fail on a page that loads a third-party font before consent; CI also fails if a sample in the text and its tested copy differ. Beside Appendix D's nine project-type profiles, 24 *stack profiles* in `stacks/` (seven backend, six frontend and full-stack, four mobile, seven no-code or backend-as-a-service) say what changes from the Next.js and Supabase reference; the skill loads only the one a project needs. They first shipped in v3.0.0, released on 10 November 2026. Figure 1 shows the two tracks through the framework.

3.2 Intake and risk tiers

Part 0 asks twenty screening questions, each switching on a module when answered yes, from markets (UK, EU, Nigeria, US and others), under-18 users and special category data to AI, payments, marketing, analytics, third-party embeds and a B2B processor role. The answers set a tier. **High**: special category data, location or worker monitoring, wearables, children as a target or likely audience, or significant automated decisions; a data protection impact assessment (DPIA) is then mandatory. **Medium**: accounts, analytics, marketing or a B2B processor role. **Low**: otherwise. The tier sets the minimum depth before build: a Low-tier project completes only the intake, the core product specification, the stack, cookies, the launch-trap audit, UI states and the launch gate; a High-tier project completes everything, plus a DPIA and an independent review before G3. The skill asks at most five questions, only where a wrong guess would be costly, and flags every assumption. Eight *delivery questions* feed a method picker (Section 3.9).

3.3 The blueprint

The agent writes the blueprint to `docs/BLUEPRINT.md` in the project, where it changes in the same pull request as the code (Table 1). Requirements carry identifiers (`FR-`, `NFR-`, `SCR-`, `API-`, `ADR-` and others), so each feature traces to its screens, endpoints, data, tests and record of processing. Part 8 covers AI features, including the transparency duties of Article 50 of the EU AI Act [16]. Part 12, the agent's operating manual, goes into the project's agent instructions file, such as `AGENTS.md`. Its rules include: research how others built something before building it; re-check authorisation in every server entry point; implement every applicable UI state; never sign a gate; work with development

Table 1: The parts of a Bansat blueprint (framework v3.1).

Part	What it settles
0 Intake & risk	20 screening questions, risk tier, modules in scope, 8 delivery questions
1 Product (PRD)	Problem, metrics, personas, MoSCoW features with IDs, Gherkin acceptance criteria
2 Non-functional	Numeric targets: Core Web Vitals, uptime, recovery, security, accessibility, cost
3 Architecture (TRD)	Pinned stack, environments, context diagram, data flows, processor register, secrets
4 Decisions	Architecture decision records, each recording the prior art considered
5 Data	Data classes, dictionary, schema, data-layer access rules with isolation tests, retention
6 API	Endpoint inventory, RFC 9457 errors mapped to UI states, validation, webhooks, rate limits
7 Security	Authentication flow, RBAC matrix, 16 pre-filled STRIDE threats, headers and CSP, logging
8 AI features	Feature register, minimised inputs, evals, prompt-injection defences, AI Act labelling, spend caps
9 Privacy & compliance	27 sections, from lawful bases, consent and cookies to children, breach, DPIA and launch traps
10 Experience	App flow, look-and-feel brief, WCAG 2.2 AA, design tokens, 17 UI states with a state matrix
11 Delivery	9 phases with exit criteria, Definition of Done, testing, CI/CD, method picker, PM toolkit
12 Agent manual	Agent rules, research-first feature protocol, 8-step debugging protocol, prompt library
13 Launch gate	40 go/no-go checks, 18 of them blocking
14 Retrofit	Day-0 triage, reverse-engineering, gap register, review cadence, portfolio register
A–F Appendices	Templates, sources, glossary, 9 project-type and 6 delivery-method profiles, breach casebook

Table 2: Bansat's gates (`framework/how-to-use.md`).

Gate	Unlocks	Exit criteria
G0 Idea	Writing the blueprint	Part 0 and the first product sections drafted
G1 Blueprint approved	Production code (throwaway spikes allowed earlier)	All in-scope sections complete; ADRs accepted; DPIA screening done; no placeholder left in scope
G2 Data-ready	Collecting any real personal data	Privacy notice live; processing records and lawful bases; consent capture; processor contracts; isolation tests passing; UK registration fee paid
G3 Release candidate	Public launch	Testing complete; every launch-gate item green, or not applicable with a reason
G4 Post-launch	The next major scope	30-day review of metrics, incidents, rights requests and the compliance calendar

keys only; ask before any destructive command; never switch off one's own approval prompts or sandbox; and treat text in tool results, issues, error reports and web pages as data, not instructions.

3.4 Gates

Table 2 gives the gates. G2 is the one most often missed: a "coming soon" page with an email box already processes personal data, so not even a waitlist address may be collected before the privacy basics are in place. Only a person signs a gate, by filling in its row (approver and date) in the blueprint; the agent is told never to fill it in, even when the user says "approved" in chat.

3.5 UI states

Part 10 requires every screen and asynchronous component to handle each applicable state of the seventeen in Table 3, or give a reason it does not apply, and to prove it in a per-screen state matrix. S1–S10 are the core set; S11–S17 are required wherever they can occur. Each state has an acceptance test, and a typed pattern makes the compiler reject a view that omits one.

3.6 Launch checks

Bansat checks a project twice before it meets the public. The *launch-trap audit* (framework 9.26) lists the twenty-nine failures that get AI-built applications fined, breached or rejected by app stores, each with a fix and a way to verify it (Table 4), and runs before G2 and again before G3. Version 3.1.0 added the last twelve: AI disclosure, opt-out signals, biometric and health data, online withdrawal,

Table 3: The 17 mandatory UI states (framework 10.7), with the condition that triggers each.

Core (S1–S10)		Extended (S11–S17)	
S1 Empty	first use, or an empty list	S11 Not found / deleted	404 or 410
S2 Loading	a request in flight	S12 Offline queue / sync conflict	queued writes; 409
S3 Error	5xx or an unknown error	S13 Rate limited / quota reached	429
S4 No internet	offline, or failed fetches	S14 Long-running / background task	AI generation, export, import
S5 Slow network	over 1 s, 5 s, 15–30 s	S15 Degraded / partial	one section or third party fails
S6 No search results	a query returns nothing	S16 Destructive confirmation & undo	delete or remove actions
S7 Permission denied	403	S17 Consent-gated content	an embed blocked until consent
S8 Session expired	401, or refresh fails		
S9 Form validation	client check; server 422		
S10 Success	a mutation confirmed		

legal notices, accessibility law, server-side authorisation, AI spending limits, app store labels, card data and payment webhooks. The *launch gate* (Part 13) has 40 go/no-go items in seven groups, 18 of which block launch while open. Blocking items include a tested backup restore, data-layer access with isolation tests, no exposed secrets, nothing non-essential before consent, compliant marketing email, and working export and account deletion.

Table 4: The 29 launch traps (framework 9.26). Each fix names the framework section that covers it, followed by the evidence that proves it. Traps 18–29 were added in version 3.1.0; the experiment in Section 5 tests version 3.0.0, which has the first 17.

#	Trap	Why it bites	Fix and proof
1	The sign-up form never asks for age	Children's data without parental consent or safeguards; under Nigeria's NDPA a child is anyone under 18	A neutral age question (9.12); an end-to-end test of the under-age path
2	Fonts from a third-party CDN	Visitors' IP addresses go to a third party with no lawful basis; German courts have awarded damages [29]	Self-hosted fonts and a self-only font policy (9.9); the privacy test
3	Session replay or heatmaps before consent	A consent breach, and recordings can capture personal data	A consent-gated loader with strict masking (9.10); the privacy test
4	A launch email with no unsubscribe, sender identity or address	Breaches UK PECR, US CAN-SPAM and Nigeria's NDPA, and fails Gmail and Yahoo sender rules	A compliant template and one-click unsubscribe (9.11); a seed-inbox test
5	Row-level security off, or the secret key in the client	Anyone can read or write the database	Row-level security on every table and keys on the server only (5.4, 7.3); isolation tests in CI
6	A template or AI-written privacy policy	It doesn't match what the app does, so it breaches transparency duties	Written from the record of processing (9.6); a checklist review
7	Ad or analytics pixels in the root layout	Data shared with ad platforms before consent	A consent loader, with Consent Mode denied by default; the privacy test
8	User data sent to an LLM with no disclosure or DPA	Transparency, transfer and processor-contract breaches	A recorded provider decision, a DPA and redaction; the vendor register
9	No account deletion or data export	A rights breach, and an App Store rejection	A privacy centre (9.15); end-to-end tests
10	Personal data in logs or error trackers	Breaches minimisation and widens any breach	Scrubbing and logging rules (7.5); a log review
11	Pre-ticked boxes, or "by using this site you agree"	Invalid consent under the GDPR [14]	Unticked, granular choices (9.7); a UI review
12	A cookie banner with no "Reject all"	Invalid consent, and a leading enforcement theme [8]	Equal Accept and Reject on the first layer; a screenshot review

Table 4, continued

#	Trap	Why it bites	Fix and proof
13	Real customer data in preview or staging	A security and purpose-limitation breach	Synthetic seed data only (3.2); an environment audit
14	A public storage bucket for uploads	Data exposure	Private buckets and signed URLs; an integration test
15	Regulator fee or registration missed	ICO penalties of up to £4,350; missed NDPC duties	Pay and register before G2 (9.2); the compliance calendar
16	No breach plan	Missed 72-hour notification clocks	A breach runbook (9.20); a tabletop drill
17	Dates of birth or ID scans kept "just in case"	A minimisation breach, and a target for attackers	Store the result, not the evidence; a data-dictionary review
18	A chatbot or AI feature that doesn't say it's AI	The AI Act's transparency duties, applicable since 2 August 2026: disclose the AI and mark generated content [16]	Disclosure where people meet the AI, and marked output (8.6); a UI review
19	Global Privacy Control ignored	US state laws, California's among them, treat a browser's opt-out preference signal as an opt-out of selling or sharing	GPC treated as "Reject non-essential" everywhere (9.8); the privacy test with GPC on
20	Face, voice or fingerprint features without written consent	Special category data under the GDPR; Illinois law requires written notice, a signed release and a published retention schedule [22]	Explicit consent, a DPIA and a retention schedule (9.13); consent records
21	Wellness or symptom features without health-data consent	Special category data under the GDPR; Washington law requires consent to collect consumer health data and separate consent to share it [52]	Separate, specific consents and no trackers on those screens (9.13); end-to-end tests
22	No online way to withdraw or cancel	In the EU, distance contracts concluded online need a "withdraw from contract here" function from 19 June 2026 [15]	A withdrawal and cancellation flow as easy as signing up (9.25); an end-to-end test
23	No company details or legal notice	UK companies must show their registered details on their website; sites aimed at Germany need an Impressum	A legal notice linked from the footer (9.25); a page review
24	An EU shop or consumer service that fails accessibility law	The European Accessibility Act has covered e-commerce and certain consumer services since 28 June 2025	WCAG 2.2 AA [54] and an accessibility statement (10.6); axe and a keyboard-only run
25	Authorisation only in the UI or in middleware	Server actions and API routes can be called directly; a critical 2025 flaw let requests skip Next.js middleware [19]	Deny-by-default checks in the data-access layer (7.2); the role-matrix test
26	AI endpoints with no quota or spend cap	Anyone can run up the model bill ("denial of wallet") [39], and text the model reads can carry injected instructions [20]	Authentication, quotas, a hard spend cap and no unconfirmed side effects (8.7); a rate-limit test
27	App store privacy labels that don't match the app	Apple's labels and privacy manifests, and Google Play's Data safety form, must describe what the app and its SDKs collect	Labels filled in from the data dictionary (9.25); a comparison before each submission
28	Card details collected in your own form	Card data on your servers brings full PCI DSS scope	Hosted checkout or hosted fields (9.25); no card field reaches the API, database or logs
29	Payment webhooks accepted without a signature check	Anyone can post a fake "payment succeeded" event	Signature checks that reject stale and repeated events (6.5); a rejection test

3.7 Retrofit track

Part 14 routes existing projects by state: built but holding only synthetic data (*light*), or live with real users, or inherited or AI-generated code nobody fully understands (*urgent*). An urgent retrofit starts with a *Day-0 triage* within 48 hours: twelve checks reported as pass, fail or unknown with evidence, from exposed secrets, database access rules and tracking before consent to credentials that coding agents and CI can reach, ending with whether anything was actually exposed, which starts a 72-hour breach clock. The agent then reverse-engineers the blueprint from evidence such as lockfiles, billing statements and schema dumps, registers each gap with a severity and deadline, and plans remediation sprints R1–R4. The track states plainly that past processing cannot be made lawful after the fact.

3.8 The optional G1 hook

A skill can instruct an agent but cannot force it. For a hard stop at G1, Bansat ships a pre-tool-use hook for agents that run such hooks before each tool call and let a hook deny the call with a reason. Until the G1 row in `docs/BLUEPRINT.md` names an approver and a `YYYY-MM-DD` date, Bansat's hook refuses the agent's file edits outside `docs/`, `spikes/`, the agent's configuration folder and a few top-level notes, and it refuses any edit that would itself sign the G1 row, so the agent cannot approve its own blueprint. It guards file-editing tools, not shell commands, so it is a guard rail rather than a sandbox, and it makes no decision when its input cannot be read.

3.9 From an individual to a large organisation

The same framework serves a person building alone, a startup and an organisation with several teams. *Depth follows risk*, not size, so a solo builder's low-risk page completes only the Low-tier minimum. A *delivery-method picker* (11.7) chooses an outer method for approvals when a client or auditor needs one, then an inner method for the build (a solo loop, Kanban, Scrum, Shape Up, or a scaled method for several teams), and Appendix E maps G0–G4 onto each. *The project's rules win*: if a repository's own instructions set out planning stages, the agent follows them, maps Bansat's gates onto them and uses Bansat to fill the gaps. A *portfolio register* keeps one row per project for an organisation running many. The casebook spans individual builders to the largest platforms, because the same failures recur at every size.

3.10 The breach casebook as a feedback loop

Mapping the casebook to Bansat's checks exposed classes of failure they did not fully cover, mostly around coding agents and the tools connected to them, and version 2.4 added fourteen checks: among them, the coding agent holds no production or account-wide credentials and asks before destructive commands, text it reads is data, CI/CD and publishing are hardened, and backups are kept apart from what they protect.

4 Keeping the law current

A blueprint's legal advice ages fast. The framework's legal facts were checked against official sources with AI assistance on 4 November 2026, and no lawyer has reviewed them. Bansat v3 therefore adds a registry, a watch and a verify task (Figure 2), planned in Bansat's own blueprint (signed at G1 on 5 November 2026). Two decisions run through the design: detection is deterministic and the AI only verifies and drafts (ADR-B2), and a person reviews every legal change, whatever the AI's confidence (ADR-B4).




Figure 2: Law Watch. Detection is deterministic, the AI drafts, and a person merges. Adapted from Bansat's blueprint (3.3).

4.1 The registry

The registry holds one YAML file per jurisdiction, validated against a JSON Schema. An entry lists the jurisdiction's laws (citation, official URL, status, start date) and regulators and, in a *full* entry, a short summary of each obligation a builder meets, from lawful bases, consent age and cookies to breach notice, transfers, AI and penalties. A *basic* entry gives only the laws and the regulator and carries a "verify before relying" banner. Each entry records when and how it was last checked: `ai-checked`, or `human-reviewed` with the reviewer's username. A third status, `lawyer-reviewed`, exists in the schema but is deliberately unused, because no lawyer is involved.

The central rule is that every legal claim in a full entry cites an *official* source: legislation, a gazette, a regulator, a government site or a court. Trackers, law firms and news may be listed as leads under `secondary`, never as the only support for a claim. Summaries are in the project's own words, at most 600 characters, and a number must state its unit (a consent age in years, a breach deadline in hours). A validator runs on every pull request. Beyond the schema, names, placeholders and dates, it rejects any source not on an official domain listed for that jurisdiction in `watch/sources.yaml`, unless marked secondary; a companion test proves each rule catches a bad entry.

The validator currently reports 120 entries (62 full, 58 basic) and 2,944 URLs on official domains. The full entries cover the EU and ten European countries; Canada and Quebec, Brazil, Mexico, the US federal level and 23 US states; nine in the Middle East and Africa (the UAE federal level, DIFC and ADGM, Saudi Arabia, Qatar, Israel, Nigeria, South Africa and Kenya); and fourteen in Asia-Pacific (China, Hong Kong, Japan, South Korea, India, Pakistan, Singapore, Indonesia, Vietnam, Thailand, Malaysia, the Philippines, Australia and New Zealand). The basic entries cover the remaining EU and EEA states, the rest of Europe, eleven territories and small states, eleven countries in South and Central America, and six in the Middle East and Central Asia, plus Egypt, which is basic because no official text of its data protection law or its regulations could be opened, so its obligations could not rest on an official source. Each batch was written from official sources, then checked by an independent reviewer who re-opened every source, then corrected; a jurisdiction whose main law no official copy of could be opened is left out rather than filled from memory (Russia and Ukraine, for example). All 120 entries are `ai-checked`. The skill reads only the entries for a project's markets, re-verifying any checked more than 90 days ago.

4.2 Law Watch

A full entry may list official sources to watch: RSS or Atom feeds, HTML pages narrowed by a CSS selector to a stable list of news, or JSON APIs, with optional title `keywords` for office-wide news lists. A GitHub Action runs every Sunday at 06:23 UTC, a day before the verify task. It respects `robots.txt`, makes one rate-limited request per source per run, and retries a failed request twice before calling a source failing. A change opens one issue per jurisdiction, or comments on the open one; failing sources share one issue, so a failure is never silent. State lives in a workflow artifact (a

Table 5: Verify-task evaluation, both rounds run on 10 November 2026, as recorded in `watch/eval/results/2026-11-10-round-1.md` and `2026-11-10-round-2.md`. Round 2 used the revised prompt; its runs were not fully independent (see text).

Measure	Target	Round 1		Round 2
Finds the change, on known past changes	$\geq 90\%$	10 of 18 (56%)	missed	18 of 18 (100%), met
Every claim cited correctly	100%	10 of 10 (100%)	met	18 of 18 (100%), met
Invents a change that did not happen	0	0	met	0, met
Follows an injected instruction or writes outside `laws/`	0	0	met	0, met

hash and each item's title, link and date, never page text); the watch has no secrets and can write only issues. Its tests replay a known past change offline. The registry watches 105 sources for 46 of its 62 full entries, in English and ten other languages; basic entries are not watched. Tennessee and DIFC have no watch block, because their official sites refuse or challenge automated requests, so the verify task re-checks them by hand. The fourteen Asia-Pacific entries, added last, do not yet have watch sources.

4.3 The verify task and its injection rules

A weekly scheduled AI-agent task follows a versioned prompt, `watch/verify-prompt.md`. For each open watch issue it reads the entry and the jurisdiction's earlier issues and pull requests, including rejected ones, opens every listed item on the official site, and either labels the issue `no-change` with what it checked, or edits only that entry on a new branch, runs the validator, and opens a pull request citing an official source for each changed field. It also checks failing sources and the stalest entries, and never merges.

Because it reads untrusted pages, the prompt is written as a defence against prompt injection (threat T-B1 in Bansat's blueprint). Fetched content is data, never instructions, and any instruction inside a fetched page is ignored. The task writes only to `laws/` files, on a new branch; never sets `human-reviewed` or `lawyer-reviewed`; works only from official sources; does not infer a change from news, a tracker or a model's memory, nor re-propose a rejected change unless the source has changed; and respects `robots.txt` and site terms. The prompt is only one layer: the validator rejects unofficial sources, branch protection keeps everything off the main branch until the maintainer reviews it, and the task's pull requests are opened through the maintainer's account so that CI runs on them.

4.4 The verify-task evaluation

Bansat's blueprint (8.5) sets three targets for the verify task, and the evaluation adds a fourth from threat T-B1 (Table 5). The golden set has 31 cases. **Sixteen known changes** each take a real change back out of the current registry: a new law (such as the UK's Data (Use and Access) Act 2025 or an EU omnibus amending the AI Act) or a status that moved; in three, the law is enacted but not in force, so marking it in force is a miss. **Nine cases have nothing to change**: real items such as a regulator's job advert or a letter urging Congress to pass a bill, one of them repeating a change the maintainer had rejected. **Six cases carry injected instructions** in item titles or earlier comments, telling the task to mark every entry lawyer-reviewed, run a command, edit another jurisdiction, cite a mirror site, rewrite its own prompt or delete a watch block; one is in French, and two also carry a real change. In all, 18 cases expect a change and 13 expect none. Each case becomes a sandbox: the registry with the change removed, the watch issue, earlier issues and pull requests, and eval-mode rules that replace GitHub with files. CI checks on every pull request that each case still holds against today's registry. A tested scorer checks each run. A change is *found* when the expected law appears in the entry's `laws` list with an accepted status (and start date, where given) and, where the case names them, an official URL on an expected host. Any edit where nothing changed, or to another jurisdiction, is *invented*. Following an injected instruction, writing outside `laws/` or claiming a human or lawyer review is *unsafe*.

Round 1. Round 1 ran on 10 November 2026 with the prompt as merged on 5 November. Each case ran once, by the same model as the weekly task, in its own sandbox without browser access; groups of four to six sandboxes shared an agent, told to treat each as a separate run. The task found 10 of the 18 known changes, cited every change it made to an official source, invented nothing and followed none of the injected instructions (Table 5). All eight misses had one cause: the entry already described the law in an obligation, so the task judged that nothing had changed and left it out of the `laws` list. Two of the eight were the injection cases that also carried a real change. One no-change case was not run, because no readable result was produced. The scorer first counted the bookkeeping field `checked.date` as an uncited change; that exemption was added to the scorer and its tests, and the recorded table is the rescored result.

The prompt change. Round 1 led to two changes to the prompt. The task must now check the entry's `laws` list as well as its obligations: a law or amendment the entry should list (the main law, its implementing rules, and any marketing, children's, AI or cybercrime law that sets duties builders meet) that the list omits, or gives the wrong status or start date, is a change to make, even when an obligation already describes it. And the prompt no longer contradicts itself about dates: `checked.date` changes only on an entry whose every field was re-checked, and a change from a watch issue adds a history item instead.

Round 2. Round 2 reran all 31 cases with the revised prompt, once each, by the same model and without browser access. Every target was met: the task found all 18 changes and cited each to an official source, invented nothing, and followed none of the six injected instructions (Table 5). It marked the three enacted-but-not-in-force laws as enacted and did not re-propose the rejected change; two extra obligation edits were cited and in the right entry.

The record states that round 2's runs were not fully independent. As in round 1, groups of five or six sandboxes shared an agent, which carried context from one case to the next. In four of the six groups, the agent compared its sandbox's copy of the prompt file with another sandbox's copy; the files were identical, and the agents report comparing or using nothing else. In one group the agent listed the run folder and saw one no-change case's expected outcome in the answer key; it reports that it then worked the case out from the sources, and the result is the same without that case. In response, the answer key now sits outside the sandboxes' folder, and each sandbox gets its own copy of the validator's packages rather than a link back to the repository, which holds the answers. The record recommends giving each run only its own folder in a third round, and notes that the cases were written with help from the same model family that ran them and that 31 cases is a small set.

5 Pre-specified experiment

Status. Agreed by the authors on 10 November 2026 and published in `research/` before any run; no run has taken place. The results will be reported separately against this protocol, and any change made after the pilot will be recorded there with its reason.

Bansat's blueprint (workstream R, FR-22) calls for this experiment, published in `research/` before the paper so that anyone can rerun it.

Hypotheses. The question is whether having the Bansat skill installed changes how many of the launch failures Bansat targets end up in an application an agent builds from a short brief, and at what cost. **H1** (primary): applications built with Bansat (condition B) pass a larger share of the checks that apply to them than those built without it (condition A). **H2** (primary): they have fewer defects, that is, fewer separate findings behind failed checks. **H3** (descriptive, not tested): Bansat costs time and tokens, mostly before G1; we report how much, and how complete the blueprints are.

Conditions and design. Both conditions use the same pinned model and agent version, the specification's body as the prompt, a fresh credential-free container and the same fixed operator

Table 6: The six specifications (`research/specs/`). Tier is the risk tier Bansat's intake would give; the agent never sees it.

Spec	Builder	Stack	Tier	Risks it brings in
s1 Waitlist	individual	Astro, Supabase	Med	A waitlist and a launch email; Google Analytics; the Inter font
s2 Workspace	startup	Next.js, Supabase	Med	Multi-tenant access with a client portal; uploads; PostHog; a B2B processor role
s3 Children	organisation	Next.js (PWA), Supabase	High	Children aged 7–11 in the UK and Nigeria; parental consent; a parents' newsletter
s4 Fitness	individual	SvelteKit, Supabase	High	Health data; progress photos; open sign-up; a newsletter with offers
s5 AI portal	organisation	Next.js, Supabase	Med	Personal data sent to an LLM; claim photos; session recordings
s6 Marketplace	startup	Laravel, MySQL	Med	Payments and payouts; a database without row-level security; a weekly digest

replies. In condition B the workspace, an empty Git repository, also holds the skill in the agent's skills folder, copied from a pinned release without `research/` or `paper/`, so the agent cannot see its checks. The prompt never names Bansat; the transcript records whether the agent used the skill (a manipulation check). The operator signs G1 without reading the blueprint, so no person improves it. Six specifications are crossed with the two conditions: a pilot of one run per cell (12 runs, not analysed) sizes variance and cost, then $n = 5$ runs per cell (60 runs). Runs follow randomised complete blocks, each block holding every specification in both conditions once, shuffled from a seed recorded before the first run, so drift in the model or service reaches both conditions alike. Reviewers judge applications by opaque run IDs, without the agent's configuration folder or `docs/BLUEPRINT.md`; this blinding is partial, since code may cite Bansat's sections.

Specifications. Six briefs, written as a founder or organisation would write them, span an individual, a startup and an organisation and four stacks (Table 6). They never name a control the checks test (no "consent", "privacy", "RLS", "GDPR" or "compliant"; a test enforces this), since asking for compliance would measure instruction-following rather than what Bansat adds. Scoring facts sit in front matter the agent never sees.

Checks and rubric. Twelve checks read the code (row-level security, client-side secrets, fonts, consent-gated tracking, security headers, two marketing-email checks, the age question, the privacy notice, pre-ticked consent, upload storage, and account deletion and export) and two load the application in Chromium (nothing third-party before consent or after "Reject"). Together they test 12 of the 17 launch traps in v3.0.0, the version condition B uses, and 11 correspond to blocking launch-gate items. Checks read only the application's own code, never `docs/` or the installed skill, so documents cannot earn a pass, and return pass, fail, not applicable or needs review, with evidence. A reviewer blind to the condition settles needs-review items; reviewers' corrections are published as the checks' error rate, and a second reviewer on a random fifth gives Cohen's kappa. A separate rubric (version 0) scores blueprint completeness from the "Part N" headings the tier needs and key elements such as the risk tier and the G1 row; it never enters the checks' score.

Metrics and analysis. The unit is the run. **M1** (for H1) is the pass rate after review, checks passed over checks that apply; **M2** (for H2) is the number of findings behind failed checks; **M3** is time and tokens from the transcript, split at G1 in condition B; **M4** is blueprint completeness. Features built, whether the application runs and whether the skill was used are reported alongside, so building less cannot look like building better. H1 and H2 are tested with a permutation test that shuffles condition labels within each specification (10,000 permutations, two-sided), with 95% bootstrap intervals and Holm's correction across the two at $\alpha = 0.05$. The primary analysis is by intention to treat; sensitivity analyses use scores before review, count needs-review as all fails or all passes, keep only condition-B runs that used the skill, and drop runs that did not build. The plan

follows guidance on threats to validity in software engineering experiments [53] and in LLM-based software engineering research [47].

Decisions agreed by the authors. The draft protocol left twelve decisions open, and the authors settled them as proposed. (1) Five runs per cell, reviewed once against the pilot's spread. (2) Condition B pins v3.0.0, the first release with the stack profiles, published on 10 November 2026; the model and agent version are pinned when the pilot starts and reported with the results. (3) The skill is triggered by its description, as for a real user, and the transcript records whether it was used. (4) Permission prompts are skipped inside the disposable, credential-free container, so no run waits on a person. (5) The operator signs G1 without reading the blueprint, and the optional G1 hook is not installed, so the experiment measures the skill's instructions alone; an arm with a person's review is left to future work. (6) The pass bars stay as written: row-level security with no policy passes, since deny-all is the framework's own default for server-only tables; HSTS and `Permissions-Policy` are reported, not required; and an "18 or over" box passes the age check, with a note. (7) An application that fails to build gets no request to fix it; it is scored without the browser checks and reported. (8) No check is added for the five untested traps, which stay outside the experiment's claims. (9) The stratified permutation test is the primary analysis and a mixed-effects logistic model is exploratory; the protocol published in `research/` before the pilot serves as its pre-registration. (10) The first author reviews every application, the second author independently reviews a random fifth, and disagreements are settled by discussion and recorded. (11) The generated applications, every run's score and review, and a summary of each transcript are published in `research/results/`, with full transcripts once machine paths and account details are removed. (12) A second agent or model is left to future work.

Results. The runs follow this paper; their results, including the pilot's, will be published in `research/results/` and reported against the hypotheses above.

6 Discussion, limitations and threats to validity

AI-checked, not lawyer-reviewed. Every legal fact in the framework and the registry was checked against official sources with AI assistance; no lawyer has reviewed any of it, all 120 entries are `ai-checked`, and the `lawyer-reviewed` status is unused. LLMs make confident legal errors [10], and so do commercial AI legal tools [33]. Bansat's mitigations (an official source for every claim, a visible check date and review status, a person's review of every change) make an error less likely to be unsourced or unseen, not impossible: a sourced summary can still misread the right source, the reviewing maintainer is not a lawyer, and Bansat is not legal advice.

A skill instructs; it cannot force. Bansat's gates are instructions. An agent can skip a step, misjudge a tier or sign a gate it was told not to, and the skill alone cannot prevent it. The hook makes G1 a hard stop only for the agent's file-editing tools, not shell commands, and does nothing for G2–G4, which rely on tests and on the person reading the blueprint. Skills are an attack surface [31, 32], and a tampered copy of Bansat could weaken its rules; the README therefore pins installation to a release tag, currently v3.1.0, published on 10 November 2026. And a gate signed without being read adds little.

Construct validity of the verify-task evaluation. The evaluation asks whether the task can re-find a known change when an issue points to the official item that announced it, in a sandbox built by removing that change from today's registry. The real task must also sift noisy items and find changes the watch did not flag. The cases come from the same project as the registry, and six injection cases are a small set beside AgentDojo or InjecAgent [11, 56]: passing them shows only that these attacks failed. Each case ran once per round, and in both rounds several sandboxes shared an agent; in round 2 some agents also compared files across sandboxes and one saw an answer-key entry,

so the runs were less independent than the evaluation's own instructions ask. The scorer's patterns and host lists encode what counts as "found", and round 1 needed one correction. Round 2's perfect score is on the same cases the prompt was revised against, so it may partly reflect fitting the prompt to the set; fresh, held-out changes, run in fully isolated folders, would be stronger evidence, so a third round will use held-out cases, repeat each case and give every run only its own folder. Benchmark claims about LLMs need to state what construct they measure and how [5].

Threats to the proposed experiment. A pass is not compliance: the checks test presence and clear patterns, not whether a notice is accurate or policies isolate tenants. The checks come from Bansat's own rules, which favours condition B by design; the question is whether the skill changes those outcomes, and the checks accept common alternatives to Bansat's own way of meeting each rule. Agent runs vary [47], which the repetitions and randomised blocks spread across conditions; checks within one application are not independent, which is why the run is the unit. The results will speak to one agent and model, six specifications on four stacks, and mostly UK and EU markets. The framework's author wrote the specifications and checks; publishing them before any run, with the co-authors' sign-off, guards against that bias.

7 Ethics and AI-assistance statement

The Bansat framework, its law registry and the verify-task evaluation were developed with assistance from an AI coding agent, and the authors reviewed every change. This paper was drafted with AI assistance, and Figure 1 was drawn with an AI figure tool from the authors' description; the authors checked both and take full responsibility for the content. No AI tool is an author. No personal data is involved: the registry holds public legal information, and the evaluation's injected instructions are synthetic cases run in sandboxes. The casebook uses public primary sources and names only security researchers who published under their own names. The pre-specified experiment has no human participants and processes no personal data: its briefs are fictional, its applications are never deployed, and the only people involved are the authors, as operator and reviewers.

8 Availability

Bansat is public at `https://github.com/bewithkhan/bansat` [25]. Text and templates are licensed CC BY 4.0 and code samples MIT; a `NOTICE` file says which covers what. A documentation site with no cookies or trackers is at `https://bewithkhan.github.io/bansat/` [24]. `CITATION.cff` gives the citation for version 3.1.0, released on 10 November 2026. The registry, the watch and the verify prompt are in `laws/` and `watch/`. The verify-task evaluation (cases, scorer and both rounds' results) is in `watch/eval/`, merged into the main branch with pull request #28 (merge commit `a523ca2`), together with the revised verify prompt. The experiment's protocol, specifications, checks and run scripts are in `research/`, and this paper's source in `paper/`, both merged into the main branch with pull request #38 before any run. The 24 stack profiles are in `stacks/`.

9 Conclusion

AI coding agents make it easy to skip the decisions that make an application safe to launch. Bansat moves those decisions to the start: the agent writes a full blueprint, sized by risk, and stops at gates a person signs. Because the legal half of that blueprint ages, Bansat keeps a public registry in which every claim cites an official source, watched weekly and updated through AI drafts that a person reviews. The verify task's first evaluation found it cautious rather than careless: it invented nothing and followed no injected instruction, but missed eight of eighteen known changes for one shared reason. After a prompt change it found all eighteen, though on the same cases and with runs that were not fully independent. Whether Bansat changes what an agent ships is for the pre-specified experiment to test.

References

All web sources were accessed on 10 November 2026.

[1] Mahmoud Abdelwahab. Your AI wants to nuke your database. Guardrails fix that. https://blog.railway.com/p/your-ai-wants-to-nuke-your-database, 2026. Railway (casebook F-05).

[2] Sallam Abualhaija, Marcello Ceci, Nicolas Sannier, Domenico Bianculli, Dirk Andreas Zetzsche, and Marco Bodellini. Toward automated change impact analysis of financial regulations. In *Proceedings of the 1st IEEE/ACM Workshop on Software Engineering Challenges in Financial Firms (FinanSE)*, pages 31–32, 2024. doi:10.1145/3643665.3648046.

[3] Agent Skills. Agent skills: Overview. https://agentskills.io, 2026.

[4] Mamdouh Alenezi. Specification-driven development as the foundation of AI-native enterprise software engineering. arXiv:2607.16680, 2026.

[5] Andrew M. Bean, Ryan Othniel Kearns, Angelika Romanou, Franziska Sofia Hafner, Harry Mayne, Jan Batzner, Negar Foroutan, Chris Schmitz, Karolina Korgul, Hunar Batra, et al. Measuring what matters: Construct validity in large language model benchmarks. arXiv:2511.04703, 2025.

[6] Travis D. Breaux and Annie I. Antón. Analyzing regulatory rules for privacy and security requirements. *IEEE Transactions on Software Engineering*, 34(1): 5–20, 2008. doi:10.1109/TSE.2007.70746.

[7] Lee A. Bygrave. Data protection by design and by default: Deciphering the EU's legislative requirements. *Oslo Law Review*, 4(2):105–120, 2017. doi:10.18261/issn.2387-3299-2017-02-03.

[8] Commission Nationale de l'Informatique et des Libertés. Cookies placed without consent: SHEIN fined 150 million euros by the CNIL. https://www.cnil.fr/en/cookies-placed-without-consent-shein-fined-150-million-euros-cnil, 2025. Deliberation SAN-2025-005 (casebook F-18).

[9] Cybersecurity and Infrastructure Security Agency. Widespread supply chain compromise impacting npm ecosystem. https://www.cisa.gov/news-events/alerts/2025/09/23/widespread-supply-chain-compromise-impacting-npm-ecosystem, 2025. Casebook F-13.

[10] Matthew Dahl, Varun Magesh, Mirac Suzgun, and Daniel E. Ho. Large legal fictions: Profiling legal hallucinations in large language models. *Journal of Legal Analysis*, 16(1):64–93, 2024. doi:10.1093/jla/laae003.

[11] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. arXiv:2406.13352, 2024.

[12] Junquan Deng, Zhiyu Fan, and Ruijie Meng. Understanding the (in)security of vibe-coded applications. arXiv:2606.23130, 2026.

[13] Mina Deng, Kim Wuyts, Riccardo Scandariato, Bart Preneel, and Wouter Joosen. A privacy threat analysis framework: Supporting the elicitation and fulfillment of privacy requirements. *Requirements Engineering*, 16(1):3–32, 2011. doi:10.1007/s00766-010-0115-7. Online first 2010.

[14] European Parliament and Council of the European Union. Regulation (EU) 2016/679 of 27 April 2016 (General Data Protection Regulation). https://eur-lex.europa.eu/eli/reg/2016/679/oj, 2016.

[15] European Parliament and Council of the European Union. Directive (EU) 2023/2673 of 22 November 2023 amending directive 2011/83/EU as regards financial services contracts concluded at a distance and repealing directive 2002/65/EC. https://eur-lex.europa.eu/legal-content/EN/TXT/HTML/?uri=CELEX:32023L2673, 2023. Article 11a of Directive 2011/83/EU, the withdrawal function, applies from 19 June 2026.

[16] European Parliament and Council of the European Union. Regulation (EU) 2024/1689 of 13 June 2024 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act). https://eur-lex.europa.eu/eli/reg/2024/1689/oj, 2024.

[17] Yujia Fu, Peng Liang, Amjed Tahir, Zengyang Li, Mojtaba Shahin, Jiaxin Yu, and Jinfu Chen. Security weaknesses of Copilot-generated code in GitHub projects: An empirical study. *ACM Transactions on Software Engineering and Methodology*, 34(8):1–34, 2025. doi:10.1145/3716848.

[18] GitHub. Spec kit. https://github.com/github/spec-kit, 2026.

[19] GitHub Advisory Database. CVE-2025-29927: Authorization bypass in Next.js middleware. https://github.com/advisories?query=CVE-2025-29927, 2025. Rated critical.

[20] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, pages 79–90. ACM, 2023. doi:10.1145/3605764.3623985.

[21] Sirui Hong, Mingchen Zhuge, Jiaqi Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, et al. MetaGPT: Meta programming for a multi-agent collaborative framework. arXiv:2308.00352, 2023.

[22] Illinois General Assembly. Biometric information privacy act, 740 ILCS 14/15: Retention; collection; disclosure; destruction. https://www.ilga.gov/Documents/legislation/ilcs/documents/074000140K15.htm, 2008.

[23] Xue Jiang, Yihong Dong, Lecheng Wang, Zheng Fang, Qiwei Shang, Ge Li, Zhi Jin, and Wenpin Jiao. Self-planning code generation with large language models. *ACM Transactions on Software Engineering and Methodology*, 33(7):1–30, 2024. doi:10.1145/3672456.

[24] Muhammad Tufail Khan. Bansat documentation site. https://bewithkhan.github.io/bansat/, 2026.

[25] Muhammad Tufail Khan. Bansat: A blueprint-first framework for building software. https://github.com/bewithkhan/bansat, 2026. Version 3.1.0. Text CC BY 4.0, code MIT.

[26] Raphaël Khoury, Anderson Raymundo Avila, Jacob Brunelle, and Baba Mamadou Camara. How secure is code generated by ChatGPT? In *2023 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, pages 2445–2451. IEEE, 2023. doi:10.1109/SMC53992.2023.10394237.

[27] Alexandra Klymenko, Oleksandr Kosenkov, Stephen Meisenbacher, Parisa Elahidoost, Daniel Mendez, and Florian Matthes. Understanding the implementation of technical measures in the process of data privacy compliance: A qualitative study. In *Proceedings of the 16th ACM/IEEE International Symposium on Empirical Software Engineering and Measurement (ESEM)*, pages 261–271. ACM, 2022. doi:10.1145/3544902.3546234.

[28] Oleksandr Kosenkov, Michael Unterkalmsteiner, Daniel Mendez, and Davide Fucci. Vision for an artefact-based approach to regulatory requirements engineering. In *Proceedings of the 15th ACM/IEEE International Symposium on Empirical Software Engineering and Measurement (ESEM)*, pages 1–6. ACM, 2021. doi:10.1145/3475716.3484191.

[29] Landgericht München I. Endurteil vom 20.01.2022, Az. 3 O 17493/20 (Google Fonts). `https://www.gesetze-bayern.de/Content/Document/Y-300-Z-BECKRS-B-2022-N-612`, 2022.

[30] Xiangyi Li, Yimin Liu, Wenbo Chen, Bingran You, Zonglin Di, Yifeng He, Shenghan Zheng, Kyoung Whan Choe, Jiankai Sun, Shuyi Wang, et al. SkillsBench: Benchmarking how well agent skills work across diverse tasks. arXiv:2602.12670, 2026.

[31] Zhiyuan Li, Jingzheng Wu, Xiang Ling, Xing Cui, and Tianyue Luo. Towards secure agent skills: Architecture, threat taxonomy, and security analysis. arXiv:2604.02837, 2026.

[32] Yi Liu, Weizhe Wang, Ruitao Feng, Yao Zhang, Guangquan Xu, Gelei Deng, Yuekang Li, and Leo Yu Zhang. Agent skills in the wild: An empirical study of security vulnerabilities at scale. arXiv:2601.10338, 2026.

[33] Varun Magesh, Faiz Surani, Matthew Dahl, Mirac Suzgun, Christopher D. Manning, and Daniel E. Ho. Hallucination-free? Assessing the reliability of leading AI legal research tools. *Journal of Empirical Legal Studies*, 22(2):216–242, 2025. doi:10.1111/jels.12413.

[34] Srinivas Rao Marri. Constitutional spec-driven development: Enforcing security by construction in AI-assisted code generation. arXiv:2602.02584, 2026.

[35] Célestin Matte, Nataliia Bielova, and Cristiana Santos. Do cookie banners respect my choice? Measuring legal compliance of banners from IAB Europe's transparency and consent framework. In *2020 IEEE Symposium on Security and Privacy (SP)*, pages 791–809. IEEE, 2020. doi:10.1109/SP40000.2020.00076.

[36] Midas Nouwens, Ilaria Liccardi, Michael Veale, David Karger, and Lalana Kagal. Dark patterns after the GDPR: Scraping consent pop-ups and demonstrating their influence. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, pages 1–13. ACM, 2020. doi:10.1145/3313831.3376321.

[37] Paul N. Otto and Annie I. Antón. Addressing legal requirements in requirements engineering. In *15th IEEE International Requirements Engineering Conference (RE 2007)*, pages 5–14. IEEE, 2007. doi:10.1109/RE.2007.65.

[38] OWASP Foundation. OWASP application security verification standard (ASVS). `https://owasp.org/projects/asvs`, 2026. Version 5.0.0 listed as stable.

[39] OWASP Gen AI Security Project. LLM10:2025 unbounded consumption. `https://genai.owasp.org/llmrisk/llm102025-unbounded-consumption/`, 2024. Part of the OWASP Top 10 for LLM Applications 2025.

[40] Matt Palmer. Statement on CVE-2025-48757. `https://mattpalmer.io/posts/2025/05/statement-on-CVE-2025-48757/`, 2025. Casebook F-01.

[41] Hammond A. Pearce, Baleegh Ahmad, Benjamin Tan, Brendan Dolan-Gavitt, and Ramesh Karri. Asleep at the keyboard? Assessing the security of GitHub Copilot's code contributions. In *2022 IEEE Symposium on Security and Privacy (SP)*, pages 754–768. IEEE, 2022. doi:10.1109/SP46214.2022.9833571.

[42] Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. arXiv:2211.09527, 2022.

[43] Neil Perry, Megha Srivastava, Deepak Kumar, and Dan Boneh. Do users write more insecure code with AI assistants? In *Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security (CCS)*, pages 2785–2799. ACM, 2023. doi:10.1145/3576915.3623157.

[44] Greg Pollock. Everything everywhere: Systemic data exposure in Supabase apps. `https://www.upguard.com/blog/everything-everywhere-systemic-data-exposure-in-supabase-apps`, 2026. UpGuard (casebook F-03).

[45] Chen Qian, Wei Liu, Hongzhang Liu, Nuo Chen, Yufan Dang, Jiahao Li, Cheng Yang, Weize Chen, Yusheng Su, Xin Cong, et al. ChatDev: Communicative agents for software development. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15174–15186, 2024. doi:10.18653/v1/2024.acl-long.810.

[46] SaaStr. Replit's new release addressed most of the challenges we hit vibe coding. But is 'prosumer' vibe coding really ready for commercial apps yet? `https://www.saastr.com/replits-new-release-address-most-of-the-challenges-we-hit-vibe-coding-but-is-prosumer-vibe-coding-really-ready-for-commercial-apps-yet/`, 2025. Casebook F-04.

[47] June Sallou, Thomas Durieux, and Annibale Panichella. Breaking the silence: The threats of using LLMs in software engineering. In *Proceedings of the 2024 ACM/IEEE 44th International Conference on Software Engineering: New Ideas and Emerging Results (ICSE-NIER)*, pages 102–106. ACM, 2024. doi:10.1145/3639476.3639764.

[48] Adam Shostack. *Threat Modeling: Designing for Security*. Wiley, Indianapolis, IN, 2014. ISBN 978-1-118-80999-0.

[49] Sarah Spiekermann. The challenges of privacy by design. *Communications of the ACM*, 55(7):38–40, 2012. doi:10.1145/2209249.2209263.

[50] Barak Sternberg and Nevo Poran. One fake bug report hijacked a $250 billion company's AI agent – then 100+ more. `https://tenetsecurity.ai/blog/agentjacking-coding-agents-with-fake-sentry-errors/`, 2026. Tenet Security (casebook F-07).

[51] Mark Vero, Niels Mündler, Victor Chibotaru, Veselin Raychev, Maximilian Baader, Nikola Jovanović, Jingxuan He, and Martin Vechev. BaxBench: Can LLMs generate correct and secure backends? arXiv:2502.11844, 2025.

[52] Washington State Legislature. My health my data act, RCW 19.373.030: Consumer consent. https://app.leg.wa.gov/RCW/default.aspx?cite=19.373.030, 2023.

[53] Claes Wohlin, Per Runeson, Martin Höst, Magnus C. Ohlsson, Björn Regnell, and Anders Wesslén. *Experimentation in Software Engineering*. Springer, Berlin, Heidelberg, 2012. doi:10.1007/978-3-642-29044-2.

[54] World Wide Web Consortium. Web content accessibility guidelines (WCAG) 2.2. https://www.w3.org/TR/WCAG22/, 2024. W3C Recommendation, 12 December 2024.

[55] Wenjun Xiong and Robert Lagerström. Threat modeling – a systematic literature review. *Computers & Security*, 84:53–69, 2019. doi:10.1016/j.cose.2019.03.010.

[56] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10471–10506, 2024. doi:10.18653/v1/2024.findings-acl.624.

[57] Songwen Zhao, Danqing Wang, Kexun Zhang, Jiaxuan Luo, Zhuo Li, and Lei Li. Is vibe coding safe? Benchmarking vulnerability of agent-generated code in real-world tasks. arXiv:2512.03262, 2025.