

Name:

\_\_\_\_\_

\_\_\_\_\_

Student Number:

\_\_\_\_\_

Please fill in your Student Number and Name.

Student Number : \_\_\_\_\_

**University of Cape Town ~ Department of Computer Science**

**Computer Science 1015F ~ 2012**

**Test 2**

**\*\* SOLUTIONS \*\***

Question	Max	Mark	Marker
1	6		
2	8		
3	8		
3	8		
<b>TOTAL</b>	<b>30</b>		

**Marks : 30**

**Time : 40 minutes**

**Instructions:**

- a) Answer all questions.
- b) Write your answers in PEN in the spaces provided.
- c) Show all calculations where applicable.

### Question 1 [6]

The function `categorize(age)` below takes a person's age (in years) as a parameter and **returns** an age category in the range “child”, “teenager”, “adult” and “pensioner”. For example, the statement

```
print(categorize(6))
```

will display:

child

whereas

```
print(categorize(67))
```

will display:

pensioner

Complete the code for this function, below.

[6]

```
def categorize(age):  
    if age < 0: #[1]  
        return("Error")  
    elif age <= 12:  
        return("Teenager") #[1]  
    elif age <= 65:  
        return("adult") #[1]  
    elif age <= 125:  
        return("Pensioner") #[1]  
    else:  
        return("error") #[1]  
and one for “return”, not “print”
```

## Question 2 [8]

Examine the module listed below:

```
def twist(input):
    max=len(input)
    for i in range(max):
        print(input)
        input= input[-1]+input[0:max-1]

twist("Neo")
```

- (a) Explain, in general and in clear English, what the function “twist” does. [2]

*Prints the string as a box [1], shifting the input string one character along with each successive line[1]*

- (b) Write down the **exact output** of the module listed above when it is run in the Python interpreter (i.e. when you press “Run” in the Wing IDE). [3]

*Neo  
oNe  
eoN*

- (c) The function `twist` uses a `for` (definite) loop. Rewrite the function in the space below so that it **works exactly the same as before** but now uses a `while` (indefinite) loop. [3]

```
def twist(input):
#QTest2.py
def twist(input):
    end=len(input)
    i=end #[1]
    while i>0: #[1]
        print(input)
        input= input[-1]+input[0:end-1]
        i-=1 #[1]
#or equivalent working code with while loop
```

### Question 3 [8]

Examine the module listed below:

```
def mystery(word):
    output=''
    for j in word.lower():
        if j=='k' or j=='e' or j=='a' or j=='n' or j=='u':
            print("--disinfecting")
            break
        output+=j
    else:
        print("--clean")
    return output

x=mystery("Morpheus")
print(x)
y=mystery(x)
print(y)
```

(a) Explain clearly and concisely why this line in the mystery function:

```
if j=='k' or j=='e' or j=='a' or j=='n' or j=='u':
```

cannot be replaced with this line:

```
if j== 'k' or 'e' or 'a' or 'n' or u':
```

[2]

*The strings 'k', 'e', 'a' etc. all evaluate as true, so this expression will always be true.*

(b) Write down the **exact output** of this module when it is run in the Python interpreter (i.e. when you press “Run” in the Wing IDE). [6]

```
--disinfecting
morph
--clean
morph
```

#### Question 4 [8]

Answer the following questions based on the program below.

```
n = eval (input ("Enter a value:"))

left = 1
right = 1
guess = 1
while not left <= n <= right:
    length = right-left+1
    left = right+1
    right = left+length
    guess += 1

print (guess)
```

- (a) What is an equivalence class? [1]  
*set of input values for which program behaves in the same manner*
- (b) Explain, using examples, what equivalence classes can be used to test this program. [2]  
*sets of sequential integers of increasing size from 1 onwards [1,1], [2,3], [4,6], [7,10]...*
- (c) Which values in the range 0-10 are NOT candidate boundary values? [1]  
*none! all are boundary values*
- (d) For what value in the range 0-10 will this program not function correctly? Is this a syntax error or a logic error? Explain your answer. [3]  
*0 [1], logic error [0], program still has correct structure and executes but produces incorrect output [2]*
- (e) What testing technique is **better** than equivalence classes and boundary values? Explain your answer. [1]  
*Exhaustive testing, because it checks every possible input [1]*  
*or*  
*Path testing or statement coverage, because it is faster [1]*