



# Readout Chain Testing for ATLAS ITk Strip Detector

Kyle Beyer, kyle.beyer@cern.ch

Dylan Hatch, dylan.brown.hatch@cern.ch

Mentors: Richard Teuscher & Olivier Arnaez

11 Oct 2018



# Agenda

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements


# ATLAS & the Inner Detector

## ATLAS Detector

- ▶ Inner Detector
- ▶ Calorimeters
- ▶ Muon Spectrometer

## Inner Detector

- ▶ Pixel Detector (PIX)
- ▶ Semiconductor Tracker (SCT)
- ▶ Transition Radiation Tracker (TRT)



## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips



Testing Setup  
Progress & Goals

## Acknowledgements

# High Luminosity LHC & ITk Upgrades

3x increase in instantaneous luminosity!



$$\blacktriangleright L = 2 \text{e}73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7 \text{e}73 \text{ fb}^{-1} \text{ s}^{-1}$$



# High Luminosity LHC & ITk Upgrades

3x increase in instantaneous luminosity!


- $L = 2 \times 10^{33} \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7 \times 10^{33} \text{ fb}^{-1} \text{ s}^{-1}$
- More particles, more problems



# High Luminosity LHC & ITk Upgrades

3x increase in instantaneous luminosity!

$$\blacktriangleright L = 2\text{e}73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7\text{e}73 \text{ fb}^{-1} \text{ s}^{-1}$$




The inner detector has insufficient:

- ▶ radiation hardness
- ▶ granularity
- ▶ readout bandwidth
- ▶ trigger readout

# High Luminosity LHC & ITk Upgrades

**3x increase in instantaneous luminosity!**

$$\blacktriangleright L = 2e73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7e73 \text{ fb}^{-1} \text{ s}^{-1}$$




**The inner detector has insufficient:**

- radiation hardness: HL-LHC will deliver  $4000 \text{ fb}^{-1}$  integrated luminosity, ID PIX is designed for  $400 \text{ fb}^{-1}$ , ID SCT for  $700 \text{ fb}^{-1}$ , IBL for  $800 \text{ fb}^{-1}$

# High Luminosity LHC & ITk Upgrades

**3x increase in instantaneous luminosity!**

$$\blacktriangleright L = 2e73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7e73 \text{ fb}^{-1} \text{ s}^{-1}$$




**The inner detector has insufficient:**

- granularity: Increasing fluence means higher granularity is needed to maintain performance; compensate for intrinsic dead time

# High Luminosity LHC & ITk Upgrades

**3x increase in instantaneous luminosity!**

- ▶  $L = 2e73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 7e73 \text{ fb}^{-1} \text{ s}^{-1}$
- ▶ More particles, more problems




**The inner detector has insufficient:**

- ▶ readout bandwidth: HL-LHC will roughly quadruple ID designed bandwidth saturation

# High Luminosity LHC & ITk Upgrades

x10 increase in instantaneous luminosity!

- $L = 1e73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 1e74 \text{ fb}^{-1} \text{ s}^{-1}$
- More particles, more problems




The inner detector has insufficient:

- trigger readout: readout chain must accomodate much higher hardware (level 1) trigger rate, and ideally include tracking info

# High Luminosity LHC & ITk Upgrades

x10 increase in instantaneous luminosity!

- $L = 1e73 \text{ fb}^{-1} \text{ s}^{-1} \rightarrow L = 1e74 \text{ fb}^{-1} \text{ s}^{-1}$
- More particles, more problems



Goal of ITk:

Same or better performance than ID in harsh environment of HL-LHC

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout


## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements


# ITk design

- ▶ Pixel detector: 600M channels (80M in PIX): 5 barrel layers, encap system
- ▶ Strip detector: 70M channels (6M in SCT): 4 barrel layers, 6 EC rings




# ITk Strip Detector

- ▶ Stave/petal: structure, cooling, power, electrical, etc.
- ▶ Module: silicon sensor + ASIC + readout hybrid + power board
- ▶ Hybrid: Flexible PCB with Hvbrid Controller Chip (HCC) to interface w/ ASIC



# ITk Strip Detector Readout

- ▶ sensor → front-end ASIC for signal amplification shaping, & discrimination
- ▶ 10-12 ABC ASICs per hybrid; each ASIC reads out 256 ch
- ▶ Hybrid Controller Chip interfaces the stave/petal service bus & front-end ASICs



## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements

## Background


ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals


## Acknowledgements

# Current DAQ Readout Chain




A look at the fully assembled readout chain, ending in the ABC130 prototype test board.

# ATLYS Board




ATLYS is a low cost, widely available board that supports single chip, hybrid, and module tests.

# Interface Connection



The ATLYS board is connected to its interface board, VMOD-IB.

# Driver Board



Orientation of the power,  
ABC130, and ATLYS  
connections.

# ABC130 Single Chip Test Card



Test card, with connection to the driver board.

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements

# Progress & Obstacles

## Progress

- ▶ Preliminary tests with ITSDAQ software
- ▶ Able to run correct versions of NI-VISA, NI-DAQMX Base, and NI-488.2 and communicate with devices

## Obstacles

- ▶ We accidentally lost a configuration and register assignment file on a formatted Windows SSD.
- ▶ We have a segmentation violation in the GUI of the ITSDAQ software.
- ▶ NI-VISA instrument control software doesn't recognize our power supplies

# Goals

- ▶ Get ITSDAQ working
- ▶ Solve NI-VISA issues and run HV controller through ITSDAQ
- ▶ Integrate FELIX chip (optical, rad-hardened comm protocol drivers) into readout chain

## Background

ATLAS & the Inner Detector  
HL-LHC & ITk  
ITk Design and Readout

## Lab Testing of Hybrid Chips

Testing Setup  
Progress & Goals

## Acknowledgements

# Acknowledgements

We would like to acknowledge the University of Michigan Department of Physics, specifically Jean Krisch, Tom Schwarz, and Steven Goldfarb. We would also like to acknowledge the support of the Lounsbury foundation.





**[www.cern.ch](http://www.cern.ch)**