1. INSERT adds rows

- INSERT INTO table VALUES (...)
- One value per column, in order
- Text in 'single quotes', numbers without

```
INSERT INTO books VALUES (9, 'The BFG',
'Roald Dahl', 1982, 'Fantasy', 208);
SELECT title FROM books WHERE id = 9;
```

title
The BFG

2. UPDATE changes rows

- UPDATE table SET column = value
- ALWAYS add WHERE
- Check first with a SELECT

```
SELECT member_id, name, email
FROM members WHERE member_id = 2;
```

member_id	name	email
2	Ben	NULL

No WHERE = every row changes!

3. DELETE removes rows

- DELETE FROM table WHERE …
- Run the same WHERE with SELECT first
- Use the unique ID to be safe

```
SELECT * FROM loans
WHERE loan_id = 8;
```

loan_id	book_id	member_id	loan_date	return_date
8	5	4	2026-05-15	NULL

4. CREATE TABLE with rules

- Each column: name + data type
- PRIMARY KEY, FOREIGN KEY (REFERENCES)
- NOT NULL and UNIQUE keep bad data out
- ALTER changes a table, DROP removes it

5. Practice free + what's next

- sqliteonline.com, db-fiddle.com, sqlime.org (choose SQLite)
- Your playground is a safe place to practice changes
- Mess up? Just run the setup again
- Next, Part 6: window functions