Tutorial II.IV - Loops

Applied Optimization with Julia



Introduction

Imagine you need to do the same task many times - like sending emails to 100 people or counting from 1 to 10. Instead of writing the same code over and over, we use loops! Loops are like having a helpful assistant who can repeat tasks for you.

Follow the instructions, input your code in the designated areas, and verify your implementations with `@assert` statements.

Section 1 - For Loops

A `for` loop is like giving instructions to that assistant: “For each item in this list, do this task.” For example:

Iterating over a range (1 to 3):

```
for i in 1:3
    println(i)
end
```

```
1
2
3
```

This prints `1`, `2`, and `3`.

Iterating over an array:

```
fruits = ["apple", "banana", "cherry"]
for fruit in fruits
    println(fruit)
end
```

```
apple
banana
cherry
```

This prints each fruit in the `fruits` array.

Sometimes we only want to run code **if** a certain condition is true. For this, we can use an `if` statement. It checks a condition (like the comparisons from the previous tutorial) and only runs the code inside if that condition is `true`. For example:

```
number = 7
if number > 5
    println("The number is larger than 5!")
end
```

```
The number is larger than 5!
```

The `break` statement can be utilized to exit the loop based on a condition. For example:

```
for x in 1:10
    println(x)
    if x == 4
        break
    end
end
```

```
1
2
3
4
```

This exits the loop in iteration `4`, as the condition `x == 4` is true here.

We can also chain conditions with `elseif` and `else`. Julia checks the conditions from top to bottom and runs the first block whose condition is `true`. If no condition is `true`, it runs the `else` block. For example:

```
for x in 1:10
    if x <= 2
        println(x)
    elseif x == 3
        println("We reached 3!")
    else
        break
    end
end
```

```
1
2
We reached 3!
```

This prints `1`, then `2`, then `We reached 3!`. Afterwards the loop ends, as the `break` statement kicks in.

> **Tip**
> Think of a `for` loop like a recipe:
>
> 1. Start with a collection of items (like numbers 1-10 or a shopping list)
> 2. For each item, follow the instructions inside the loop
> 3. When done with one item, move to the next
> 4. Stop when you've used all items (or when told to break)

> **Running the Tutorial as a Script?**
> When you run the cells one by one in Zed, the following exercises work exactly as described. But if you download this tutorial as a `.jl` file and run the whole file as a script (for example with `julia tutorial-02-04-loops.jl`), Julia is stricter: to change a variable that was created **outside** a loop from **inside** the loop, you have to write `global` in front of it. Otherwise, Julia treats it as a new variable inside the loop, and you get a warning and an `UndefVarError`. For example:
>
> ```
> sum_numbers = 0
> for i in 1:5
>     global sum_numbers = sum_numbers + i
> end
> ```
>
> This applies to all exercises in this tutorial where you change a variable inside a loop. The examples in the next section already include `global` where it is needed, so they work in both settings.

Exercise 1.1 - Sum the Numbers from 1 to 5

Sum the numbers from `1` to `5` in a loop. The next lines initialize `sum_numbers` to `0`. The sum you compute should accumulate in this variable.

```
sum_numbers = 0
# YOUR CODE BELOW
```

```
# Test your answer
@assert sum_numbers == 15
println("Sum of numbers from 1 to 5: ", sum_numbers)
```

Exercise 1.2 - Sum Only the Even Numbers from 1 to 10

Sum only the even numbers from `1` to `10`. Again, we initialize a variable `sum_evens` to `0`. The sum you compute should accumulate in this variable.

```
sum_evens = 0
# YOUR CODE BELOW
```

```
# Test your answer
@assert sum_evens == 30
println("Sum of even numbers from 1 to 10: ", sum_evens)
```

> **Tip**
> Hint: You can use the modulo operator `%` to check if a number is even. The modulo operator returns the remainder of the division of two numbers. If a number is divisible by another number, the remainder is `0`. The following example checks if `4` is even: `4 % 2 == 0`.

Exercise 1.3 - Exit the Loop if the Current Fruit is Banana

Iterate over each fruit in the `fruits` array, store the current fruit in `current_fruit`, and exit the loop if `current_fruit` is `"banana"`. The next lines initialize the `fruits` array and `current_fruit` variable.

```
fruits = ["apple", "banana", "cherry"]
current_fruit = "None"
# YOUR CODE BELOW
```

```
# Test your answer
@assert current_fruit == "banana"
println("The current fruit is: ", current_fruit)
```

Section 2 - While Loops

A `while` loop is like giving instructions to your assistant: “Keep doing this task as long as this condition is true.” They’re particularly useful when the number of iterations is dynamic or unknown in advance. For example:

```
# Keep subtracting 1 until we get below 5
number = 10
while number >= 5
    println("Number is: $number")
    global number = number - 1
end
println("Final number: $number")
```

```
Number is: 10
Number is: 9
Number is: 8
Number is: 7
Number is: 6
```

```
Number is: 5
Final number: 4
```

Real-world examples:

```
# Keep playing game while player has lives
lives = 3
while lives > 0
    println("Playing game... Lives left: $lives")
    global lives = lives - 1
end
println("Game Over!")
```

```
Playing game... Lives left: 3
Playing game... Lives left: 2
Playing game... Lives left: 1
Game Over!
```

```
# Keep filling water bucket until full
current_liters = 0
bucket_size = 5
while current_liters < bucket_size
    println("Adding 1 liter...")
    global current_liters = current_liters + 1
end
println("Bucket is full!")
```

```
Adding 1 liter...
Adding 1 liter...
Adding 1 liter...
Adding 1 liter...
Adding 1 liter...
Bucket is full!
```

> **Tip**
> Think of a `while` loop like these everyday situations:
>
> - Keep studying WHILE you don't understand the topic
> - Keep adding ingredients WHILE the recipe isn't complete
> - Keep saving money WHILE you don't have enough

Exercise 2.1 - Subtract from 10 in Increments of 1 Until the Result is Less Than 3

Subtract from `10` in increments of `1` until the result is less than `3`. The next line initializes `current_value` to `10`. The result should be in this variable.

```
current_value = 10
# YOUR CODE BELOW
```

```
# Test your answer
@assert current_value == 2
println("The first value smaller than 3 is: ", current_value)
```

Exercise 2.2 - Find the First Multiple of 7 Greater Than 50

Find the first multiple of `7` greater than `50` using an indefinite loop. The next line initializes `first_multiple_of_7` to `0`. The first multiple should be in this variable.

```
first_multiple_of_7 = 0
# YOUR CODE BELOW
```

```
# Test your answer
@assert first_multiple_of_7 == 56
println("First multiple of 7 greater than 50: ", first_multiple_of_7)
```

> **Tip**
> 'while true ... end' constructs an infinite loop. You can exit the loop using a 'break' statement if a condition is met.

Section 3 - Nested Loops

Nested loops are loops inside other loops. Think of it like organizing your closet: - First loop: Go through each shelf - Second loop: For each shelf, go through each item

```
# Checking sizes and colors of t-shirts
sizes = ["Small", "Medium", "Large"]
colors = ["Red", "Blue"]

for size in sizes
    for color in colors
        println("Found $color t-shirt in size $size")
    end
end
```

```
Found Red t-shirt in size Small
Found Blue t-shirt in size Small
Found Red t-shirt in size Medium
Found Blue t-shirt in size Medium
```

```
Found Red t-shirt in size Large
Found Blue t-shirt in size Large
```

Exercise 3.1 - Compute the Product of Each Pair of Elements from Two Arrays

Compute the product of **each pair of elements** from two arrays. For example, the product of two numbers `a` and `b` is `a * b`. The next lines initialize `numbers1`, `numbers2` arrays, and the `products` array to store your results.

```
numbers1 = [1, 2, 3]
numbers2 = [4, 5, 6]
products = Int[]
# YOUR CODE BELOW
```

```
# Test your answer
@assert products == [4, 5, 6, 8, 10, 12, 12, 15, 18]
println("Products of each pair from two arrays: ", products)
```

> **Tip**
> Remember, you can use push!() to append elements to an array. Loop over `numbers1` in the outer loop and over `numbers2` in the inner loop, so your products appear in the expected order. By the way: `Int[]` creates an empty array that can only hold integers - this is better practice than a plain `[]`, which can hold anything.

Section 4 - List Comprehensions

List comprehensions provide a concise way to create lists based on existing lists. They can often replace for loops and are considered more “Julia-like”. Basic syntax:

```
[expression for item in collection if condition]
```

For example:

```
# The long way
squares = []
for n in 1:5
    push!(squares, n^2)
end

# The short way (list comprehension)
squares = [n^2 for n in 1:5]
```

Both create `[1, 4, 9, 16, 25]`, but the second way is more concise!

> **Note**
> This syntax is worth learning well: later in the course, we will use almost the same pattern to define sums and constraints in optimization models with JuMP, for example `sum(x[i] for i in 1:10)`.

Exercise 4.1 - Create a List of Even Numbers

Create a list of even numbers from 1 to 10 using a list comprehension and store it in `even_numbers`.

```
# YOUR CODE BELOW
```

```
# Test your answer
@assert even_numbers == [2, 4, 6, 8, 10]
println("Even numbers from 1 to 10: ", even_numbers)
```

Conclusion

Great work! You've successfully navigated through the basics of loops in Julia. You've seen for and while loops, tackled iterable structures, and worked on nested loops. Continue to the next file to learn more.

Solutions

You will likely find solutions to most exercises online. However, I strongly encourage you to work on these exercises independently without searching explicitly for the exact answers to the exercises. Understanding someone else's solution is very different from developing your own. Use the lecture notes and try to solve the exercises on your own. This approach will significantly enhance your learning and problem-solving skills.

Remember, the goal is not just to complete the exercises, but to understand the concepts and improve your programming abilities. If you encounter difficulties, review the lecture materials, experiment with different approaches, and don't hesitate to ask for clarification during class discussions.

Bibliography