Lecture VII - Pandas and AI

Programming with Python

Dr. Tobias Vlćek

Quick Recap of the last Lecture

What is NumPy?

- · NumPy is a package for scientific computing in Python
- · Provides multi-dimensional arrays and matrices
- · Much faster than Python lists for numerical operations
- Operations are implemented in C and C++



Tip

NumPy arrays are stored in contiguous memory blocks, making operations very efficient.

Creating Arrays

- Core data structure is the ndarray
- · Can create arrays from lists, tuples, or other data structures
- · Special functions like:
 - np.zeros() for arrays of zeros
 - np.random.rand() for random values
 - np.arange() for evenly spaced values
 - np.linspace() for linearly spaced values

Working with Arrays

- Support for multi-dimensional operations
- · Common operations:
 - Element-wise arithmetic (+, -, *, /)
 - Array indexing and slicing
 - Shape manipulation (reshape, flatten)
 - Sorting and transposing



¶ Tip

NumPy operations are vectorized, meaning they operate on entire arrays at once rather than element by element.

Pandas Module

What is Pandas?

- Pandas is a data manipulation and analysis library
- · It provides data structures like DataFrames and Series
- · Tools for data cleaning, analysis, and visualization
- It can also be used to work with Excel files!

How to install Pandas

- In the last lecture, we have installed it with pip install pandas or with Thonny
- · Now, import the package import pandas as pd

. . .

Note

You can also use a different abbreviation, but pd is the most common one.

Creating DataFrames

- DataFrames behave quite similar to Numpy arrays
- But they have row and column labels

. . .

```
import pandas as pd
df = pd.DataFrame({ # DataFrame is created from a dictionary
    "Name": ["Tobias", "Robin", "Nils", "Nikolai"],
    "Kids": [2, 1, 0, 0],
    "City": ["Oststeinbek", "Oststeinbek", "Hamburg", "Lübeck"],
    "Salary": [3000, 3200, 4000, 2500]}); print(df)
```

```
Name Kids City Salary
O Tobias 2 Oststeinbek 3000
1 Robin 1 Oststeinbek 3200
2 Nils 0 Hamburg 4000
3 Nikolai 0 Lübeck 2500
```

Reading from CSV Files

```
df = pd.read_csv("employees.csv") # Reads the CSV file
print(df)
```

	Name	Age	Department	Position	Salary
0	Alice	30	HR	Manager	50000
1	Bob	25	IT	Developer	60000
2	Charlie	28	Finance	Analyst	55000
3	David	35	Marketing	Executive	52000
4	Eve	32	Sales	Representative	48000
5	Frank	29	IT	Developer	61000
6	Grace	31	HR	Assistant	45000
7	Hank	27	Finance	Analyst	53000
8	Ivy	33	Marketing	Manager	58000
9	Jack	26	Sales	Representative	47000
10	Kara	34	IT	Developer	62000
11	Leo	30	HR	Manager	51000
12	Mona	28	Finance	Analyst	54000
13	Nina	35	Marketing	Executive	53000
14	Oscar	32	Sales	Representative	49000
15	Paul	29	IT	Developer	63000
16	Quinn	31	HR	Assistant	46000
17	Rita	27	Finance	Analyst	52000
18	Sam	33	Marketing	Manager	59000
19	Tina	26	Sales	Representative	48000
20	Uma	34	IT	Developer	64000
21	Vince	30	HR	Manager	52000
22	Walt	28	Finance	Analyst	55000
23	Xena	35	Marketing	Executive	54000
24	Yara	32	Sales	Representative	50000
25	Zane	29	IT	Developer	65000
26	Anna	31	HR	Assistant	47000
27	Ben	27	Finance	Analyst	53000
28	${\tt Cathy}$	33	Marketing	Manager	60000
29	Dylan	26	Sales	Representative	49000
30	Ella	34	IT	Developer	66000
31	Finn	30	HR	Manager	53000
32	Gina	28	Finance	Analyst	56000
33	Hugo	35	Marketing	Executive	55000
34	Iris	32	Sales	Representative	51000
35	Jake	29	IT	Developer	67000
36	Kyla	31	HR	Assistant	48000
37	Liam	27	Finance	Analyst	54000
38	Mia	33	Marketing	Manager	61000
39	Noah	26	Sales	Representative	50000
40	Olive	34	IT	Developer	68000
41	Pete	30	HR	Manager	54000
42	Quincy	28	Finance	Analyst	57000
43	Rose	35	Marketing	Executive	56000
44	Steve	32	Sales	Representative	52000
45	Tara	29	IT	Developer	69000
46	Umar	31	HR	Assistant	49000

```
        47
        Vera
        27
        Finance
        Analyst
        55000

        48
        Will
        33
        Marketing
        Manager
        62000

        49
        Zara
        26
        Sales
        Representative
        51000
```

Basic Operations

- Use the df.head() method to display the first 5 rows
- Use the df.tail() method to display the last 5 rows

. . .

```
df = pd.read_csv("employees.csv")
print(df.tail())
```

	Name	Age	Department	Position	Salary
45	Tara	29	IT	Developer	69000
46	Umar	31	HR	Assistant	49000
47	Vera	27	Finance	Analyst	55000
48	Will	33	Marketing	Manager	62000
49	Zara	26	Sales	Representative	51000

Information about the DataFrame

• Use df.info() to display information about a DataFrame

. . .

```
df = pd.read_csv("employees.csv")
print(df.info())
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 50 entries, 0 to 49
Data columns (total 5 columns):
   Column Non-Null Count Dtype
    ----
              -----
0 Name 50 non-null object
1 Age 50 non-null int64
                              object
                           object
2 Department 50 non-null
3 Position 50 non-null
                              object
4 Salary
              50 non-null
                              int64
dtypes: int64(2), object(3)
memory usage: 2.1+ KB
None
```

Statistics about a DataFrame

- Use df.describe() to display summary statistics
- Use the df.index attribute to access the index

. .

```
df = pd.read_csv("employees.csv")
print(df.describe())
```

```
Salary
            Age
count 50.000000
                    50.000000
mean 30.320000 54980.000000
      2.958488 6175.957333
std
min
      25.000000 45000.000000
25%
    28.000000 50250.000000
50%
    30.000000 54000.000000
      33.000000 59750.000000
75%
max
      35.000000 69000.000000
```

Filtering DataFrames

- Use df ['column_name'] to access a column
- Use the df [df ['column'] > value] method to filter

. . .

```
df = pd.read_csv("employees.csv")
df_high_salary = df[df['Salary'] >= 67000]
print(df_high_salary)
print(df_high_salary.iloc[2]["Name"]) #Access the third row and the "Name" column
print(df_high_salary.loc[40]["Name"]) #Access the label 40 and the "Name" column
```

```
Age Department
    Name
                        Position Salary
35
    Jake
          29
                 IT Developer
                                   67000
40 Olive
          34
                    IT Developer
                                   68000
          29
                   IT Developer
45
    Tara
                                   69000
Tara
Olive
```

Filtering in Action

Task: Complete the following task:

```
# TODO: Load the employees.csv located in the git repository into a DataFrame
# First, filter the DataFrame for employees with a manager position
# Then, print the average salary of the remaining employees
# Finally, print the name of the employee with the lowest salary
```

. . .

i Note

Note, that we can use the mean() method on the Salary column, as it is a numeric column. In addition, we can use the min() method on the Salary column to find the lowest salary.

Grouping DataFrames

Grouping

- · Grouping is a powerful feature of Pandas
- · Groups data by one or more columns
- And then perform operations
- Syntax is df.groupby('column').method()

. .

```
df = pd.read_csv("employees.csv")
df = df.drop(columns=["Name", "Department"])
df.groupby(['Position']).mean() # Mean per position
```

Age	Salary
27.5	54400.0
	47000.0
	64500.0
	54000.0
31.5	56000.0
29.0	49500.0
	27.5 31.0 30.6 35.0 31.5

Grouping by Multiple Columns

- Group by multiple columns ['column1', 'column2']
- · You can use lists or tuples to specify multiple columns

. .

```
df = pd.read_csv("employees.csv")
df = df.drop(columns=["Name"])
# Max per position and department
df.groupby(['Position', "Department"]).max()
```

Position	Department
Analyst	Finance
Assistant	HR
Developer	IT
Executive	Marketing

Position	Department
Manager	HR Marketing
Representative	Sales

Grouping with Aggregations

· As seen, we can use aggregation functions:

sum(): sum of the valuesmean(): mean of the values

max(): maximum of the valuesmin(): minimum of the values

- count (): count of the values

Melting DataFrames

• Use pd.melt() to transform from wide to long

. .

```
df = pd.read_csv("employees.csv").drop(columns=["Name"])
df = pd.melt(df, id_vars=['Position'])
print(df.head()); print(df.tail())
```

```
Position variable value
0
         Manager
                      Age
1
       Developer
                             25
                      Age
                             28
2
         Analyst
                      Age
3
       Executive
                             35
                      Age
4 Representative
                      Age
                             32
          Position variable value
145
         Developer Salary 69000
146
         Assistant
                     Salary 49000
147
           Analyst
                     Salary 55000
148
                     Salary 62000
           Manager
    Representative
                     Salary 51000
```

Pandas in Action

Task: Complete the following task:

```
# TODO: Load the employees.csv again into a DataFrame
# First, group by the "Position" column and count the employees per position
# Then, group by the "Department" column and calculate the sum of all other columns per
    department
df = pd.read_csv("employees.csv")
# Your code here
```

. . .

Note

Do you notice any irregularities while calculating the sum per department?

Concatenating DataFrames

• pd.concat() to concatenate along shared columns

```
df1 = pd.DataFrame({"A": [1, 2, 3], "B": [4, 5, 6]})
df2 = pd.DataFrame({"A": [7, 8, 9], "B": [10, 11, 12]})
df = pd.concat([df1, df2])
print(df)

A B
0 1 4
1 2 5
2 3 6
0 7 10
1 8 11
2 9 12
```

Joining DataFrames

- Use pd.join() to join DataFrames along columns
- Joining is done on the index by default!

```
df1 = pd.DataFrame({"A": [1, 2, 3], "B": [4, 5, 6]}, index=['x', 'y', 'z'])
df2 = pd.DataFrame({"C": [7, 8, 9], "D": [10, 11, 12]}, index=['z', 'y', 'w'])
df = df1.join(df2)
print(df)
```

```
A B C D
x 1 4 NaN NaN
y 2 5 8.0 11.0
z 3 6 7.0 10.0
```

Merging DataFrames on Columns

- pd.merge(df_name, on='column', how='type')
- merge DataFrames along shared columns
- how specifies the type of merge
 - inner: rows with matching keys in both DataFrames
 - outer: rows from both are kept, missing values are filled
 - left: rows from the left are kept, missing values are filled
 - right: rows from right are kept, missing values are filled

Outer Merge

```
df3 = pd.DataFrame({"A": [1, 2, 3], "B": [4, 5, 6]})
df4 = pd.DataFrame({"A": [2, 3, 4], "C": [7, 8, 9]})
df_merged = df3.merge(df4, on="A", how="outer")
print(df_merged)

A B C
0 1 4.0 NaN
```

0 1 4.0 NaN 1 2 5.0 7.0 2 3 6.0 8.0 3 4 NaN 9.0

Working with Excel Files

Working with Excel Files

Reading Excel Files

- Read using the pd.read_excel(file_path) function
- Write using the df.to_excel(file_path) method

. . .

```
import pandas as pd
df = pd.read_csv("employees.csv")
df.to_excel("employees.xlsx", index=False)
```

. . .

i Note

Note, that you likely need to install the <code>openpyxl</code> package to be able to write Excel files, as it handles the file format.

Advanced Excel file handling

```
df = pd.read_excel("employees.xlsx")

# Writes to the Employees sheet and does not include row indices
df.to_excel("employees.xlsx", sheet_name="Employees", index=False)

# Reads from the Employees sheet
df = pd.read_excel("employees.xlsx", sheet_name="Employees")
```

. . .

Note

And that's it for todays lecture!

You now have the basic knowledge to start working with tabular data.

Literature

Interesting Books

- Downey, A. B. (2024). Think Python: How to think like a computer scientist (Third edition). O'Reilly. Link to free online version
- Elter, S. (2021). Schrödinger programmiert Python: Das etwas andere Fachbuch (1. Auflage). Rheinwerk Verlag.

. . .

For more interesting literature to learn more about Python, take a look at the literature list of this course.