Lecture V - Errors and Debugging

Programming with Python

Dr. Tobias Vlćek



Checkpoint 2

The first 40 minutes are the checkpoint. It starts now.

- **Individual work**: no AI, no neighbors, no messaging
- Slides, the cheatsheet and your own notebooks **may be open**
- The **link is on Moodle**. Open it and start
- ~6 short tasks: write code, trace code, fix a bug, answer a multiple choice
- It sweeps **Sessions III-IV**: functions, scope, classes, lists and dictionaries, comprehensions

When you're done

Cmd/Ctrl+S, then menu → *Download* → *Download Python code* → upload the `.py` to the **"Checkpoint 2"** assignment on Moodle, before the 40 minutes are up. **No retakes**: one sitting.

> **Note**
> The live checks under the tasks are **provisional**. The final grading runs on my side. Everything in it comes from Sessions III-IV.

EP 5: 3-AM Checkout

After the checkpoint

On to Episode 5.

At 3 AM, running on his fourth energy drink, Tobi rewrote the **entire checkout** "to make it faster." He went to bed very pleased. This morning two things are true: the register is a minefield of crashes, and the **health inspector** just called to announce a surprise visit.

So today the code learns to survive things going wrong. We read a **traceback**, catch failures with try/except, and let our own code refuse bad input.

Reading the Explosion

Tobi's 3-AM checkout, live

`float(...)` turns text into a number: `float("4.50")` is `4.5`. Then a customer typed `generous` into the tip box:

```
tip_text = "generous"
tip = float(tip_text) # crashes here
```

Python stopped and printed a **traceback**, a crash report. It tells you what went wrong and where:

```
Traceback (most recent call last):
  File "checkout.py", line 12, in <module>
    tip = float(tip_text)
ValueError: could not convert string to float: 'generous'
```

Read the traceback bottom-up

You read a traceback from the **bottom up**:

- the **last line** names *what* went wrong (`ValueError`) and gives a hint
- the lines **above** show *where*: the file, the line number, the guilty code

```
      File "checkout.py", line 12, in <module>   ← WHERE it happened
        tip = float(tip_text)                    ← the exact line
    ValueError: could not convert ...            ← WHAT went wrong (read me
first)
```

Two facts and you know where to go: **line 12**, and it's a **`ValueError`**. The rest of the traceback is context around those two facts.

The big five (1)

Python calls an error an **exception**, and a handful of exception types cover almost everything you'll hit. The first three:

- **`ValueError`**: right *type*, senseless *value*, as in `int("lots")`
- **`TypeError`**: the wrong type entirely, like `"Bowl " + 9`
- **`KeyError`**: a dictionary key that isn't there (`table_map["C3"]`)

Each one is Python refusing to guess. `int("lots")` has no sensible number; `"Bowl " + 9` mixes text and a number; `table_map["C3"]` asks for a key that was never added.

Predict: comma or point?

A regular from Hamburg types the price the German way. What happens when this runs?

```
price_text = "5,50"
price = float(price_text)
print(price)
```

a) prints `5.5` as a float
b) raises `ValueError`
c) raises `TypeError`

Answer: right type, senseless value

```
price_text = "5,50"
price = float(price_text)
print(price)
```

```
ValueError: could not convert string to float: '5,50'
[31m---------------------------------------------------------------------------[39m
[31mValueError[39m                                Traceback (most recent call last)
[36mCell[39m[36m [39m[32mIn[1][39m[32m, line 2[39m
[32m      1[39m price_text = [33m"[39m[33m5,50[39m[33m"[39m
[32m----> [39m[32m2[39m price = [38;5;28mfloat[39;49m([49m[43mprice_text[49m[43m)[49m
[32m      3[39m [38;5;28mprint[39m(price)

[31mValueError[39m: could not convert string to float: '5,50'
```

b) raises `ValueError`: `float()` got what it expects, a string, so the *type* is fine. But `"5,50"` is not a number Python can read (it only knows the decimal point), so the *value* is refused. `TypeError` would need a non-string, like `float(None)`.

The big five (2)

The other two you'll meet constantly:

- **`IndexError`**: a list position past the end, like `seats[9]` on a 3-item list
- **`ZeroDivisionError`**: dividing by zero, as in `88.00 / 0` when splitting a bill among no guests

You don't have to memorize all of Python's exceptions. Recognize these five on sight, and read the last line for the rest.

Your turn

Open the exercise

Scan the QR or type the link:

python.tobiasvlcek.com/notebooks/ex_05_a/



Any questions? Let me know!

`try` / `except`: catch the fall

First, the happy path: text that **looks** like a number converts cleanly; text that doesn't, explodes. A **`try` / `except`** block runs the risky code and catches the failure instead of stopping the program:

```
print(float("5.50"))          # numeric text converts cleanly → 5.5

try:
    tip = float("generous")   # non-numeric text raises ValueError...
except ValueError:
    tip = 0.0                 # ...caught here, so the checkout keeps going

print(tip)


5.5
0.0
```

The risky line goes in the `try`; the recovery goes in the `except`. No crash. The program lands in the `except` and carries on.

Catch the *specific* type

Name the exact exception you expect. `except ValueError:` catches **only** value errors and lets anything else through:

```
try:
    tip = float(tip_text)
```

```
except ValueError:            # only this kind
    tip = 0.0
```

> ⚠ **Warning**
> A **bare** `except:` catches *everything*, including your own typos (a misspelled variable would vanish silently). Catch the **specific** type, so real bugs still surface.

Predict: which explosion?

Tobi builds a table label. `guests` is the number `3`. What happens when this runs?

```
guests = 3
label = "Party of " + guests
print(label)
```

a) raises `TypeError`
b) prints `Party of 3`
c) raises `ValueError`

Answer: text plus number fails

```
guests = 3
try:
    label = "Party of " + guests
except TypeError as e:
    print("TypeError:", e)
```

```
TypeError: can only concatenate str (not "int") to str
```

a) raises `TypeError`: `+` can glue two strings *or* add two numbers, but it refuses to mix a string and an `int`. The fix is to convert first (`str(guests)`).

`as e` keeps the error object in a variable, so you can print its message instead of losing it. Any name works; `e` is the habit.

Your turn

Open the exercise

Scan the QR or type the link:

python.tobiasvlcek.com/notebooks/ex_05_b/



Any questions? Let me know!

Debug and Defend

The debugging loop

When something is wrong, you don't guess randomly. You follow a loop:

1. **Read** the traceback: it hands you the *what* and the *where*
2. **Reproduce** the crash: make it happen on demand
3. **Isolate**: narrow down to the smallest failing piece
4. **Fix**: change one thing, then run again

Find the broken thing, make it repeat, corner it, fix it. Panic is not a step.

`print()`: the beginner's help

The simplest debugger is a well-placed `print()`. When you can't see what a value *is*, shine a light on it:

```
def line_total(qty, price):
    print("DEBUG qty =", qty, "price =", price)   # the help
    return round(qty * price, 2)

print(line_total(3, 5.50))
```

```
DEBUG qty = 3 price = 5.5
16.5
```

Real debuggers with breakpoints exist and are wonderful, but a `print()` in the right spot solves most beginner bugs in seconds. Remove it once you've seen enough.

`raise`: when your code should refuse

Sometimes *your own* code should reject bad input on the spot. The inspector's rule is non-negotiable: **every price ≥ 0**. `raise` throws an error deliberately:

```
def charge(amount):
    if amount < 0:
        raise ValueError("price cannot be negative")
    return amount

try:
    charge(-4.50)                  # your code refuses it...
except ValueError as e:
    print("refused:", e)           # ...on your terms


refused: price cannot be negative
```

A bad value stops *here*, instead of poisoning the program three screens later.

`assert`: a tripwire for invariants

An **`assert`** guards an *invariant*, a fact that must **always** hold. If it's true, nothing happens; if it's false, the program stops right there with an `AssertionError`:

```
subtotal = 9.60
assert subtotal >= 0, "subtotal went negative: bug upstream"
print("passed the tripwire:", subtotal)


passed the tripwire: 9.6
```

Think of it as a note to yourself, checked automatically: *"if this is ever false, something broke earlier. Stop before it spreads."*

Predict: does the `print` survive?

The bill is being split, but nobody is at the table. What shows up?

```
guests = 0
assert guests > 0, "no guests at the table"
print("splitting the bill among", guests)
```

a) `AssertionError`, and the `print` never runs
b) prints `splitting the bill among 0`
c) the message, then the `print` line as well

Answer: the tripwire stops it all

```
guests = 0
assert guests > 0, "no guests at the table"
print("splitting the bill among", guests)
```

```
AssertionError: no guests at the table
[31m---------------------------------------------------------------------------[39m
[31mAssertionError[39m                            Traceback (most recent call last)
[36mCell[39m[36m [39m[32mIn[7][39m[32m, line 2[39m
[32m      1[39m guests = [32m0[39m
[32m----> [39m[32m2[39m [38;5;28;01massert[39;00m guests >
[32m0[39m, [33m"[39m[33mno guests at the table[39m[33m"[39m
[32m      3[39m [38;5;28mprint[39m([33m"[39m[33msplitting the bill among[39m[33m"[39m, guests)

[31mAssertionError[39m: no guests at the table
```

a) `AssertionError`, and the `print` never runs: a failing `assert` raises on the spot, and nothing after it in the program executes. That's the point of a tripwire: stop *before* a wrong number spreads.

Try, then fall back

A friendly, common pattern: **try** the risky thing; if it fails, **fall back** to a sensible default so the program keeps moving.

```
def seats(text):
    try:
        return int(text)
    except ValueError:
        return 2                # a table seats two, unless told otherwise

print(seats("6"))               # a clean number → 6
print(seats("full"))            # nonsense → the safe default, 2
```

```
6
2
```

The caller never sees a crash. Garbage in, sane default out. Not every check needs a `try`: `isinstance(x, (int, float))` answers *is this a number?* with `True`/`False`, so an `if` skips bad values first.

Predict: after the `except`?

`to_price` catches a bad value and returns `0.0`. After that, does the program reach the **next line**?

```
def to_price(text):
    try:
        return float(text)
    except ValueError:
        return 0.0

print(to_price("bad"))
print("checkout still running")
```

a) it never runs: the program already stopped
b) the `try` block runs a second time
c) it runs normally: the program carried on

Answer: it carries on

```
def to_price(text):
    try:
        return float(text)
    except ValueError:
        return 0.0

print(to_price("bad"))           # 0.0, recovered
print("checkout still running")  # ...and we get here


0.0
checkout still running
```

c) it runs normally. That's the whole point of `try` / `except`. It *handles* the failure; once the `except` has run, control simply drops to the code after it, as if nothing had gone wrong.

Your turn

Open the exercise

Scan the QR or type the link:

python.tobiasvlcek.com/notebooks/ex_05_c/

Any questions? Let me know!

To the Lab

After the break: the lab

- Head to the lab notebook: Episode 5: The 3-AM Checkout
- You'll read a traceback, write a price box that won't crash, fix Tobi's 3-AM receipt, make your code **refuse** negative prices with `raise`, and harden the whole checkout against a batch of poisoned orders
- It runs entirely in your browser: no setup, just click and code

> ! **Important**
> **Download your `.py` before you leave.** Closing the tab without downloading loses your work, and downloading is exactly how you just handed in the checkpoint. Expect **red cells** in this lab: you'll cause errors on purpose. A red cell pauses everything below it. Fix it, and everything springs back.

Wrap-up

Three things to remember

1. A **traceback** is a crash report you read **bottom-up**: the last line names *what* broke, the lines above show *where*
2. **`try`** / **`except`** catches a failure so the program recovers instead of stopping. Catch the specific type (`except ValueError`), never a bare `except` that also hides your own typos
3. Defend your own code: **`raise`** to refuse bad input (prices ≥ 0), **`assert`** to guard invariants, and a safe default if a conversion fails

> **Note**
> **Next time, Episode 6** starts with **Checkpoint 3**: 40 minutes, **still no AI**, everything from Sessions I-V. Slides, the cheatsheet and your own notebooks may be open. Then someone new walks into the shop, uncaps a marker, and writes one question on the whiteboard. Part II begins.

Literature

Books to start with

> **Note**
> Nothing new here, but these are still great books to start with!

For more, see the literature list of this course.

Bibliography