

# Lecture II - Control Structures for Your Code

## Programming with Python

Dr. Tobias Vlček

Kühne Logistics University Hamburg - Fall 2026

### Episode 2: The Curfew

#### A decree from the city

Overnight the city banned delivery after **22:00**. Your app can no longer just say yes to every order. Today the code starts making decisions, repeating work over every order, and tidying up Tobi's menu.

...

(Tobi's fix: "we just deliver yesterday's orders the next morning." A lawyer disagreed.)

#### Warm-up

Three questions from Episode 1. Commit. Hands up **before** the reveal.

#### Question 1

```
price = 8.90
print(f"{price * 2:.2f}")
```

a) 17.8 b) 17.80 c) Error

#### Answer 1

b): `:.2f` always prints two decimals. That's the whole receipt trick.

#### Question 2

```
print(type("9.99"))
```

a) float b) int c) str

#### Answer 2

c): quotes make it text, no matter how numeric it looks. (Tobi learned this the hard way.)

#### Question 3

```
print(7 // 2, 7 % 2)
```

a) 3.5 1 b) 3 1 c) 3 0.5

## Answer 3

b): `//` floors, `%` gives the remainder. Together: “how many fit, what’s left.”

## Making Decisions

### Asking a yes/no question

A **comparison** asks a question and answers with a **boolean**: `True` or `False`, the `bool` type you met last week:

```
delivery_hour = 21
print(delivery_hour < 22)    # before curfew?
print(delivery_hour == 22)   # exactly at curfew?
```

```
True
False
```

### The comparison operators

Six operators, all returning `True` or `False`:

- `<` less than · `>` greater than
- `<=` at most · `>=` at least
- `==` equal · `!=` not equal

...

#### ⚠ Warning

`=` **assigns** a value; `==` **compares** two values. Mixing them up is the classic first-week bug.

### Combining conditions

`and`, `or`, `not` glue booleans together:

```
is_weekday = True
before_curfew = 21 < 22
print(is_weekday and before_curfew)    # both must be True
```

```
True
```

...

`and` needs **both** sides true; `or` needs **at least one**; `not` flips it.

### `if`: do something only when

An `if` runs its indented block **only** when the condition is `True`:

```
delivery_hour = 21
if delivery_hour < 22:
    print("Open: send the courier.")
```

```
Open: send the courier.
```

...

The **indentation** (4 spaces) is what marks the block. Python is strict about it.

### **if / else: two paths**

**else** catches every case the **if** missed:

```
delivery_hour = 23
if delivery_hour < 22:
    print("Open: send the courier.")
else:
    print("Curfew: kitchen closed.")
```

```
Curfew: kitchen closed.
```

### **if / elif / else: a ladder**

More than two cases? Stack **elif** branches. Reward loyal customers by tier:

```
past_orders = 8
if past_orders >= 20:
    tier = "Gold"
elif past_orders >= 5:
    tier = "Silver"
else:
    tier = "Bronze"
print(tier)
```

```
Silver
```

### **Predict: Tobi reorders the ladder**

Tobi rewrote the tier ladder “to keep the common case on top”. A customer with **25 past orders** walks in. Which tier do they get?

```
past_orders = 25
if past_orders >= 5:
    tier = "Silver"
elif past_orders >= 20:
    tier = "Gold"
else:
```

```
tier = "Bronze"
print(tier)
```

a) Gold b) Bronze c) Silver

...

Predict first. Pick a letter, then I reveal the answer.

### Answer: the first true branch wins

c) **Silver**: Python checks branches top to bottom and takes the first **True** one. `25 >= 5` is already **True**, so the **Gold** branch is never even looked at. Order your ladder from strictest to loosest.

```
past_orders = 25
if past_orders >= 5:
    tier = "Silver"
elif past_orders >= 20:
    tier = "Gold"
else:
    tier = "Bronze"
print(tier)
```

```
Silver
```

...

(One misplaced **elif** and Tobi demotes every VIP.)

### Predict: exactly at curfew

The curfew is 22:00. An order comes in at **exactly** 22:00. What prints?

```
delivery_hour = 22
print(delivery_hour < 22)
```

a) False b) True c) Error

...

Predict first. Pick a letter, then I reveal the answer.

### Answer: `22 < 22`

a) **False**: `<` is **strict**. 22 is not *less than* 22, so at 22:00 sharp the kitchen is already closed. Use `<=` when the boundary should count.

```
delivery_hour = 22
print(delivery_hour < 22)
```

False

## Your turn — 10 minutes

Open the exercise (scan the QR or type the link):

[beyondsimulations.github.io/Introduction-to-Python/notebooks/ex\\_02\\_a/](https://beyondsimulations.github.io/Introduction-to-Python/notebooks/ex_02_a/)



First **predict** what happens, then run it.

## Doing Things Many Times

### The copy-paste pain

Tobi totals the day's orders by hand, one `print` per order:

```
print("Falafel Wrap")
print("Pad Thai")
print("Miso Ramen")
```

```
Falafel Wrap
Pad Thai
Miso Ramen
```

...

Three lines for three items. A hundred orders? A hundred lines. There is a better way.

### **for:** one step for every item

A **for** loop runs its block once for each item in a list:

```
menu = ["Falafel Wrap", "Pad Thai", "Miso Ramen"]
for item in menu:
    print(item)
```

```
Falafel Wrap
Pad Thai
Miso Ramen
```

...

`item` is the **loop variable**. It takes each value in turn, and the name is yours to choose.

## The accumulator pattern

Start a total at 0, then **add each item** as the loop visits it:

```
prices = [5.00, 3.50, 6.50]
total = 0
for price in prices:
    total = total + price
print(total)
```

```
15.0
```

...

After the loop, `total` holds the sum. This is how you replace Tobi's hand-counted dashboard.

## `range()`: count without a list

`range(n)` counts from 0 up to, but **not including**, `n`:

```
for i in range(3):
    print(i)      # ping the courier's phone 3 times
```

```
0
1
2
```

...

Three passes: 0, 1, 2. (It stops *before* 3, a beginner's favorite surprise.)

## `range()` with two and three arguments

- `range(start, stop)`: begin at `start`, stop before `stop`
- `range(start, stop, step)`: jump by `step` each time

```
print(list(range(2, 5)))      # list() shows the range as a list: 2, 3, 4
print(list(range(0, 10, 3))) # every 3rd order gets a flyer: 0, 3, 6, 9
```

```
[2, 3, 4]
[0, 3, 6, 9]
```

## Looping over a string

A string is a sequence too, and a `for` loop walks it character by character:

```
for letter in "Pad":
    print(letter)
```

```
P
a
d
```

## A loop in one line (a preview)

A **list comprehension** is a `for` loop compressed into one line that builds a list:

```
doubled = [n * 2 for n in [4, 5, 6]]
print(doubled)
```

```
[8, 10, 12]
```

...

### Note

Just a taste. Session IV gives comprehensions their proper treatment. For now: recognize the shape.

## Predict: where does `print` run?

The `print` is **not** indented. What does this show?

```
total = 0
for n in [10, 20]:
    total = total + n
print(total)
```

a) 10 b) 10 then 30 c) 30

...

Predict first, then turn the page.

### Answer: the unindented `print`

c) `30: print` sits outside the loop, so it runs once, after the loop finishes, showing the final total. Indent it and it would print on every pass. Indentation decides what repeats.

```
total = 0
for n in [10, 20]:
    total = total + n
print(total)
```

30

## Your turn — 10 minutes

Open the exercise (scan the QR or type the link):

[beyondsimulations.github.io/Introduction-to-Python/notebooks/ex\\_02\\_b/](https://beyondsimulations.github.io/Introduction-to-Python/notebooks/ex_02_b/)



First **predict** what happens, then run it.

## Repeat Until, and Clean Text

### **while:** repeat as long as

A **while** loop repeats **as long as** its condition stays **True**. Suppose MunchCorp undercuts you. Cut your price each round until you drop below their price:

```
price = 10.00
rounds = 0
while price >= 7.00:
    price = round(price * 0.8, 2)    # 20% off each round
    rounds = rounds + 1
print(rounds, price)
```

2 6.4

...

Two rounds and you're under 7.00. (The lab's price war against MunchCorp is your boss fight after the break.)

## The loop must move toward its goal

Every pass must nudge the condition **closer to False**: here the price shrinks, so the loop is guaranteed to end.

...

If nothing changes, the condition never flips and the loop runs **forever**:

```
# ⚠ NEVER run this. It never stops, and freezes the browser tab
count = 1
while count > 0:
    count = count + 1    # count only grows, so the condition stays True forever
```

...

### ⚠ Warning

An endless `while` will freeze your marimo tab. Always check that **something inside the loop changes** the condition.

## break: an early exit

`break` jumps out of a loop immediately, handy with `while True`:

```
count = 0
while True:
    count = count + 1
    if count == 3:
        break
print(count)
```

3

...

The loop would run forever, but `break` stops it the moment `count` hits 3.

## Cleaning up text

Tobi typed the daily special IN ALL CAPS with stray spaces. Strings have **methods** that return a cleaned-up **copy**:

```
raw = "  miso ramen  "
print(raw.strip())           # drop outer spaces
print(raw.strip().title())   # then Capitalise Each Word
print("special".upper())     # SHOUT
print("MOIN".lower())        # whisper
```

```
miso ramen
Miso Ramen
SPECIAL
moin
```

...

Methods can be **chained** left to right: `raw.strip().title()`.

## Trimming specific characters

`.strip()` drops spaces; `.rstrip("!")` drops trailing `!`. Chain them to fix Tobi's shouting:

```
print("SALE!!!".rstrip("!"))      # SALE
print("SALE!!!".rstrip("!").title()) # Sale
```

```
SALE
Sale
```

...

The original string is never changed. Each method hands back a **new** one.

## Predict: chained methods

What does this print?

```
print("  MOIN  ".strip().lower())
```

a) `MOIN` b) `moin` c) `moin`

...

Predict first, then reveal.

**Answer:** `" MOIN ".strip().lower()`

**b) `moin`:** `.strip()` removes the outer spaces, then `.lower()` lowercases the result. Chained methods run left to right, each acting on the previous one's output.

```
print("  MOIN  ".strip().lower())
```

```
moin
```

## Your turn — 10 minutes

Open the exercise (scan the QR or type the link):

[beyondsimulations.github.io/Introduction-to-Python/notebooks/ex\\_02\\_c/](https://beyondsimulations.github.io/Introduction-to-Python/notebooks/ex_02_c/)



First **predict** what happens, then run it.

### Checkpoint 0: dress rehearsal

**A practice board review.** Fifteen minutes, before the lab, **ungraded**. Same format as the five real checkpoints, so that nothing is new next week when it counts.

- **Individual work**, as in the real thing: no AI, no neighbors, no chat
- The **link and QR** are handed out in class. Open it and start
- 3 short tasks: compute a price, trace a line, fix one of Tobi's bugs
- Fill in your **name and student ID** as code at the top, exactly as you will next week

### When you're done

Menu → *Download* → *Download Python code* → upload the `.py` to the “Checkpoint 0” assignment on Moodle. Nothing is graded today: the point is that download and upload are muscle memory by Session III.

...

#### Note

Next week this exact routine is **Checkpoint 1**: 40 minutes, 12 points, Sessions I–II. Today you get to make every mistake for free.

## To the Lab

### After the break: the lab

- Head to the lab notebook: [Episode 2 — The Curfew](#)
- You'll enforce the 22:00 curfew, total the day's orders in a loop, de-shout Tobi's menu, and fight the **MunchCorp price war** with a `while` loop
- It runs entirely in your browser: no setup, just click and code

...

#### ! Important

**Download your `.py` before you leave.** Closing the tab without downloading loses your work, and downloading is exactly how you hand in the checkpoints.

## Wrap-up

### Three things to remember

1. `if / elif / else` run the first true branch: test the strictest condition first
2. `for` repeats over every item (accumulator: start at 0, add each); `while` repeats until its condition flips, and something inside must move it there
3. **String methods** (`.strip()`, `.title()`, `.upper()`, `.rstrip("!")`) return a cleaned copy, and chain left to right

...

#### i Note

**Next time — Episode 3** starts with Checkpoint 1: 40 minutes, no AI, everything from Episodes 1–2, so keep this notebook and the last one close. Then: Tobi has pasted the same receipt code 14 times, and one small change now takes him an afternoon. We bring in functions to the rescue.

## Literature

### Books to start with

- Downey, A. B. (2024). Think Python: How to think like a computer scientist (Third edition). O'Reilly. [Link to free online version](#)
- Elter, S. (2021). Schrödinger programmiert Python: Das etwas andere Fachbuch (1. Auflage). Rheinwerk Verlag.

...

**i Note**

Nothing new here, but these are still great books to start with!

...

For more, see the [literature list](#) of this course.