

# Lecture VI - Modules and the Standard Library

## Programming with Python

Dr. Tobias Vlček

Kühne Logistics University Hamburg - Fall 2026

### Checkpoint 3

**Sessions I–V.** The first **40 minutes** are the checkpoint. It starts **now**, before the investor sits down.

- **Individual work:** no AI, no neighbors, no chat
- The **link and QR** are handed out in class. Open it and start
- ~6 short tasks: write code, trace code, fix a bug, answer a multiple choice
- It sweeps **everything from Sessions I–V**: variables, control flow, functions, data structures, errors

### When you're done

Menu → *Download* → *Download Python code* → upload the `.py` to the “**Checkpoint 3**” assignment on Moodle. **No retakes:** one sitting.

...

#### Note

The green  live checks are **provisional**. The final grading runs on our side. And take a breath: everything in it was rehearsed in the labs.

## Episode 6: Due Diligence Week

### The investor walks in

Pens down. The checkpoint is behind you. Now the reason today matters.

...

An hour ago the **investor** walked into the shop unannounced. It's **due-diligence week**: before she signs anything, she wants to see how this place actually runs. Kevin offered her a coffee and a spreadsheet he “mostly trusts.”

...

She didn't drink the coffee. She walked to the whiteboard, uncapped a marker, and wrote one question:

“Why is everything built from scratch?”

## Part II: the rules change

For five sessions you built everything by hand, on purpose. From today, that changes.

- **AI is now allowed and taught.** We work *with* it, deliberately, starting in tonight’s lab.
- **The disclosure habit:** every submission that used AI carries a **one-line note** saying what you used it for. Not a confession. A professional reflex.
- **The course chatbot** (sidebar widget) now gives you **full code** on request, not just hints.

...

You spent five sessions learning to think without a co-pilot. Now you get one — and you’ll be the pilot.

## Two accounts this week

Both are free, both are on the [AI Tools page](#), together about ten minutes:

- **Mistral:** a Le Chat account for questions, plus an API key. The same key later powers the AI agent inside your editor
- **Zed student plan:** sign in with the GitHub account you made in Session I (it’s old enough now) and apply with your KLU e-mail. Verification takes up to 72 hours, so the free year of Zed Pro is ready long before Session X

...

### ! Important

Turn **off** Mistral’s training-data toggle before you paste coursework (steps on the AI Tools page). Nothing here needs a credit card.

## Don’t build it, import it

### What’s a module?

The investor’s question has an answer: **you shouldn’t build it from scratch**. Most of what you need is already written.

- A **module** is a toolbox of code someone already wrote and tested
- Python ships with a whole shelf of them: the **standard library**
- You `import` a module, then reach for the tools inside it with a dot: `math.ceil(...)`

...

Kevin has been hand-rolling arithmetic for months. The standard library did most of it before he was born.

## `import math`: stop rounding by hand

130 pastries need to ship. They go in crates of 48. How many crates? You need to round **up**: a half-full crate still ships as a whole one.

```
import math

pastries = 130
per_crate = 48
crates = math.ceil(pastries / per_crate)    # ceil = round UP
print(crates)
```

```
3
```

...

`130 / 48` is `2.7...`; `math.ceil` bumps it to **3**. No fiddling with “if there’s a remainder, add one.” The tool already knows.

## `from statistics import ...`

Sometimes you only want a couple of tools, not the whole box. Import them **by name** and use them directly, no `statistics.` prefix:

```
from statistics import mean, median

ratings = [4.5, 4.8, 1.0, 5.0, 4.2]
print(mean(ratings))    # the average
print(median(ratings))  # the middle value
```

```
3.9
4.5
```

...

One furious review (a **1.0**) drags the mean down to **3.9**. The investor asked for the **typical** rating: `median` sorts the values and hands back the middle one (**4.5**), unmoved by one angry customer.

## Aliases: a shorter name

Some module names are long, or you’ll type them fifty times. `import ... as` gives a module a **nickname** for the rest of the file:

```
import statistics as stats

print(stats.median([4.5, 4.8, 1.0, 5.0, 4.2]))
```

```
4.5
```

...

`stats.median` is the same tool as `statistics.median`, just less to type. You'll meet fixed conventions soon (`import pandas as pd`); using the community's nickname makes your code instantly readable to everyone else.

## Looking inside a module

You don't have to memorize a module. Python will tell you what's in it and what each tool does:

```
import math

dir(math)          # lists every name in the module
help(math.ceil)    # prints what ceil does, and how to call it
```

...

### 💡 Tip

`dir()` is the drawer of tools; `help()` is the little instruction card taped to each one. Between them you can explore any module without leaving your editor.

## Predict: which way does floor go?

`math.ceil` rounds up. Its partner `math.floor` rounds **down**, but *down* from a negative number is the tricky part. What does the last line print?

```
import math
print(math.floor(-2.5))
```

a) `-3` b) `-2` c) an error

...

Predict first. Commit to an answer before the next slide.

## Answer: floor goes down, not toward zero

a) `-3` — `floor` always heads **down** the number line, toward more negative. From `-2.5`, down is `-3`, not the `-2` you'd get by rounding toward zero:

```
import math
print(math.floor(-2.5))    # down the number line → -3
```

```
-3
```

...

“Down” means *smaller*, and `-3` is smaller than `-2`. Keep the number line in your head, not the distance to zero.

## ⚡ Your turn — 10 minutes

Open the exercise (scan the QR or type the link):

[beyondsimulations.github.io/Introduction-to-Python/notebooks/ex\\_06\\_a/](https://beyondsimulations.github.io/Introduction-to-Python/notebooks/ex_06_a/)



First **predict** what happens, then run it.

## Rehearsing luck

### The `random` toolbox

The investor wants to see how the shop copes with a **busy day**, but the busy day hasn't happened yet. So we *rehearse* it with made-up numbers. The `random` module deals them:

```
import random

print(random.random())           # a float in [0.0, 1.0)
print(random.randint(1, 20))     # an integer 1–20, ends included
print(random.choice(["latte", "mocha", "tea"])) # one item, picked at random

queue = [1, 2, 3, 4, 5]
random.shuffle(queue)            # reorders the list in place
print(queue)
```

```
0.5342877039143773
14
tea
[3, 2, 1, 5, 4]
```

...

Four tools, four flavors of luck: a raw float, a bounded integer, a pick from a list, and a reshuffle.

## “Run it again”

The investor leans over and says: “Run it again.” Kevin does, and gets **completely different numbers**:

```
import random

print([random.randint(1, 20) for _ in range(5)]) # one run
print([random.randint(1, 20) for _ in range(5)]) # ...and again – different!
```

```
[4, 14, 5, 17, 6]
[19, 1, 16, 8, 3]
```

...

Two runs, two answers. That’s *exactly* what random is supposed to do, but it’s useless for due diligence. A projection nobody can reproduce is a projection nobody can trust.

## random.seed makes luck repeatable

`random.seed(n)` fixes the starting point of the number stream. Same seed → **same sequence, every time**:

```
import random

random.seed(7)
print([random.randint(1, 20) for _ in range(5)]) # → [11, 5, 13, 2, 3]

random.seed(7)
print([random.randint(1, 20) for _ in range(5)]) # same seed → same list
```

```
[11, 5, 13, 2, 3]
[11, 5, 13, 2, 3]
```

...

Both lines print `[11, 5, 13, 2, 3]`. The numbers still *look* random, but now the investor can run it herself and land on the identical result.

## Predict: seeded once, built twice

Kevin seeds **once**, then builds two lists the same way, without touching the seed in between. Are `first` and `second` equal?

```
import random

random.seed(42)
```

```
first = [random.randint(1, 20) for _ in range(3)]
second = [random.randint(1, 20) for _ in range(3)]

print(first)
print(second)
```

a) different: the second list continues where the first stopped b) equal: the seed is set, so both come out the same c) an error: the stream is empty after three draws

...

Predict first. Commit to an answer before the next slide.

### Answer: different

a) **different** — a seed doesn't freeze `random`, it fixes the whole **sequence**. The first list eats the first three numbers of the stream; the second list simply **continues** from number four:

```
import random

random.seed(42)
first = [random.randint(1, 20) for _ in range(3)]
second = [random.randint(1, 20) for _ in range(3)]

print(first)    # [4, 1, 9] - the stream's first three numbers
print(second)  # [8, 8, 5] - the stream carries on
```

```
[4, 1, 9]
[8, 8, 5]
```

...

To get the *same* list twice, you re-seed before each run, and that rewinds the stream to the start. One seed, one fixed sequence: that's the entire job of a seed.

### Your turn — 10 minutes

Open the exercise (scan the QR or type the link):

[beyondsimulations.github.io/Introduction-to-Python/notebooks/ex\\_06\\_b/](https://beyondsimulations.github.io/Introduction-to-Python/notebooks/ex_06_b/)



First **predict** what happens, then run it.

## To the Lab

### Tonight's episode

- Head to the lab notebook: [Episode 6 — Due Diligence Week](#)
- You'll `import math` and `statistics` for investor-grade counts and averages, then use `random` (with and without a `seed`) to rehearse a busy day she can reproduce
- It's the **first lab where AI is allowed**, so try the chatbot, and add your one-line disclosure note
- This week's homework: the **Mistral account** and the **Zed student plan** from the [AI Tools page](#)
- It runs entirely in your browser: no setup, just click and code

...

#### ! Important

**Download your `.py` before you leave.** Closing the tab without downloading loses your work, and downloading is exactly how you handed in the checkpoint this morning.

## Wrap-up

### Three things to remember

1. **Don't build it, import it.** A **module** is a toolbox someone already wrote: `import math`, `from statistics import median`, `import ... as` for a nickname. `dir()` and `help()` show you what's inside.
2. **`random` deals the luck** (`random()`, `randint`, `choice`, `shuffle`), perfect for rehearsing a day that hasn't happened yet.



3. `random.seed(n)` makes luck repeatable. Same seed → same sequence, every run. A projection you can reproduce is a projection an investor can trust.

...

#### Note

**Next episode: one array to rule a thousand orders.** The shop's data has outgrown plain lists, and NumPy turns a thousand numbers into a single, fast object.

## Literature

### Books to start with

- Downey, A. B. (2024). Think Python: How to think like a computer scientist (Third edition). O'Reilly. [Link to free online version](#)
- Elter, S. (2021). Schrödinger programmiert Python: Das etwas andere Fachbuch (1. Auflage). Rheinwerk Verlag.

...

#### Note

New this session: the [AI Tools page](#): how and when to use AI in Part II, and the one-line disclosure habit that goes on every submission from here on.

...

For more, see the [literature list](#) of this course.