

Installing Python

A short guide using uv

Why we use uv for this course

uv is a new (and very fast) Python tool written in Rust. It:

- Installs Python for you (no manual downloads).
- Creates isolated *virtual environments* (safe sandboxes per project).
- Installs and updates packages quickly.

Note

WHAT is a virtual environment? Think of each project as its own coffee shop with its own supplies. One shop changing its menu does **not** affect the others. WHY it matters: You avoid random breakage when different projects need different versions of the same package.

Install uv

Everything below happens in a **terminal**, a window where you type commands. On macOS open the Terminal app (Spotlight: `Cmd+Space`, type *Terminal*). On Windows open PowerShell (Start menu, type *PowerShell*, pick the entry called *Windows PowerShell*). To run a command, type or paste its line and press Enter. Choose the instructions for your operating system.

macOS or Linux (Terminal)

```
curl -LsSf https://astral.sh/uv/install.sh | sh
```

If `curl` is missing:

```
wget -qO- https://astral.sh/uv/install.sh | sh
```

After installation: **close and reopen** your terminal (so your PATH updates).

Windows (PowerShell)

Open PowerShell and run:

```
powershell -ExecutionPolicy Bypass -c "irm https://astral.sh/uv/install.ps1 | iex"
```

If you see a script execution warning, you can alternatively first run:

```
Set-ExecutionPolicy -ExecutionPolicy Bypass -Scope Process
```

Then re-run the install line.

After installation: **close and reopen** PowerShell, so that it finds the new `uv` command.

Verify installation

Run (macOS / Linux / Windows):

```
uv --version
```

If you see a version number: great!

Warning

If you get “command not found” or “uv’ is not recognized”:

1. Close and reopen the terminal (important).
2. On Windows: make sure you used PowerShell (not Command Prompt).
3. Still broken? Ask for help, no need of guessing the error.

Install Python

We want everyone on the **same** Python version for consistency. Thus, we’ll use Python 3.12 for the course this year.

Install (you only need to do this once):

```
uv python install 3.12
```

Check the installation:

```
uv run python --version
```

Expected output starts with:

```
Python 3.12.
```

Create your first project

Pick a folder where you keep course work. **If you do not have one, make sure to create one!** In the terminal, move into that folder: type `cd` and a space, drag the folder from Finder or Explorer onto the terminal window (that pastes the folder’s location), and press Enter. Then run these two lines, each one **once**:

```
uv init --no-package python-labs  
cd python-labs
```

The first line creates a new folder named `python-labs`. Keep that name: from Session VIII the labs live in this folder. The second line moves you into that folder. In Session X you will instead run `uv init --no-package` inside a folder cloned from GitHub; same command, no name.

`uv init --no-package` creates:

- `main.py` (starter script)
- `pyproject.toml` (project + dependencies config)
- `.python-version` (records the Python version we chose)
- `README.md`, and `.gitignore` if git is on your machine (only when the folder is new; a folder cloned from GitHub already has both)
- (A `.venv` folder will appear later once packages are added or synced.)

Note

Why `--no-package`? Without it, recent versions of uv build an installable *package* layout (`src/python_labs/`) with no `main.py`. For scripts, which is all this course needs, the flat layout is simpler.

You do **not** need to edit any of these (except maybe `README.md` for your notes and `main.py` if you want to run something different).

Run the starter script

Inside the project folder:

```
uv run python main.py
```

You should see something like:

```
Hello from python-labs!
```

(If you want, you can open `main.py` and change the message, then re-run.)

What does that code mean?

```
def main():
    print("Hello from python-labs!")

if __name__ == "__main__":
    main()
```

- `def main():` defines a function (a reusable block of code).
- `print(...)` shows text in the terminal.

- The line `if __name__ == "__main__":` ensures this only auto-runs when the file is executed directly.

Don't worry about this yet, we'll gradually build up to it.

Adding packages

The labs from Session VIII need two packages. Inside `python-labs`, run:

```
uv add pandas matplotlib
```

Check that both arrived. This line prints `ready`:

```
uv run python -c "import pandas, matplotlib; print('ready')"
```

If you added the wrong one (example: `numpi`, a typo):

```
uv remove numpi
```

If your `pyproject.toml` changed (e.g. you pulled code from someone else):

```
uv sync
```



Tip

If something seems “off”, just close the terminal and reopen in the project folder. Fresh starts fix many early mistakes.

Updating `uv`

Occasionally:

```
uv self update
```

(If it ever errors, you can just reinstall using the same one-liner from earlier.)

Best practices for this course

- One folder for the course keeps everything tidy.
- Never install packages “globally” outside a project.
- Keep a short personal log in each project's `README.md` (What did I do? What still confuses me?).
- Ask early for help, guessing usually takes much more time than asking.

You can always see available commands:

```
uv --help
```

Recap

You can now:

1. Install `uv`.
2. Create a project.
3. Run a script.
4. Add/remove/sync packages.

Next come Zed and Mistral Vibe: [AI inside Zed](#).