Forecasting the Future

Lecture 5 - Management Science

Dr. Tobias Vlćek

Introduction

Client Briefing: MegaMart

Operations Director’s Crisis:

“Last Christmas, we ran out of PlayStation 5s but had **500 unsold fitness trackers**. We lost €2M in missed sales and clearance losses. How do we predict what customers will actually buy?”

Business: The Unknown Future


Question: Why can’t we just order the same as last year?

- **Market:** New products, competition
- **Seasonal Shifts:** Weather, holidays, economic conditions
- **Trend Changes:** Changing preferences, new technologies
- **Randomness:** Viral TikToks, supply chain disruptions, pandemics

> ⚠ **Reality:** Large retailers process several thousand orders per hour. Each stockout basically means **lost revenue + unhappy customers**.

Hidden Patterns in Data

Look at this daily sales data. **What patterns do you see?**



Core Concepts

Decomposing Time Series

Time series can often be decomposed:

$$Y_t = T_t + S_t + R_t$$

Where:

- Y_t = Observed value at time t
- T_t = Trend component
- S_t = Seasonal component
- R_t = Random/Residual component

Additive vs Multiplicative Models

How do the components combine?

Additive Model

$$Y_t = T_t + S_t + R_t$$


- Seasonal fluctuations are constant
- “We always sell 200 extra in December”
- Good: Stable, mature products

Multiplicative Model

$$Y_t = T_t \times S_t \times R_t$$

- Seasonal fluctuations scale with trend
- “December sales are 40% higher”
- Good: Growing businesses


Visual Decomposition



Here: Sales = Trend + Seasonality + Random Noise

Moving Average

Question: How do we separate signal from noise?



Simple vs Weighted Averages

Which forecast would you trust more?

Simple Moving Average

- All days equally important
- We just take the average
- [14, 15, 16, 14, 15, 16, 17]
- Forecast: **15.3**

Weighted Moving Average

- Recent days matter more
- Days closer are weighted more
- [0.05, 0.05, 0.1, 0.1, 0.2, 0.2, 0.3]
- Forecast: **15.9**



Recent data often predicts the future better than old data!

Simple Smoothing

Simple Exponential Smoothing

Not too simple, not too complex

$$\text{Forecast}_{t+1} = \alpha \times \text{Actual}_t + (1 - \alpha) \times \text{Forecast}_t$$

- α (alpha) = smoothing parameter (0 to 1)
- α = 0.9: Trust recent data (reactive)
- α = 0.1: Trust historical patterns (stable)
- α = 0.3: Balanced approach (common default)




Think of α like: How much do you trust the latest data point?

When Simple Smoothing Fails

Simple smoothing assumes the data is flat. What if it's not?





Adding Trend

Holt's Method: The Idea

Track TWO things separately: Level and Trend

1. **Level (L):** Where are we right now? (like simple ES)
2. **Trend (b):** How fast are we growing/declining per period?
3. **Forecast:** Combine both: Level + (Trend × periods ahead)

Why This Works:

- Simple ES only tracks level (current position)
- Holt's also tracks the slope (direction and speed)

> *i* Think of driving a car: Simple ES only knows your position. Holt's also knows your speed!

Holt's Method: The Math I

The formulas (simplified for intuition):

Level Equation:

$$L_t = \alpha \times Y_t + (1 - \alpha) \times (L_{t-1} + b_{t-1})$$

Trend Equation:

$$b_t = \beta \times (L_t - L_{t-1}) + (1 - \beta) \times b_{t-1}$$

Forecast Equation:

$$\hat{Y}_{t+h} = L_t + h \times b_t$$

Holt's Method: The Math II

In plain English

- **Level:** "Smooth current observation with previous forecast"
- **Trend:** "Smooth the change in level with our previous trend"
- **Forecast:** "Start at current, add trend for each period ahead"

> *i* Not too complicated, right?

Step-by-Step I

Let's walk through 6 periods manually to build intuition

```python
# Sample data with clear upward trend
sales_data = np.array([100, 105, 112, 118, 124, 130])

# Parameters
alpha = 0.3  # Level smoothing
beta = 0.2   # Trend smoothing

# Initialize
level = sales_data[0]  # Start at first observation
trend = sales_data[1] - sales_data[0]  # Initial trend estimate

print(f"Period 1: Level={level:.1f}, Trend={trend:.1f}")

# Store level and trend history for visualization
level_history = [level]
trend_history = [trend]
```

```
Period 1: Level=100.0, Trend=5.0
```

Step-by-Step II

```python
# Apply Holt's method for periods 2-6
for t in range(1, len(sales_data)):
    # Update level
    prev_level = level
    level = alpha * sales_data[t] + (1 - alpha) * (prev_level + trend)

    # Update trend
    trend = beta * (level - prev_level) + (1 - beta) * trend

    # Store for visualization
    level_history.append(level)
    trend_history.append(trend)

    print(f"Period {t+1}: Sales={sales_data[t]}, Level={level:.1f}, Trend={trend:.1f}")
```


```
Period 2: Sales=105, Level=105.0, Trend=5.0
Period 3: Sales=112, Level=110.6, Trend=5.1
Period 4: Sales=118, Level=116.4, Trend=5.3
Period 5: Sales=124, Level=122.4, Trend=5.4
Period 6: Sales=130, Level=128.4, Trend=5.5
```

Step-by-Step III

```
# Forecast next 3 periods
print(f"\nForecasts:")
forecast_values = []
for h in range(1, 4):
    forecast = level + h * trend
    forecast_values.append(forecast)
    print(f"  Period {len(sales_data)+h}: {forecast:.1f} units")
```

```
Forecasts:
  Period 7: 134.0 units
  Period 8: 139.5 units
  Period 9: 145.0 units
```

Holt's Method: Visual Comparison



Choosing Alpha and Beta

How do you pick the right smoothing parameters?

Alpha (Level Smoothing)

- **High α (0.7-0.9):** Responsive
  - Use: Volatile markets
- **Low α (0.1-0.3):** Stable
  - Use: Steady business

Beta (Trend Smoothing)

- **High β (0.5-0.8):** Quickly
  - Use: Dynamic growth/decline
- **Low β (0.1-0.3):** Stable trend
  - Use: Consistent growth

Best Practice: Let the algorithm optimize parameters automatically!



You can implement Holt's method using Python's `statsmodels` library!

When to Use

Question: When should you use Holt's method?

- Clear upward or downward trend
- No seasonal patterns


Question: When should you use **NOT** Holt's method?

- Data is flat (use simple ES instead)
- Strong seasonality present
- Trend direction changes frequently

Adding Seasonality

The Problem: Trend + Seasonality

What if your data has BOTH trend AND seasonality?




Holt-Winters: Three Components

Track THREE things separately: Level, Trend, AND Seasonality

1. **Level (L):** Current baseline demand (deseasonalized)
2. **Trend (b):** Growth rate per period
3. **Seasonal Indices (s):** Multipliers for each season

Holt-Winters Visualized



Seasonality

How does seasonality combine with the level?

Additive Model

$$Y_t = L_t + b_t + s_t$$

- Seasonal variation is constant
- “We sell +50 units every December”
- Pattern: ±constant amount

Multiplicative Model

$$Y_t = L_t \times b_t \times s_t$$

- Seasonal variation scales with level
- “December is 1.5× normal sales”
- Pattern: ×percentage change

Holt-Winters: The Math I

The formulas (don't panic - Python does this for you!)

Additive Model:

$$L_t = \alpha(Y_t - s_{t-m}) + (1-\alpha)(L_{t-1} + b_{t-1})$$

$$b_t = \beta(L_t - L_{t-1}) + (1-\beta)b_{t-1}$$

$$s_t = \gamma(Y_t - L_t) + (1-\gamma)s_{t-m}$$

$$\hat{Y}_{t+h} = L_t + hb_t + s_{t+h-m}$$

Holt-Winters: The Math II

In plain English

- **Level:** Remove seasonality from observation, then smooth
- **Trend:** Same as Holt's method
- **Seasonal:** Update the seasonal index for this period
- **Forecast:** Level + trend + seasonal adjustment

Parameters:

α (level), β (trend), γ (seasonal), m (seasonal period length)

Holt-Winters: Intuition I

Understanding seasonal patterns with quarterly sales

Quarterly Sales Pattern:

- **Q1:** Low season (after holidays) → Factor: 0.85
- **Q2:** Spring pickup → Factor: 0.95
- **Q3:** Summer growth → Factor: 1.05
- **Q4:** Holiday peak! → Factor: 1.15

Holt-Winters: Intuition I


How Holt-Winters Works

1. **Deseasonalize** the data (remove seasonal effect)
2. **Calculate trend** from deseasonalized data
3. **Update seasonal indices** based on actual vs. expected
4. **Forecast** by combining level + trend + seasonal pattern



Q4 is typically 35% higher than Q1 in retail! Holt-Winters captures this automatically.

Holt-Winters: Visual



Notice how the forecast continues the seasonal pattern while following the trend!

When to Use Holt-Winters

Question: When should you use Holt-Winters method?

- Data with trend AND seasonality
- At least 1 full seasonal cycle (2 are better!)
- Regular, repeating patterns

Question: When should you AVOID Holt-Winters method?

- Irregular or changing seasonal patterns
- Flat data with no trend
- Seasonal pattern length unknown

Selection & Validation

Measuring Forecast Accuracy

How wrong were we?

Mean Absolute Error (MAE): Average size of mistakes

$$\text{MAE} = \frac{1}{n}\sum_{i=1}^{n}|Actual_i - Forecast_i|$$

Root Mean Squared Error (RMSE): Penalizes large errors more

$$\text{RMSE} = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(Actual_i - Forecast_i)^2}$$

Forecast Accuracy

Easy with Python

```python
# Example: Compare two forecasting methods
actual = np.array([100, 105, 110, 108, 112])
forecast_a = np.array([98, 107, 109, 110, 111])
forecast_b = np.array([102, 103, 112, 106, 113])


mae_a = np.mean(np.abs(actual - forecast_a))
mae_b = np.mean(np.abs(actual - forecast_b))

print(f"Method A - MAE: {mae_a:.2f} units")
print(f"Method B - MAE: {mae_b:.2f} units")
print(f"\nBetter method: {'A' if mae_a < mae_b else 'B'}")
```

```
Method A - MAE: 1.60 units
Method B - MAE: 1.80 units

Better method: A
```

When to Use Which Method?



Start simple: Try moving average first as baseline, then add complexity only if needed!

The Real Cost of Being Wrong

Not all forecast errors are equal!

Example: Winter Coats

- Cost: €50, Selling Price: €150, Margin: €100
- Storage cost: €5/month
- Clearance markdown: 70% off

Question: What is your intuition here?

Under and Overforecasting

Sometimes it's cheaper to overstock than to miss sales!

Underforecast by 100 units:

- Lost profit: 100 × €100
  - €10,000
- Customer disappointment
- Competitor gains market share

Overforecast by 100 units:

- Storage: 100 × €5 × 3 months
  - €1,500
- Clearance loss: 100 × €70
  - €7,000

> ⚠ The "best" forecast depends on your business context.

Implementation

Your Python Practice Notebook

All the hands-on coding happens in the interactive tutorial!

1. Working with dates in Pandas
2. Implementing moving averages
3. Building forecast functions
4. Applying Holt's method
5. Using Holt-Winters
6. Measuring accuracy



The notebook guides you step-by-step through Bean Counter's seasonal demand forecasting challenge!

AI & Machine Learning

The Promise of AI

Can machines predict better than classical methods?

What AI/ML brings to forecasting:

- Handle hundreds of variables simultaneously
- Detect complex non-linear patterns
- Learn from massive datasets
- Adapt automatically to changes

> *i* AI doesn’t replace human judgment, it augments it when you have enough data!

Common AI/ML Forecasting

Overview of popular techniques

Traditional ML:

- **Random Forest:** Ensemble of decision trees
- **XGBoost:** Gradient boosting (very popular)
- **Support Vector Machines:** Pattern recognition

Deep Learning:


- **LSTM (Long Short-Term Memory):** For sequences
- **Prophet (Facebook):** Automated forecasting
- **Neural Networks:** Complex patterns

⚠ More complex ≠ Better! Simple methods often win in forecasting.

The Issue: Overfitting


Question: What happens when we train an AI on all our data and use it to predict... the same data?





Training vs Test Data

Never judge a complex model on the data it learned from!



- **Training Data:** Where the model learns patterns (70-80%)
- **Validation Data:** Where you tune hyperparameters (10-15%)
- **Test Data:** The “future”, only once for final evaluation (10-15%)

Data Leakage: The Silent Problem


When future information sneaks into your training data

1. Target leakage
    - Wrong: Including “total_sales” when predicting “monthly_sales”
    - Right: Only use information available at prediction time
2. Temporal leakage
    - Wrong: Random split for time series (mixes past and future)
    - Right: Always split chronologically



Data leakage can make a terrible model look amazing… until it fails in production!

Time Series Cross-Validation



Unlike regular cross-validation, we NEVER use future data to predict the past!

When to Use AI/ML Forecasting I

Use AI when you have:

- Sufficient historical data (2+ years)
- Rich feature data (weather, promotions, events)
- Non-linear patterns
- Resources for training/maintenance

Examples:

- Large retailers (Amazon, Walmart)
- Demand forecasting with many variables

When to Use AI/ML Forecasting II

Don’t use AI when you have:

- Limited historical data
- High noise, low signal
- Need explainable forecasts
- Limited expertise


Examples:

- New products (no history)
- Regulatory environments

Advanced Topics


Forecast Horizons

How far into the future can we predict?



Confidence Intervals

A forecast without confidence intervals is incomplete!



Forecast Combination

Why choose one method when you can combine several?


```python
# Example: Combining multiple forecasts
ma_forecast = 120       # Moving average prediction
exp_forecast = 125      # Exponential smoothing prediction
seasonal_forecast = 135 # Seasonal model prediction

# Simple average (equal weights)
simple_combo = (ma_forecast + exp_forecast + seasonal_forecast) / 3
print(f"Simple combination: {simple_combo:.0f} units")

# Weighted average (based on historical accuracy)
weights = [0.3, 0.5, 0.2]  # Exp smoothing was most accurate historically
weighted_combo = (ma_forecast * weights[0] +
                  exp_forecast * weights[1] +
                  seasonal_forecast * weights[2])
print(f"Weighted combination: {weighted_combo:.0f} units")
```

```
Simple combination: 127 units
Weighted combination: 126 units
```

Lead Times and Safety Stock



Long lead times = Forecasting further out = Less accuracy = More safety stock!

Safety Stock Calculation

How much buffer do you need?

```python
# Safety stock formula
import scipy.stats as stats

avg_weekly_demand = 300; std_weekly_demand = 40; lead_time_weeks = 3
service_level = 0.95  # Want 95% availability

# Z-score for 95% service level
z_score = stats.norm.ppf(service_level)

# Safety stock calculation
safety_stock = z_score * std_weekly_demand * np.sqrt(lead_time_weeks)
reorder_point = (avg_weekly_demand * lead_time_weeks) + safety_stock

print(f"Average demand during lead time: {avg_weekly_demand * lead_time_weeks} units")
print(f"Safety stock needed: {safety_stock:.0f} units")
print(f"Reorder point: {reorder_point:.0f} units")
```

```
Average demand during lead time: 900 units
Safety stock needed: 114 units
Reorder point: 1014 units
```

Today’s Tasks

Today

Hour 2: This Lecture

- Patterns & decomposition
- Simple ES, Holt's, Holt-Winters
- Method selection
- Practical pandas

Hour 3: Notebook

- Bean Counter CEO
- Daily and weekly aggregation
- Implement methods
- Compare accuracy

Hour 4: Competition

- MegaMart challenge
- 3 real products
- 4-week forecast
- €10K per error unit!

The Competition Challenge

“The Christmas Predictor”

1. **Analyze** 2 years of weekly sales for 3 products
2. **Identify** patterns (trend, seasonality, volatility)
3. **Forecast** 4 December weeks for each product
4. **Minimize** Mean Absolute Error across all 12 predictions

Key Takeaways

Remember This!

The Rules of Forecasting

1. **Always plot first** - Your eyes catch patterns algorithms miss
2. **Start simple** - Complexity is not your friend
3. **Recent matters more** - Weight recent data higher
4. **Match method to pattern** - Trend? Seasonality? Match!
5. **Validate on holdout** - Never test on training data
6. **Add confidence intervals** - Uncertainty is information
7. **Consider business context** - Cost of errors matters

Final Thought

Forecasting is both art and science

The Science:

- Statistical methods
- AI based forecasting
- Error metrics (MAE, RMSE)
- Confidence intervals
- Systematic validation

The Art:

- Choosing the right method
- Balancing complexity vs simplicity
- Interpreting context
- Communicating uncertainty

> ⚠ Make better decisions, not perfect predictions!

Break!

Take 20 minutes, then we start the practice notebook

Next up: You'll become Bean Counter's forecasting expert, preparing for seasonal demand!

Then: The MegaMart Christmas Challenge!