Introduction to Metaheuristics

Lecture 9 - Management Science

Dr. Tobias Vlćek

Introduction



Client Briefing: La Étoile

Restaurant Manager's Crisis:

"I need to schedule my **18 servers across 6 shifts** this weekend. Shifts have **different lengths (4-6 hours)**, and if I don't have enough experienced servers on busy shifts, we face **penalties** per missing experienced server from our parent company!"

The Staffing Challenge

A restaurant facing a weekend scheduling crisis:

La Étoile's Problem:

- 18 servers available (6 experienced @ €75/hr, 12 junior @ €25/hr)
- 6 shifts with **varying lengths** (4-6 hours each)
- Each shift needs 3 servers (at least 1 experienced)
- Server **preferences** matter (1-10 scale, affects quality)

Question: How to balance labor costs, penalties, AND staff?

The Cost Impact: Why This Matters


The financial stakes are significant with these large penalties:


- **Minimum Labor Cost**: ~€3,500 (everyone works once)
- **Experience Penalties**: €0-€1,200 per missing experienced server
- **Preference Penalties**: €0-€180 per unhappy assignment
- **Worst Case**: Over €9,000 if poorly scheduled!
- **Best Case**: ??? with smart optimization


> ⚠ Potentially up to **large difference** between good and bad scheduling!

Restaurant Staffing: The Numbers

The real-world complexity we're dealing with:







⚠ With varying shifts, preferences, and penalties, this is will be a real challenge!

Today's Objectives

What you'll understand after this lecture:

1. **Why local search fails:** Recap on the local optima trap
2. **Escape mechanisms:** How to accept worse solutions strategically
3. **Four powerful metaheuristics:** SA, GA, Tabu Search, ACO
4. **Selection criteria:** When to use which algorithm

Hiking in Fog

Remember the metaphor with blindfolded eyes from last lecture?


- **Goal**: Find the highest peak in a mountain range
- **Challenge**: You're hiking in thick fog (can only see 10 meters)
- **Position**: Your X,Y coordinates = your decisions
- **Altitude**: Your current solution quality
- **Problem**: You might climb a small hill and think it's the summit!



This metaphor will guide us through all metaheuristics today!

Recap: Local Optima

Real problems often have thousands of local optima!



Question: Any idea how to escape local optima?

Simple Methods Fail

The Silo Problem

Why neighborhood optimization fails:

Technical View: Local Optima

- Algorithm climbs nearest hill
- Gets stuck on “foothill”
- Can’t see the mountain beyond
- Every move looks worse
- Believes it found the best


Analogy: Department Silos


- Sales optimizes sales metrics
- Engineering optimizes quality
- Finance optimizes costs
- Each department “wins”
- **Company performance loses!**

> ⚠ Sum of local bests ≠ Global best

Why Greedy Gets Stuck

Greedy algorithms can simply trap themselves:







⚠ Greedy allocates resources early, creating problems later!

Local Search Also Struggles

Because we only ever accept better solutions during search:





Question: What can we do to cope with this situation?

Simulated Annealing

Core Concepts

The fundamental components:

- Solution = One complete schedule/route/plan
- Neighbor = A slightly modified version
- Cost = How good/bad the solution is

The Strategy

- Always accept improvements
- Sometimes accept worse solutions (the change!)

Think of it as strategic risk-taking that decreases over time!

The Metallurgy Metaphor

How annealing steel inspired an optimization algorithm:

Annealing Metal:

1. Heat to high temperature
2. Atoms move freely
3. Slowly cool down
4. Forms crystal structure


Optimization:

1. Start with high “temperature”
2. Accept bad moves often
3. Gradually reduce temperature
4. Converge to good solution

> ⚠ The willingness to temporarily accept worse solutions is what enables finding the summit!

Temperature Controls Acceptance

Probability of accepting worse solutions lowers with temp:



We essentially compare the cost of the new schedule to the current cost and decide whether to accept the change based on the temperature and the difference in cost.

Concept

How Simulated Annealing Works (Pseudocode)

```
def simulated_annealing_concept(current_schedule):
    temperature = 500  # Start "hot" (adventurous)
    best_schedule = current_schedule

    while temperature > 1:
        # Step 1: Try a random change (like swapping two shifts)
        new_schedule = make_random_change(current_schedule)

        # Step 2: Is it better?
        if cost(new_schedule) < cost(current_schedule):
            current_schedule = new_schedule  # Always accept improvements
        else:
            # NEW: Sometimes accept worse solutions!
            # Hot temperature = more likely to accept
            # Cold temperature = less likely to accept
            if random() < acceptance_probability(temperature):
                current_schedule = new_schedule  # Accept anyway!
```

Concept (continued)

How Simulated Annealing Works (Pseudocode)

```
        # Step 3: Cool down (become less adventurous)
        temperature = temperature * 0.95

        # Remember the best we've ever seen
        if cost(current_schedule) < cost(best_schedule):
            best_schedule = current_schedule

    return best_schedule
```

SA in Action: Restaurant Staffing

A simplified weekend scheduling problem we'll use throughout:

```
# SIMPLIFIED PROBLEM (used across ALL metaheuristics today)
"""
La Étoile's Weekend Challenge:
- 12 servers: 4 experienced (E1-E4), 8 junior (J1-J8)
- 6 shifts: Need 2 servers each
- Everyone works exactly 1 shift
"""
```

The initial greedy schedule has the following results:


```
Greedy Schedule Cost: €5,240
  Labor: €2250, Penalties: €1700, Unhappiness: €1290
```



Let's see how Simulated Annealing can improve the solution!

Visualizing SA Performance

How temperature affects the search behavior:



See how SA accepts worse solutions early, enabling escape from local optima!

Common SA Mistakes

Avoid these common implementation errors:

Mistake #1: Starting Too Cold


- If temperature is too low → Acts like greedy (no exploration)
- Fix: Start hot enough to accept bad moves

Mistake #2: Cooling Too Quickly

- If you cool fast → Get stuck early
- Fix: Cool slowly (multiply by 0.95-0.99, not 0.5)

⚠ Quick cooling is tempting for speed, but defeats the purpose of SA!

Temperature Parameter Impact



The “Good Balance” explores widely early, then refines carefully. Often you need to balance exploration and exploitation by experimenting with different parameters.

Genetic Algorithms

Evolution as Optimization

How natural selection inspires computational optimization:

Natural Selection:

1. Population of individuals
2. Fittest survive & reproduce
3. Offspring inherit traits
4. Mutations create diversity
5. Evolution finds adaptation

Optimization:

1. Population of solutions
2. Best solutions selected
3. Crossover combines solutions
4. Mutation adds variation
5. Evolution finds optimum



Just like successful products get more market share, better solutions get more “offspring” in the next generation. It’s survival of the fittest, but for schedules, routes, or designs!

The Genetic Process

Four stages repeat each generation:


1. **Selection:** Choose parents based on fitness
2. **Crossover:** Combine to create children
3. **Mutation:** Randomly modify children
4. **Replacement:** New generation replaces old
5. **Population Evolution:** Improve population quality




Let’s see each stage in detail with our restaurant problem!

Stage 1: Selection (Tournament)

How to choose which schedules get to “reproduce”:






Each tournament selects one parent, then we pair them up sequentially for crossover.

Stage 2: Crossover (Recombination)

Combine two parent schedules to create offspring:




First 3 shifts from Parent 1, last 3 from Parent 2

Crossover randomly combines good building blocks from both parents!

Stage 3: Mutation

Random changes maintain diversity and explore new solutions:



Mutation rate: 20% (happens to 1 in 5 offspring)

Mutation adds random exploration, like trying something completely new occasionally!


Stage 4: Replacement I

How do offspring join the population?

- **Generational:** Replace entire population with offspring
- **Steady-State:** Replace only worst individuals
- **Elitism:** Always keep the best solutions

> *i* Our approach: **Generational with Elitism**, we create 20 offspring via repeated selection/crossover/mutation, but preserve the 2 best from current generation.


Stage 4: Replacement II



Elitism ensures we never lose our best solutions while exploring new ones!

Stage 5. Population Evolution


How the population improves over generations:



ⓘ Notice how population average also improves (not just the best)!

GA vs SA: Head-to-Head

Comparing exploration strategies on the restaurant problem:



GA maintains population diversity, SA explores single solution path!

GA Mistakes: Population Issues

Avoid these population-related errors:

Mistake #1: Everyone Becomes Identical

- If all solutions look the same → Lost diversity
- Fix: More mutation, bigger population, tournament selection

Mistake #2: Too Greedy in Selection

- Only keeping the very best → Premature convergence
- Fix: Keep some variety, even if not perfect (elitism of 10-20%)

GA Mistakes: Implementation

Technical pitfalls to watch out for:

Mistake #3: Breaking the Rules

- Crossover might create invalid schedules
- Fix: Always check and repair after crossover/mutation

Mistake #4: Evolution Too Slow

- Population too large or too many generations
- Fix: Start small (50-100), tune based on convergence

Tabu Search

Core Idea

Using memory to avoid cycling through bad solutions:

Analogy:

- Keep a list of recent dates
- “Not going back there!”
- Forces you to meet new people
- After time, memory fades

In Optimization:

- Recent solutions = “tabu”
- Don’t revisit same schedules
- Forces exploration of new areas
- Tabu list has limited size



Like keeping “lessons learned”, you remember not to use them again, but after a while, you might reconsider!

Concept

How Tabu Search Works (Pseudocode)

```
def tabu_search_concept():
    tabu_list = []  # Our "never again" list
    current_solution = initial_schedule
    best_solution = current_solution

    while not done:
        # Look at all possible moves
        possible_moves = get_all_neighbor_moves(current_solution)

        # Filter out the "forbidden" moves
        allowed_moves = []
        for move in possible_moves:
            if move not in tabu_list:  # Not forbidden
                allowed_moves.append(move)
```

Concept (continued)

How Tabu Search Works (Pseudocode)

```
        # Pick the best allowed move (even if worse!)
        best_move = select_best(allowed_moves)
        current_solution = apply(best_move)


        # Update best if improved
        if cost(current_solution) < cost(best_solution):
            best_solution = current_solution

        # Remember this move (add to tabu list)
        tabu_list.append(best_move)
        if len(tabu_list) > 10:  # Keep list size manageable
            tabu_list.pop(0)  # Forget oldest

    return best_solution
```

Tabu Search on Restaurant Problem

Real implementation with memory-based exploration:



Tabu Search's memory prevents revisiting bad solutions!

Ant Colony (ACO)

The Core Idea

Collective intelligence through chemical signals:

Reviews:

- Popular choices get more 5-star reviews
- More reviews → more visibility
- But old reviews fade over time
- New patterns can emerge

In Optimization:

- Good assignments get “pheromones”
- Stronger choosen more likely
- Evaporation against stagnation
- Colony finds patterns



Imagine each server-shift pairing has a “rating” that increases when it works well in a schedule. Over time, the best pairings naturally get chosen more often!

How ACO Works on Scheduling

Four key stages in each iteration:

1. **Construction:** Each ant builds a schedule probabilistically
2. **Evaluation & Evaporation:** Measure quality, then fade all pheromones
3. **Reinforcement:** Good schedules deposit pheromones
4. **Evolution:** Repeat until colony converges

> Let's see each stage visually!

ACO: Key Parameters

Two critical parameters control the balance:

Evaporation Rate (ϱ)

- Higher ϱ → More forgetting
- Lower ϱ → Stronger memory
- Typical: 0.1 - 0.5
- **Too high**: Colony never learns
- **Too low**: Gets stuck early

Number of Ants


- More ants → More exploration
- Fewer ants → Faster iterations
- Typical: 10 - 50
- **Too many**: Slow, redundant
- **Too few**: Miss good patterns



Start with ϱ=0.3 and n_ants=20, then tune based on problem size.

Stage 1: Pheromone Construction


Ants don’t pick randomly, they follow the chemical trails




To build the initial pheromone matrix, each cell is initialized with a small positive value.

Stage 2: Evaluation & Evaporation

After all ants build schedules:






Evaporation prevents premature convergence as old patterns can fade away!

Stage 3: Reinforcement

Good ants deposit more pheromones:




Deposit Formula: $\Delta\tau = Q / cost$
(Q=1000, so better solutions deposit more)

The best solutions leave the strongest trails for future iterations!

Stage 4: Evolution Over Iterations


Full ACO implementation on restaurant staffing:



The colony learns collectively step by step.

ACO vs Other Algorithms

How does the ant colony compare?



Any idea why ACO fares worse?

Why did ACO struggle?

The Right Tool for the Wrong Job

ACO is designed for **Sequential Path-Finding** (Graph Traversal).

- **Best For:** “I am at City A, where should I go next?” (TSP)
- **Our Problem:** “Who should work Friday Dinner?” (Assignment)

> ⚠ We forced a “Graph” algorithm onto a “Bin Packing” problem. SA and GA don’t care about geometry, so they adapted better!

Decision Framework

When to Use Which Metaheuristic?

A decision guide for algorithm selection:

Method	Time	Quality	Complexity	Best For
Random	xxxx	x	Trivial	Baseline
Greedy	xxx	xx	Simple	Quick decisions
LS	xx	xxx	Medium	Improvement
SA	xx	xxxx	Medium	Single solution
GA	x	xxxx	High	Population
TS	xx	xxx	Medium	Avoid cycles
ACO	x	xxxx	High	Changing Paths

The No Free Lunch Theorem

Why there's no universal best algorithm:

"No Free Lunch Theorem": No single algorithm is best for all problems. Your choice must match your problem structure:

- Path/Network Problems → ACO (pheromones for paths)
- Scheduling Problems → SA or Tabu (neighborhood swaps)
- Complex Design → GA (population diversity)

Implementation Strategy

Guidelines for successful implementation:

1. **Start Simple**: Always try greedy first as baseline
2. **Profile Your Problem**: Understand constraints before choosing
3. **Tune Incrementally**: Don’t optimize all parameters at once
4. **Track Progress**: Monitor convergence to know when to stop
5. **Hybrid Approaches**: Combine methods (e.g., GA + Local Search)
6. **Use AI Assistance**: Bridge the “knowledge gap” with GenAI

Today's Briefing

Today

Hour 2: This Lecture

- Metaheuristics
- Simulated annealing
- Genetic algorithms
- Tabu search & ACO

Hour 3: Notebook

- Bean Counter delivery
- Implement SA
- Tune parameters
- Compare performance

Hour 4: Competition

- Restaurant staffing
- Multi-objective
- Schedule optimization
- Justify choice!

The Competition Challenge

La Étoile Restaurant Weekend Staffing

1. **Schedule** 18 servers across 6 shifts (different lengths)
2. **Minimize** labor + experience penalties + preference costs
3. **Ensure** experienced coverage (strategic placement)
4. **Respect** 2 servers per shift requirement

> ⚠ Choose your metaheuristic wisely as this is a tough problem!

Parameter Tuning Strategies

How to find good parameters without wasting time:

1. Start with Rules of Thumb
   - SA: Initial temp = max cost difference you'd accept
   - GA: Population = 10-20× number of decision variables
   - Tabu: Tenure (limit) = √(problem size)
2. Grid Search on Small Instance
   - Test 3-4 values per parameter
   - Use 10% of full dataset
   - Example: `temps = [100, 500]`, `cooling = [0.95, 0.99]`

Real-World Considerations

Technical realities when putting metaheuristics into production:

Factor	Questions to Ask
Time Budget	How long can optimization run?
Solution Quality	Need optimal or “good enough”?
Explainability	Must justify decisions?
Problem Changes	Static or dynamic data?
Team Skills	Who maintains this code?



Use the **simplest method** that meets your quality target. Complex metaheuristics are great but more costly to maintain!

Summary

Key Takeaways:

- Metaheuristics escape local optima when exact methods fail
- SA uses temperature, GA uses evolution, Tabu uses memory
- Parameter tuning is critical for performance
- No universal best - problem structure matters
- Start simple, add complexity only if needed

Break!

Take 20 minutes, then we start the practice notebook

Next up: You'll implement metaheuristics for Bean Counter