# Cheatsheet

Useful commands and tips



## Variables and Types

### Variables

- **Definition**: Containers for storing information.
- **Example**: `x = 10`

### Data Types

- **Integers (int)**: Whole numbers (e.g., count of dates).
- **Floats (float)**: Decimal numbers (e.g., compatibility score).
- **Booleans (bool)**: True/False values (e.g., availability).
- **Strings (str)**: Text values (e.g., names).

```
name = "Alexander"  # String variable
flags = 0           # Integer variable
butterflies = True  # Boolean variable
```

### Type Conversion

- **Checking**: Use `type()` to check the type of a variable.
- **Conversion**:
  - `int()`: Converts to integer.
  - `float()`: Converts to float.
  - `str()`: Converts to string.
  - `bool()`: Converts to boolean.

### String Formatting

- **Concatenation**: Combine strings using `+`.
- **Formatting**: Use `f"..."` for formatted strings.

```
name = "Alexander"
print(f"Hello, {name}!")
```

```
Hello, Alexander!
```

# Comparisons

## Comparison Operators

| Symbol | Meaning | Example |
|---|---|---|
| == | Equal to | score == 100 |
| != | Not equal to | degree != “Computer Science” |
| < | Less than | salary < 80000 |
| > | Greater than | experience > 5 |
| <= | Less than or equal to | age <= 65 |
| >= | Greater than or equal to | test_score >= 80 |

## Logical Operators

| Symbol | Meaning | Example |
|---|---|---|
| and | Both conditions must be true | score > 80 and experience > 5 |
| or | At least one condition must be true | score > 80 or experience > 5 |
| not | Condition must be false | not (score > 80) |

# Decision-Making

## if Statements

- **Structure**:

```
if condition:
    # code to execute if condition is True
```

- **Example**:

```
flat_rating = 8
if flat_rating >= 7:
    print("This is a good apartment!")


This is a good apartment!
```

## if-else Statements

- **Structure**:

```
if condition:
    # code to execute if condition is True
else:
    # code to execute if condition is False
```

- **Example**:

```
flat_rating = 4
if flat_rating >= 7:
    print("Apply for this flat!")
else:
    print("Keep searching!")


Keep searching!
```

## if-elif-else Statements

- **Structure**:

```
if condition:
    # code to execute if condition is True
elif condition:
    # code to execute if condition is False
else:
    # code to execute if condition is False
```

- **Example**:

```
flat_rating = 8
if flat_rating >= 9:
    print("Amazing flat - apply immediately!")
elif flat_rating >= 7:
    print("Good flat - consider applying")
else:
    print("Keep looking")


Good flat - consider applying
```

## Complex Conditions

- **Nested if Statements**: Use if statements inside other if statements.
- **Logical Operators**: Combine conditions using `and`, `or`, `not`.
- **Structure**:

```
if (condition1) and (condition2):
    # code if both conditions are True
```

```
elif (condition1) or (condition2):
    # code if at least one condition is True
else:
    # code if none of the conditions are True
```

- **Example**:

```
flat_rating = 9
price = 900
if (flat_rating >= 9) and (price < 1000):
    print("Amazing flat - apply immediately!")
```

```
Amazing flat - apply immediately!
```

# Lists and Tuples

# Lists

- **Definition**: Ordered, mutable collections of items.
- **Creation**: Use square brackets `[]`.

```
ratings = [4.5, 3.8, 4.2]
restaurants = ["Magic Place", "Sushi Bar", "Coffee Shop"]
```

## Accessing Elements

- **Indexing**: Use `[index]` to access elements.

```
print(restaurants[0])  # Access the first element
```

```
Magic Place
```

- **Negative Indexing**: Use `[-1]` to access the last element.

```
print(restaurants[-1])  # Access the last element
```

```
Coffee Shop
```

- **Slicing**: Use `[start:end]` to access a range of elements.

```
print(restaurants[0:2])  # Access the first two elements
```

```
['Magic Place', 'Sushi Bar']
```

## Adding Elements

- **Appending**: Use `append()` to add an element to the end of the list.

```
restaurants.append("Pasta Place")
```

- **Inserting**: Use `insert()` to add an element at a specific index.

```
restaurants.insert(0, "Pasta Magic")
```

## Removing Elements

- **Removing**: Use `remove()` to remove an element by value.

```
restaurants.remove("Pasta Place")
```

- **Removing by Index**: Use `pop()` to remove an element by index.

```
restaurants.pop(0)
```

```
'Pasta Magic'
```

## Nested Lists

- **Definition**: Lists containing other lists or tuples.
- **Accessing**: Use nested indexing.

```
restaurant_data = [
    ["Pasta Place", 4.5, 3],
    ["Sushi Bar", 4.2, 1]
]
print(restaurants[0][1])  # Access the second element of the first list
```

```
a
```

## Tuples

- **Definition**: Ordered, immutable collections of items.
- **Creation**: Use parentheses `()`.
- **Immutability**: Once created, cannot be changed.
- **Memory Efficiency**: Use less memory than lists.
- **Use Cases**: Ideal for fixed data (e.g., restaurant location).

```
ratings = (4.5, 3.8, 4.2)
restaurant_info = ("Pasta Place", "Italian", 2020)
```

# Loops

## for Loops

- **Definition**: Iterate over a sequence of items.
- **Structure**:

```
for item in sequence:
    # code to execute for each item
```

- **Example**:

```
treatments = ["Standard Drug", "New Drug A", "New Drug B"]
for treatment in treatments:
    print(f"Evaluating efficacy of {treatment}")
```

```
Evaluating efficacy of Standard Drug
Evaluating efficacy of New Drug A
Evaluating efficacy of New Drug B
```

## Range in for Loops

- **Definition**: Generate a sequence of numbers.
- **Structure**:

```
range(start, stop, step)
```

- **Example**:

```
for phase in range(5):  # 0 to 4
    print(f"Starting Phase {phase + 1}")
```

```
Starting Phase 1
Starting Phase 2
Starting Phase 3
Starting Phase 4
Starting Phase 5
```

```
for phase in range(1, 5):  # 1 to 4
    print(f"Starting Phase {phase}")
```

```
Starting Phase 1
Starting Phase 2
Starting Phase 3
Starting Phase 4
```

```
for phase in range(1, 5, 2):  # 1 to 4, step 2
    print(f"Starting Phase {phase}")
```

```
Starting Phase 1
Starting Phase 3
```

## break and continue

- **break**: Exit the loop.
- **continue**: Skip the current iteration and continue with the next.

```
efficacy_scores = [45, 60, 75, 85, 90]
for score in efficacy_scores:
    if score < 50:
        continue
        print(f"Treatment efficacy: {score}%")
    if score >= 85:
        break
```

## Tuple unpacking

- **Definition**: Assign elements of a tuple to variables.
- **Structure**:
- **Example**:

```
restaurant_info = ("Pasta Place", "Italian", 2020)
name, cuisine, year = restaurant_info
print(name)
print(cuisine)
print(year)
```

```
Pasta Place
Italian
2020
```

## while Loops

- **Definition**: Execute code repeatedly as long as a condition is true.
- **Structure**:

```
while condition:
    # code to execute while condition is True
```

- **Example**:

```
phase = 1
while phase <= 5:
    print(f"Starting Phase {phase}")
    phase += 1
```

```
Starting Phase 1
Starting Phase 2
Starting Phase 3
Starting Phase 4
Starting Phase 5
```

# Functions

## Basic Function

- **Definition**: Use the `def` keyword.
- **Structure**:

```
def function_name(parameters):
    # code to execute (function body)
    return value  # Optional
```

- **Example**:

```
def greet_visitor(name):
    return f"Welcome to the library, {name}!"

greet_visitor("Student")
```

```
'Welcome to the library, Student!'
```

## Return Value

- **Definition**: The value returned by a function.
- **Example**:

```
def multiply_by_two(number):
    return number * 2

result = multiply_by_two(5)
print(result)
```

```
10
```

- **Note**: If a function does not return a value, it implicitly returns `None`.

### Default Parameters

- **Definition**: Provide default values for function parameters.
- **Structure**:

```
def greet_visitor(name="People"):
    return f"Welcome to the library, {name}!"

print(greet_visitor()) # Calls the function with the default parameter
print(greet_visitor("Tobias")) # Calls the function with a custom parameter
```

### Multiple Parameters

- **Definition**: Functions can have multiple parameters.
- **Structure**:

```
def greet_visitor(name, age):
    return f"Welcome to the library, {name}! You are {age} years old."

print(greet_visitor("Tobias", 30))
```

## String Methods

- **Definition**: Methods are functions that are called on strings.
- **Structure**:

```
string.method()
```

- **Common String Methods**:
  - `.strip()` - Removes whitespace from start and end
  - `.title()` - Capitalizes first letter of each word
  - `.lower()` - Converts to lowercase
  - `.upper()` - Converts to uppercase
- **Example**:

```
title = "the hitchhikers guide"
print(title.title())
```

```
The Hitchhikers Guide
```

```
title = "   the hitchhikers guide    "
print(title.strip())
```

```
the hitchhikers guide
```

# Packages

## Standard Libraries

- **Definition**: Libraries that are part of the Python standard library.
- **Access**: Import them using `import`.

```
import math
import random
```

- For long package names, you can use the `as` keyword to create an alias.

```
import random as rd
```

- To call a function from an imported package, use the package name as a prefix.

```
random_number = rd.random()
print(random_number)
```

```
0.7236662361570383
```

## Installing Packages

- **Definition**: Install packages using `uv`.

```
uv add package_name
```