Enrolment No:	92500588046		
Student Name:	Booker A Tengbeh		
Subject	**DBMS-ii**	**Academic Year**	**2025-2026**
Subject Code	**05BS0204**	**Subject Type**	**Department level**

2	1) Write a PL/SQL block that uses a cursor attribute SQL%ROWCOUNT to raise the basic salary of employees by 10% that are working in department number 10 and also display the appropriate message based on the existence to the record in the EMP table. (Use Implicit Cursor) 2) Write a PL/SQL block that uses a cursor attribute %ISOPEN and %NOTFOUND to raise the basic salary of employees of department number 20 by 5% and also display the appropriate message based on the existence to the record in the EMP table. Whenever any such raise is given to the employees, a record for the same is maintained in the emp_update table. (Perform using both Implicit and Explicit Cursor) 3) Write a PL/SQL block that uses a cursor attribute %ROWCOUNT to display the name, department and basic salary of first 5 employees getting the highest basic salary. (Use Explicit Cursor) 4) Write a PL/SQL block using a cursor FOR loop to display name and the basic salary of top 3 highest paid employees. (Use Cursor For Loop) 5) Write a PL/SQL block using a parameterized cursor that displays the department wise basic salary of each employee and department wise total gross salary. (Parameterized Cursor and Use Cursor For Loop)

1) PL/SQL Block Using Implicit Cursor (SQL%ROWCOUNT)
Raise **basic salary by 10%** for employees in **Deptno = 10.**

```
Set serverout on;
DECLARE
BEGIN
    UPDATE EMP
    SET BasicSal = BasicSal * 1.10
    WHERE Deptno = 10;
```

```
    IF SQL%ROWCOUNT > 0 THEN
        DBMS_OUTPUT.PUT_LINE(SQL%ROWCOUNT || ' Employee record(s)
updated.');
    ELSE
        DBMS_OUTPUT.PUT_LINE('No employee found in Department 10.');
    END IF;

END;
/
```

2) PL/SQL Block Using %ISOPEN and %NOTFOUND

Raise salary **5% for Deptno = 20** and insert record into **emp_update table.**

First create update table

Set serverout on;

```
CREATE TABLE emp_update(
eid NUMBER,
old_salary NUMBER,
new_salary NUMBER,
update_date DATE
);
```

(A) Using Implicit Cursor

```
Set serveroutput on;
DECLARE
BEGIN
    UPDATE EMP
    SET BasicSal = BasicSal * 1.05
    WHERE Deptno = 20;

    IF SQL%ROWCOUNT = 0 THEN
        DBMS_OUTPUT.PUT_LINE('No employee found in Department 20');
    ELSE
        INSERT INTO emp_update
        SELECT Eid, BasicSal/1.05, BasicSal, SYSDATE
        FROM EMP
        WHERE Deptno = 20;

        DBMS_OUTPUT.PUT_LINE('Salary Updated Successfully');
    END IF;
END;
/
```

(B) Using Explicit Cursor

```
DECLARE
CURSOR c1 IS
SELECT Eid, BasicSal
FROM EMP
WHERE Deptno = 20;

v_eid EMP.Eid%TYPE;
```

```
v_sal EMP.BasicSal%TYPE;

BEGIN

OPEN c1;

IF c1%ISOPEN THEN
DBMS_OUTPUT.PUT_LINE('Cursor Opened');
END IF;

LOOP
FETCH c1 INTO v_eid, v_sal;

EXIT WHEN c1%NOTFOUND;

UPDATE EMP
SET BasicSal = BasicSal * 1.05
WHERE Eid = v_eid;

INSERT INTO emp_update
VALUES(v_eid, v_sal, v_sal*1.05, SYSDATE);

END LOOP;

CLOSE c1;

END;
/
```

3) PL/SQL Block Using Explicit Cursor and %ROWCOUNT

Display **first 5 highest paid employees.**

```
DECLARE

CURSOR c1 IS
SELECT EName, Deptname, BasicSal
FROM EMP
ORDER BY BasicSal DESC;

v_name EMP.EName%TYPE;
v_dept EMP.Deptname%TYPE;
v_sal EMP.BasicSal%TYPE;

BEGIN

OPEN c1;

LOOP
FETCH c1 INTO v_name, v_dept, v_sal;

EXIT WHEN c1%NOTFOUND OR c1%ROWCOUNT > 5;
```

```
DBMS_OUTPUT.PUT_LINE(v_name || '  ' || v_dept || '  ' || v_sal);

END LOOP;

CLOSE c1;

END;
/
```

4) PL/SQL Block Using Cursor FOR LOOP
Display **top 3 highest paid employees.**

```
DECLARE

CURSOR c1 IS
SELECT EName, BasicSal
FROM EMP
ORDER BY BasicSal DESC;

i NUMBER := 0;

BEGIN

FOR rec IN c1 LOOP

i := i + 1;

EXIT WHEN i > 3;

DBMS_OUTPUT.PUT_LINE(rec.EName || '  ' || rec.BasicSal);

END LOOP;

END;
/
```

5) PL/SQL Block Using Parameterized Cursor
Displays **department wise salary and total gross salary**

```
DECLARE

CURSOR c1(p_dept NUMBER) IS
SELECT EName, BasicSal
FROM EMP
WHERE Deptno = p_dept;

v_total NUMBER := 0;

BEGIN

FOR rec IN c1(10) LOOP
```

```
DBMS_OUTPUT.PUT_LINE('Employee: ' || rec.EName ||
                     ' Salary: ' || rec.BasicSal);

v_total := v_total + rec.BasicSal;

END LOOP;

DBMS_OUTPUT.PUT_LINE('Total Salary of Dept 10 = ' || v_total);

END;
/
```