

Java Reflection

Programação III
José Luis Oliveira; Carlos Costa

1

What is reflection?

- When you look in a mirror:
 - You can see your reflection
 - You can act on what you see, for example, straighten your tie
- In computer programming:
 - Reflection is infrastructure enabling a program can see and manipulate itself
 - It consists of metadata plus operations to manipulate the metadata
- Meta means self-referential
 - So metadata is data (information) about oneself

Introduction to Java Reflection, Ciaran McHale.

What is reflection?

Reflection

- “Reflection is the ability of a program to manipulate as data something representing the state of the program during its own execution.” [Demers and Malenfant]

Java Tutorials

- “Reflection is commonly used by programs which require the ability to examine or modify the runtime behavior of applications running in the Java virtual machine.”
- “... advanced feature ... a powerful technique ... can enable applications to perform operations which would otherwise be impossible.”

3

Java looking at Java

- Reflection permite que um programa se examine a si mesmo.

Podemos:

- Determinar a classe de um objecto
- Descobrir toda a informação associada a determinada classe:
 - access modifiers, superclass, fields, constructors, and methods
- Obter informação relativa ao conteúdo de uma interface.
- Mesmo sem saber o nome (classes, métodos,...) podemos:
 - Criar uma instância de uma classe
 - ler/modificar variáveis
 - Invocar métodos
 - Criar e manipular vectores de objectos

Utilização de Java Reflection

- JavaBeans (component architectures)
- Database applications
- Serialization
- Scripting applications
- Runtime Debugging/Inspection Tools
- etc

5

Acesso a metadados

- Java armazena metadados em classes
 - Metadata for a class: `java.lang.Class`
 - Metadata for a constructor: `java.lang.reflect.Constructor`
 - Metadata for a field: `java.lang.reflect.Field`
 - Metadata for a method: `java.lang.reflect.Method`
- Podemos aceder à Class de um objecto de duas formas:

```
Class<?> c11 = Class.forName("java.util.Properties");  
ou  
Object obj = ... // e.g. new StringBuffer("Teste");  
Class<?> c12 = obj.getClass();
```
- As classes do package Reflection são inter-dependentes
 - Exemplos a seguir...

Metadata de tipos primitivos e vetores

- Java associa uma instância de Class a cada tipo primitivo:
`Class<?> c1 = int.class;`
`Class<?> c2 = boolean.class;`
`Class<?> c3 = void.class;`
- Podemos usar `Class.forName()` para aceder à classe de um vector
`Class<?> c4 = byte.class; // byte`
`Class<?> c5 = Class.forName("[B"); // byte[]`
`Class<?> c6 = Class.forName("[[B"); // byte[][]`
- Encoding scheme utilizado por `Class.forName()`
B → byte; C → char; D → double; F → float; I → int; J → long;
Lclass-name → class-name[]; S → short; Z → boolean
Use as many "["s as there are dimensions in the array

Reflection API - Class

```
public final class Class<T>
extends Object
implements Serializable, GenericDeclaration,
    Type, AnnotatedElement

    static Class<?> forName(String className);
    T newInstance();
    Field[] getFields();
    Method[] getMethods();
    boolean isInstance(Object obj);
    String getName();

    getInterfaces(), getSuperclass(),
    getModifiers(), getField(), getMethod(), ...

void printClassName(Object obj) {
    System.out.println("The class of " + obj +
        " is " + obj.getClass().getName());
}
```

8

Reflection API - Field

```
public final class Field
extends AccessibleObject
implements Member

    Object get(Object obj);
    void set(Object obj, Object val);

    getType(), getDeclaringClass(),
    setDouble(...), setInt(...), .....
```

```
Field[] flds = someObject.getClass().getFields();
for (Field f: flds)
    System.out.println(f.getName());
```

9

Reflection API - Method

```
public final class Method
extends AccessibleObject
implements GenericDeclaration, Member

    Object invoke(Object obj, Object... args);
    Class<?> getReturnType();
    Class<?>[] getParameterTypes();

    getExceptionTypes(), getDeclaringClass(),...
```

```
Method methods[] = someClass.getMethods();
for (Method m: methods)
    System.out.println(m);
```

10

Reflection API - others...

```
class Constructor<T>
class AccessibleObject
    ← Constructor,
    ← Field,
    ← Method
class Array;
class Proxy;
Class Modifier
```

java.lang.reflect

Interfaces

AnnotatedElement
GenericArrayType
GenericDeclaration
InvocationHandler
Member
ParameterizedType
Type
TypeVariable
WildcardType

Classes

AccessibleObject
Array
Constructor
Field
Method
Modifier
Proxy
ReflectPermission

Exceptions


InvocationTargetException
MalformedParameterizedTypeException
UndeclaredThrowableException

Errors

GenericSignatureFormatError

A Classe Class

- Para cada objecto carregado pela JVM, existe um objecto do tipo *Class* associado.
 - Os tipos primitivos também são representados por objectos *Class*.
- As instâncias do tipo *Class* armazenam informações sobre a classe:
 - Nome da classe
 - Herança
 - Interfaces Implementadas
 - Métodos
 - Atributos
- Permite invocar métodos e referenciar atributos



12

Métodos de java.lang.Class - 1

- `public static Class<?> forName(String className)`
 - returns a Class object that represents the class with the given name
- `public String getName()`
 - returns the full name of the Class object, such as "java.lang.String".
- `public int getModifiers()`
 - returns an integer that describes the class modifier: public, final or abstract
- `public T newInstance()`
 - creates an instance of this class at runtime

13

Exemplo - newInstance

```
public class ReflectionNew {  
    public static void main(String[] args) throws Exception {  
        Class<?> sc = Class.forName("aula5_1.Circulo");  
  
        System.out.println("Name = " + sc.getName());  
        System.out.println("SimpleName = " + sc.getSimpleName());  
        System.out.println("CanonicalName = " + sc.getCanonicalName());  
  
        Class<?>[] paramTypes = { Double.TYPE, Double.TYPE, Double.TYPE };  
        Constructor<?> cons = sc.getConstructor(paramTypes);  
        Object ar[] = { 2, 4, 10 };  
        Object theObject = cons.newInstance(ar);  
        System.out.println("New object: " + theObject);  
  
        Constructor<?> cs = sc.getConstructor(new Class<?>[]{Double.TYPE});  
        System.out.println("New object: " + cs.newInstance(new Object[]{20}));  
    }  
}
```

```
Name = aula5_1.Circulo  
SimpleName = Circulo  
CanonicalName = aula5_1.Circulo  
New object: Circulo de Centro (2.0,4.0) e de raio 10.0  
New object: Circulo de Centro (0.0,0.0) e de raio 20.0
```

14

Exemplo - Modifiers

```
public class SampleModifier {
    public static void main(String[] args) {
        printModifiers(new String());
        printModifiers(new SampleModifier());
    }
    public static void printModifiers(Object o) {
        Class<?> c = o.getClass(); // returns the Class object of o
        System.out.print("***** Class " + c.getName()+" : ");

        int m = c.getModifiers(); // return the class modifiers
        if (Modifier.isPublic(m)) // checks if is public
            System.out.print("public ");
        if (Modifier.isAbstract(m)) // checks if it is abstract
            System.out.print("abstract ");
        if (Modifier.isFinal(m)) // checks if it is final
            System.out.print("final "); System.out.println();
    }
}
```

```
***** Class java.lang.String : public final
***** Class reflection.SampleModifier : public
```

15

Métodos de java.lang.Class - 2

- `public Class[] getClasses()`
 - returns an array of all inner classes of this class
- `public Constructor[] getConstructors(Class[] params)`
 - returns all public constructors of this class whose formal parameter types match those specified by params
- `public Constructor[] getConstructors()`
 - returns all public constructors of this class

16

Exemplo - Construtores

```
public class Reflection2 {
    public static void main(String[] args) throws InstantiationException,
        IllegalAccessException {
        String s="Mar";
        Class<?> sc = s.getClass();
        System.out.println("\n***** Construtores *****\n");
        Constructor<?> contrs[] = sc.getConstructors();
        for (Constructor<?> c: contrs)
            System.out.println(c);
    }
}
```

```
***** Construtores *****
public java.lang.String()
public java.lang.String(java.lang.String)
public java.lang.String(char[])
public java.lang.String(char[],int,int)
public java.lang.String(int[],int,int)
public java.lang.String(byte[],int,int,int)
public java.lang.String(byte[],int)
public java.lang.String(byte[],int,int,java.lang.String) throws java.io.UnsupportedEncodingException
public java.lang.String(byte[],int,int,java.nio.charset.Charset)
public java.lang.String(byte[],java.lang.String) throws java.io.UnsupportedEncodingException
public java.lang.String(byte[],java.nio.charset.Charset)
public java.lang.String(byte[],int,int)
public java.lang.String(byte[])
public java.lang.String(java.lang.StringBuffer)
public java.lang.String(java.lang.StringBuilder)
```

17

Métodos de java.lang.Class - 3

- public Field getField(String name)
 - returns an object of the class Field that corresponds to the instance variable of the class that is called name
- public Field[] getFields()
 - returns all accessible public instance variables of the class
- public Field[] getDeclaredFields()
 - returns all declared fields (instance variables) of the class

18

Exemplo - Fields

```
public class Reflection2 {
    public static void main(String[] args) throws InstantiationException,
        IllegalAccessException {
        String s="Mar";
        Class<?> sc = s.getClass();
        System.out.println("\n***** Fields *****\n");
        Field fields[] = sc.getFields();
        for (Field f: fields)
            System.out.println(f);
    }
}
```

```
public static final java.util.Comparator java.lang.String.CASE_INSENSITIVE_ORDER
```

19

Exemplo - Fields

```
public static void main(String[] args) throws Exception {
    Class<?> sc = Class.forName("aula5_1.Circulo");
    System.out.println("\n***** Fields *****\n");
    Field fields[] = sc.getFields();
    for (Field f: fields)
        System.out.println(f);
    System.out.println("\n***** Declared Fields *****\n");
    Field dfields[] = sc.getDeclaredFields();
    for (Field f: dfields)
        System.out.println(f);
    System.out.println("\n***** raio Field *****\n");
    Field field = sc.getField("raio"); // deve usar-se getDeclaredField
    System.out.println(field);
}
```


```
***** Fields *****
***** Declared Fields *****
private double aula5_1.Circulo.raio
***** raio Field *****

Exception in thread "main" java.lang.NoSuchFieldException: aula5_1.Circulo.raio
at java.lang.Class.getField(Class.java:1520)
at reflection.Reflection2.main(Reflection2.java:39)
```

20

Ler atributos


```
class SampleGet {
    public static void main(String[] args) {
        Rectangle r = new Rectangle(100, 325);
        printHeight(r);
    }
    static void printHeight(Rectangle r) {
        Field heightField; //declares a field
        Integer heightValue;
        Class<?> c = r.getClass(); //get the Class object
        try {
            heightField = c.getField("height"); //get the field object
            heightValue = (Integer)heightField.get(r); //get the value of the
field
            System.out.println("Height: " + heightValue.toString());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```



21

Modificar atributos

```
class SampleSet {
    public static void main(String[] args) {
        Rectangle r = new Rectangle(100, 20);
        System.out.println("original: " + r.toString());
        modifyWidth(r, new Integer(300));
        System.out.println("modified: " + r.toString());
    }
    static void modifyWidth(Rectangle r, Integer widthParam ) {
        Field widthField; //declare a field
        Integer widthValue;
        Class<?> c = r.getClass(); //get the Class object
        try {
            widthField = c.getField("width"); //get the field object
            widthField.set(r, widthParam); //set the field to widthParam =300
        } catch (Exception e ) {
            // . . .
        }
    }
}
```



22

Métodos de java.lang.Class - 4

- public Method getMethod(String name, Class[] params)
 - returns an object Method that corresponds to the method called name with a set of parameters params
- public Method[] getMethods()
 - returns all accessible public methods of the class
- public Method[] getDeclaredMethods()
 - returns all declared methods of the class.
- public Package getPackage()
 - returns the package that contains the class
- public Class getSuperClass()
 - returns the superclass of the class

23

Exemplo - Métodos

```
public class Reflection2 {  
    public static void main(String[] args) throws InstantiationException,  
        IllegalAccessException {  
        String s="Mar";  
        Class<?> sc = s.getClass();  
        System.out.println("\n***** Métodos *****\n");  
        Method methods[] = sc.getMethods();  
        for (Method m: methods)  
            System.out.println(m);  
    }  
}
```

```
***** Métodos *****  
  
public boolean java.lang.String.equals(java.lang.Object)  
public java.lang.String java.lang.String.toString()  
public int java.lang.String.hashCode()  
  
.....  
public final native void java.lang.Object.notify()  
public final native void java.lang.Object.notifyAll()
```

24

Manipulação de vetores

```
public static void main(final String[] args) {
    try {
        String[] z = new String[] { "Jim", "John", "Joe" };
        final Class<?> type = z.getClass();
        if (!type.isArray()) {
            throw new IllegalArgumentException();
        } else {
            System.out.println("Name = " + type.getName() +
                               "\nType = " + type.getComponentType());
        }
    } catch (final Exception ex) {
        ex.printStackTrace();
    }
}
```

```
Name = [Ljava.lang.String;
Type = class java.lang.String
```

25

Manipulação de vetores

```
public class ArrayNew {
    public static void main(String[] args) throws ClassNotFoundException {
        System.out.println(createNativeArray("int", 12).getClass());
        System.out.println(createNativeArray("boolean", 10, 10).getClass());
        System.out.println(createNativeArray("double", 5, 5, 5).getClass());
    }
    public static Object createNativeArray(String typeName, int... dim)
    throws ClassNotFoundException {
        Class<?> clazz = null;
        if ("int".equals(typeName)) {
            clazz = Integer.TYPE;
        } else if ("boolean".equals(typeName)) {
            clazz = Boolean.TYPE;
        } else if ("double".equals(typeName)) {
            clazz = Double.class;
        } // All other native types: short, long, float .....
        else {
            throw new ClassNotFoundException(typeName);
        }
        return Array.newInstance(clazz, dim);
    }
}
```

```
class I
class IZ
class [[[Ljava.lang.Double;
```

26

Utilização de Plugins

```
public interface IPlugin {  
    public void metodo();  
}
```

IPlugin.java

```
public class Plugin1 implements IPlugin {  
    public void metodo() {  
        System.out.println("Plugin1: metodo invocado");  
    }  
}
```

Plugin1.java

```
public class Plugin2 implements IPlugin {  
    public void metodo() {  
        System.out.println("Plugin2: metodo invocado");  
    }  
}
```

Plugin2.java

```
public class Plugin3 implements IPlugin {  
    public void metodo() {  
        System.out.println("Plugin3: metodo invocado");  
    }  
}
```

Plugin3.java

27

Utilização de Plugins

```
package reflection;  
import java.io.File;
```

Plugin.java

```
abstract class PluginManager {  
    public static IPlugin load(String name) throws Exception {  
        Class<?> c = Class.forName(name);  
        return (IPlugin) c.newInstance();  
    }  
}
```

```
public class Plugin {  
    public static void main(String[] args) throws Exception {  
  
        File proxyList = new File("reflection/plugins");  
        for (String f: proxyList.list()) {  
            try {  
                IPlugin obj =  
                    PluginManager.load("reflection."+f.substring(0,f.lastIndexOf('.')));  
                obj.metodo();  
            }  
            catch (Exception e) {  
                e.printStackTrace();  
            }  
        }  
    }  
}
```

```
Plugin1: metodo invocado  
Plugin2: metodo invocado  
Plugin3: metodo invocado
```

28

Padrões: Fábrica sem reflection

```
class Viveiro {  
    public static Arvore factory(String pedido) {  
        if (pedido.equalsIgnoreCase("Figueira"))  
            { return new Figueira(); }  
        if (pedido.equalsIgnoreCase("Pessequeiro"))  
            { return new Pessequeiro(); }  
        if (pedido.equalsIgnoreCase("Nespereira"))  
            { return new Nespereira(); }  
        else  
            throw new IllegalArgumentException("Árvore não  
            existente!");  
    }  
}
```

29

Padrões: Fábrica com reflection

```
class Viveiro {  
    public static Arvore factory(String pedido){  
        Arvore arv = null;  
        try {  
            arv =  
(Arvore) Class.forName("patterns."+pedido).newInstance();  
        }  
        catch(Exception e) {  
            throw new IllegalArgumentException("Arvore nao  
            existente!");  
        }  
        return arv;  
    }  
}
```

30

java.lang.reflect.Proxy

- Proxy provides static methods for creating dynamic proxy classes and instances, and it is also the superclass of all dynamic proxy classes created by those methods.
- To create a proxy for some interface Foo:

```
InvocationHandler handler = new MyInvocationHandler(...);
Class proxyClass = Proxy.getProxyClass(
    Foo.class.getClassLoader(), new Class[] { Foo.class });
Foo f = (Foo) proxyClass.
    getConstructor(new Class[] { InvocationHandler.class }).
    newInstance(new Object[] { handler });
```

- or more simply:

```
Foo f = (Foo) Proxy.newProxyInstance(Foo.class.getClassLoader(),
    new Class[] { Foo.class },
    handler);
```

31

Criação de proxies

- Podemos criar dinamicamente um proxy usando o método `Proxy.newProxyInstance()`. Este método aceita 3 parâmetros:
 1. O `ClassLoader` que “carrega” dinamicamente a class proxy
 2. Um vector das interfaces implementadas
 3. Um `InvocationHandler` para reencaminhar as chamadas aos métodos

- Exemplo:

```
InvocationHandler handler = new MyInvocationHandler();
MyInterface proxy = (MyInterface) Proxy.newProxyInstance(
    MyInterface.class.getClassLoader(),
    new Class[] { MyInterface.class },
    handler);
```

- A variável proxy passa a referenciar uma implementação dinâmica da interface `MyInterface`.
- Todas as invocações ao proxy serão passadas à implementação do handler (do tipo `InvocationHandler`)

32

Proxy - utilização

- Database Connection and Transaction Management
- Dynamic Mock Objects for Unit Testing
- Adaptation of DI Container to Custom Factory Interfaces
- AOP-like Method Interception
- ..

33

Dynamic Proxy Classes

```
package reflection;

import java.lang.reflect.InvocationHandler;
import java.lang.reflect.Method;
import java.lang.reflect.Proxy;

interface MyInterface {
    void method();
}

class MyInterfaceImpl implements MyInterface {
    public void method() {
        System.out.println("method");
    }
}

class MyInterfaceImpl2 implements MyInterface {
    public void method() {
        System.out.println("outro método");
    }
}
```

34

Dynamic Proxy Classes

```
class ProxyClass implements InvocationHandler {
    Object obj;

    public ProxyClass(Object o) {
        obj = o;
    }

    public Object invoke(Object proxy, Method m, Object[] args) throws Throwable
    {
        Object result = null;
        try {
            System.out.println("before the method is called ");
            result = m.invoke(obj, args);
        } catch (Exception eBj) {
        } finally {
            System.out.println("after the method is called");
        }
        return result;
    }
}
```

35

Dynamic Proxy Classes

```
public class ProxySample {
    public static void main(String[] argv) throws Exception {

        MyInterface myintf =
            (MyInterface) Proxy.newProxyInstance(MyInterface.class.getClassLoader(),
                new Class[] { MyInterface.class },
                new ProxyClass(new MyInterfaceImpl()));
        myintf.method();

        myintf =
            (MyInterface) Proxy.newProxyInstance(MyInterface.class.getClassLoader(),
                new Class[] { MyInterface.class },
                new ProxyClass(new MyInterfaceImpl2()));
        myintf.method();
    }
}
```

```
before the method is called
method
after the method is called
before the method is called
outro método
after the method is called
```

36