

A Algorithms

Algorithms 1 and 2 outline the balancing procedures implemented for this purpose.

Algorithm 1 Balance Dataset by Gender

Require: Dataset D , Objective $\text{objective} \in \{\text{Mentions}, \text{Targets}\}$

Ensure: Balanced Dataset $\tilde{D}$

```
1:  $s_k \leftarrow \infty$  for all  $k \in \{0, 1, 2\}$ .
2: for all  $v \in \{\text{"violent"}, \text{"non-violent"}\}$  do
3:   for all  $g \in \{\emptyset, \{M\}, \{F\}, \{M, F\}\}$  do
4:      $s_{|g|} \leftarrow \min\{s_{|g|}, |D_{v,g}|\}$ .
5:   end for
6: end for
7:  $s_0 \leftarrow \min\{s_0, s_1 + \lfloor \frac{s_2}{2} \rfloor\}$ 
8: Initialize  $\tilde{D} \leftarrow \emptyset$ .
9: for all  $v \in \{\text{"violent"}, \text{"non-violent"}\}$  do
10:  for all  $g \in \{\emptyset, \{M\}, \{F\}, \{M, F\}\}$  do
11:     $S \leftarrow \text{Sample } s_{|g|} \text{ rows from } D_{v,g}$ .
12:     $\tilde{D} \leftarrow \tilde{D} \cup S$ .
13:  end for
14: end for
15: return  $\tilde{D}$ .
```

Algorithm 2 Debias Dataset by Gender

Require: Dataset D , Objective $\text{objective} \in \{\text{Mentions}, \text{Targets}\}$

Ensure: Debaised Dataset $\tilde{D}$

```
1:  $s_g \leftarrow \infty$  for all  $g \in \{\emptyset, \{M\}, \{F\}, \{M, F\}\}$ .
2: for all  $v \in \{\text{"violent"}, \text{"non-violent"}\}$  do
3:   for all  $g \in \{\emptyset, \{M\}, \{F\}, \{M, F\}\}$  do
4:      $s_g \leftarrow \min\{s_g, |D_{v,g}|\}$ .
5:   end for
6: end for
7: Initialize  $\tilde{D} \leftarrow \emptyset$ .
8: for all  $v \in \{\text{"violent"}, \text{"non-violent"}\}$  do
9:   for all  $g \in \{\emptyset, \{M\}, \{F\}, \{M, F\}\}$  do
10:     $S \leftarrow \text{Sample } s_g \text{ rows from } D_{v,g}$ .
11:     $\tilde{D} \leftarrow \tilde{D} \cup S$ .
12:   end for
13: end for
14: return  $\tilde{D}$ .
```
