ECE 14:332:456, NETWORK CENTRIC PROGRAMMING Assignment 3: Concurrent Web Proxy

1 Introduction

In this assignment, you are required to upgrade your sequential Basic Web Proxy of Assignment 2 so that it uses threads or processes to deal with multiple clients concurrently. That is, if your proxy is waiting for some event on behalf of one connection, it should be able to able to handle events for other connections as well. This part will give you some experience with concurrency and synchronization, which are crucial computer systems concepts. You will be required to implement **two** versions of the concurrent web proxy: a **threaded version** and a **multi-process version**.

2 Handout Instructions

There is no handout for this assignment as the code written for the sequential Basic Web Proxy serves as the code base for the Concurrent Web Proxy. You may either use your own implementation of the Web Proxy or the proxy.c (a sample solution to Basic Web Proxy in Resources section on Sakai) as your code base. You will have to reorganize the code base and write additional code to make it work for Concurrent proxy. Maintain the same project directory structure as in Assignment 2.

3 Implementation

Real proxies do not process requests sequentially. They deal with multiple requests concurrently. Once you have a working sequential logging proxy (Assignment 2), you should alter it to handle multiple requests concurrently. Following are are two approaches to achieve concurrency;

- 1. Process based using file locking for synchronization: Create a new process to deal with each new connection request that arrives
- 2. Thread based using mutexes for synchronization: Create a new thread to deal with each new connection request that arrives.

You are required to implement both the versions.

Additionally, you need to ensure the following:

- The proxy should log all client requests to a shared log file proxy.log
- Access to shared resources like the log file is synchronized. Logging format and requirements is same
 as that of Assignment 2. For example, in the multithreading approach, it is possible for multiple peer
 threads to access the log file concurrently. Thus, you will need to use a semaphore to synchronize
 access to the file such that only one peer thread can modify it at a time. If you do not synchronize the
 threads, the log file might be corrupted. For instance, one line in the file might begin in the middle of
 another
- Your multithreaded version should be thread-safe. Protect calls to thread unsafe functions such as gethostbyaddr and gethostbyname to keep these functions thread safe. (A piece of code is **thread-safe** if it only manipulates shared data structures in a manner that guarantees safe execution by multiple threads at the same time)

Please note that the concurrent proxy is an extension of the Basic Web proxy and thus contains all the functionalities and features mandated by Assignment 2

4 Testing your Proxy

For this assignment too, there is no script to check your implementation. You will have to come up with your own tests to help you debug your code and decide when you have a correct implementation. Below is one way by which you can test your proxy.

- Open a connection to your proxy using telnet, and then leave it open without typing in any data.
- Use a Web browser (pointed at the proxy) to request a simple Web from some end server

5 Submission and Demo Instructions

You will need to submit your complete project directory on Sakai.

To receive full credit, your solution needs to be well-commented (in your own words, of course). At the top of your source code file, please include a comment of about 2 paragraphs explaining how your program solves this assignment. At the start of every function in your program explain what this function does in 1-5 sentences, depending on the complexity of the function. Include a short comment every 3-5 program lines explaining what the next sequence of code will accomplish. Add additional comments for non-obvious lines of code or parameters to explain how this works. Note that deductions for completely uncommented code can be substantial.

- Create a gzipped tar ball that includes all your source code.
- The filename for the tarball must be username-concurrent-proxy.tar.gz.
- All your files in the tarball must be in a directory, named username-concurrent-proxy

The submission will be due on the date mentioned on Sakai. After the submission date, you will have to give a demo, of the exact implementation that you submitted on Sakai, at a time that we will announce later on Sakai.