

CPSC-354 Report

Brandon Foley
Chapman University

September 21, 2025

Abstract

Contents

1	Introduction	1
2	Week by Week	1
2.1	Week 1	1
2.1.1	Homework	1
2.1.2	Questions	2
2.2	Week 2	2
2.2.1	Homework	2
2.2.2	Questions	5
2.3	Week 3	5
2.3.1	Homework	5
2.3.2	Questions	6
2.4	Week 4	6
2.4.1	Homework	6
2.4.2	Questions	7
3	Essay	8
4	Evidence of Participation	8
5	Conclusion	8

1 Introduction

2 Week by Week

2.1 Week 1

2.1.1 Homework

Here is my work on the MU Puzzle:

$$MIU \rightarrow MIUIU \rightarrow MIUIUIU \rightarrow \dots$$

$$MI \rightarrow MII \rightarrow MIII \rightarrow MUI \Rightarrow MUI$$

$$MUI \rightarrow MUIU$$

$$MUI \rightarrow MUIU \rightarrow MUIUIU \rightarrow MUIUIUIU \rightarrow MUUIU \rightarrow MUUIUIU \rightarrow \dots$$

$$MUIIU \rightarrow MUIIUUIU \rightarrow MUIU$$

$$MUIIU \rightarrow MUUIU \rightarrow MUIU$$

$$MUIU \rightarrow MUUIU \rightarrow MUIUIU \rightarrow MUIUIUIU \rightarrow \dots$$

$$MUIUIUIU \rightarrow MUIUIUIUIU \rightarrow MUIUIUIUIUIU \rightarrow \dots$$

The MU Puzzle is unsolvable because it is impossible to reach the string MU starting from MI using the given rules. After a little research and thinking on my part it is the number of I's that make this impossible: rule applications can double the count, add one, or remove three at a time, however, none of these operations ever reduce the number of I's to exactly zero. Since MU has no I's, it can never be derived.

2.1.2 Questions

What rules could we add or remove in order to make this possible? I was thinking are there any ways to make this question solvable by adding only one more rule or maybe altering a rule. I think that this is an interesting question and concept.

2.2 Week 2

2.2.1 Homework


Here is my work on the Rewriting Homework:

Rewriting


1. $A = \{\}$




2. $A = \{a\}$ $R = \{\}$




3. $A = \{a\}$ $R = \{(a, a)\}$




4. $A = \{a, b, c\}$ $R = \{(a, b), (a, c)\}$




5. $A = \{a, b\}$ $R = \{(a, a), (a, b)\}$



6. $A = \{a, b, c\}$ $R = \{(a, b), (b, b), (a, c)\}$



7. $A = \{a, b, c\}$ $R = \{(a, b), (b, b), (a, c), (c, c)\}$



0 = false C = confluent
 1 = true + = terminating
 U = unique normal form

	Confluent	terminating	unique normal form
1.	1	1	1
2.	0	1	1
3.	1	0	1
4.	0	1	0
5.	1	0	1
6.	0	0	1
7.	0	0	0

	C	+	U	A	R
2.	1	1	1	$A = \{a\}$	$R = \{\}$
	1	1	0	X	X
5.	1	0	1	$A = \{a, b\}$	$R = \{(a, a), (a, b)\}$
	1	0	0	X	X
	0	1	1	X	X
4.	0	1	0	$A = \{a, b, c\}$	$R = \{(a, b), (a, c)\}$
6.	0	0	1	$A = \{a, b, c\}$	$R = \{(a, b), (a, c), (b, b)\}$
	0	0	0	$A = \{a, b, c, d, e, f\}$	$R = \{(a, b), (a, c), (b, d), (c, e), (f, f)\}$

$$\begin{array}{ccc}
 a & \rightarrow & b \\
 \downarrow & & \downarrow \\
 c & & d \\
 & \searrow & \\
 & e & \text{FR}
 \end{array}$$

In our homework we discovered 3 separate combinations that are impossible to create. The first confluent, terminating and no unique normal form is impossible because if a system is confluent and terminating then it must have a unique normal form. The second confluent, not terminating and no unique normal form is impossible because if a system is confluent but not terminating then it must have a unique normal form when it exists. The third not confluent, terminating and unique normal form is impossible because if a system is terminating and has a unique normal form then it must be confluent.

2.2.2 Questions

When relating to programming, if a system is confluent but not terminating, like in some programs with infinite loops, how does confluence still guarantee that the result of a program is unique when it exists?

2.3 Week 3

2.3.1 Homework

Here is the work on ARS rewriting HW:

Exercise 5:

- Reduce some example strings such as **abba** and **bababa**.

$$abba \rightarrow baba \rightarrow baab \rightarrow bb \rightarrow b \rightarrow \{\}$$

$$bababa \rightarrow baabba \rightarrow bbba \rightarrow bba \rightarrow ba \rightarrow a$$

- Why is the ARS not terminating?
The ARS is not terminating because you can infinitely go from ab to ba and vice versa.
- How many equivalence classes does $\leftrightarrow^*$ have? Can you describe them in a nice way? What are the normal forms?
There are two equivalence classes: words with an even number of a 's vs words with an odd number of a 's.
The normal forms are the empty string $\{\}$ and the string **a**.
- Can you change the rules so that the ARS becomes terminating without changing its equivalence classes?
You can change $ba \rightarrow ab$ to $ba \rightarrow b$. This keeps the same equivalence classes but makes the system terminating.
- Write down a question or two about strings that can be answered using the ARS.
 - Does this string reduce to the empty string?
 - Are two given strings equivalent under the ARS?

Exercise 5b:

- Reduce some example strings such as **abba** and **bababa**.

$$abba \rightarrow baba \rightarrow baab \rightarrow bab \rightarrow ba \rightarrow a$$

$$bababa \rightarrow baabba \rightarrow babba \rightarrow baba \rightarrow aba \rightarrow aa \rightarrow a$$

- Why is the ARS not terminating?
The ARS is not terminating because you can infinitely go from ab to ba and vice versa.
- How many equivalence classes does $\leftrightarrow^*$ have? Can you describe them in a nice way? What are the normal forms?
There is one equivalence class: all words reduce to one a .
The normal form is just **a**.

- Can you change the rules so that the ARS becomes terminating without changing its equivalence classes?
You can change $ba \rightarrow ab$ to $ba \rightarrow b$. This keeps the same equivalence classes but makes the system terminating.
- Write down a question or two about strings that can be answered using the ARS.
 - Is there a unique normal form for this ARS?
 - Are two given strings equivalent under the ARS?

Bonus: Exercise 8

- Starting configuration:

$aaaaaaaaaaaaabbbbbbbbbbbcccccccccc$
 $\rightarrow^* acccccccccccccccccccccccccccccc$
 $\rightarrow bcccccccccccccccccccccccccccccc$
 $\rightarrow^* bbbbbbbcccccccccccccccccccccccc$

- It is impossible to reach a configuration of only a 's, only b 's, or only c 's.
- At each step, the rules correspond to the following change-vectors:

$$(a - 1, b - 1, c + 2), \quad (a - 1, b + 2, c - 1), \quad (a + 2, b - 1, c - 1)$$

- Reducing these modulo 3 gives

$$(-1, -1, -1)$$

for each move (since $+2 \equiv -1 \pmod{3}$).

- Thus, we can simply subtract the numbers of a 's, b 's, and c 's directly:

$$a - b = 15 - 14 = 1 \pmod{3}$$

$$b - c = 14 - 13 = 1 \pmod{3}$$

- Since these differences never reduce to 0, there will always be one leftover letter that prevents the string from reducing to a uniform string of only a 's, b 's, or c 's.

Questions Given the rules for changing letters in Exercise 8 ARS, why is it impossible to end up with a string containing only one type of letter, and how can we use modular arithmetic to prove it?

2.4 Week 4

2.4.1 Homework

HW 4.1

Consider the following algorithm:

```

while b != 0:
    temp = b
    b = a mod b
    a = temp
return a

```

Under certain conditions this algorithm always terminates. In order for the algorithm to terminate:

- $b \geq 0$
- $a \geq 0$
- a and b must be integers, since doubles may cause unexpected mod results

A suitable measure function is:

$$m(a, b) = b$$

Proof of termination: Each iteration replaces b with $a \bmod b$, which is always strictly smaller than the previous b but still nonnegative. Since b is a nonnegative integer, it cannot decrease indefinitely, so eventually $b = 0$ and the loop terminates.

HW 4.2

Consider the following fragment of an implementation of merge sort:

```
function merge_sort(arr, left, right):  
    if left >= right:  
        return  
    mid = (left + right) / 2  
    merge_sort(arr, left, mid)  
    merge_sort(arr, mid+1, right)  
    merge(arr, left, mid, right)
```

We define the measure function:

$$m(left, right) = right - left + 1$$

Proof:

- m maps to positive integers when $left \leq right$ since $m \geq 1$. If $left \geq right$ the function returns immediately (base case).
- If $left < right$ then $left \leq mid < right$, so both recursive calls shrink the measure:

$$m(left, mid) = mid - left + 1 < right - left + 1 = m(left, right)$$

$$m(mid + 1, right) = right - mid < right - left + 1 = m(left, right)$$

Thus both recursive calls are on strictly smaller natural numbers.

- The natural numbers have no infinite strictly decreasing sequence, so repeated decreases of m force termination.

Therefore $m(left, right) = right - left + 1$ is a valid measure function for `merge_sort`: it is integer-valued, nonnegative, and strictly decreases on every recursive call.

2.4.2 Questions

Question: In a recursive backtracking algorithm, the procedure explores possible options and recurses until either a valid solution is found or all possibilities are exhausted. Since recursion can branch in many ways, how can we define a measure function that guarantees termination of the backtracking process, and what does this reveal about the relationship between the number of remaining choices and the maximum recursive depth?

3 Essay

4 Evidence of Participation

5 Conclusion

References

[BLA] Author, [Title](#), Publisher, Year.