

Programmer – C++ Evaluation and Problem Question

Programmer - C++ Evaluation - Part 1 of 2

Specification:

Design and Implement a C++ program that implements the following:

- 2D Rectangle Class with floating point coordinates
 - Include methods for constructing an axis-aligned Rectangle with initial size and coordinates
 - o Include a Copy constructor and an Assignment operator
- Algorithm that checks whether or not a 2D point is contained in an axis-aligned Rectangle
- Algorithm that checks whether or not two axis-aligned Rectangles intersect
- Simple test code that creates instances of your class and tests your implementation

Given:

You can use this class in your implementation. Feel free to modify this class as well.

```
class Point2D
{
     float x;
     float y;
};
```

Programmer - Problem Question - Part 2 of 2

Multiples of 2, 3, 5

Consider a series in ascending order that only consists of numbers that can be factored by any combination of 2, 3 and 5. e.g. 1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15....

For example the numbers 7 (prime), 13 (prime) or 14 (2*7, 7 is not a valid factor), are not in the above series. They are not factorable by 2, 3, 5. The number 1 is included by definition.

For example, the number in position 18 would be 30:

```
1.
         1
         2
2.
         3
3.
         4 = 2*2
4.
5.
         5
6.
         6 = 2*3
         8 = 2*2*2
7.
8.
         9 = 3*3
9.
         10=2*5
         12=2*2*3
10.
         15=3*5
11.
         16=2*2*2*2
12.
         18=2*3*3
13.
14.
         20=2*2*5
```

15. 24=2*2*2*3 16. 25=5*5 17. 27=3*3*3 18. 30=2*3*5

Question:

Design an algorithm to find the number that occupies position 1500 in this series. NOTE: the correct answer is 859963392, use this to verify your algorithm.

Please be prepared to discuss your solution/solutions to this problem, as well as the steps you used to arrive at the solution.