

SeedHammer II — the hashlock vault

Six seeds, three engraved passphrases, four degrading tiers, one taproot tree.

A wallet that hands control on in stages. Three keys and a passphrase can spend today; two other keys and a second passphrase can spend after a relative delay; a sixth key alone can spend after an absolute height; and after a longer height **a passphrase alone** can spend — no key at all.

```
tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(edeb28a805feca09a77c48f82babc1249c79aa840de94fa4a85bf55a453c813),multi_a(3,@0/270028'/0'/0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768),and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad),multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*))),{and_v(v:after(1173520),pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520),sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708637dddf771c36d214056954))}}})
```

tier	who can spend	when
1	3-of-3 (@0,@1,@2) + passphrase A	any time
2	2-of-2 (@3,@4) + passphrase B	older(32768) — relative, ~7.6 months after funding
3	@5 alone	after(1173520) — 963,520 + 210,000
4	passphrase C alone	after(1383520) — 963,520 + 420,000

Test material only — never put funds behind these keys.

The six seeds come from entropy 0x0...01 through 0x0...06 and the three passphrases are printable strings in `derive-hashvault-keys.sh`. Everything here is regenerable by design; that is the point, and it is also why it is worthless.

The internal key is the BIP-341 NUMS point

, so there is no key-path spend and every spend reveals which tier was used.

The source material

One seed per key, so every key has its own master fingerprint. That is the difference from this constellation's other multi-key journey, where three masters supplied eleven keys across four accounts.

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-0.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon diesel
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-1.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon abandon false
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-2.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon abandon kite
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-3.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon abandon organ
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-4.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon abandon ready
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/seeds/key-5.seed
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon
don abandon abandon abandon abandon abandon abandon abandon surface
[exit 0]
```

Derived at the constellation's own path

m/270028'/coin'/account'/script' — purpose 270028' reads bg002h in a single component, and level 4 is the script type with 0' = tr. Ruled 2026-08-18.

The ruling had no implementation until this journey needed it.

ms_derive offered only the BIP templates and mk_derive --path is relative-and-unhardened-only, so nothing in the constellation could derive at its own path. ms_derive --template bq002h-tr is what closed that.

```
$ ./scratch/code/shibboleth/mnemonic-secret/target/release/ms derive --phrase abandon abandon abandon abandon abandon abandon
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon aban
don abandon diesel --template bg002h-tr --account 0
warning: secret material on argv (--phrase) - pipe via --phrase - to avoid /proc/$PID/cmdline exposure
master_fingerprint: 39ec1b6e
account_path: m/270028'/0'/0'/0'
account_xpub: xpub6E6MpT6t5MBYlPoaJ5rEJ4DN5E73e58TWta6SVLs4eYpJ6hDNKqhwLxFcVmuTJnDSQJpdKThXEma9t23WiHrYAJbK9GUu672nJH
HFenKt88
language: english (DEFAULT)
note: --language defaulted to english; the master fingerprint and xpub depend on the wordlist language (record it alongside
the backup)
note: stdout is watch-only - public keys only, cannot spend
[exit 0]
```

The six key files this produced:

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-0.xpub
# @0 - tier 1 - 3-of-3 with hash A, spendable at any time
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000001 (TEST ONLY), origin [39ec1b6e/270028'/0'/0']
xpub6E6MpT6SMBY1Poj5rEJ4DN5E73e58TWta6SVLs4eYpJ6hDNKqhwLxFcvMutJnDSQJpdKThXEma9t23WiHhRYAJbK9GUu672njHHFenKt88
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-1.xpub
# @1 - tier 1 - 3-of-3 with hash A, spendable at any time
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000002 (TEST ONLY), origin [d02bcdcf/270028'/0'/0']
xpub6F5JjvRbObuuiwNQLy9ifRCK1HbewqyYk3PkMPNsrgkPcGGuDYXdYUDmHqMsQeBzq58tf8eRXLtWJPaa1pcE9TmRZTAFVkvU61UxQtMUNFj
[exit 0]
```

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-2.xpub
# @2 - tier 1 - 3-of-3 with hash A, spendable at any time
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000000 (TEST ONLY), origin [5fd78eb3/270028'/0'/0'/0']
xpub6EaVZPPwamQQKVnw8V5wJjXHJHC4hqX3ET8wLc9cWnCMzUgNZ2Gx4B7u9PQHUE9KrPgrRVZnt2oXakKwFeQ3WuWKekiN1TKGzUat5vPAfKT
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-3.xpub
# @3 - tier 2 - 2-of-2 with hash B, after older(32768) relative
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000004 (TEST ONLY), origin [92c4c8b2/270028'/0'/0'/0']
xpub6DkD3EFiJE6o9VL2wwc5x9aSkZG7GVQzEEYPdaJwCGUfYza5Rsrl1xk25aG9J29cfHpyxEr6L39oH4mTmtJXVKK7KPVtVgT7HznajRzKepK
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-4.xpub
# @4 - tier 2 - 2-of-2 with hash B, after older(32768) relative
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000005 (TEST ONLY), origin [086c047e/270028'/0'/0'/0']
xpub6EEvgwBtdaoGsFWY6pNAuYMyWfCYrPivnW1zLM7myyvjhrSgVxwgmqHFjBuY54o7tJbacmtFvT3UGWta9PZXPTbf575rfBAvdHS6FDGxkC1
[exit 0]

$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/keys/key-5.xpub
# @5 - tier 3 - sole key, after(1173520) absolute
# seed entropy 0x0000000000000000000000000000000000000000000000000000000000000006 (TEST ONLY), origin [cef8224c/270028'/0'/0'/0']
xpub6E6vdTn7c2KFho1tuTeb9SPYiHxmFPsXSzgLzphMMDBu6LHJzjDSX8Huf6sy9cZb3Bwwib3ZY92P1RPqPhcR4X7thfAzzhHELKrSJqdGm2EL
[exit 0]
```

The passphrases, and what the policy commits to

These are engraved as TEXT + QR plates rather than as ms1: ms encode takes a BIP-39 mnemonic or hex entropy, and these are human passphrases.

The hash is over the UTF-8 bytes with NO trailing newline.

printf %s, never echo. A stray \n changes the hash, and the tier it belongs to is then locked forever — with a plate beside it that looks correct.

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/preimages/preimage-0.txt
correct horse battery staple vault alpha
$ printf %s '<that file>' | sha256sum
ede0b28a805feca09a77c48f82babc1249c79aa840de94fa4a85bf55a453c813
```

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/preimages/preimage-1.txt
seven bridges over a quiet river bravo
$ printf %s '<that file>' | sha256sum
9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad
```

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/inputs-hashvault/preimages/preimage-2.txt
the last plate rings twice charlie
$ printf %s '<that file>' | sha256sum
4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708637dddf771c36d214056954
```

Tier 4 has no key, and the default parser refuses it

rust-miniscript answers All spend paths must require a signature. That is a **safety policy, not a language rule**: `and_v(v:after(N),sha256(H))` is well-formed miniscript that compiles to valid script. `sanity_check()` applies five rules and `requires_sig()` is the first; the library documents them as guarantees rather than validity — "results cannot be relied upon" — and ships `ExtParams` precisely so individual rules can be relaxed.

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md encode tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d54
7bfee9ace803ac0,{and_v(v:sha256(ede0b28a805fec09a77c48f82bab1249c79aa840de94fa4a85bf55a453c813),multi_a(3,@0/270028'/0'/
0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768),and_v(v:sha256(9ce09a8df1d1f8b
c8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad),multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*))),{and
_v(v:after(1173520),pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520),sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708
637dddf771c36d214056954))}})) --group-size 0
md: template parse error: miniscript parse failed: All spend paths must require a signature
[exit 1]

--- and with the flag ---

$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md encode tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d54
7bfee9ace803ac0,{and_v(v:sha256(ede0b28a805fec09a77c48f82bab1249c79aa840de94fa4a85bf55a453c813),multi_a(3,@0/270028'/0'/
0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768),and_v(v:sha256(9ce09a8df1d1f8b
c8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad),multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*))),{and
_v(v:after(1173520),pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520),sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708
637dddf771c36d214056954))}})) --group-size 0 --experimental
chunk-set-id: 0x32d89
md1fxtvfpspp2040veppppqqu2nxh0duzeg4qzlj5f5a7y37pt40qj8re42zqmcu2f6fyh39ju2s
md1fxtvfps2205j59ha26g57gzvsyypg2nxhqzqqqxhvuuzdgmuw3lz7g3yjjr2g6r2u6yrzhvgt3
md1fxtvfpshtxrg2rz78mwqmkran74xxmyryu7mk45szuz5e4kqq3aqqz4fntvqp2q45nzqzs5e3s8r
md1fxtvfpslrqw5ws7hc37ly8ffu0knmlk96rq23pxvcfgvd7amam3cdkjzskj4qqldk6mrjrhcc87
warning: --experimental relaxed the signature rule. This descriptor has at least one spend path that needs NO key, so whoever
r learns its preimage can spend it alone. If that preimage is engraved, THE PLATE IS BEARER ACCESS. Malleability, resource l
imits, repeated keys and timelock mixing were still checked.
note: stdout is a keyless descriptor template (no keys)
[exit 0]

The engraved template set is 4 md1 chunk(s).
```

--experimental relaxes ONLY that rule.

Malleability, resource limits, repeated keys and timelock mixing are still enforced per leaf — those admit scripts that are *unspendable* rather than merely unguaranteed, which is a worse class of mistake. And it warns on every use, because the card carries no record that a flag authored it.

What tier 4 means in practice.

After block 1,383,520, whoever holds passphrase C can spend this wallet alone. That passphrase is engraved on a plate. **The plate is bearer access.** That is the design, not an oversight — but it is the reason this wallet's plates are not all equal, and the reason the passphrase plates want a different hiding place from the key plates.

The cards

The keyless template — what gets engraved

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md verify --template tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(ede0b28a805feca09a77c48f82babc1249c79aa840de94fa4a85bf55a453c813)},multi_a(3,@0/270028'/0'/0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768)},and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad)},multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:after(1173520)},pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520)},sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708637ddd771c36d214056954))}}}) md1fxtvfpspp2040veppppqxxqu2nxh0duzeg4qzljajsf5a7y3pt40qjf8re42zqmcu2f6fyh39ju2s md1fxtvfps2205j59ha26g57gzvsyypg2nxhqqzqqqnxhvuuzdgmw3lz7g3yjr2g6r2u6yrzhvgt3 md1fxtvfpshtxrg2r278mwqmkran74xxmyryu7mk45szuz5e4kq3aaggz4fntvqp2q45nzqzs5e3s8r md1fxtvfpslrqw5ws7hc37ly8ffu0knmlk96rq23pxvcfcgvd7amam3cdkjszskj4qqldk6mrjrhcc87 --experimental
OK
[exit 0]
```

What the cards carry

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md inspect md1fxtvfpspp2040veppppqxxqu2nxh0duzeg4qzljajsf5a7y3pt40qjf8re42zqmcu2f6fyh39ju2s md1fxtvfps2205j59ha26g57gzvsyypg2nxhqqzqqqnxhvuuzdgmw3lz7g3yjr2g6r2u6yrzhvgt3 md1fxtvfpshtxrg2r278mwqmkran74xxmyryu7mk45szuz5e4kq3aaggz4fntvqp2q45nzqzs5e3s8r md1fxtvfpslrqw5ws7hc37ly8ffu0knmlk96rq23pxvcfcgvd7amam3cdkjszskj4qqldk6mrjrhcc87
template: tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(ede0b28a805feca09a77c48f82babc1249c79aa840de94fa4a85bf55a453c813)},multi_a(3,@0/270028'/0'/0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768)},and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad)},multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:after(1173520)},pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520)},sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708637ddd771c36d214056954))}}})
n: 6
wallet-policy-mode: false
md1-encoding-id: 32d898ab04d9725fe084ffe360e1c2f4
wallet-descriptor-template-id: 68a1a88838579733ce5debc90cfb1e
origins:
  @0: m/270028'/0'/0'/0'
  @1: m/270028'/0'/0'/0'
  @2: m/270028'/0'/0'/0'
  @3: m/270028'/0'/0'/0'
  @4: m/270028'/0'/0'/0'
  @5: m/270028'/0'/0'/0'
wallet-policy-id: f97fdce3d1d0096f9fe7f8bc82f5648b
wallet-policy-id-fingerprint: 0xf97fdce3
note: stdout is a keyless descriptor template (no keys)
[exit 0]
```

The keyed set, and the bind

Two card sets, one wallet. The **template id** is key-stable, so it is the same across the keyless and keyed forms — which is exactly what makes it the right thing to compare.

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md encode tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(ede0b28a805feca09a77c48f82babc1249c79aa840de94fa4a85bf55a453c813)},multi_a(3,@0/270028'/0'/0'/0'/<0;1>/*,@1/270028'/0'/0'/0'/<0;1>/*,@2/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:older(32768)},and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad)},multi_a(2,@3/270028'/0'/0'/0'/<0;1>/*,@4/270028'/0'/0'/0'/<0;1>/*)),{and_v(v:after(1173520)},pk(@5/270028'/0'/0'/0'/<0;1>/*)),and_v(v:after(1383520)},sha256(4743d7c47df21d29e3ed3dfec5d0c0a884ccc2708637ddd771c36d214056954))}}}) --key @0=xpub6E6MpT6SMBY1Poaj5rEJ4DN5E7f3e58TWta6SVLS4eYpJ6hDNKqhwLxFcvMuTJnDSQJpdKThEma9t23WiHhrYAJbK9GUu672njHHFenKt88 --fingerprint @0=39ec1b6e --key @1=xpub6F5JrVbobbuiwNQLy9iFRCK1HbewqYk3PkMPNsrgkPcGGuDYXdYUDMHqMsQeBzQ58t7f8eRXLtWJPaa1pcE9TmrZTAfVkJ7U61UxQtMUNfj --fingerprint @1=d02bcedf --key @2=xpub6EaVZPPwamQQKvNw85vJjXJHC4hqX3ET8wLc9CwNcmZUgN22Gx4B7u9PQHUE9KrPgrRVZnt2oXakKwFeQ3WuWkKiN1TKGzUat5vPAfKt --fingerprint @2=5fd78eb3 --key @3=xpub6DkD3EFiJE6o9VL2wvc5x9aSkG7GVQzEEYPdaJwCGUfYza5Rsrl1xk25aG9J29cfHpyxEr6L39oH4mTmtJXVKK7KPvtVgT7HznajRzKepK --fingerprint @3=92c4c8b2 --key @4=xpub6EEvgwBtdaoGsFW6pNAuYMyWfCYrPivnW1zLM7myyvjhrSgVxwgmqHFjBuY54o7tJbacmtFvT3UGWta9PZXPtbF575rfBAVdHS6FDGxKC1 --fingerprint @4=086c047e --key @5=xpub6E6vdtN7c2KFho1tuTeb9SPYiHxmFPsXZgZlpMMDBu6LHZjD5X8Huf6sy9cZb3Bwwib3ZY92P1RPqPhcR4X7thfAzzhHELKR5JqdGm2EL --fingerprint @5=cef8224c --group-size 0 --experimental
chunk-set-id: 0x5c65a
md1ft3j68qpp2040veppppqxxqu2nxh0duzeg4qzljajsf5a7y3pt40qjf8re42zqm6205jszsc4se5llmr2r
md1ft3j68q2zm74dy20yypxgzzq59fntsqppqqfntkwpx5d78gl30ygfzpj484np59p30rsc4yeyz26j9m5u
md1ft3j68qkmsxaslv14f3keqe88ka4dyqshq4xddsqy0gzq42v6mqz23ccr4r5847y0heps9l67a05dt0knv
md1ft3j68qa98376007chgv2pyyennp8pp3hnh0hw8k6pg2q2625p35s88kpmk36q4uah6tlqwje9qdewahkh
md1ft3j68p9uwkde93xgk2qsmqy06ua7pzfstxyyz3zxsepgqyfnq77a5wjjm5algyuj9x3qqeznva37mzkkw
md1ft3j68p080xt2r2gurr8eg76rf7wquey879utkmyfycq2cmwgr5jg8guvv8x0laek8pmsgxjpa2xpsrqcu
md1ft3j68p3z838gk0xtf6vgukk6k3n7fad605n0qh85kk36vwn925x83qqpfejlmdc9w27qlp9ljldat7q
md1ft3j68paap6qmmnjamh02w3ea4gsaf2qthswkxx3pt86wlw35cqa62sr5mtsdu92539qspxlk86fzj20z
md1ft3j68zrnc8vvpw6m86xny4ee5emm35vyjr3n9dvqns59trd4nu57vppmaxrx72mlxrpzvp8p8vfnfh
md1ft3j68z2gtf5myx93n9v8m2rtwgsuv8v4pczrx3s2psc4x342fmln4pcwk7dsf3rnj5ysn433nmdq42vn0
md1ft3j68zk7y2x8zt8rvt8u7fn6fnj7yg5zsg0yprph3t5rm53lqrkh2ag0a5v5amlkusp0ma52gt4ydt2
md1ft3j68zlw4ppqsjnurdez74zz0x652t6f0ujaz62x47krxplz7f63rxwsnz7zz4jgeu4qr5u2m8jyplgqh
```

```
mdlft3j68r8y233tf3e0s4scpv2j0nr3nq5xd05hc3nxxf2zmc50n5vjsftzlf7wqklx2uws5mkv4cfranke6
mdlft3j68r0gyv66k5fuy7qvphvvqfpm8w9nfgsz9c7swxhxvqfexn0ktr088l8cvw4sz2qsuscfxqtufkzzj
mdlft3j68rs69vpkder6z9x6g90uzs2fqg5m0nu7lhhpcpxh5x468n3jeqms6qv872fxvmz2j
warning: --experimental relaxed the signature rule. This descriptor has at least one spend path that needs NO key, so whoever
r learns its preimage can spend it alone. If that preimage is engraved, THE PLATE IS BEARER ACCESS. Malleability, resource l
imits, repeated keys and timelock mixing were still checked.
note: stdout is watch-only – public keys only, cannot spend
[exit 0]

The keyed set is 15 mdl chunk(s).

keyless template-id: 68a1a888385797337ce5debc90fcfb1e
keyed   template-id: 68a1a888385797337ce5debc90fcfb1e
SAME WALLET.
```

Addresses, derived from the card

From the cards, not from the policy string — this proves what the cards carry, not what was typed to make them. A taproot address commits to the **taptree shape** as well as the keys, so a wrong tree gives wrong addresses even when every key is right.

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md address md1ft3j68qpp2040veppppqxxqu2nxh0duzeg4qzla jsf5a7y37
pt40qjf8re42zqm6205jszxc4se5llmr2r md1ft3j68q2zm74dy20ypxgzq59fntsqqpqqqfntkwwpx5d78gl30yggfzpa484np59p30rsc4yezy26j9m5u md1
ft3j68qkmsxaslv14f3keqe88ka4dyqshq4xddsqy0gzq42v6mq23ccr4r5847y0heps9l67a05dt0knv md1ft3j68qa98376007chgv2yyenp8pp3hnh0hw8
pk6g2q2625p35s88kpk36q4uah6tlqw2e9qdewahkh md1ft3j68p9uwwkde93xgk2qsmqy06ua7pzfstxyyz3zxsepgqyfng77a5wj5algyuj9x3qqeznva3
7mzkkw md1ft3j68p080xt2r2gurh8eg76rf7wquey879utkmgfyfc2cmwgr5jg8guvv8x0laek8pmsgxjpa2xpsrqcu md1ft3j68p3z838gk0xtf6vgukk6k3n
7fad605n0qh85kk36vwn925x83qppfejlmdc9w27qlpf9ljlhdat7q md1ft3j68paap6qmnjmamh02w3ea4gsaf2qthswkxx3pt86wlw35cqa62sr5mtsdu925
39qspxlk86fzj20z md1ft3j68zrnec8vvwp6m86xny4ee5emm35vyjr3n9dvqns59trd4nu57vppmaxrx72mlxrqrpzvp8p8vnfhf md1ft3j68z2gtf5myx93n
9v8m2rtwgsuv8v4pczrx3s2psc4x342fmln4pcwk7dsf3rnj5ysn433nmdq42vn0 md1ft3j68zk7y2x8zt8x8rvt8u7fn6fnj7yg5zsg0yprph3t5rm53lqrkh2
ag0a5v5amlkusp0ma52gt4ydt2 md1ft3j68zlw4pqqsjnurdez74zz0x652t6f0ujaz62x47krxplzf763rxwsnz7zz4jgeu4qr5u2m8jyplgqh md1ft3j68r8
y233tf3e0s4scpv2j0nr3nq5xd05hc3nxxf2zmc50n5vjsftzlf7wqklx2uws5mkv4cfranke6 md1ft3j68r0gyv66k5fuy7qvpvvpqfpm8w9nfgsz9c7swxhvx
qfexn0ktr088l8cww4sz2qsuscfxtufkzzj md1ft3j68rs69vpkder6z9x6g90uzs2fqg5m0nu7lhpcpxh5x468n3jeqms6qv872fvmz2j --chain 0 --c
ount 2
bc1puyvd9zxz6uvz0y0ehq7r5qz6h30txl4mgr8fxl3dqjp6xzpspy0qsgpgyny
bc1ptnvw76k6kqcdn7ra9906xp0j5966wgjwtrfjjd8u08m4r6rf8fsjkcc6w
note: stdout is watch-only — public keys only, cannot spend
[exit 0]
```

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md address md1ft3j68qpp2040veppppqxxqu2nxh0duzeg4qzla jsf5a7y37
pt40qjf8re42zqm6205jszxc4se5llmr2r md1ft3j68q2zm74dy20ypxgzq59fntsqqpqqqfntkwwpx5d78gl30yggfzpa484np59p30rsc4yezy26j9m5u md1
ft3j68qkmsxaslv14f3keqe88ka4dyqshq4xddsqy0gzq42v6mq23ccr4r5847y0heps9l67a05dt0knv md1ft3j68qa98376007chgv2yyenp8pp3hnh0hw8
pk6g2q2625p35s88kpk36q4uah6tlqw2e9qdewahkh md1ft3j68p9uwwkde93xgk2qsmqy06ua7pzfstxyyz3zxsepgqyfng77a5wj5algyuj9x3qqeznva3
7mzkkw md1ft3j68p080xt2r2gurh8eg76rf7wquey879utkmgfyfc2cmwgr5jg8guvv8x0laek8pmsgxjpa2xpsrqcu md1ft3j68p3z838gk0xtf6vgukk6k3n
7fad605n0qh85kk36vwn925x83qppfejlmdc9w27qlpf9ljlhdat7q md1ft3j68paap6qmnjmamh02w3ea4gsaf2qthswkxx3pt86wlw35cqa62sr5mtsdu925
39qspxlk86fzj20z md1ft3j68zrnec8vvwp6m86xny4ee5emm35vyjr3n9dvqns59trd4nu57vppmaxrx72mlxrqrpzvp8p8vnfhf md1ft3j68z2gtf5myx93n
9v8m2rtwgsuv8v4pczrx3s2psc4x342fmln4pcwk7dsf3rnj5ysn433nmdq42vn0 md1ft3j68zk7y2x8zt8x8rvt8u7fn6fnj7yg5zsg0yprph3t5rm53lqrkh2
ag0a5v5amlkusp0ma52gt4ydt2 md1ft3j68zlw4pqqsjnurdez74zz0x652t6f0ujaz62x47krxplzf763rxwsnz7zz4jgeu4qr5u2m8jyplgqh md1ft3j68r8
y233tf3e0s4scpv2j0nr3nq5xd05hc3nxxf2zmc50n5vjsftzlf7wqklx2uws5mkv4cfranke6 md1ft3j68r0gyv66k5fuy7qvpvvpqfpm8w9nfgsz9c7swxhvx
qfexn0ktr088l8cww4sz2qsuscfxtufkzzj md1ft3j68rs69vpkder6z9x6g90uzs2fqg5m0nu7lhpcpxh5x468n3jeqms6qv872fvmz2j --chain 1 --c
ount 2
bc1p3dgh5j4etfscn5nmnuqhnju58lh12jw0snnnuf4hqt4dw3uldpcqercf6r
bc1pg2ufelj9t7jvvexdm1xjekyymjr6evl7wm8t2uzakpqs8z5yugjs4kcuc2
note: stdout is watch-only — public keys only, cannot spend
[exit 0]
```

chain	index	address
receive	0	bc1puyvd9zxz6uvz0y0ehq7r5qz6h30txl4mgr8fxl3dqjp6xzpspy0qsgpgyny
receive	1	bc1ptnvw76k6kqcdn7ra9906xp0j5966wgjwtrfjjd8u08m4r6rf8fsjkcc6w
change	0	bc1p3dgh5j4etfscn5nmnuqhnju58lh12jw0snnnuf4hqt4dw3uldpcqercf6r
change	1	bc1pg2ufelj9t7jvvexdm1xjekyymjr6evl7wm8t2uzakpqs8z5yugjs4kcuc2

The concrete descriptor

The whole wallet in one string: every key, every hash, every timelock. This is what a coordinator wants pasted in.

```
$ /scratch/code/shibboleth/descriptor-mnemonic/target/release/md_descriptor md1ft3j68qpp2040veppppqqxqu2nxh0duzeg4qzlj5f5a7
y37pt40qjf8re42zqm6205jszxc4se5llmr2r md1ft3j68q2zm74dy20ypxgzqz59fntsqppqqqfntkwwpx5d78gl30yggfz484np59p30rsc4yezy26j9m5u
md1ft3j68qkmsxaslv14f3keqe88ka4dyqshq4xddsqy0gzq42v6mqq23ccr4r5847y0heps9l67a05dt0knv md1ft3j68qa98376007chgv2pyyenp8pp3hnh0
hw8pk6g2q2625p35s88kpk36q4uah6tlqwj2e9qdewahkh md1ft3j68p9uwkde93xgk2qsmqy06ua7pzfstxyyz3zxsepgqyfnq77a5wj5m5algyuj9x3qqeqzn
va37mzkkw md1ft3j68p080xt2r2gurr8eg76rf7wquey879utkmgfyfcq2cmwgr5jg8guvv8x0laek8pmsgxjpa2xpsrqcu md1ft3j68p3z838gk0xtfv6gukk6
k3n7fad605n0qh85kk36vwn925x83qqpfejlmdc9w27qlpf9ljldat7q md1ft3j68paap6qmmjamh02w3ea4gsaf2qthswkxx3pt86wlw35cqa62sr5mtsdu
92539qspxlk86fzj20z md1ft3j68zrnc8vvpw6m86xny4ee5emm35vyjr3n9dvqns59trd4nu57vppmaxrx72mlxrqrzvp8p8vnfhf md1ft3j68z2gtf5myx
93n9v8m2rtwgsuv8v4pczrx3s2psc4x342fmln4pcwk7dsf3rnj5ysn433nmdq42vn0 md1ft3j68zk7y2x8ztx8rvt8u7fn6fnj7yg5zsg0yprhph3t5rm53lqr
kh2ag0a5v5amlkusp0ma52gt4ydt2 md1ft3j68zlw4pqqsjnurdez74zz0x652t6f0ujaz62x47krxplzf763rxwsnz7zz4jgeu4qr5u2m8jyplgqh md1ft3j6
8r8y233tf3e0s4scpv2j0nr3nq5xd05hc3nxxf2zmc50n5vjsftzlf7wqklx2uws5mkv4cf فرانك6 md1ft3j68r0gyv66k5fuy7qvphvvqfpm8w9nfgsz9c7swx
hxvqfexn0ktr088l8cvw4sz2qsuscfxqtufkzzj md1ft3j68rs69vpkder6z9x6g90uzs2fqg5m0nu7lhhpcpxh5x468n3jeqms6qv872fxvmz2j
tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(ed0b28a805feca09a77c48f82babc1249c79aa8
40de94fa4a85bf55a453c813),multi_a(3,[39ec1b6e/270028'/0'/0'/0']xpub661MyMwAQRbcFMFJZ12DzU5adoUivgK5xCwDYMxC5UtTBRgwLXEjCzEDX
RWWZvPxWmecGx1wCjNsiPhXcuaruVrdBLsH6YUzhyru8gcSM8x/<0;1>/*,[d02bcdedf/270028'/0'/0'/0']xpub661MyMwAQRbcEq1guB2Dk15LELDLjDKnPY
gNC4gRtjPrEHJVroxpQheWf6WkUggvm53V8Q6EShWwbscTAiEfESspxWDqJG9iVLQ96wt1FMr/<0;1>/*,[5fd78eb3/270028'/0'/0'/0']xpub661MyMwAQRb
cGEkmscab1t5uovpwez4gX8LECKkeuJgpjbmbj8Hgs5ceurpkWwGtptyWDfDhLV3YgSiXbTd5NhyFp6mwCX3xYVXkBxpzk2/<0;1>/*)),{and_v(v:older(32
768),and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad),multi_a(2,[92c4c8b2/270028'/0'/0'/0']x
pub661MyMwAQRbcFPc8eXw9DQ7rqUSCMmx4N9PcaqvwmivT9mTEWSJeoJyF8K8B5PLsvPwzgJeQ8DWHWmv52AfJHTQqpTx2TdhoAWpiU1nx2/<0;1>/*,[086c
047e/270028'/0'/0'/0']xpub661MyMwAQRbcGRf77NwDwRF8S0rHvZEU7xj4eYUkYg1d4AQc2pxkJmZurzYaaJ8wgtfrmQbVtRY3XreZFsdtS9PRQ4Q50j17
cp4DmMY2G/<0;1>/*))),{and_v(v:after(1173520),pk([cef8224c/270028'/0'/0'/0']xpub661MyMwAQRbcFbjUAobTvfU9fkXESZ8VoB5jMdcDQP2Dj
wHjkyNmnxxkhquwzerhugnad1WHQT4dn7GPqPJXA6v5t2vPxJjoswhxQ6KEPLd4/<0;1>/*)),and_v(v:after(1383520),sha256(4743d7c47df21d29e3ed3
dfec5d0c0a884ccc2708637dddf771c36d214056954))}})#he4degaz
note: stdout is watch-only – public keys only, cannot spend
[exit 0]
```

That descriptor is 1299 bytes.

```
tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfee9ace803ac0,{and_v(v:sha256(ed0b28a805feca09a77c48f82babc1249c79aa8
40de94fa4a85bf55a453c813),multi_a(3,[39ec1b6e/270028'/0'/0'/0']xpub661MyMwAQRbcFMFJZ12DzU5adoUivgK5xCwDYMxC5UtTBRgwLXEjCzEDX
RWWZvPxWmecGx1wCjNsiPhXcuaruVrdBLsH6YUzhyru8gcSM8x/<0;1>/*,[d02bcdedf/270028'/0'/0'/0']xpub661MyMwAQRbcEq1guB2Dk15LELDLjDKnPY
gNC4gRtjPrEHJVroxpQheWf6WkUggvm53V8Q6EShWwbscTAiEfESspxWDqJG9iVLQ96wt1FMr/<0;1>/*,[5fd78eb3/270028'/0'/0'/0']xpub661MyMwAQRb
cGEkmscab1t5uovpwez4gX8LECKkeuJgpjbmbj8Hgs5ceurpkWwGtptyWDfDhLV3YgSiXbTd5NhyFp6mwCX3xYVXkBxpzk2/<0;1>/*)),{and_v(v:older(32
768),and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db81bb0fb3f54c6d9064e7b76ad),multi_a(2,[92c4c8b2/270028'/0'/0'/0']x
pub661MyMwAQRbcFPc8eXw9DQ7rqUSCMmx4N9PcaqvwmivT9mTEWSJeoJyF8K8B5PLsvPwzgJeQ8DWHWmv52AfJHTQqpTx2TdhoAWpiU1nx2/<0;1>/*,[086c
047e/270028'/0'/0'/0']xpub661MyM...
```

The six key cards

An mk1 card binds a cosigner's key to the wallet. They bind to the **keyless template**, not the keyed set: the stub is form-aware, so a card minted against the keyed policy carries a different stub and is refused against the template. **One wallet, two stubs.**

```
$ cat /scratch/code/shibboleth/mnemonic-engrave/design/journeys/out/hashvault/keys.txt
[39ec1b6e/270028'/0'/0'/0']xpub6E6MpT6SMBY1Poaj5rEJ4DN5E73e58TWta6SVLs4eYpJ6hDNKqhwLxFcvMUTJnDSQJpdKThXEma9t23WiHh rYAJbK9GUu
672njHHFenKt88
[d02bcedf/270028'/0'/0'/0']xpub6F5JvRbobbuiwNQLy9ifRCK1HbewqyYk3PkMPNsrgkPcGGuDYXdYUDmHqMsQeBzq58tf8eRxLaTWJPaa1pcE9TmRZTAfV
k7U61UxQtMUNFj
[5fd78eb3/270028'/0'/0'/0']xpub6EaVZPPwamQQKVnw8V5wJjXHJHC4hqX3ET8wLc9cWnCMzUgNZ2Gx4B7u9PQHUE9KrPgrRVZnt2oXakKwFeQ3WuWKeKiN1
TKGzUat5vPAfKT
[92c4c8b2/270028'/0'/0'/0']xpub6Dkd3EFiJE6o9VL2wwc5x9aSkZG7GVQzEEYPdaJwCGUfYza5Rsr11xk25aG9J29cfHpyxEr6L39oH4mTmtJXVKK7KPVtV
gT7HznajRzKepK
[086c047e/270028'/0'/0'/0']xpub6EEvgwBtdaoGsFWY6pNAuYMyWfCYrPivnW1zLM7myyvJhrSgVxwgmqHFjBuY54o7tJbacmtFvT3UGWta9PZXPtb575rf
BAvdHS6FDGxkC1
[cef8224c/270028'/0'/0'/0']xpub6E6vdTn7c2KFho1tuTeb9SPYiHxmFPsXSzgLzphMMDBu6LHZjDSX8Huf6sy9cZb3Bwwib3ZY92P1RPqPhcR4X7thfAzzh
HElKrSJqdGm2EL
[exit 0]
```

note: stdout is watch-only – public keys only, cannot spend

```
$ /scratch/code/shibboleth/mnemonic-engrave/design/journeys/mk_cards_from_json.py /scratch/code/shibboleth/mnemonic-engrave/
design/journeys/out/hashvault/mk-encode.json /scratch/code/shibboleth/mnemonic-engrave/design/journeys/out/hashvault/mk-enco
de-raw.txt
6 key cards -> 18 mk1 chunks
[exit 0]
```

template-id prefix: 68a1a888 stub mk embedded: 68a1a888

What goes on which plate

The device caps a QR at dim 37 — QR v5, about 106 bytes at ECC-L (engrave/engrave.go:420). Measured against that cap, the three kinds of content land in three different places:

```
device QR cap (dim 37 = QR v5, ECC-L byte mode): ~106 bytes
single-plate TEXT budget:                        300 chars

md1 chunks   4, longest 80 chars  -> TEXT + QR    (fits)
mk1 chunks  18, longest 111 chars -> TEXT ONLY    (over the QR cap)
descriptor   1298 bytes          -> 5 TEXT plates (12.2x the QR cap)

The mk1 cards lose their QR to 5 characters: 111 against a 106-byte cap.
Nothing is lost by it -- an mk1 is BCH-protected either way -- but it is
the difference between scanning a plate and typing it.

$ /scratch/code/shibboleth/mnemonic-engrave/design/journeys/split_descriptor_plates.py /scratch/code/shibboleth/mnemonic-engrave/design/journeys/out/hashvault/descriptor.txt /scratch/code/shibboleth/mnemonic-engrave/design/journeys/out/hashvault/descriptor-plates
descriptor: 1298 bytes -> 5 TEXT plates (300-char budget, 16 for the header)
sha256:      2c5a381fbb1797176ac4f10759b3aef8e55d650ccccfccf0e2896085a69404572
NOTE: these plates carry NO checksum. md1 does; this does not.
part 1/5  284 chars
part 2/5  284 chars
part 3/5  284 chars
part 4/5  284 chars
part 5/5  162 chars
rejoin check: 5 parts -> 1298 bytes, sha256 matches
[exit 0]

The five descriptor plates, as they will read:

$ cat descriptor-part-1-of-5.txt
part 1/5
tr(50929b74c1a04954b78b4b6035e97a5e078a5a0f28ec96d547bfec9ace803ac0,{and_v(v:sha256(ede0b28a805feca09a77c48f82b ...

$ cat descriptor-part-2-of-5.txt
part 2/5
YUzhryu8gcSM8x/<0;1>/*,[d02bcdcf/270028'/0'/0'/0']xpub661MyMwAQRbcEq1guB2Dk15LELDLjDKnPYgNC4gRtjPrEhJVroxpQheWf ...

$ cat descriptor-part-3-of-5.txt
part 3/5
5NhyFp6mwCX3xYVXkBxpzk2/<0;1>/*)),{and_v(v:older(32768),and_v(v:sha256(9ce09a8df1d1f8bc8892441a9eb30d0a18bc7db ...

$ cat descriptor-part-4-of-5.txt
part 4/5
x2/<0;1>/*,[086c047e/270028'/0'/0'/0']xpub661MyMwAQRbcGRf7TNwDwRF8SoRHvZEU7xj4eYUkYG1d4AQc2pxkJmZurzYaaJ8wgtfr ...
... clipped; full text in transcript_hashvault.txt
```

The mk1 cards lose their QR to five characters

— 111 against a 106-byte cap. Nothing is lost by it; an mk1 is BCH-protected either way. It is the difference between scanning a plate and typing one.

The descriptor plates carry NO checksum.

An md1 chunk has a BCH checksum and a shared chunk-set-id, so a mis-transcribed character is detected and a mixed-up set is refused. These five plates are raw text split at a byte offset: one wrong character yields a descriptor that is still syntactically plausible and describes a *different wallet*. They are a convenience for a coordinator. **The md1 card set is the backup.**

The bundle, and the secrets

```
The engraved set: 4 mdl + 18 mkl = 22 public strings.
$ /scratch/code/shibboleth/mnemonic-engage/target/release/me bundle --in /scratch/code/shibboleth/mnemonic-engage/design/j
ourneys/out/hashvault/backup-strings.txt --preview /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/p
lates --png --manifest /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/manifest.json
me: rendered plate 1 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-1.png
me: rendered plate 2 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-2.png
me: rendered plate 3 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-3.png
me: rendered plate 4 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-4.png
me: rendered plate 5 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-5.png
me: rendered plate 6 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-6.png
me: rendered plate 7 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-7.png
me: rendered plate 8 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-8.png
me: rendered plate 9 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-9.png
me: rendered plate 10 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-10.png
me: rendered plate 11 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-11.png
me: rendered plate 12 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-12.png
me: rendered plate 13 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-13.png
me: rendered plate 14 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-14.png
me: rendered plate 15 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-15.png
me: rendered plate 16 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-16.png
me: rendered plate 17 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-17.png
me: rendered plate 18 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-18.png
me: rendered plate 19 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-19.png
me: rendered plate 20 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-20.png
me: rendered plate 21 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-21.png
me: rendered plate 22 → /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/plates/plate-22.png
me: wrote manifest to /scratch/code/shibboleth/mnemonic-engage/design/journeys/out/hashvault/manifest.json
me: backup needs 23 plates (22 public + msl on device):
  plate 1/23  mdl policy → push via NFC & engrave
  plate 2/23  mdl policy → push via NFC & engrave
  plate 3/23  mdl policy → push via NFC & engrave
  plate 4/23  mdl policy → push via NFC & engrave
... clipped; full text in transcript_hashvault.txt
```

The secrets

me refuses an msl outright — it will not render, preview or transmit a secret, which is what makes the rest of the bundle safe to preview at all.

```
$ /scratch/code/shibboleth/mnemonic-secret/target/release/ms encode --phrase abandon abandon abandon abandon abandon abandon
abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon abandon aban
don abandon diesel
msl0e ntrs qqqqq qqqqq qqqqq qqqqq qqqqq qqqqq qqqqq qqr3h cpkas 7yqr8
word count: 24
language: english (BIP-39 checksum valid)
passphrase: not stored in msl (record separately if used)
warning: stdout carries private key material (can spend) – redirect or encrypt (e.g. '> file.txt' or '| age -e ...')
[exit 0]

$ /scratch/code/shibboleth/mnemonic-engage/target/release/me --in /dev/fd/63 --hex
me: refusing to emit msl over NFC: msl is secret seed entropy and must never be transmitted by radio (RF eavesdropping ris
k). Enter it by hand on the device: New > Input Seed > CODEX32.
[exit 3]
```

The gap: the engraved set does not name the slots

Every key sits at the **same path** from a **different seed**. So the keyless template's six origins are identical, and it carries no fingerprints — while the keyed card does. The engraved backup is the template plus the six mk1 cards, and those bind to the same template with the same stub at the same origin, so they add no signal either.

Slot order is load-bearing. `multi_a` commits to key *order*, so a different assignment is a different script, a different taptree leaf, and a different address:

```
The keyless template's origins, as engraved:
origins:
@0: m/270028'/0'/0'/0'
@1: m/270028'/0'/0'/0'
@2: m/270028'/0'/0'/0'
@3: m/270028'/0'/0'/0'
@4: m/270028'/0'/0'/0'
@5: m/270028'/0'/0'/0'
wallet-policy-id: f97fdce3d1d0096f9fe7f8bc82f5648b

The keyed card's origins, which DO name a master:
origins:
@0: [39ec1b6e/270028'/0'/0'/0']
@1: [d02bcedf/270028'/0'/0'/0']
@2: [5fd78eb3/270028'/0'/0'/0']
@3: [92c4c8b2/270028'/0'/0'/0']
@4: [086c047e/270028'/0'/0'/0']
@5: [cef8224c/270028'/0'/0'/0']
wallet-policy-id: a0b128ceaf3155a40af6f8e88765ecb

What a wrong assignment costs, measured:
canonical @0..@5 = key-0..key-5 : bc1puvyd9zxz6uvz0y0ehq7r5qz6h30txl4mgr8fxl3dqjp6xzpsy0qsgpgyny
swap @0/@1 (tier 1 3-of-3) : bc1p57pwugukl4a87nydmgyxmd779qv3qfyqu20elc60fyt5dhq7nfsststjq
swap @3/@4 (tier 2 2-of-2) : bc1p855ry9mfe2xxx509p92v2pgkgta53qkhufdty7gq6dguakcax9jq57dvx0

Three different wallets from one set of six keys. 6! = 720 assignments,
and the engraved template distinguishes none of them.
```

Three different wallets from one set of six keys, and the engraved template distinguishes none of them.

A restorer holding these plates and all six seeds has 720 candidate assignments and no way to choose. This is not a tooling defect — it is a property of the wallet's shape, and it is the thing this journey exists to have found before anything was cut.

The three ways out

- **Give each key its own account index** — `m/270028'/0'/N'/0'`. The origins then differ, and the existing seating rule (match on declared origin) assigns slots with no extra data. This is how the pathological wallet avoids the problem, and it changes no policy semantics.
- **Engrave the KEYED card** instead of the template. It carries a fingerprint per slot, so the assignment is on the plate — at the cost of 15 chunks rather than 4, and of putting the cosigner xpubs on metal.
- **Record the assignment out of band** — the weakest option, because it is the one thing here that is not engraved and not checkable.

This is the same class as F-216 (mapping an mk1 to an @N slot) in its hardest form: there, seating could match on a declared origin, because the origins differed. Here they do not.

What this journey does NOT show

- **No device walk.** Every command here is host-side. The cards have not been carried to a SeedHammer II, and no screen in this document is a framebuffer. The sibling taproot journey does that; this one does not yet.
- **No restore test — and as engraved, one cannot pass.** A restore rebuilds the wallet from the plates and the seeds and requires the same addresses. That is impossible here until the slot-assignment gap on the previous page is closed: the plates admit 720 assignments and only one is the wallet. Writing the test before fixing that would produce a test that fails for the right reason and teaches nothing new — the measurement on the previous page already says it.
- **No hardware.** Nothing has been cut. The plate counts and the QR capacity are computed from the device's own constants, not measured on metal.
- **The descriptor plates are unchecked text.** Stated again because it is the one place this backup is weaker than the constellation's usual guarantees.

Reproducing this document

```
bash derive-hashvault-keys.sh
bash transcript_hashvault.sh > transcript_hashvault.txt
python3 build_pdf_hashvault.py
```

The builder refuses a transcript snapshot that does not match the script that produced it, so this document cannot quietly describe a toolchain that has moved on underneath it.