

MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010706/24010437
Fax: 24023516
Website: <http://mpcb.gov.in>
Email: cac-cell@mpcb.gov.in



Kalpataru Point, 2nd, 3rd
and 4th floor, Opp. Cine
Planet Cinema, Near Sion
Circle, Sion (E),
Mumbai-400022

RED/L.S.I (R21)
No:- Format1.0/CAC/UAN No.MPCB-
CONSENT-0000165835/CR/2403003134

Date: 28/03/2024

To,
M/s Sudarshan Chemical Industries Limited,
Plot No. 19-A/1+2, MIDC Mahad, Tal. Mahad, Dist.
Raigad - 402 309.



Your Service is Our Duty



Sub: Grant of Renewal of Consent to Operate under Red/LSI

- Ref:**
1. Environment Clearance accorded by Env. Dept GoM vide No. SEIAA- EC-0000001484 dtd. 23.04.2019.
 2. Consent to Operate accorded by Board vide No. Format 1.0/CAC/UAN No. MPCB-CONSENT-00001304031/CR/2211001552 dated 18/11/2022
 3. Minutes of Consent Appraisal Committee meeting held on ---

Your application No.MPCB-CONSENT-0000165835 Dated 21.03.2023

For: grant of Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 6 and Rule 18(7) of the Hazardous & Other Wastes (Management & Transboundary Movement) Rules 2016 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

1. **The consent to renewal is granted for a period up to 30/04/2028**
2. **The capital investment of the project is Rs.318.28 Crs. (As per C.A Certificate submitted by industry Existing- CI Rs. 310.79 Cr + Increased- CI Rs. 7.49 Cr)**
3. **Consent is valid for the manufacture of:**

Sr No	Product	Maximum Quantity	UOM
Products			
1	HETEROCYCLIC PIGMENTS AND DYES (COPPER PHTHALOCYANINE BLUE, ALPHA BLUE, BETA BLUE, PIGMENT GREEN, etc.)	29496	MT/A
2	MICA PEARL PIGMENTS	3000	MT/A
3	COGEN Plant	10	MW
4	Chemical Gypsum	16869	MT/A
5	Sulphuric Acid (15-25%)	72000	MT/A
6	Aluminium Chloride (5-15%)	39150	MT/A

Sr No	Product	Maximum Quantity	UOM
7	Hypochloride (<10%)	13383	MT/A
8	Copper Sulphate	664	MT/A

4. **Conditions under Water (P&CP), 1974 Act for discharge of effluent:**

Sr No	Description	Permitted (in CMD)	Standards to	Disposal Path
1.	Trade effluent	10660	As per Schedule-I	Discharged to MIDC final treated effluent disposal sump.
2.	Domestic effluent	234	As per Schedule-I	Discharged to MIDC final treated effluent disposal sump.

5. **Conditions under Air (P& CP) Act, 1981 for air emissions:**

Sr No.	Stack No.	Description of stack / source	Number of Stack	Standards to be achieved
1	S-1	Boiler	1	As per Schedule -II
2	S-2	Thermic fluid heater (01 Nos)	1	As per Schedule -II
3	S-3	Calciner Crude Mica	1	As per Schedule -II
4	S-4	Green drowing vessel	1	As per Schedule -II
5	S-5	Wet Scrubbing system (Green charging Vessel) (Proposed)	1	As per Schedule -II
6	S-6	Emergency Chlorine Scrubbing System	1	As per Schedule -II
7	S-7	Continues Dryer	1	As per Schedule -II
8	S-8	Spin Flash dryer (P/A)	1	As per Schedule -II
9	S-9	60 ACM DC	1	As per Schedule -II
10	S-10	Spin Flash dryer (Green SD plant)	1	As per Schedule -II
11	S-11	Spray Dryer (Green SD Plant)	1	As per Schedule -II
12	S-12	Calciner Crude	1	As per Schedule -II
13	S-13	Calciner/ Blender- Mica Plant	1	As per Schedule -II
14	S-14	Scrubber Mica Reactor	1	As per Schedule -II
15	S-15	DG Set (1500 KVA)	1	As per Schedule -II
16	S-16	Boilers (10 TPH)	1	As per Schedule -II
17	S-17	HCl Scrubber	1	As per Schedule -II
18	S-18	Chlorine Scrubber	1	As per Schedule -II
19	S-19	Mica Dryer	1	As per Schedule -II
20	S-20	DG Set (1000 KVA)	1	As per Schedule -II

Sr No.	Stack No.	Description of stack / source	Number of Stack	Standards to be achieved
21	S-21	Hot Air Generator (4950 Kg/Hr)	1	As per Schedule -II

6. **Non-Hazardous Wastes:**

Sr No	Type of Waste	Quantity	UoM	Treatment	Disposal
1	Broken discarded Glass	2500	Kg/Annum	Sale	Sale to authorized party
2	Insulating Material	5004	Kg/Annum	Sale	Sale to Auth. Party/ CHWTSDF
3	Paper/Canteen waste	18	MT/A	Composting	Used as manure
4	Rubber Hand gloves, PVC shoes, Trapolien, paper bags	5	MT/A	NA	Sale to Offsite recycling/ CHWTSDF
5	Mica Waste	3600	MT/A	NA	Offsite recycling/ CHWTSDF
6	Fly ash	11386	MT/A	NA	Sale to Brick Manufacturers/ offsite recycling/ CHWTSDF
7	Biomass	200.8	MT/A	NA	Sale as Bio fertilizer/ Compost

7. **Conditions under Hazardous & Other Wastes (M & T M) Rules 2016 for Collection, Segregation, Storage, Transportation, Treatment and Disposal of hazardous waste:**

Sr No	Category No./ Type	Quantity	UoM	Treatment	Disposal
1	5.1 Used or spent oil	5000	Ltr/A	Recycle	Sale to authorised party
2	36.2 Spent carbon or filter medium	1000	Kg/Annum	Incineration/ Recycle*	Sale to authorised party / CHWTSDF
3	33.1 Empty barrels /containers /liners contaminated with hazardous chemicals /wastes	22500	Nos./Y	Incineration/ Recycle*	Sale to authorised party / CHWTSDF
4	34.1 Chemical-containing residue arising from decontamination.	0.5	MT/A	Incineration	CHWTSDF
5	35.3 Chemical sludge from waste water treatment	1037	MT/A	Landfill	CHWTSDF

Sr No	Category No./ Type	Quantity	UoM	Treatment	Disposal
6	28.1 Process Residue and wastes (Recovered Pigment)	863	MT/A	Landfill/ Recycle*	Sale to authorised party / CHWTSDF
7	28.1 Process Residue and wastes (Ammonium Sulphate (wet 30%))	20926	MT/A	Landfill/ Recycle*	Sale to authorised party / CHWTSDF
8	28.1 Process Residue and wastes (BaSO ₄)	16986	MT/A	Landfill/ Recycle*	Sale to authorised party / CHWTSDF
9	5.2 Wastes or residues containing oil	1.25	MT/A	Incineration	CHWTSDF
10	15.2 Discarded asbestos	1.2	MT/A	Landfill	CHWTSDF
11	20.2 Spent solvents	50	Ltr/A	Incineration/ Recycle*	Sale to authorised party / CHWTSDF
12	Filter & Filter Materials	05	MT/A	Incineration	CHWTSDF
13	28.1 Process Residue and wastes (Copper Oxide)	84	MT/A	Landfill/ Recycle*	Sale to authorised party / CHWTSDF

*** The applicant shall ensure disposal of by-products to Actual user/ End user having permission under Rule 9 of Hazardous and Other Wastes (Management & Transboundary Movement) Rules 2016 or else disposed of at CHWTSDF.**

8. The Board reserves the right to review, amend, suspend, revoke this consent and the same shall be binding on the industry.
9. This consent should not be construed as exemption from obtaining necessary NOC/ permission from any other Government authorities.
10. PP shall comply with the conditions stipulated in the Environment Clearance dtd. 23.04.2019.
11. PP shall achieve BOD standards of 30 mg/l for treated effluent that will be discharged at the MIDC outlet sump. If BOD parameter exceeds consented limit shall stop the discharge of substandard effluent.
12. PP shall ensure uninterrupted and direct data transmission of OCEMS, provided at ETP outlet and MIDC outlet sump, to the Board's server.
13. The applicant shall make an application for renewal of consent 60 days prior to date of expiry of the consent
14. This consent is issued as per the minutes of Consent Appraisal Committee meeting held on 03/11/2022

Received Consent fee of -

Sr.No	Amount(Rs.)	Transaction/DR.No.	Date	Transaction Type
1	636560.00	TXN2303003416	23/03/2023	Online Payment

Copy to:

1. Regional Officer, MPCB, Raigad and Sub-Regional Officer, MPCB, Mahad
- They are directed to ensure the compliance of the consent conditions.
2. Chief Accounts Officer, MPCB, Sion, Mumbai
3. CC-CAC Desk- for record & website updating purpose.



SCHEDULE-I

Terms & conditions for compliance of Water Pollution Control:

1. A] As per your application, you have provided Effluent Treatment Plant (ETP) of designed capacity of 4000.00 CMD consisting of Primary (Collection tank, Neutralization tank, Equalization tank, Flash mixer, Primary Clarifier/Primary Settling Tank), Secondary (Activated sludge process) for the treatment of 10660 CMD of trade effluent.
- B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent:

Sr.No	Parameters	Limiting concentration not to exceed in mg/l, except for pH
(1)	pH	6.5 - 8.5
(2)	Total Suspended solid (TSS)	100
(3)	Bio-Chemical Oxygen Demand (BOD) (3 days at 27°C)	30
(4)	COD	250
(5)	Phenolics as C ₆ H ₅ OH	1.0
(6)	Oil and Grease	10
(7)	Bio-Assay Test	90% survival in 100% effluent in 96 hours
(8)	Lead as Pb	0.1
(9)	Chromium (Hexavalent)	0.1
(10)	Total Chromium	2.0
(11)	Copper as Cu	2.0
(12)	Nicket as Ni	2.0
(13)	Zinc as Zn	5.0
(14)	Arsenic as As**	0.2
(15)	Cobalt as Co	0.2
(16)	Total Heavy metals	7.0

- C] The Industry shall ensure connectivity online monitoring system to the MPCB server including separate energy meter for pollution control system.
- D] The 6894 CMD treated effluent shall be recycled into process, for cooling tower make-up and remaining 4000 CMD treated effluent shall be discharged to MIDC final treated effluent disposal sump for further disposal after confirming above standards. In no case effluent shall find its way for gardening/ outside factory premises

2. A] As per your application, primary treated sewage connected to Effluent Treatment Plant for further treatment & disposal.
B] Industry shall comply prescribed standards & disposal path as prescribed at Sr. No. 1 B & C of schedule I.
3. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification there of & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.
4. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
5. The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Act, 1974 and as amended, by installing water meters and other provisions as contained in the said act:

Sr. No.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	1473.00
2.	Domestic purpose	268.00
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	11388.00
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	0.00
5.	Gardening	232

6. The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.
7. Guidelines for Storm-Water:
 - i Storm water for a plant, a unit (having plot size at least 250 square meters) shall not be allowed to mix with scrubber water, effluent and/or floor washings.
 - ii Storm water within the battery limits of a unit shall be channelized through separate drain or pipe passing through a High Density Poly ethylene (HDPE) lines pit having holding capacity of 10 minutes (hourly average) of rainfall.

SCHEDULE-II**Terms & conditions for compliance of Air Pollution Control:**

1. As per your application, you have provided the Air pollution control (APC) system and erected following stack (s) to observe the following fuel pattern:

Stack No.	Source	APC System provided/proposed	Stack Height(in mtr)	Type of Fuel	Sulphur Content(in %)	Pollutant	Standard
S-1	Boiler (25 TPH)	ESP	66.00	Coal 10760 Kg/Hr	0.5	SO ₂	2582.4 Kg/Day
						TPM	150 Mg/Nm ³
S-2	Thermic fluid heater (15 Lac Kcal/Hr)	Dust Collector	36.00	Coal 1364 Kg/Hr	0.5	SO ₂	327.36 Kg/Day
						TPM	150 Mg/Nm ³
S-3	Calcliner Crude Mica	Dust collector	6.00	-	-	TPM	150 Mg/Nm ³
S-4	Green drowing vessel	Caustic Scrubbing System	22.00	-	-	HCL	35 Mg/Nm ³
S-5	Wet Scrubbing system (Green charging Vessel - Proposed)	Water Scrubbing & Caustic Scrubbing System	10.00	-	-	Chlorine	3 PPM
						HCL	35 Kg/Day
S-6	Emergency Chlorine Scrubbing System	Water Scrubbing & Caustic Scrubbing System	16.00	-	-	Chlorine	3 PPM
						HCL	35 Mg/Nm ³
S-7	Continues Dryer	Dust collector	7.00	-	-	TPM	150 Mg/Nm ³
S-8	Spin Flash dryer (P/A)	Dust collector	10.00	-	-	TPM	150 Mg/Nm ³
S-9	60 ACM DC	Dust collector	4.00	-	-	TPM	150 Mg/Nm ³
S-10	Spin Flash dryer (Green SD plant)	Dust collector	9.00	-	-	TPM	150 Mg/Nm ³
S-11	Spray Dryer (Green SD Plant)	Dust collector	12.50	-	-	TPM	150 Mg/Nm ³
S-12	Calcliner Crude	Dust collector	12.56	-	-	TPM	150 Mg/Nm ³
S-13	Mica Plant - Calcliner/ Blender	Dust collector	23.00	-	-	TPM	150 Mg/Nm ³

Stack No.	Source	APC System provided/proposed	Stack Height(in mtr)	Type of Fuel	Sulphur Content(in %)	Pollutant	Standard
S-14	Mica Reactor Scrubber	Wet Scrubbing System	16.00	-	-	TPM	150 Mg/Nm ³
S-15	DG Set (1500 KVA)	Acoustic Enclosure	16.50	Diesel 400 Kg/Hr	1	SO ₂	192 Kg/Day
S-16	Boilers (10 TPH)	Multi Cyclone Dust Collector & Bag Filter	36.00	Coal 34 MT/Day	0.5	SO ₂	1260 Kg/Day
				Briquette 54 MT/Day	0.2	TPM	150 Mg/Nm ³
S-17	HCL Scrubber	Scrubber	20.00	-	-	HCL	35 Mg/Nm ³
S-18	Chlorine Scrubber	Scrubber	20.00	-	-	Chlorine	3 PPM
S-19	Mica Dryer	Wet Scrubber	18.00	-	-	TPM	150 Mg/Nm ³
S-20	DG Set (1000 KVA)	Acoustic Enclosure	10.00	Diesel 2.5 KL/M	1	SO ₂	35 Kg/Day
						TPM	150 Mg/Nm ³
S-21	Hot Air Generator (4950 Kg/Hr)	Stack	23.00	LDO 1 MT/Day	1.8	SO ₂	38 Kg/Day
						TPM	150 Mg/Nm ³

- i. All the dust generating equipments or process shall be provided with dust extraction arrangement.
 - ii. The bag houses, etc. shall be connected to chimneys or stacks of atleast twelve meters height or at least two meters above the top most point of the building, shed or the plant in the industry, which so ever is higher.
 - iii. The unit shall channelize shop floor or fugitive emission through a stack of twelve meters height or at least two meters above the top most point of the building or shed or plant in the industry, which so ever is higher.
2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.
 3. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
 4. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
 5. Guidelines for Solvent Losses:
 - i The total losses of solvent should not be more than 5% of the solvent consumed, if solvent consumption less than 1000 tons/Annum; and
 - ii The solvent loss should not be more than 3% of the solvent consumed, if solvent consumption greater than 1000/tons/Annum.

SCHEDULE-III

Details of Bank Guarantees:

Sr. No	Consent (C2E/C2O/C2R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	C2O (Expansion & Amalgamation)	2500000	Existing	Towards O & M of pollution control system & compliance of consent to operate	30.04.2028	31.10.2028

The above Bank Guarantee(s) shall be submitted by the applicant in favour of Regional Officer at the respective Regional Office within 15 days from the date of issue of Consent.

BG Forfeiture History

Srno.	Consent (C2E/C2O/C2R)	Amount of BG imposed	Submission Period	Purpose of BG	Amount of BG Forfeiture	Reason of BG Forfeiture
NA						

BG Return details

Srno.	Consent (C2E/C2O/C2R)	BG imposed	Purpose of BG	Amount of BG Returned
NA				



SCHEDULE-IV

General Conditions:

1. The Energy source for lighting purpose shall preferably be LED based
2. The PP shall harvest rainwater from roof tops of the buildings and storm water drains to recharge the ground water and utilize the same for different industrial applications within the plant
3. Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
 - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
 - f) D.G. Set shall be operated only in case of power failure.
 - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - h) The applicant shall comply with the notification of MoEFCC, India on Environment (Protection) second Amendment Rules vide GSR 371(E) dated 17.05.2002 and its amendments regarding noise limit for generator sets run with diesel.
4. The applicant shall maintain good housekeeping.
5. The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
6. The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
7. The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
8. The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).
9. The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
10. The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification No. B-29016/20/90/PCI-L dated. 18.11.2009 as amended.
11. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.

12. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
13. The PP shall provide personal protection equipment as per norms of Factory Act
14. Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
15. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
16. The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
17. The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the Hazardous and Other Wastes (M & TM) Rules 2016, which can be recycled /processed /reused /recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc. should go for that purpose, in order to reduce load on incineration and landfill site/environment.
18. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
19. Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).
20. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
21. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
22. The industry should not cause any nuisance in surrounding area.
23. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
24. The industry shall create the Environmental Cell by appointing an Environmental Engineer, Chemist and Agriculture expert for looking after day to day activities related to Environment and irrigation field where treated effluent is used for irrigation.

25. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
26. The industry should comply with the Hazardous and Other Wastes (M & TM) Rules, 2016 and submit the Annual Returns as per Rule 6(5) & 20(2) of Hazardous and Other Wastes (M & TM) Rules, 2016 for the preceding year April to March in Form-IV by 30th June of every year.
27. The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
28. The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
29. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions.
30. The firm shall submit to this office, the 30th day of September every year, the Environment Statement Report for the financial year ending 31st March in the prescribed FORM-V as per the provisions of Rule 14 of the Environment (Protection) (second Amendment) Rules, 1992.
31. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
32. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
33. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

This certificate is digitally & electronically signed.
