Cyber + IKP: Security AI Agent — Information Sharing and Vulnerability Handling

BGIN Block 15 · Georgetown University Capitol Campus, 111 Massachusetts Avenue NW, Washington, D.C.

Date	16 October 2026
Room	Room B (2416)
Published time	09:50–11:20
Workstream	security-ai-agent; cybersecurity-information-sharing
Status	Draft for working-group review. Source: closed captions.
Rule	Chatham House Rule. Information may be used without revealing the identity or affiliation of speakers or other participants, directly or indirectly.

This is a session record, not a transcript. Substantive discussion is retained with uncertainty and disagreement made explicit. Reported claims are not verified findings. Candidate agreements require working-group confirmation before use as decisions. Actions omit personal owners and identifying roles.

Agreements

The following sentences stand on their own. These are candidate agreements and reported points of convergence for working-group review. Inclusion does not establish consensus, verify a technical claim, or record formal adoption. The working group must confirm each decision before it is cited as such. Claims that were only discussed, including figures and alternatives that were not adopted, remain in full under Discussion.

The community security agent's loop, as demoed, is the working concept: read the firm's own procedures and architecture, combine them with shared intelligence, show the attack path and the first fix, send unknowns to the community, let one verification clear every dependent, share under TLP with TLP:AMBER as the worked example, anonymize outbound questions, cite sources, and require the firm to approve every action and every word that leaves.

The agent should use standards that already exist and should still record the dependency and routing facts that do not yet have a standard.

English and Japanese operation, and role-specific views including an audit view, are part of the demo and were not challenged.

A verifiable trust agent and an open verifiable trust community are the trust layer to try. Without zero-knowledge proofs, the trust graph is a surveillance graph.

The Linux kernel maintainers are the first OpenVTC implementer, moving off a PGP web of trust. The work was presented at Linux Plumbers about two weeks earlier and at GDC in September, and it was well received in those rooms.

Delegation and proof of control match the accountability problem. The demo side agreed they are a

necessary base, because membership in the community does not prove quality or good faith. IEEE My Terms was accepted as the illustration that contextual privacy is not anonymity and is not a release from liability.

BGIN should have its own verifiable trust community, and the incident-response work should have a separate one, with separate decentralized identifiers.

The practical sequence over about six months is software, an always-on host or a secure enclave that can issue BGIN community credentials, and key ceremonies at a block meeting or a working-group meeting.

The git repository should be findable from the BGIN project page, should sit under BGIN, and should show activity, because an NSF open-source-ecosystem application is in progress and partners including SEAL are named on it.

OpenVTC, My Terms, and proof of control should be referenced from that repository as standards to fold in.

Coordinate sharing, Merkle roots, and a prover/verifier split are the research offer for putting less plaintext on the wire. They were not adopted as the architecture of the demo.

Supply-chain incidents can be community comments on the same trust graph. Customer identity data should remain a proof bound to a vertex.

Ethereum's public execution is a constraint. Post-quantum signatures and greater privacy, including ZK virtual machines, are the directions the room named.

The next months should put real operational data into the agent, not only illustrations.

Proof-of-personhood comparison belongs to the privacy-enhanced authentication session. This slice only shows that the comparison was about to be made.

Documents considered

The session referred to the following documents, repositories, and standards. Bibliographic identifications and factual checks added during review are marked as editorial clarifications; they do not imply that the links were spoken or that the meeting adopted the findings. Names of the people who introduced the material are omitted.

First Person Project is the documented name of the model implemented by OpenVTC. This project reference does not identify a meeting speaker.

Silent recorded demo of the community security agent, about six minutes, shown during the session. A second contributor's advance document was for another session and was not used.

Working document for the agent project, on screen and open for comment. Title not spoken.

OpenVTC page, shown in the room. The trust spanning protocol, verifiable trust agents, and the credential types listed above.

Community security agent git repository, to be circulated and linked from the BGIN project page. This extract does not copy a URL from chat.

IEEE My Terms, used as the contextual-privacy illustration.

Advanced AI Society proof-of-control material, discussed and offered on screen. Months old, still thin.

Proof-of-personhood paper, cited as prior work and deferred to the next session.

GDC meeting report on vulnerability handling and agentic AI, to be shared in the chat.

Linux Plumbers presentation of OpenVTC, about two weeks before the meeting, and the September GDC presentation.

No Zoom links.

Discussion

The following is the substance of the session. It preserves claims, figures, alternatives, and objections. Discussion does not establish a decision. Any candidate agreement requires explicit working-group confirmation.

Recording coverage. The recording begins after the published start time. The captured opening introduces the vulnerability-handling and security-agent work. Content before the recording began cannot be assessed.

Agenda. The session considered a recorded community-security-agent demonstration, BGIN project progress, a grant application, and potential integration with agent-privacy work. Another submitted contribution belonged to a different session and was not presented.

The community-security-agent work had previously been presented at a GDC meeting in September. Further contributions and incident-response collaboration were being sought.

What the demo showed. The demo was about six minutes, silent, of a planned open-source community security agent for community cyber defense. A group whose name the caption rendered unclear contributed to the demo [unverified]. The picture was an Ethereum network plus the off-chain services around it.

One node was a payment company, used as the worked example.

Red marks were known or shared information: attack bodies, short intelligence, and similar.

A chart of vulnerabilities by month was used to say that published vulnerabilities are not the only thread, and that unknown threats keep arriving.

Green marks were other members of the security community. Some of them can test a service that other members depend on.

The payment company uploads its own institutional files: operating procedures, systems architecture, and similar. The agent reads those files and extracts actions from the runbook.

The agent then reads the company's information together with shared vulnerability and threat intelligence, applied to that company's context.

A red path was a potential attack path against the payment company. A green path was where to fix first, the earliest priority given the shared intelligence.

Unknown was explicitly not treated as safe. A risk the company cannot check alone is sent to the community. One member's check serves every company that needs the result.

A worked incident assumed a bridge was attacked. The agent proposed mitigation steps the payment company can run immediately, and it showed what the community had shared.

Distribution follows TLP. In the example, TLP:AMBER: the shared item goes only to those who need it.

A forum view lets a company check dependency risks and related information. Different roles, including an audit firm, use the same picture from their own position.

The agent works in English and Japanese. A user can ask about the alert, the risk analysis, or a proposed private-verification target, and the answer cites sources.

The reported capabilities and limitations were as follows:

The agent matched a new alert to a typical incident, to common misconfigurations, to other companies' incident reports, and to the company's own files, and it proposed what to do first and what to do now.

When the company's files cannot show whether a service it depends on is safe, the agent asks other members to verify, starting where the web paths run, before anything has failed. The ask does not say who is asking. Anything that leaves the company is anonymized first.

One answer can clear the same unknown for every company that depends on that single issue.

Organizations do not send material to each other as a full dump. A shared risk is evaluated. Incident reports and answers go into protected shared records. Typical incidents and common misconfigurations go to every member. A report about one service goes only to the agents of its users. TLP defines the split.

The agent stops at the decision. It finds what applies to the company, proposes the first actions, plans the response, and drafts what to share. The company's team approves every action and every word that leaves. The community decides whom it trusts, what it shares, and how contributions are funded and rewarded. Contribution types named: risk verification, software checking, and behavior analysis.

Unsettled inside the demo's own design: how to rank by incident impact, who is responsible for which decision, and what a contributor receives in return.

Where a standard already exists, the agent uses it: advisory fact statements, threat reports, and exchange formats members already run. The precise format name was garbled [unverified].

There is no standard way to state what a company could lose through a dependency, whether an attack pattern applies to it, who should receive a given report, or who is allowed to answer a question about a dependency. The agent records those items even though they are not standardized.

The communication path can already carry an organization from new information to steps it can run.

Still open: how to assure the quality of what gets defined, whom to trust, and how contributions are funded so the system lasts. A proper name in that sentence was garbled and is not treated as an organization [unverified].

The open challenges were discussed.

Verifiable trust as the layer underneath. The response from the room was a set of standards to fold into this agent, not a critique of the demo's loop. Trust over IP's communication layer, the trust spanning protocol, was described as requiring digital-identity credentials before agents communicate. The relevant object is a verifiable trust agent. The proposal was to build a trust graph of the companies that connect through the community security agent. Each participant would keep a fog of war on the globe the demo used: they append information locally, and a connection to another party's verifiable trust agent is what opens the channel.

Open Verifiable Trust Community (OpenVTC) was offered as the concrete implementation. One of the first open VTCs was described as already set up, and as useful for open-source standards. The proposed contribution to the community security agent is to make this work one of the first open verifiable trust communities for cybersecurity, while both the agent and OpenVTC are early enough to grow together. A page was shown.

The first implementer named was the Linux kernel's core maintainers, moving from a PGP web of trust to OpenVTC for the trust graph. An open trust graph was called a surveillance graph unless zero-knowledge proofs are part of it. That ZK requirement was called essential. OpenVTC was presented at the Linux Plumbers Summit about two weeks before this meeting, described as well received and as having gone from zero to one for the kernel groups. It was also presented at the September GDC meeting. Reception among Linux Foundation participants was attributed to the use of decentralized identifiers and verifiable credentials, and to an ethical framing of the tools.

Vocabulary used for the stack:

A verifiable trust agent (VTA) and a verifiable trust community (VTC).

The trust spanning protocol as the communication layer.

Decentralized identifiers for participants, held in a system whose name was garbled [unverified].

Credentials: a verifiable relationship credential, a verifiable membership credential, an invitation credential.

A persona: the presentation a participant chooses to show inside the community.

A statement: an endorsement. In the kernel case, an endorsement by the lead maintainer is what attaches to the invitation and admits someone to the trust graph as a maintainer.

Delegation, still in progress on the spec, and described as a proof-of-control idea. A keynote point from this meeting, that accountability for AI matters, was cited as the reason delegation fits. It was also called one of the harder problems.

An authority credential, likewise unfinished.

Continued coordination with BGIN on the open-source trust-graph implementation was proposed. This line of work was also described as continuous with soulbound-token discussions from about two years ago: a long search for an expression of the same membership-and-trust problem.

A predicate credential was mentioned as a new form of zero-knowledge proof, and as the implementation path related to the proof-of-personhood paper that this community already cites. The implementation has shifted and was explicitly deferred to the privacy-enhanced authentication session. The technical point left in this session: it resembles a Groth16 setup without a trusted ceremony. Position in the trust graph replaces the ceremony that would otherwise collect entropy. That was offered as a different expression of a zero-knowledge proof, and as a topic for the next session rather than a result of this one.

What it would take to stand a BGIN community up. An experimental community had already been created as a personal test, on the order of six hours of iterative prompting. The creation experience is still rough. Recreating a verifiable trust community was offered as a next step. The requirement was described as cryptography for pairwise relationships, analogous to PGP, rather than as a mandatory wallet. Entry is by invitation. Setup means creating the community credential, running a Linux host that holds it and that runs a verifiable trust agent, inviting people, and holding key ceremonies.

The six-month picture: finish the software; run an always-on machine, or pay for a secure enclave, so a verifiable trust agent can issue community credentials for BGIN; then, at the next block or at a working-group meeting, do the key ceremonies that join people to the graph.

Two communities, not one. There should be a verifiable trust community for the vulnerability and incident-response work, outside BGIN, and a verifiable trust community for BGIN itself. They would liaise. Membership would overlap. They would be separate implementations with separate decentralized identifiers.

Proof of control, liability, and contextual privacy. A question on the proof-of-control work at the Advanced AI Society was taken in this session because it sits next to delegation. The work was described as a response to a keynote problem: Web2 companies want agentic commerce and then discover they lack the reporting. It was called reactionary and, at the same time, a rapidly developing agent-identity effort. An IEEE industry-connections program on digital trust is managing it. The impression in the room: the direction is right, the documents are still thin, and they will fill a gap people already perceive. "Open verification" was praised as a frame for proof of control and for verifiable AI. The society was credited with convening people, including people whose agent-privacy research did not previously have a home. Larger decentralization efforts were described as less organized. The effort is months old, which was itself treated as evidence of the current pace, including AI-authored pull requests. Insurance was noted as one subcategory of proof of control. A connection to Linux Foundation Decentralized Trust and an "agent jail" idea were mentioned and not specified. Another item involving a Merkle tree and legal-person concepts was garbled [unverified].

The liability exchange that followed was left open. If consequences are serious enough, some participants asked whether an agent, or the people who ship it, could face personal-equivalent sanctions. Longstanding internet engineers were paraphrased as saying that a person who did some of these things would be jailed. That question was called unresolved, and it was called newly hard for open source, which has often been able to avoid it. If a rule is impractical to enforce, states and large firms were expected to build conditions under which something is enforceable. The desirable outcome was framed

as privacy and liberty together with some predictable recourse. A position carried from the keynote, and restated here, was that the need for privacy does not decide the liability question. Taking an action is what creates liability. Privacy was distinguished from anonymity. The IEEE My Terms standard was the illustration: privacy controls exist in context, including in a public room, and an action taken in that room still carries liability.

The discussion supported the view that the trust-graph picture and proof of control are essential to this kind of security agent. The agent does not, by itself, prove that a community member is legitimate, of good quality, or free of malicious intent. In a token-economy setting, those controls were called the right base for community cybersecurity.

Repository, grant, and standards to cite. The follow-up agreed in the room: in the community security agent git repository, add references to the standards to be folded in, including OpenVTC and My Terms, and others as they prove useful. A working document for the project was on screen and open for comment. A regular working group already carries the work. The repository link is to be circulated. It should also be on the BGIN project page; if it is missing, the page should be updated. The repository's root is the demo authors' work, and it has been or is being moved under BGIN. More contributors were requested.

The grant context: an application to the NSF program for an open-source ecosystem. Approval is uncertain. Either way, the GitHub activity has to look alive, which is why stakeholders need the link. Partners named in the application included a group whose short name was garbled [unverified] and SEAL. The next steps stated at that point were: include the standards discussed today; write an implementation plan for launching this as a verifiable trust community and as one of the first cybersecurity-oriented ones; and use proof of control, or contribute back to it.

Geometry as a way to share less plaintext. A research strand was then shown as a possible encoding for the demo's sphere. The sphere was described as having a definite geometry. If each community, or each vulnerability, can overlap that sphere, the overlap produces coordinates. The research claim: put those coordinates on the wire, so what is shared is the state of the sphere and of a torus, not the underlying documents. A personal knowledge graph was the visual analogy. A dot might be a vulnerability write-up, an action plan, a network, or an exposure. Folding between a torus and a codex, or between 2D and 3D, was shown. Sharing locations, while each side holds its own state, was argued to reduce what crosses the trust spanning protocol, or A2A, or whichever agent protocol is used, and to reduce the tokens spent. Compression and vectorization were described as something current models handle well. A lattice-style circuit sits in the middle of the construction.

A related GDC visualization was described as a star tetrahedron: a perturbed sphere made of two overlapping spheres, read as one party's perspective inside the trust graph. The Ethereum network in the demo would be one sphere. An agent reads that sphere's coordinates, encodes them, and overlaps them with another party's version. The separation between the spheres changes the perturbation. That was offered as geometry for agentic sharing that does not put plaintext on the wire. The same picture was used to teach post-quantum signature sizes. SPHINCS+ was shown as large. A classical elliptic-curve signature was shown as small. The tiny mark versus two large spheres was ECDSA versus

SPHINCS in a two-dimensional size comparison. Signatures can be folded into the star.

Asked whether the size picture is only educational or is also a signature, the answer was that folding public signature material into the shape is the current research bet. Samples of SPHINCS and ML-DSA used so far do not yet carry the uniqueness of a real public key. The intended step is a hybrid classical-plus-post-quantum presentation in the geometry, so the shape is a collection of signatures a party wants to show, not only a diagram. The project name, clarified after the meeting, is The Star Holds; the demonstrated shape holds the current set of public keys. Hybrid classical and post-quantum signatures had been discussed the day before. The manifold was offered as a way to visualize that hybrid and to hold it under geometric constraints. The GDC version was to be dropped into the chat as a meeting report.

A City Key was shown as a JSON object encoded into 64 state transitions, so it can be hashed and used as a verifiable label. Those hashes can be Merkle leaves. The root is what gets shared. The object includes a public-key hex and a root hex. Two examples, one of them the GDC encoding, were said to share 20 common trust tasks inside the 64-cell lattice and to differ as 256-bit hashes. Discovery is possible because the lattice size and the values on the vertices are fixed. The same state can be walked on the lattice or by stratum.

Watching the cycle was called a proof of presence: a human observed the agent's runtime. The example on screen was three laps of a success cycle, a little under 30 seconds, or four laps for 30 seconds, with each vertex encoded. If each vertex is a monitor, attack, or defend technique, one agent can share the City Key and another can walk the response order without receiving the full document. The 63-step transition is the pattern. Reproducibility without shipping the runtime was called the trust task. An observer or a server in the middle is not required for that reproduction.

Different models behind the two agents were explicitly allowed. The split that matters: one agent sets the boundary and encodes the vertices, including what the success cycle is; the other has access to the knowledge base or to the company's thread. That split was compared to a zero-knowledge proof. One side proves, one side verifies, the information spaces stay separate, and they still have to communicate across the gap. A signature in the middle means the boundary-setting side assigned the encoding. One elliptic-curve signature was called enough for now. For more sensitive sharing, three signatures folded into the shape might be required. The construction reminded at least one participant of earlier work on visualizing digital signatures.

An observable surface, discussed in MCP terms, was the human-factors piece. If the shape is on a second screen and it collapses while an observing agent is approving permissions, a person can see that the runtime has left its separation. Distinct geometric vectors were argued to give the human observer an intuition the raw model trace does not. About twenty minutes remained at that point, with governance still on the agenda. Further questions were invited.

The six dimensions encoded on the star were stated as compute, memory, connection, delegation, protection, and value. Another community could choose a different encoding of the six. These six were claimed as the most universal for an AI system and, more loosely, for sovereignty. Value was defined as the community's choice. The example was conservation, an "eternal forest," occupying the value

dimension of the 64-cell lattice. A vertex can have several dimensions on at once. One displayed state was only value. The all-but-one state had everything except value. The intended story is: start from what the community cares about, then walk phase transitions an agent can follow because the machine is a 64-state bit flip. That regularity is what makes a hash of the lattice state possible. The hash-width explanation was unclear and remains unverified. Today the vertices are filled with workshop trust tasks. For this project, the community security agent would govern what protection, delegation, and value mean in a state that does not include memory, connection, or computation. If an AI touches memory while it is in a state that does not include memory, it is outside scope, which is the verifiability claim. Protection was weighted as the largest dimension, with a Fibonacci-like sizing. The shape is a way of holding a presentation of information. This encoding was reported to be in use in relation to the demo project.

Repository review using a knowledge graph and agent context was described as a way to find overlap without imposing a rule that there must always be two agents, or that delegation and protection must always be the frame. The collaboration is supposed to pull the ideas that fit. Pull requests into the demo authors' work were described as the method. The agreed ambition for the next few months is real data rather than toy data, which is where the operational demo matters. A further hope, not a decision, was that the star becomes a hybrid aggregate key presentation. A comparison to a QR code was rejected as too small.

Supply chain, hardware, and privacy. A participant connected the previous day's supply-chain session. The issue is not only software vulnerabilities. A recent story about a physical distribution channel was mentioned. The question was whether this agent system can take that channel, and whether blockchain supply-chain risk and the protection-profile discussion from the afternoon can sit in one system, with different players using the same technology. The answer in the room was that the demo already has some of that structure, and that a next step of the supply-chain project is a list of supply-chain risks. A community comment, for example from Ledger or from SEAL 911, could be encoded when an incident happens and distributed on the trust graph. Each accepting party's sphere would update: a supply-chain attack has hit Ledger; further detail on which devices failed would be a separate trust task back to Ledger. Hardware modification was distinguished from a software expression, and was still treated as something that can be translated into observables. The illustration was an attack in which on-chain tests were noticed only afterwards, used to check whether drained phones and stolen seeds would work. At larger scale those tests may be observable, including to volunteers if many parties share sphere state. A wallet with a very small balance, drained, might be one of many and a precursor rather than the whole event.

The privacy warning attached to that example: a hardware-wallet vendor's list of customer names and addresses is exactly the information an attacker would use to steal the physical device. Privacy was called an ambiguous word, which is why standards should define it from a privacy-engineering point of view. The analysis asked for was the privacy impact, on a person, of information stored in the city-key structure. The ideal stated in the room: that information is never read in plaintext. What the agent observes is a proof that the information is correct, assigned to a vertex.

Ethereum privacy was confirmed in one sentence: smart-contract state on Ethereum is public. Two current Ethereum priorities were named: post-quantum readiness, and moving the public permissionless system toward greater privacy, using zero-knowledge virtual machines. Layer-2 ZK work was described as already substantial and as on the roadmap (the caption's "straw map"). Whether privacy lands on layer 2, on layer 1, or in a wallet was left open. A privacy-wallet implementation was named and the spelling was garbled [unverified]. It was described as a mix of account abstraction and an opt-in privacy path, with ordinary non-private transfers still available, so a user would not have to go find a separate mixer.

The security-agent session then broke. The caption says both about ten minutes and about fourteen minutes, at a numbered table. The workshop itself was at time.

What the slice continues into. After the break the next session is privacy-enhanced authentication. The slice includes the hallway before that session and the start of its setup. The next session was to compare biometric and credential-based approaches. The preparatory exchange was a comparison with a proof-of-human paper, kept here only as a topic that spilled into this slice.

As discussed in the room, that paper anchors proof of human in a credential from a trusted issuer. A passport was the example of a proxy inside their own cryptographic set. Portability was compared with a World ID credential using zero-knowledge proofs. Other anchors mentioned: ride-hail history, driver credentials, cell-tower pings, and evidence that a student attended a class. Each was described as fakeable or unreliable on its own, and as a possible signal in a trust-graph approach if many of them are combined and if relying parties standardize the weight of each one. The biometric design, as the room prepared to explain it, was chosen after considering web-of-trust, government documents, and social graphs, on the argument that it covers more people, depends less on an issuer who can revoke, and was judged the most secure of the options they examined. Revocation was the concrete objection to an issuer proxy: if a ride-hail credential is what proves a person is human, the issuer can withdraw it. The planned introduction was to say why biometrics were chosen and to set the trade-offs next to the trust-graph work. Lunch followed that session, not this one.

Informal networking after the workshop is outside this session record and is omitted.

Matters not resolved

How the community ranks incident impact, who is responsible for a decision, and what a contributor is paid or otherwise given. The demo listed these as unsettled.

There is no standard statement for loss-through-dependency, for whether an attack pattern applies, or for who may receive a report and who may answer a dependency question. The agent records them anyway.

Quality of contributed intelligence, whom the community trusts, and how verification work is funded so the system continues.

One verifiable trust community or two. The proposal was two: incident response outside BGIN, and BGIN itself, with distinct identifiers and a liaison. That was a plan, not a deployed split.

Whether OpenVTC's credential set, especially delegation and authority, is mature enough to be a base. Both were described as unfinished. Proof of control was described as high-momentum and still thin.

Whether agent liability should look like personal liability, and how open source avoids rules that only states and large firms can make enforceable. Privacy was agreed not to be a liability waiver, and the recourse question stayed open.

Whether the star, the City Key, and the 64-state lattice are a research encoding, an educational picture of signature size, or a signature scheme. Uniqueness of real public keys is not in the current samples. One signature versus three was an example, not a rule.

Whether a two-agent rule (boundary-setter versus knowledge-holder, or delegation versus protection) should be imposed on the demo. The research side asked not to impose it. The demo side called the trust graph and proof of control essential.

Toy data versus real vulnerability and supply-chain data. Real data was the stated goal and is not in the system yet.

Whether hardware supply-chain incidents, including customer lists, can be encoded without creating a targeting list. The ideal was proofs on vertices rather than plaintext. No implementation was shown.

Where Ethereum privacy should land: layer 2 ZK virtual machines, layer 1, or a wallet. The public nature of Ethereum state was not disputed.

Proof of personhood via biometrics versus via issuer credentials, social graphs, or many weak signals. This was the next session's argument, present only as setup. Relying-party standards for signal weight, and issuer revocation, were the open points.

A document initially assigned to this session belonged elsewhere and was not presented.

Disposition of the work

Both projects are this session. The community security agent is a planned open-source cyber-defense tool, demoed against an Ethereum network and surrounding off-chain services, with TLP-scoped sharing and human approval. It is past the "idea" stage as a demo and not past the "early implementation" stage as a network of users. A grant application to the NSF open-source-ecosystem program is in progress, with SEAL and at least one other partner whose name was garbled. The repository is being moved under BGIN. Standards integration is agreed as a follow-up and was not done in the session. A personal experimental verifiable trust community exists. A BGIN community and a separate incident-response community do not yet. The geometric encoding is research shown alongside the project, with pull-request-style review started, and it is not the agent's architecture. GDC in September is the previous public presentation of the vulnerability-handling and agentic-AI line. Further contributions were being sought.

Actions

Each action is written so that it can be tracked without the rest of the record. Where the room named only a person, the action is kept and the name is omitted.

Circulate the repository link and confirm it on the BGIN project page. Invite contributors so the NSF

application has a visible body of work whether or not it is funded.

Add references in the repository to OpenVTC, IEEE My Terms, proof of control, and other standards the implementation actually uses.

Write the implementation plan for a cybersecurity verifiable trust community and a separate BGIN verifiable trust community.

Over about six months, finish the software, host the verifiable trust agent on an always-on machine or in a secure enclave so it can issue BGIN credentials, and schedule key ceremonies for the next block or a working-group meeting.

Keep the regular working group. The document that was on screen stays open for comment.

Put real vulnerability data and a list of supply-chain risks into the system. Community comments from incident-response groups, including SEAL 911, are the intended intake when an incident is live. Sensitive personal data stays as proofs, not plaintext.

Track the Advanced AI Society proof-of-control work and the Linux Foundation Decentralized Trust connection without treating them as adopted.

The GDC meeting report on vulnerability handling and agentic AI was offered for the chat. It is prior reading for this project.

The predicate-credential and proof-of-personhood comparison was deferred to the privacy session that this slice shows beginning after the break.

Coverage

This record covers the published security-agent session in Room B. The recording file starts at 10:04 EDT, so the first minutes of the 09:50 slot are missing. The captured portion opens with the session already underway. Figures are reported session claims, not independently validated measurements. Technical names are corrected where supported by the recording, chat, or identified primary documentation. Where a name could not be checked against another part of the same recording, it is left unverified rather than guessed. Logistics, introductions, and names of speakers are omitted.

Cues 0–6360, the opening stretch of the Day 2 Room B recording. The slice starts a few minutes after the scheduled open, with informal talk already underway, including a remote audio check. The captured opening introduces the vulnerability-handling and security-agent discussion. The demo, the OpenVTC proposal, the proof-of-control and liability exchange, the repository and NSF plans, the geometric research, and the supply-chain and Ethereum-privacy bridge are all inside the slice. One pre-submitted contribution was mis-assigned and skipped. The slice does not end at the workshop close. It runs through the break into the setup for privacy-enhanced authentication, including the proof-of-human comparison, and then into networking. Those later minutes are boundary material. Caption quality is moderate. Protocol names and several organization names are the unreliable layer. The demo's operational claims are only as precise as a silent video narrated afterward.

Source clarifications and open checks

Exchange-format name ("prefix move formats" or similar) that the agent is supposed to consume.

The identifier system "holding the DIDs.".

NSF application partner short name ("LIDA" or similar). SEAL was clear.

Privacy-wallet spelling ("Waku" was guessed in the room and then spelled uncertainly).

Project names confirmed after the meeting (19 October 2026): City Key / The Star Holds. The SHA-width / 64-state comparison remains unverified; the demonstration remains research and does not establish a validated signature scheme or real-key uniqueness.

"Agent jail" and the Merkle / legal-person item in the proof-of-control aside.