

METRIC

MIL-DTL-38999/43B
w/AMENDMENT 1
2 July 2024
SUPERSEDING
MIL-DTL-38999/43B
8 September 2010

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, RECEPTACLE,
JAM NUT MOUNTING, HERMETIC, BREECH COUPLING,
HERMETIC SOLDER CONTACTS, SERIES IV, METRIC

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein
shall consist of this specification sheet and MIL-DTL-38999.




FIGURE 1. Receptacle, classes N and Y.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5935

MIL-DTL-38999/43B
w/AMENDMENT 1

Shell size	Shell size code	A	B flat	C dia boss	E dia	F dia
11	B	35.2 (1.38)	19.17 (.754)	20.70 (.814)	18.6 (.732)	19.8 (.779)
		34.6 (1.36)	18.92 (.744)	20.40 (.803)	18.2 (.716)	19.3 (.759)
13	C	38.4 (1.51)	23.92 (.941)	25.50 (1.00)	21.8 (.858)	23.1 (.909)
		37.8 (1.488)	23.67 (.931)	25.20 (.992)	21.3 (.838)	22.6 (.889)
15	D	41.6 (1.63)	27.07 (1.06)	28.60 (.992)	25.0 (.984)	26.3 (1.03)
		41.0 (1.64)	26.82 (1.05)	28.30 (1.11)	24.6 (.968)	25.8 (1.01)
17	E	44.8 (1.76)	30.25 (1.19)	31.98 (1.25)	28.2 (1.11)	29.4 (1.15)
		44.2 (1.74)	30.00 (1.18)	MAX	27.7 (1.09)	28.9 (1.13)
19	F	49.5 (1.94)	33.44 (1.31)	35.15 (1.38)	31.4 (1.23)	32.6 (1.28)
		48.9 (1.92)	33.17 (1.30)	MAX	31.0 (1.32)	32.1 (1.26)
21	G	52.7 (2.07)	36.62 (1.44)	38.28 (1.507)	34.5 (1.35)	35.8 (1.27)
		52.1 (2.05)	36.35 (1.43)	MAX	34.1 (1.34)	35.3 (1.38)
23	H	55.9 (2.20)	39.75 (1.56)	41.30 (1.62)	37.7 (1.48)	39.0 (1.53)
		55.3 (2.17)	39.52 (1.55)	41.00 (1.61)	37.3 (1.46)	38.5 (1.51)
25	J	59.1 (2.32)	42.98 (1.55)	44.50 (1.61)	40.9 (1.61)	42.1 (1.61)
		58.4 (2.29)	42.70 (1.68)	44.20 (1.74)	40.5 (1.59)	41.6 (1.63)

FIGURE 1. Receptacle, classes N and Y – Continued.

MIL-DTL-38999/43B
w/AMENDMENT 1

Shell size	Shell size code	G thread	S	V ref	W	O-ring
11	B	M20X1- 6g 0.100R	32.2 (1.27) 31.3 (1.23)	28.4 (1.11) 27.5 (1.08)	3.0 (.118) 2.4 (.094)	AS 3582-022
13	C	M25X1- 6g 0.100R	35.4 (1.39) 34.5 (1.35)			AS 3582-024
15	D	M28X1- 6g 0.100R	38.6 (1.51) 37.7 (1.48)			AS 3582-026
17	E	M32X1- 6g 0.100R see note 2	41.7 (1.64) 40.8 (1.60)			AS 3582-028
19	F	M35X1- 6g 0.100R	46.5 (1.83) 45.6 (1.79)		3.8 (.149) 3.2 (.125)	AS 3582-128
21	G	M38X1- 6g 0.100R	49.7 (1.95) 48.8 (1.92)			AS 3582-130
23	H	M41X1- 6g 0.100R	52.8 (2.07) 51.9 (2.04)			AS 3582-132
25	J	M44X1- 6g 0.100R	56.0 (2.20) 55.1 (2.16)			AS 3582-134

NOTES:

1. Dimensions are in millimeters.
2. Modified major DIA 31.80-31.95.
3. Inch-pound conversion are provided in parentheses for information only.

FIGURE 1. Receptacle, classes N, and Y – Continued.

MIL-DTL-38999/43B
w/AMENDMENT 1

REQUIREMENTS:

Dimensions and configurations: See figure 1.


Interface dimensions shall conform to MIL-DTL-38999.

This connector mates with MIL-DTL-38999/46 and /47.

Main key color: Blue.

For insert arrangements: See MIL-STD-1560.

Part or Identifying Number (PIN) example:



For contact termination: See MIL-DTL-38999.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents: In addition to MIL-DTL-38999, this document references the following:

MIL-DTL-38999/46
MIL-DTL-38999/47
MIL-STD-1560
SAE-AS3582

MIL-DTL-38999/43B
w/AMENDMENT 1

CONCLUDING MATERIAL

Custodians:

Army – CR
Navy - AS
Air Force – 85
DLA - CC

Preparing activity:

DLA - CC

(Project 5935-2024-144)

Review activities:

Army - AR, MI
Navy - EC, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.