

SBML Level 3 Package: Flux Balance Constraints (‘fbc’)

Brett G. Olivier

b.g.olivier@vu.nl

Systems Bioinformatics
VU University Amsterdam
Amsterdam, NH, The Netherlands

Frank T. Bergmann

fbergmann@caltech.edu

Computing and Mathematical Sciences
California Institute of Technology
Pasadena, CA, US

Version 1, Release Candidate 1

December 11, 2012

This is a draft specification for the package “fbc” and not a normative document. Please send feedback to the Package Working Group mailing list at sbml-flux@lists.sourceforge.net

The latest release, past releases, and other materials related to this specification are available at [http://sbml.org/Documents/Specifications/SBML_Level_3/Packages/Flux_Balance_Constraints_\(flux\)](http://sbml.org/Documents/Specifications/SBML_Level_3/Packages/Flux_Balance_Constraints_(flux))

This release of the specification is available at
http://sbml.org/Documents/Specifications/Fbc_Level_1_Version_1



Contents

1	Introduction and motivation	3
1.1	Proposal corresponding to this package specification	3
1.2	Tracking number	4
1.3	Package dependencies	4
1.4	Document conventions	4
2	Background	5
2.1	Problems with current SBML approaches	5
2.2	Past work on this problem or similar topics	5
3	Proposed syntax and semantics	6
3.1	Namespace URI and other declarations necessary for using this package	6
3.2	Primitive data types	6
3.2.1	Type FbcSid	6
3.2.2	Type FbcSidRef	6
3.2.3	Type FbcType	6
3.2.4	Type FbcOperation	7
3.3	The extended Model class	7
3.3.1	The FBC listOfFluxBounds	7
3.3.2	The FBC listOfObjectives	7
3.4	The extended Species class	8
3.5	The FBC FluxBound class	8
3.6	The FBC Objective class	9
3.7	The FBC FluxObjective class	11
4	Examples	12
4.1	Example of the FBC syntax	12
4.1.1	Kinetic model description	12
4.1.2	Capacity constraints	13
4.1.3	Objective function	13
4.1.4	Complete worked example	13
5	Best practices	16
5.1	Examples contrasting the current SBML L2 encoding with L3 and FBC	16
6	Future development	19
6.1	Model annotation	19
6.1.1	Gene association annotation	19
6.1.2	Generic annotation mechanism	19
A	Validation of SBML documents	22
A.1	Validation and consistency rules	22
	Acknowledgments	27
	References	28

1 Introduction and motivation

Constraint based modelling is a widely accepted methodology used to analyze and study biological networks on both a small and whole organism (genome) scale. Typically these models are underdetermined and constraint based methods (e.g. linear, quadratic optimization) are used to optimize specific model properties. This is assumed to occur under a defined set of constraints (e.g. stoichiometric, metabolic) and bounds (e.g. thermodynamic, experimental and environmental) on the values that the solution fluxes can obtain.

Perhaps the most well known (and widely used) analysis method is Flux Balance Analysis (FBA; Orth et al., 2010) which is performed on Genome Scale Reconstructions (GSR's; Oberhardt et al., 2009). Using FBA a target flux is optimized (e.g. maximizing a flux to biomass or minimizing ATP production) while other fluxes can be bounded to simulate a selected growth environment or specific metabolic state.

As constraint based models are generally underdetermined, i.e. few or none of the kinetic rate equations and related parameters are known, it is crucial that a model definition includes the ability to define optimization parameters such as objective functions, flux bounds and constraints ... currently this is not possible in the Systems Biology Markup Language (SBML) Level 2 or Level 3 core specification (Hucka et al., 2011, 2003).

The question of how to encode constraint based (a.k.a. 'FBA') models in SBML is not new. However, advances in the methods used to construct GSR scale models and the wider adoption of constraint based modelling in biotechnological/medical applications have led to a rapid increase in both the number of models being constructed and the tools used to analyze them.

Faced with such growth, both in number and diversity, the need for a standardized data format for the definition, exchange and annotation of constraint based models has become critical. As the core model components (e.g. species, reactions, stoichiometry) can already be efficiently described in SBML (with its significant community, software and tool support) the Flux Balance Constraints Package aims to extend SBML core by adding the elements necessary to describe current and future constraint based models.

1.1 Proposal corresponding to this package specification

This specification for Flux Balance Constraints in SBML Level 3 Version 1 is based on the proposal by the same authors, located at the following URL:

[http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Flux_Balance_Constraints_Proposal_\(2012\)](http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Flux_Balance_Constraints_Proposal_(2012))

The tracking number in the SBML issue tracking system (SBML Team, 2010) for Flux Balance Constraints package activities is 3154219. The version of the proposal used as the starting point for this specification is the version of March 2012. Previous versions of the current proposal are:

Version 3 (March 2012)

[http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Flux_Balance_Constraints_Proposal_\(2012\)](http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Flux_Balance_Constraints_Proposal_(2012))

Version 2 (March 2011)

http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Flux_Constraints_Proposal

Version 1 (February 2010)

<http://precedings.nature.com/documents/4236/version/1>

Details of earlier independent proposals are provided in Section 2.

1.2 Tracking number

As initially listed in the SBML issue tracking system under: http://sourceforge.net/tracker/?func=detail&aid=3154219&group_id=71971&atid=894711.

1.3 Package dependencies

The Flux Balance Constraints package adds additional classes to SBML Level 3 Version 1 Core and has no dependency on any other SBML Level 3 package.

1.4 Document conventions

Following the precedent set by the SBML Level 3 Core specification document, we use UML 1.0 (Unified Modeling Language; Eriksson and Penker 1998; Oestereich 1999) class diagram notation to define the constructs provided by this package. We also use color in the diagrams to carry additional information for the benefit of those viewing the document on media that can display color. The following are the colors we use and what they represent:

- *Black*: Items colored black in the UML diagrams are components taken unchanged from their definition in the SBML Level 3 Core specification document.
- *Green*: Items colored green are components that exist in SBML Level 3 Core, but are extended by this package. Class boxes are also drawn with dashed lines to further distinguish them.
- *Blue*: Items colored blue are new components introduced in this package specification. They have no equivalent in the SBML Level 3 Core specification.

We also use the following typographical conventions to distinguish the names of objects and data types from other entities; these conventions are identical to the conventions used in the SBML Level 3 Core specification document:

AbstractClass: Abstract classes are classes that are never instantiated directly, but rather serve as parents of other object classes. Their names begin with a capital letter and they are printed in a slanted, bold, sans-serif typeface. In electronic document formats, the class names defined within this document are also hyperlinked to their definitions; clicking on these items will, given appropriate software, switch the view to the section in this document containing the definition of that class. (However, for classes that are unchanged from their definitions in SBML Level 3 Core, the class names are not hyperlinked because they are not defined within this document.)

Class: Names of ordinary (concrete) classes begin with a capital letter and are printed in an upright, bold, sans-serif typeface. In electronic document formats, the class names are also hyperlinked to their definitions in this specification document. (However, as in the previous case, class names are not hyperlinked if they are for classes that are unchanged from their definitions in the SBML Level 3 Core specification.)

Something, otherThing: Attributes of classes, data type names, literal XML, and generally all tokens *other* than SBML UML class names, are printed in an upright typewriter typeface. Primitive types defined by SBML begin with a capital letter; SBML also makes use of primitive types defined by XML Schema 1.0 (Biron and Malhotra, 2000; Fallside, 2000; Thompson et al., 2000), but unfortunately, XML Schema does not follow any capitalization convention and primitive types drawn from the XML Schema language may or may not start with a capital letter.

For other matters involving the use of UML and XML, we follow the conventions used in the SBML Level 3 Core specification document.

2 Background

2.1 Problems with current SBML approaches

While there is currently no official way of encoding constraint based models in SBML L2 there have been pragmatic approaches used by a variety of groups and applications. Arguably the best and most widely used format is that used by the COBRA toolbox (Becker et al., 2007) where the metabolic network is well defined using SBML **Reaction** and **Species** classes. However, flux bounds and reactions that take part in the objective function are defined as **LocalParameter** objects and (implicitly) rely on all tools using the same naming convention. Similarly, reaction annotations are generally stored as key-value pairs in HTML **Notes** objects which has routinely led to different groups and software using in-house key definitions describing the same entity. While a step in the right direction this format is not suitable for implementation in SBML Level 3.

2.2 Past work on this problem or similar topics

The problem of describing and annotating 'FBA' models in SBML has been raised at various times in the past few years. In this regard there are two known putative proposals one by Karthik Raman and the other by the Church Laboratory. As far as we are aware these proposals never developed beyond their initial presentation at SBML forum/hackathons. In 2009 the discussion was reopened at the SBML Forum held in Stanford and has subsequently developed into the current active package proposal and this document (see Section 1).

Brett Olivier (2009) SBML Level 3 FBA package discussion

http://sbml.org/images/4/4a/Olivier_sbml_forum_2009_09_04.pdf

Karthik Raman (2005) Flux annotations in SBML

<http://sbml.org/images/d/d9/Raman-flux-annotations.pdf>

Church laboratory (pre 2005) Metabolic flux model annotations

http://sbml.org/Community/Wiki/Old_known_SBML_annotations_list

3 Proposed syntax and semantics

In this section, we define the syntax and semantics of the Flux Balance Constraints package for SBML Level 3 Version 1. We expound on the various data types and constructs defined in this package, then in [Section 4 on page 12](#), we provide complete examples of using the constructs in example SBML models.

3.1 Namespace URI and other declarations necessary for using this package

Every SBML Level 3 package is identified uniquely by an XML namespace URI. For an SBML document to be able to use a given SBML Level 3 package, it must declare the use of that package by referencing its URI. The following is the namespace URI for this version of the Flux Balance Constraints package for SBML Level 3 Version 1:

`"http://www.sbml.org/sbml/level3/version1/fbc/version1"`

In addition, SBML documents using a given package must indicate whether understanding the package is required for complete mathematical interpretation of a model, or whether the package is optional. This is done using the attribute `required` on the `<sbml>` element in the SBML document. For the Flux Balance Constraints package, the value of this attribute must be set to `"true"`.

The following fragment illustrates the beginning of a typical SBML model using SBML Level 3 Version 1 and this version of the Flux Balance Constraints package:

```
<?xml version="1.0" encoding="UTF-8"?>
<sbml xmlns="http://www.sbml.org/sbml/level3/version1/core" level="3"
version="1"
      xmlns:fbc="http://www.sbml.org/sbml/level3/version1/fbc/version1"
      fbc:required="true">
```

3.2 Primitive data types

Section 3.1 of the SBML Level 3 Version 1 Core specification defines a number of primitive data types and also uses a number of XML Schema 1.0 data types ([Biron and Malhotra, 2000](#)). More specifically we make use of `integer`, `double`, `string` and `SIIDRef`. In addition we make use of four new primitives `FbcSIID`, `FbcSIIDRef` as well as the enumerations `FbcType` and `FbcOperation`, see [Figure 1](#) for the interrelation between these entities.

3.2.1 Type FbcSIID

The type `FbcSIID` is derived from `SIID` (SBML Level 3 Version 1 Core specification Section 3.1.7) and has identical syntax. The `FbcSIID` type is used as the data type for the identifiers of **FluxBound** ([Section 3.5](#)) and **Objective** ([Section 3.6](#)) classes. By using a separate identifier type we differentiate them from others defined in the **SBML** model and thus ensuring data encapsulation.

3.2.2 Type FbcSIIDRef

Type `FbcSIIDRef` is used for all attributes that refer to identifiers of type `FbcSIID`. Derived from `FbcSIID` it has the restriction that the value of an attribute having type `FbcSIIDRef` must match the value of a `FbcSIID` attribute in the current model. In the FBC package the **ListOfObjectives** has an attribute of this type that is used to refer to an 'active' **Objective**.

3.2.3 Type FbcType

The Flux Balance Constraints package defines a new enumerated type `FbcType` which represents the optimization sense of the objective function. It can have one of the following two values `"maximize"` or `"minimize"`.




Figure 1: A UML representation of the Flux Balance Constraints package classes. See [Section 1.4](#) for conventions related to this figure. The individual classes are further discussed in the text.

3.2.4 Type **FbcOperation**

The Flux Balance Constraints package defines a new enumerated type **FbcOperation** which represents a boolean operator. It can take only one of the following values: “lessEqual”, “greaterEqual”, “less”, “greater” or “equal”.

3.3 The extended **Model** class

The **SBML Model** class is extended with the addition of two children, i.e. a **listOfFluxBounds** and a **listOfObjectives**. The **Model** may contain at most one of these lists.

3.3.1 The **FBC** **listOfFluxBounds**

As shown in [Figure 1](#) the **ListOfFluxBounds** is derived from **SBase** and inherits the attributes **metaid** and **sboTerm**, as well as the subcomponents for **Annotation** and **Notes**. **ListOfFluxBounds** must contain at least one **FluxBound** (defined in [Section 3.5](#)).

3.3.2 The **FBC** **listOfObjectives**

As shown in [Figure 1](#) the **ListOfObjectives** is derived from **SBase** and inherits the attributes **metaid** and **sboTerm**, as well as the subcomponents for **Annotation** and **Notes**. Unlike most other **SBML ListOf__** classes, **ListOfObjec-**

tives introduces an additional required attribute **activeObjective**. The **ListOfObjectives** must contain at least one **Objective** (defined in Section 3.6).

The **activeObjective** attribute

This attribute is of type **FbcSIdRef** and can only refer to an existing **Objective** (**FbcSId**). This required attribute exists so that when multiple **Objective** 's are included in a single model, the model will always be well described i.e. there is a single, primary objective function which defines a single optimum and its associated solution space.

3.4 The extended **Species** class

The Flux Balance Constraints package extends the SBML Level 3 Version 1 Core **Species** class with the addition of two attributes:

The **charge** attribute

The optional attribute **charge** which contains a signed **integer** referring to the **Species** object's charge and is defined as it was in the **SBML** Level 2 Version 1 specification : *"The optional field charge takes an integer indicating the charge on the species (in terms of electrons, not the SI unit coulombs)."*

The **chemicalFormula** attribute

The optional attribute **chemicalFormula** containing a **string** that represents the **Species** objects elemental composition.

```
<species metaid="meta_M_atp_c" id="M_atp_c" name="ATP"
  compartment="Cytosol" boundaryCondition="false"
  fbc:charge="-4" fbc:chemicalFormula="C10H12N5O13P3"
  initialConcentration="0" hasOnlySubstanceUnits="false"
/>
```

While there are many ways of referring to an elemental composition the purpose of the **chemicalFormula** attribute is to allow reaction balancing and validation which is particularly important in constraint based models. To this end it is recommended that the format of **chemicalFormula** should follow the Hill system (or notation). Here the number of carbon atoms in a molecule is indicated first, followed by the number of hydrogen atoms and then the number of all other chemical elements in alphabetical order. When the formula contains no carbon; all elements, including hydrogen, are listed alphabetically.




Figure 2: A UML representation of the extended **SBML Species** class used in the Flux Balance Constraints package. See Section 1.4 for conventions related to this figure.

3.5 The FBC FluxBound class

FluxBound is a new FBC class derived from **SBML SBBase** that inherits **metaid** and **sboTerm**, as well as the sub-components for **Annotation** and **Notes**. The purpose of this class is to hold a single (in)equality that provides the maximum or minimum value that a reaction flux can obtain at steady state. It implements four attributes.

The **id** and **name** attributes

A **FluxBound** has two optional attributes: **id** an attribute of type **FbcSId** and **name** an attribute of type **string**.

The **reaction** attribute

The required **reaction** attribute of type **SIdRef**. This attribute must refer to a **Reaction** element defined within the enclosing model.

The **operation** attribute

The **operation** attribute contains a value of type **FbcOperation** that can take a limited set of boolean operators as defined in [Section 3.2.4](#). The **operation** attribute represents a mathematical (in)equality of the form `<reaction> <operator> <value>` e.g. $R_5 \geq 0$, $R_5 < \infty$ and $R_7 = 1.0$. The mapping between traditional mathematical symbols and **FbcOperation** values is as follows:

<code><=</code>	\mapsto	<code>"lessEqual"</code>
<code>>=</code>	\mapsto	<code>"greaterEqual"</code>
<code><</code>	\mapsto	<code>"less"</code>
<code>></code>	\mapsto	<code>"greater"</code>
<code>=</code>	\mapsto	<code>"equal"</code>

The **value** attribute

The **value** attribute holds a **double** value representing the numerical value of the flux bound. This may include an explicitly defined $\pm\infty$ encoded as a value, e.g. `"INF"`.

Encoding the **FluxBound**

As described in [Section 3.5](#) the flux bound represents a mathematical (in)equality of the form

`<reaction> <operator> <value>`.

In SBML Level 3 Version 1 with FBC this is encoded as:

```

<fbc:listOfFluxBounds>
  <fbc:fluxBound fbc:id="R1b" fbc:reaction="R1" fbc:operation="greaterEqual" fbc:value="1.2"/>
  <fbc:fluxBound fbc:id="R2b" fbc:reaction="R2" fbc:operation="lessEqual" fbc:value="-1.2"/>
  <fbc:fluxBound fbc:id="R3b" fbc:reaction="R3" fbc:operation="greaterEqual" fbc:value="-INF"/>
  <fbc:fluxBound fbc:id="R4b" fbc:reaction="R4" fbc:operation="lessEqual" fbc:value="INF"/>
  <fbc:fluxBound fbc:id="R5b" fbc:reaction="R5" fbc:operation="equal" fbc:value="1"/>
  <fbc:fluxBound fbc:id="R6b" fbc:reaction="R6" fbc:operation="greater" fbc:value="-1"/>
  <fbc:fluxBound fbc:id="R7b" fbc:reaction="R7" fbc:operation="less" fbc:value="1"/>
</fbc:listOfFluxBounds>

```

This example illustrates two things: the encoding of ∞ and that care should be used when selecting inequalities such as `"less"` or `"greater"`. While mathematically there is a difference, this difference is only practically relevant when working with rational arithmetic (solvers).

3.6 The FBC **Objective** class

The FBC **Objective** class is derived from **SBML SBase** and inherits **metaid** and **sboTerm**, as well as the subcomponents for **Annotation** and **Notes**. An integral component in a complete description of a steady-state model is the so-called 'objective function' which generally consist of a linear combination of model variables (fluxes) and a sense (direction). In the FBC package this concept is succinctly captured in the **Objective** class.

The **id** and **name** attributes

An **Objective** has a required attribute **id** of type **FbcSId** and an optional attribute **name** of type **string**.




Figure 3: A UML representation of the Flux Balance Constraints package **FluxBound** class. See [Section 1.4](#) for conventions related to this figure.

The **type** attribute

The required **type** attribute contains an **FbcType** type which represents the sense of the optimality constraint and can take one of two values:

$maximize \mapsto "maximize"$
 $minimize \mapsto "minimize"$

The **listOfFluxObjectives** element

The element **listOfFluxObjectives** which contains a **ListOfFluxObjectives** is derived from and functions like a typical **SBML ListOf__** class with the restriction that it must contain one or more elements of type **FluxObjective** (see [Section 3.7](#)). This implies that if an **Objective** is defined there should be at least one **FluxObjective** contained in a **ListOfFluxObjectives**.




Figure 4: A UML representation of the Flux Balance Constraints package **Objective** class. See [Section 1.4](#) for conventions related to this figure.

Encoding the **Objective**

The Flux Balance Constraints package allows for the definition of multiple model objectives with one being designated as active (see [Section 3.6](#)) as illustrated in this example:

```

<fbc:listOfObjectives fbc:activeObjective="obj1">
  <fbc:objective fbc:id="obj1" fbc:type="maximize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R101" fbc:coefficient="1"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
  <fbc:objective fbc:id="obj2" fbc:type="minimize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R102" fbc:coefficient="-2.5"/>
      <fbc:fluxObjective fbc:reaction="R103" fbc:coefficient="1"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
</fbc:listOfObjectives>

```

Note how both **Objective** instances differ in **type** and each contains different set of **FluxObjectives** (see [Section 3.7](#)).

3.7 The FBC FluxObjective class

The FBC **FluxObjective** class is derived from **SBML SBBase** and inherits **metaid** and **sboTerm**, as well as the sub-components for **Annotation** and **Notes**.

The **FluxObjective** class is a relatively simple container for a model variable weighted by a signed linear coefficient.

The id and name attributes

A **FluxObjective** has two optional attributes: **id** an attribute of type **FbcSId** and **name** an attribute of type **string**.

The reaction and coefficient attributes

The required **reaction** is of type **SIdRef** and is restricted to refer only to an **SBML Reaction** while the **coefficient** attribute holds a **double** referring to the coefficient that this **FluxObjective** takes in the enclosing **Objective** . For example the objective **Maximize: 1 R1 + 2 R2** would be encoded as

```
<fbc:listOfObjectives fbc:activeObjective="obj1">
  <fbc:objective fbc:id="obj1" fbc:type="maximize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R1" fbc:coefficient="1"/>
      <fbc:fluxObjective fbc:reaction="R2" fbc:coefficient="2"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
</fbc:listOfObjectives>
```




Figure 5: A UML representation of the Flux Balance Constraints package **FluxObjective** class. See [Section 1.4](#) for conventions related to this figure.

4 Examples

This section contains a worked example showing the encoding of a model suitable for Flux Balance Analysis using the Flux Balance Constraints package.

4.1 Example of the FBC syntax

4.1.1 Kinetic model description




Figure 6: FBC syntax example: a simple four reaction pathway. The reactions are R1, R2, X1, X2 with fixed species IN, OUT, ATP, NADH and variable species A, B.

As shown in Figure 6 this example is a simple four reaction pathway that transforms metabolite IN to OUT. The model was created and analyzed using the SBW Flux Balance FBC implementation Bergmann (2012); Bergmann and Sauro (2006). In SBML each reaction is represented as a chemical process transforming reactants to products, e.g. reaction R1 is encoded in XML as (see also the complete example provided at the end of this section):

```
<reaction id="R1" reversible="false" fast="false">
  <listOfReactants>
    <speciesReference species="IN" stoichiometry="1" constant="true"/>
  </listOfReactants>
  <listOfProducts>
    <speciesReference species="A" stoichiometry="1" constant="true"/>
  </listOfProducts>
</reaction>
```

Using the reagent identity and stoichiometry it is possible to compactly describe this network in terms of its reaction stoichiometry as shown in Table 1 where each reaction is represented as a column. While the stoichiometry

	R1	R2	X1	X2
A	1	0	-1	-1
B	0	-1	1	1

Table 1: Example one: stoichiometric matrix, N

contains the structural properties of the reaction network the full description of a biological model can be described as a set of ordinary differential equations (ODE's). Of course other formalisms do exist, but here we will

concentrate exclusively on kinetic models where the change in concentration of each variable component in the system ($\frac{ds}{dt}$) is a non-linear function of the rates of the reactions which either create or consume it (the product of the stoichiometric matrix, \mathbf{N} and the vector of reaction rates, \mathbf{v}).

$$\frac{ds}{dt} = \mathbf{N}\mathbf{v} \quad (1)$$

The formulation of the kinetic model, as shown in Equation 1 is typical of the kind that can already be described using SBML Level 3 Version 1 Core where the vector \mathbf{v} would contain rate equations as a function of parameters and variable species. In a steady-state, constraint based model these rates are considered unknowns and the system of equations can be rewritten as a set of linear constraints (see Equation 2):

$$\mathbf{N}\mathbf{J} = 0 \quad (2)$$

Note that the rate vector \mathbf{v} is now represented as the steady-state flux vector \mathbf{J} . However, in order to perform a typical steady-state analysis such as flux balance analysis (FBA) we need to include more information into the model description. SBML Level 3 Version 1 Core does not have an unambiguous way of encoding either a capacity constraint or an objective target and for this we need to use the additional constructs provided by the Flux Balance Constraints package. In the following sections the same model data is shown encoded as both XML and in the LP format (as used by IBM CPLEX).

4.1.2 Capacity constraints

A capacity constraint: in this example the maximum limit (upper bound) of the flux through reaction *R1* is set to be one (with an arbitrary unit of flux). In LP format this can be written as:

```
Bounds
R1 <= 1.0
```

the same information encoded as XML:

```
<fbc:listOfFluxBounds>
  <fbc:fluxBound fbc:reaction="R1" fbc:operation="lessEqual" fbc:value="1"/>
</fbc:listOfFluxBounds>
```

4.1.3 Objective function

This describes a target which can be maximized or minimized: in this example the flux through reaction *R2* will be *maximized*.

```
Maximize
objective1_objf: + 1.0 R2
```

the same information encoded as XML:

```
<fbc:listOfObjectives fbc:activeObjective="objective1">
  <fbc:objective fbc:id="objective1" fbc:type="maximize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R2" fbc:coefficient="1"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
</fbc:listOfObjectives>
```

4.1.4 Complete worked example

To conclude we show how the complete model described in Figure 6 encoded as both an LP and as XML. Formulated as an LP the problem can be written as:

```

\\ Example one LP format

Maximize
objective1_objf:  + 1.0 R2

Subject To
A: + R1 - X1 - X2 = 0.0
B: - R2 + X1 + X2 = 0.0

Bounds
R1 <= 1.0
0.0 <= R2 <= +inf
0.0 <= X1 <= +inf
0.0 <= X2 <= +inf

END

```

Solving this we find that maximization of flux through $R2$ gives an optimal solution of *one* shown with one possible solution for **J** (see Equation 3).

$$\begin{pmatrix} 1 & 0 & -1 & -1 \\ 0 & -1 & 1 & 1 \end{pmatrix} \begin{pmatrix} 1.0 \\ \mathbf{1.0} \\ 0.0 \\ 1.0 \end{pmatrix} = \mathbf{0} \quad (3)$$

Finally we provide the complete model, described above, encoded using the Flux Balance Constraints package:

```

<?xml version="1.0" encoding="UTF-8"?>
<sbml xmlns="http://www.sbml.org/sbml/level3/version1/core"
      xmlns:fbc="http://www.sbml.org/sbml/level3/version1/fbc/version1"
      level="3" version="1" fbc:required="false">
  <model id="fbcSpecExample1" timeUnits="time">
    <listOfUnitDefinitions>
      <unitDefinition id="volume">
        <listOfUnits>
          <unit kind="litre" exponent="1" scale="0" multiplier="1"/>
        </listOfUnits>
      </unitDefinition>
      <unitDefinition id="substance">
        <listOfUnits>
          <unit kind="mole" exponent="1" scale="0" multiplier="1"/>
        </listOfUnits>
      </unitDefinition>
      <unitDefinition id="time">
        <listOfUnits>
          <unit kind="second" exponent="1" scale="0" multiplier="1"/>
        </listOfUnits>
      </unitDefinition>
    </listOfUnitDefinitions>
    <listOfCompartments>
      <compartment id="compartment" spatialDimensions="3" size="1"
        units="volume" constant="true"/>
    </listOfCompartments>
    <listOfSpecies>
      <species id="IN" compartment="compartment" initialConcentration="0"
        substanceUnits="substance" hasOnlySubstanceUnits="false"
        boundaryCondition="true" constant="false"/>
      <species id="OUT" compartment="compartment" initialConcentration="0"
        substanceUnits="substance" hasOnlySubstanceUnits="false"
        boundaryCondition="true" constant="false"/>
      <species id="A" compartment="compartment" initialConcentration="0"
        substanceUnits="substance" hasOnlySubstanceUnits="false"
        boundaryCondition="false" constant="false"/>
      <species id="B" compartment="compartment" initialConcentration="0"

```

```

    substanceUnits="substance" hasOnlySubstanceUnits="false"
    boundaryCondition="false" constant="false"/>
  <species id="ATP" compartment="compartment" initialConcentration="0"
    substanceUnits="substance" hasOnlySubstanceUnits="false"
    boundaryCondition="true" constant="false"/>
  <species id="NADH" compartment="compartment" initialConcentration="0"
    substanceUnits="substance" hasOnlySubstanceUnits="false"
    boundaryCondition="true" constant="false"/>
</listOfSpecies>
<listOfReactions>
  <reaction id="R1" reversible="false" fast="false">
    <listOfReactants>
      <speciesReference species="IN" stoichiometry="1" constant="true"/>
    </listOfReactants>
    <listOfProducts>
      <speciesReference species="A" stoichiometry="1" constant="true"/>
    </listOfProducts>
  </reaction>
  <reaction id="R2" reversible="false" fast="false">
    <listOfReactants>
      <speciesReference species="B" stoichiometry="1" constant="true"/>
    </listOfReactants>
    <listOfProducts>
      <speciesReference species="OUT" stoichiometry="1" constant="true"/>
    </listOfProducts>
  </reaction>
  <reaction id="X1" reversible="false" fast="false">
    <listOfReactants>
      <speciesReference species="A" stoichiometry="1" constant="true"/>
    </listOfReactants>
    <listOfProducts>
      <speciesReference species="ATP" stoichiometry="1" constant="true"/>
      <speciesReference species="B" stoichiometry="1" constant="true"/>
    </listOfProducts>
  </reaction>
  <reaction id="X2" reversible="false" fast="false">
    <listOfReactants>
      <speciesReference species="A" stoichiometry="1" constant="true"/>
    </listOfReactants>
    <listOfProducts>
      <speciesReference species="B" stoichiometry="1" constant="true"/>
      <speciesReference species="NADH" stoichiometry="1" constant="true"/>
    </listOfProducts>
  </reaction>
</listOfReactions>
<fbc:listOfFluxBounds>
  <fbc:fluxBound fbc:reaction="R1" fbc:operation="lessEqual" fbc:value="1"/>
</fbc:listOfFluxBounds>
<fbc:listOfObjectives fbc:activeObjective="objective1">
  <fbc:objective fbc:id="objective1" fbc:type="maximize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R2" fbc:coefficient="1"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
</fbc:listOfObjectives>
</model>
</sbml>

```

5 Best practices

In this section, we recommend a number of practices for using and interpreting various constructs in the Flux Balance Constraints package. These recommendations are non-normative, but we advocate them strongly; ignoring them will not render a model invalid, but may reduce inter-operability between software and models.

5.1 Examples contrasting the current SBML L2 encoding with L3 and FBC

These examples contrast some elements of an existing model, iJR904 from the BiGG Database encoded in the COBRA format [Becker et al. \(2007\)](#); [Reed et al. \(2003\)](#); [Schellenberger et al. \(2010\)](#) that have been translated into SBML Level 3 Version 1 using the CBMPy implementation of the FBC package [Olivier \(2012\)](#); [Olivier et al. \(2005\)](#) and libSBML experimental ver. 5.6.0 [Bornstein et al. \(2008\)](#).

Objective function definition

SBML Level 2 objective function

```
<reaction id="R_BiomassEcoli" name="BiomassEcoli" reversible="false">
  <kineticLaw>
    <math xmlns="http://www.w3.org/1998/Math/MathML">
      <ci>FLUX_VALUE</ci>
    </math>
    <listOfParameters>
      <parameter id="LOWER_BOUND" value="0" units="mmol_per_gDW_per_hr"/>
      <parameter id="UPPER_BOUND" value="999999" units="mmol_per_gDW_per_hr"/>
      <parameter id="OBJECTIVE_COEFFICIENT" value="1" />
      <parameter id="FLUX_VALUE" value="0" units="mmol_per_gDW_per_hr"/>
    </listOfParameters>
  </kineticLaw>
</reaction>
```

The SBML Level 3 objective function

```
<fbc:listOfObjectives fbc:activeObjective="obj1">
  <fbc:objective fbc:id="obj1" fbc:type="maximize">
    <fbc:listOfFluxObjectives>
      <fbc:fluxObjective fbc:reaction="R_BiomassEcoli" fbc:coefficient="1"/>
    </fbc:listOfFluxObjectives>
  </fbc:objective>
</fbc:listOfObjectives>
```

Species definition

It is particularly useful to contrast the differences in the **Species** definition as it is used in genome scale models.

SBML Level 2 Species annotation version 1

To begin with we let's examine the **SBML** Level 2 Version 1 species definition used by the BiGG database and COBRA [Becker et al. \(2007\)](#); [Schellenberger et al. \(2010\)](#). Note how the **name** attribute is overloaded with the chemical formula.

```
<species id="M_atp_c" name="ATP_C10H12N5O13P3"
  compartment="Cytosol" charge="-4" />
```


SBML Level 2 Species annotation version 2

A newer variation of the above, probably necessitated by the discontinuation of the **charge** attribute in **SBML** and libSBML

```
<species id="M_atp_c" name="ATP" compartment="c">
  <notes>
    <body xmlns="http://www.w3.org/1999/xhtml">
      <p>FORMULA: C10H12N5O13P3</p>
      <p>CHARGE: -4</p>
    </body>
  </notes>
</species>
```

The SBML Level 3 Species attributes

Hopefully, with the adoption of **SBML** FBC these species properties can be unified into a common format.

```
<species metaid="meta_M_atp_c" id="M_atp_c" name="ATP"
  compartment="Cytosol" boundaryCondition="false"
  fbc:charge="-4" fbc:chemicalFormula="C10H12N5O13P3"
  initialConcentration="0" hasOnlySubstanceUnits="false"
/>
```

Reaction definition and flux bounds**SBML Level 2 Reaction**

```
<reaction id="R_GTHS" name="glutathione_synthetase" reversible="false">
  <notes>
    <html:p>Abbreviation: R_GTHS</html:p>
    <html:p>Synonyms: _0</html:p>
    <html:p>EC Number: 6.3.2.3</html:p>
    <html:p>SUBSYSTEM: Cofactor and Prosthetic Group Biosynthesis</html:p>
    <html:p>Equation: [c] : atp + glucys + gly --> adp + gthrd + h + pi</html:p>
    <html:p>Confidence Level: 0</html:p>
    <html:p>NCD</html:p>
    <html:p>genes:</html:p>
    <html:p>LOCUS:b2947#ABBREVIATION:gshB#ECNUMBERS:6.3.2.3#</html:p>
    <html:p>proteins:</html:p>
    <html:p>NAME:glutathione synthase#ABBREVIATION:GshB#</html:p>
    <html:p>GENE ASSOCIATION: (b2947)</html:p>
  </notes>
  <listOfReactants>
    <speciesReference species="M_atp_c" stoichiometry="1"/>
    <speciesReference species="M_glucys_c" stoichiometry="1"/>
    <speciesReference species="M_gly_c" stoichiometry="1"/>
  </listOfReactants>
  <listOfProducts>
    <speciesReference species="M_adp_c" stoichiometry="1"/>
    <speciesReference species="M_gthrd_c" stoichiometry="1"/>
    <speciesReference species="M_h_c" stoichiometry="1"/>
    <speciesReference species="M_pi_c" stoichiometry="1"/>
  </listOfProducts>
  <kineticLaw>
    <math xmlns="http://www.w3.org/1998/Math/MathML">
      <ci>FLUX_VALUE</ci>
    </math>
    <listOfParameters>
      <parameter id="LOWER_BOUND" value="0" units="mmol_per_gDW_per_hr"/>
      <parameter id="UPPER_BOUND" value="999999" units="mmol_per_gDW_per_hr"/>
      <parameter id="OBJECTIVE_COEFFICIENT" value="0" />
    </listOfParameters>
  </kineticLaw>
</reaction>
```

```

<parameter id="FLUX_VALUE" value="0" units="mmol_per_gDW_per_hr"/>
</listOfParameters>
</kineticLaw>
</reaction>

```

The **SBML** Level 3 Reaction and FluxBound

As an example and where (unambiguously) possible the **SBML** Level 2 annotation has been converted into MIRIAM compliant RDE, in this case the *EC number*. In addition this example highlights an open issue, namely, how to deal with the information currently encoded in the **Notes** element. Currently this information is not completely encodable using the current **SBML** annotation mechanism, however, for an example of an alternative mechanism, implemented as a tool specific annotation please see [Section 6](#).

```

<reaction metaid="meta_R_GTHS" id="R_GTHS" name="glutathione_synthetase" reversible="false">
  <annotation>
    <rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
      xmlns:dc="http://purl.org/dc/elements/1.1/" xmlns:dcterms="http://purl.org/dc/terms/"
      xmlns:vCard="http://www.w3.org/2001/vcard-rdf/3.0#"
      xmlns:bqbiol="http://biomodels.net/biology-qualifiers/"
      xmlns:bqmodel="http://biomodels.net/model-qualifiers/">
      <rdf:Description rdf:about="#meta_R_GTHS">
        <bqbiol:is>
          <rdf:Bag>
            <rdf:li rdf:resource="http://identifiers.org/ec-code/6.3.2.3"/>
          </rdf:Bag>
        </bqbiol:is>
      </rdf:Description>
    </rdf:RDF>
  </annotation>
  <listOfReactants>
    <speciesReference species="M_atp_c" stoichiometry="1"/>
    <speciesReference species="M_glucys_c" stoichiometry="1"/>
    <speciesReference species="M_gly_c" stoichiometry="1"/>
  </listOfReactants>
  <listOfProducts>
    <speciesReference species="M_adp_c" stoichiometry="1"/>
    <speciesReference species="M_gthrd_c" stoichiometry="1"/>
    <speciesReference species="M_h_c" stoichiometry="1"/>
    <speciesReference species="M_pi_c" stoichiometry="1"/>
  </listOfProducts>
</reaction>

```

```

<fbc:listOfFluxBounds>
  <fbc:fluxBound fbc:id="R_GTHS_lower_bnd" fbc:reaction="R_GTHS" fbc:operation="greaterEqual"
    fbc:value="0"/>
  <fbc:fluxBound fbc:id="R_GTHS_upper_bnd" fbc:reaction="R_GTHS" fbc:operation="lessEqual"
    fbc:value="999999"/>
</fbc:listOfFluxBounds>

```

6 Future development

In this section we highlight some open issues not addressed in this version of the FBC specification.

6.1 Model annotation

While the Flux Balance Constraints package address the basic constraint based model structure the effective annotation of individual model components is critical to its efficient (re)use. Here two examples of custom annotations are provided as an example of how this could be achieved.

6.1.1 Gene association annotation

An example of an annotation currently encoded in the **Notes** element that is not encodable using the **SBML Annotation** mechanism is the so called “Gene Association”.

In order to capture this information we propose the following mechanism which can be used to represent a logical expression containing “genes” in this case the final (transcribed/translated) protein product of a gene which forms a sub-component of a protein.

```
<fbc:listOfGeneAssociations>
  <fbc:geneAssociation fbc:id="ga1" fbc:reaction="R_ACGAptspp">
    <fbc:or>
      <fbc:and>
        <fbc:gene>b2415</fbc:gene>
        <fbc:gene>b2417</fbc:gene>
        <fbc:gene>b2416</fbc:gene>
        <fbc:gene>b1101</fbc:gene>
      </fbc:and>
      <fbc:and>
        <fbc:gene>b2415</fbc:gene>
        <fbc:gene>b0679</fbc:gene>
        <fbc:gene>b2416</fbc:gene>
      </fbc:and>
    </fbc:or>
  </fbc:geneAssociation>
</fbc:listOfGeneAssociations>
```

6.1.2 Generic annotation mechanism

An annotation issue previously introduced in the example shown in [Section 4](#) where a **SBML Level 2 Reaction** is encoded using the Flux Balance Constraints package.

SBML Level 2 Reaction

```
<reaction id="R_GTHS" name="glutathione_synthetase" reversible="false">
  <notes>
    <html:p>Abbreviation: R_GTHS</html:p>
    <html:p>Synonyms: _0</html:p>
    <html:p>EC Number: 6.3.2.3</html:p>
    <html:p>SUBSYSTEM: Cofactor and Prosthetic Group Biosynthesis</html:p>
    <html:p>Equation: [c] : atp + glucys + gly --> adp + gthrd + h + pi</html:p>
    <html:p>Confidence Level: 0</html:p>
    <html:p>NCD</html:p>
    <html:p>genes:</html:p>
    <html:p>LOCUS:b2947#ABBREVIATION:gshB#ECNUMBERS:6.3.2.3#</html:p>
    <html:p>proteins:</html:p>
    <html:p>NAME:glutathione synthase#ABBREVIATION:GshB#</html:p>
    <html:p>GENE ASSOCIATION: (b2947)</html:p>
  </notes>
```

```

<listOfReactants>
  <speciesReference species="M_atp_c" stoichiometry="1"/>
  <speciesReference species="M_glucys_c" stoichiometry="1"/>
  <speciesReference species="M_gly_c" stoichiometry="1"/>
</listOfReactants>
<listOfProducts>
  <speciesReference species="M_adp_c" stoichiometry="1"/>
  <speciesReference species="M_gthrd_c" stoichiometry="1"/>
  <speciesReference species="M_h_c" stoichiometry="1"/>
  <speciesReference species="M_pi_c" stoichiometry="1"/>
</listOfProducts>
<kineticLaw>
  <math xmlns="http://www.w3.org/1998/Math/MathML">
    <ci>FLUX_VALUE</ci>
  </math>
  <listOfParameters>
    <parameter id="LOWER_BOUND" value="0" units="mmol_per_gDW_per_hr"/>
    <parameter id="UPPER_BOUND" value="999999" units="mmol_per_gDW_per_hr"/>
    <parameter id="OBJECTIVE_COEFFICIENT" value="0" />
    <parameter id="FLUX_VALUE" value="0" units="mmol_per_gDW_per_hr"/>
  </listOfParameters>
</kineticLaw>
</reaction>

```

SBML Level 3 Reaction

Note how that in order to maintain all the annotations encoded in the **SBML Level 2 Reaction** notes a custom annotation is introduced i.e. the `KeyValueData` class¹.

In general this example highlights the need for a community supported annotation mechanism for genome scale, constraint based models.

```

<reaction metaid="meta_R_GTHS" id="R_GTHS" name="glutathione_synthetase" reversible="false">
  <annotation>
    <listOfKeyValueData xmlns="http://pysces.sourceforge.net/KeyValueData">
      <data id="subsystem" type="string" value="Cofactor_and_Prosthetic_Group_Biosynthesis"/>
      <data id="name" type="string" value="glutathione_synthase#ABBREVIATION:GshB#"/>
      <data id="gene_association" type="string" value="(b2947)"/>
      <data id="equation" type="string" value="[c]_atp+_glucys+_gly_-->_adp+_gthrd+_h+_pi"/>
      <data id="genes" type="string"/>
      <data id="proteins" type="string"/>
      <data id="locus" type="string" value="b2947#ABBREVIATION:gshB#ECNUMBERS:6.3.2.3#"/>
      <data id="abbreviation" type="string" value="R_GTHS"/>
      <data id="synonyms" type="string" value="_0"/>
      <data id="confidence_level" type="string" value="0"/>
    </listOfKeyValueData>
    <rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
      xmlns:dc="http://purl.org/dc/elements/1.1/" xmlns:dcterms="http://purl.org/dc/terms/"
      xmlns:vCard="http://www.w3.org/2001/vcard-rdf/3.0#"
      xmlns:bqbiol="http://biomodels.net/biology-qualifiers/"
      xmlns:bqmodel="http://biomodels.net/model-qualifiers/"
      <rdf:Description rdf:about="#meta_R_GTHS">
        <bqbiol:is>
          <rdf:Bag>
            <rdf:li rdf:resource="http://identifiers.org/ec-code/6.3.2.3"/>
          </rdf:Bag>
        </bqbiol:is>
      </rdf:Description>
    </rdf:RDF>
  </annotation>
  <listOfReactants>
    <speciesReference species="M_atp_c" stoichiometry="1"/>
    <speciesReference species="M_glucys_c" stoichiometry="1"/>
  </listOfReactants>

```

¹ More information about this annotation is available at <http://pysces.sourceforge.net/KeyValueData>

```
<speciesReference species="M_gly_c" stoichiometry="1"/>
</listOfReactants>
<listOfProducts>
  <speciesReference species="M_adp_c" stoichiometry="1"/>
  <speciesReference species="M_gthrd_c" stoichiometry="1"/>
  <speciesReference species="M_h_c" stoichiometry="1"/>
  <speciesReference species="M_pi_c" stoichiometry="1"/>
</listOfProducts>
</reaction>
```

1
2
3
4
5
6
7
8
9
10

A Validation of SBML documents

A.1 Validation and consistency rules

This section summarizes all the conditions that must (or in some cases, at least *should*) be true of an SBML Level 3 Version 1 model that uses the Flux Balance Constraints package. We use the same conventions as are used in the SBML Level 3 Version 1 Core specification document. In particular, there are different degrees of rule strictness. Formally, the differences are expressed in the statement of a rule: either a rule states that a condition *must* be true, or a rule states that it *should* be true. Rules of the former kind are strict SBML validation rules—a model encoded in SBML must conform to all of them in order to be considered valid. Rules of the latter kind are consistency rules. To help highlight these differences, we use the following three symbols next to the rule numbers:

- ☑ A checked box indicates a *requirement* for SBML conformance. If a model does not follow this rule, it does not conform to the Flux Balance Constraints specification. (Mnemonic intention behind the choice of symbol: “This must be checked.”)
- ▲ A triangle indicates a *recommendation* for model consistency. If a model does not follow this rule, it is not considered strictly invalid as far as the Flux Balance Constraints specification is concerned; however, it indicates that the model contains a physical or conceptual inconsistency. (Mnemonic intention behind the choice of symbol: “This is a cause for warning.”)
- ★ A star indicates a strong recommendation for good modeling practice. This rule is not strictly a matter of SBML encoding, but the recommendation comes from logical reasoning. As in the previous case, if a model does not follow this rule, it is not strictly considered an invalid SBML encoding. (Mnemonic intention behind the choice of symbol: “You’re a star if you heed this.”)

The validation rules listed in the following subsections are all stated or implied in the rest of this specification document. They are enumerated here for convenience. Unless explicitly stated, all validation rules concern objects and attributes specifically defined in the Flux Balance Constraints package.

- 🔍 For convenience and brevity, we use the shorthand “**fbc:x**” to stand for an attribute or element name **x** in the namespace for the Flux Balance Constraints package, using the namespace prefix **fbc**. In reality, the prefix string may be different from the literal “**fbc**” used here (and indeed, it can be any valid XML namespace prefix that the modeler or software chooses). We use “**fbc:x**” because it is shorter than to write a full explanation everywhere we refer to an attribute or element in the Flux Balance Constraints package namespace.

General rules about this package

- fbc-10101** ☑ To conform to the Flux Balance Constraints package specification for SBML Level 3 Version 1, an SBML document must declare the use of the following XML Namespace: [-25]“<http://www.sbml.org/sbml/level3/version1/fbc/version1>”. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.1 on page 6.](#))
- fbc-10102** ☑ Wherever they appear in an SBML document, elements and attributes from the Flux Balance Constraints package must be declared either implicitly or explicitly to be in the XML namespace “<http://www.sbml.org/sbml/level3/version1/fbc/version1>”. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.1 on page 6.](#))

General rules about identifiers

- fbc-10301** ☑ (Extends validation rule #10301 in the SBML Level 3 Version 1 Core specification.) Within a **Model** the values of the attributes **id** and **fbc:id** on every instance of the following classes of objects must be unique across the set of all **id** and **fbc:id** attribute values of all such objects in a model: the **Model** itself, plus all contained **FunctionDefinition**, **Compartment**, **Species**, **Reaction**, **SpeciesReference**, **ModifierSpeciesReference**, **Event**, and **Parameter** objects, plus

the **FluxBound** , **Objective** and **FluxObjective** objects defined by the Flux Balance Constraints package. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.2 on page 6.](#))

Rules for the extended SBML class

- fbc-20101** ✓ In all SBML documents using the Flux Balance Constraints package, the **SBML** object must include a value for the attribute **fbc:required** attribute. (References: SBML Level 3 Version 1 Core, Section 4.1.2.)
- fbc-20102** ✓ The value of attribute **fbc:required** on the **SBML** object must be of the data type **boolean**. (References: SBML Level 3 Version 1 Core, Section 4.1.2.)
- fbc-20103** ✓ The value of attribute **fbc:required** on the **SBML** object must be set to “**true**”. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.1 on page 6.](#))

Rules for extended Model object

- fbc-20201** ✓ There may be at most one instance of each of the following kinds of objects within a **Model** object using Flux Balance Constraints: **ListOfFluxBounds** and **ListOfObjectives** . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20202** ✓ The various **ListOf__** subobjects with an **Model** object are optional, but if present, these container object must not be empty. Specifically, if any of the following classes of objects are present on the **Model**, it must not be empty: **ListOfFluxBounds** and **ListOfObjectives** . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20203** ✓ Apart from the general notes and annotation subobjects permitted on all SBML objects, a **ListOfFluxBounds** container object may only contain **FluxBound** objects. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20204** ✓ Apart from the general notes and annotation subobjects permitted on all SBML objects, a **ListOfObjectives** container object may only contain **Objective** objects. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20205** ✓ A **ListOfFluxBounds** object may have the optional **metaid** and **sboTerm** defined by SBML Level 3 Core. No other attributes from the SBML Level 3 Core namespace or the Flux Balance Constraints namespace are permitted on a **ListOfFluxBounds** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20206** ✓ A **ListOfObjectives** object may have the optional attributes **metaid** and **sboTerm** defined by SBML Level 3 Core. Additionally the **ListOfObjectives** must contain the attribute **activeObjective**. No other attributes from the SBML Level 3 Core namespace or the Flux Balance Constraints namespace are permitted on a **ListOfObjectives** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.3 on page 7.](#))
- fbc-20207** ✓ The value of attribute **fbc:activeObjective** on the **ListOfObjectives** object must be of the data type **FbcIdRef**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.2.2 on page 6.](#))
- fbc-20208** ✓ The value of attribute **fbc:activeObjective** on the **ListOfObjectives** object must be set to the **FbcId** of an existing **Objective** . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.2.2 on page 6.](#))

Rules for extended Species object

- fbc-20301** ✓ A **SBML Species** object may have the optional attributes **fbc:charge** and **fbc:chemicalFormula**. No other attributes from the Flux Balance Constraints namespaces are permitted on a **Species**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.4 on page 8](#))
- fbc-20302** ✓ The value of attribute **fbc:charge** on the **SBML Species** object must be of the data type **integer**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.4 on page 8](#)).
- fbc-20303** ✓ The value of attribute **fbc:chemicalFormula** on the **SBML Species** object must be set to the **string**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.4 on page 8](#).)

Rules for FluxBound object

- fbc-20401** ✓ A **FluxBound** object may have the optional SBML Level 3 Core attributes **metaid** and **sboTerm**. No other attributes from the SBML Level 3 Core namespaces are permitted on a **FluxBound**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20402** ✓ A **FluxBound** object may have the optional SBML Level 3 Core subobjects for notes and annotations. No other elements from the SBML Level 3 Core namespaces are permitted on a **FluxBound**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20403** ✓ A **FluxBound** object must have the required attributes **fbc:reaction**, **fbc:operation** and **fbc:value**, and may have the optional attributes **fbc:id** and **fbc:name**. No other attributes from the SBML Level 3 Flux Balance Constraints namespace are permitted on a **FluxBound** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20404** ✓ The attribute **fbc:reaction** in **FluxBound** must be of the data type **SIdRef**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20405** ✓ The attribute **fbc:name** in **FluxBound** must be of the data type **string**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20406** ✓ The attribute **fbc:operation** in **FluxBound** must be of the data type **enum**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20407** ✓ The attribute **fbc:value** in **FluxBound** must be of the data type **double**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20408** ✓ The value of the attribute **fbc:reaction** in a **FluxBound** object must be the identifier of an existing **Reaction** object defined in the enclosing **Model** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20409** ✓ The value of the attribute **fbc:operation** in a **FluxBound** object must be one of “**lessEqual**”, “**greaterEqual**”, “**less**”, “**greater**” or “**equal**”. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)
- fbc-20410** ✓ The combined set of all **FluxBound**’s with identical value for **fbc:reaction** must be consistent. That is while it is possible to define a lower and an upper bound for a reaction, it is not possible to define multiple lower or upper bounds. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.5 on page 8](#).)

Rules for Objective object

- fbc-20501** ✓ A **Objective** object may have the optional SBML Level 3 Core attributes **metaid** and **sboTerm**. No other attributes from the SBML Level 3 Core namespaces are permitted on a **Objective**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20502** ✓ A **Objective** object may have the optional SBML Level 3 Core subobjects for notes and annotations. No other elements from the SBML Level 3 Core namespaces are permitted on a **Objective**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20503** ✓ A **Objective** object may have the required attribute **fbc:id** and **fbc:type** and the optional attribute **fbc:name**. No other attributes from the SBML Level 3 Flux Balance Constraints namespace are permitted on a **Objective** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20504** ✓ The attribute **fbc:name** in **Objective** must be of the data type **string**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20505** ✓ The attribute **fbc:type** in **Objective** must be of the data type **FbcType**. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20506** ✓ The value of the attribute **fbc:type** in a **Objective** object must be one of “**minimize**” or “**maximize**”. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20507** ✓ A **Objective** must have one and only one instance of the **ListOfFluxObjectives** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20508** ✓ The **ListOfFluxObjectives** subobject with a **Objective** object must not be empty. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20509** ✓ Apart from the general notes and annotation subobjects permitted on all SBML objects, a **ListOfFluxObjectives** container object may only contain **Objective** objects. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))
- fbc-20510** ✓ A **ListOfFluxObjectives** object may have the optional **metaid** and **sboTerm** defined by SBML Level 3 Core. No other attributes from the SBML Level 3 Core namespace or the Flux Balance Constraints namespace are permitted on a **ListOfFluxObjectives** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.6 on page 9.](#))

Rules for FluxObjective object

- fbc-20601** ✓ A **FluxObjective** object may have the optional SBML Level 3 Core attributes **metaid** and **sboTerm**. No other attributes from the SBML Level 3 Core namespaces are permitted on a **FluxObjective**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20602** ✓ A **FluxObjective** object may have the optional SBML Level 3 Core subobjects for notes and annotations. No other elements from the SBML Level 3 Core namespaces are permitted on a **FluxObjective**. (References: SBML Level 3 Version 1 Core, Section 3.2.)
- fbc-20603** ✓ A **FluxObjective** object must have the required attributes **fbc:reaction** and **fbc:coefficient**, and may have the optional attributes **fbc:id** and **fbc:name**. No other attributes from the SBML Level 3 Flux Balance Constraints namespace are permitted on a **FluxObjective** object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, [Section 3.7 on page 11.](#))

fbc-20604 ✓	The attribute fbc:name in FluxObjective must be of the data type string . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, Section 3.7 on page 11.)	1 2
fbc-20605 ✓	The value of the attribute fbc:reaction of a FluxObjective object must conform to the syntax of the SBML data type SIdRef . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, Section 3.7 on page 11.)	3 4 5
fbc-20606 ✓	The value of the attribute fbc:reaction of a FluxObjective object must be the identifier of an existing Reaction object defined in the enclosing Model object. (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, Section 3.7 on page 11.)	6 7 8
fbc-20607 ✓	The value of the attribute fbc:coefficient of a FluxObjective object must conform to the syntax of the SBML data type double . (References: SBML Level 3 Package Specification for Flux Balance Constraints, Version 1, Section 3.7 on page 11.)	9 10 11

Acknowledgments

We would like to thank the following people who contributed in various ways to the development of both the original proposal and this document.

For financial/travel/technical/moral and general support we thank especially Herbert Sauro (University of Washington, USA), Ursula Kummer (Heidelberg University, Germany), Bas Teusink (VU University Amsterdam) and Michael Hucka (CalTech, USA).

A special work of thanks goes to Sarah Keating for her invaluable work with the libSBML and SBML Toolbox implementations and critical reading of this document.

We also would like to thank Neil Swainston, Keiran Smallbone, Daniel Hyduke, Nicolas Le Novère and all those who contributed ideas and held discussions with us on various occasions.

References

- Becker, S. A., Feist, A. M., Mo, M. L., Hannum, G., Palsson, B. O., and Herrgard, M. J. (2007). Quantitative prediction of cellular metabolism with constraint-based models: the COBRA Toolbox. *Nat. Protocols*, 2(3):727–738. 1750-2799 10.1038/nprot.2007.99 10.1038/nprot.2007.99.
- Bergmann, F. T. (2012). Sbw flux balance. Available via the World Wide Web at <https://github.com/fbergmann/FluxBalance>.
- Bergmann, F. T. and Sauro, H. M. (2006). SBW - a modular framework for systems biology. In *Proceedings of the 38th conference on Winter simulation, WSC '06*, pages 1637–1645. Winter Simulation Conference.
- Biron, P. V. and Malhotra, A. (2000). XML Schema part 2: Datatypes (W3C candidate recommendation 24 October 2000). Available via the World Wide Web at <http://www.w3.org/TR/xmlschema-2/>.
- Bornstein, B. J., Keating, S. M., Jouraku, A., and Hucka, M. (2008). LibSBML: an API Library for SBML. *Bioinformatics*, 24(6):880–881.
- Eriksson, H.-E. and Penker, M. (1998). *UML Toolkit*. John Wiley & Sons, New York.
- Fallside, D. C. (2000). XML Schema part 0: Primer (W3C candidate recommendation 24 October 2000). Available via the World Wide Web at <http://www.w3.org/TR/xmlschema-0/>.
- Hucka, M., Bergmann, F. T., Hoops, S., Keating, S. M., Sahle, S., and Wilkinson, D. J. (2011). Available via the World Wide Web at <http://sbml.org/Documents/Specifications>.
- Hucka, M., Finney, A., Sauro, H., Bolouri, H., Doyle, J., Kitano, H., Arkin, A., Bornstein, B., Bray, D., Cornish-Bowden, A., Cuellar, A., Dronov, S., Gilles, E., Ginkel, M., Gor, V., Goryanin, I., Hedley, W., Hodgman, T., Hofmeyr, J., Hunter, P., Juty, N., Kasberger, J., Kremling, A., Kummer, U., Novère, N. L., Loew, L., Lucio, D., Mendes, P., Minch, E., Mjolsness, E., Nakayama, Y., Nelson, M., Nielsen, P., Sakurada, T., Schaff, J., Shapiro, B., Shimizu, T., Spence, H., Stelling, J., Takahashi, K., Tomita, M., Wagner, J., and Wang, J. (2003). The Systems Biology Markup Language (SBML): a medium for representation and exchange of biochemical network models. *Bioinformatics*, 19(4):524–31.
- Oberhardt, M. A., Palsson, B. Ø., and Papin, J. A. (2009). Applications of genome-scale metabolic reconstructions. *Molecular Systems Biology*, 5:320.
- Oestereich, B. (1999). *Developing Software with UML: Object-Oriented Analysis and Design in Practice*. Addison-Wesley.
- Olivier, B. G. (2012). CBMPy: Constraint Based Modelling in Python. Available via the World Wide Web at <http://pysces.sf.net/cbm>.
- Olivier, B. G., Rohwer, J. M., and Hofmeyr, J.-H. S. (2005). Modelling cellular systems with PySCeS. *Bioinformatics*, 21(4):560–561.
- Orth, J. D., Thiele, I., and Palsson, B. Ø. (2010). What is flux balance analysis? *Nature Biotechnology*, 28(3):245–248.
- Reed, J. L., Vo, T. D., Schilling, C. H., and Palsson, B. O. (2003). An expanded genome-scale model of Escherichia coli K-12 (iJR904 GSM/GPR). *Genome Biol*, 4(9):R54.
- SBML Team (2010). The SBML Issue Tracker. Available via the World Wide Web at <http://sbml.org/issue-tracker>.
- Schellenberger, J., Park, J., Conrad, T., and Palsson, B. (2010). BiGG: a Biochemical Genetic and Genomic knowledgebase of large scale metabolic reconstructions. *BMC Bioinformatics*, 11(1):213.

Thompson, H. S., Beech, D., Maloney, M., and Mendelsohn, N. (2000). XML Schema part 1: Structures (W3C candidate recommendation 24 October 2000). Available online via the World Wide Web at the address <http://www.w3.org/TR/xmlschema-1/>.

1
2
3