

NAME- Bhagesh Rankhamb

PRN NO- 202501050035

BATCH- CH2

PRACTICAL NO.3

Write a Python program to create a NumPy array based on user input and display the following:

The created NumPy array.

The number of dimensions of the array using `ndim`

The shape of the array using `shape`

The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

The first line contains two space-separated integers, `r` and `c`, representing the number of rows and the number of columns.

The next lines contain space-separated integers representing the elements of the array, entered row by row.

Output Format:

The created NumPy array (printed as a 2D array).

An integer representing the number of dimensions of the array.

A tuple representing the shape of the array.

An integer representing the total number of elements in the array

CODE:

```
import numpy as np
```

```
r,c = map(int, input().split())
```

```
elements = []
```

```
for i in range(r):
```

```
    row= list(map(int, input().split()))
```

```
    elements.extend(row)
```

```
arr=np.array(elements).reshape(r, c)
```

```
print(arr)
```

```
print(arr.ndim)
```

```
print(arr.shape)
```

```
print(arr.size)
```

OUTPUT:



```
3 4
1 2 3 4
5 6 7 8
9 10 11 12
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]]
2
(3, 4)
12
YOUR PROGRAM HAS ENDED
```

Terminal Test cases

3.2.1. Numpy: Matrix Operations

14:23

The given code takes two 3×3 matrices, `matrix_a`, and `matrix_b`, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** (`matrix_a + matrix_b`)
2. **Subtraction** (`matrix_a - matrix_b`)
3. **Element-wise Multiplication** (`matrix_a * matrix_b`)
4. **Matrix Multiplication** (`matrix_a · matrix_b`)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for `matrix_a`, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for `matrix_b`, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.

CODE:

```
import numpy as np
```

```
#Input matrices
```

```
print("Enter Matrix A:")
```

```
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
```

```
print("Enter Matrix B:")
```

```
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])
```

```
# Addition
addition_result = matrix_a + matrix_b
print("Addition (A + B):")
print(addition_result)

# Subtraction
subtraction_result = matrix_a - matrix_b
print("Subtraction (A - B):")
print(subtraction_result)

# Multiplication (element-wise)
elementwise_multiplication_result = matrix_a * matrix_b
print("Element-wise Multiplication (A * B):")
print(elementwise_multiplication_result)

# Matrix multiplication (dot product)
matrix_multiplication_result = np.dot(matrix_a, matrix_b)
print("A dot B:")
print(matrix_multiplication_result)

# Transpose
transpose_a = matrix_a.T
print("Transpose of A:")
print(transpose_a)
```

OUTPUT:

```
Enter Matrix A:
1 2 3
4 5 6
7 8 9
Enter Matrix B:
1 1 1
2 2 2
3 3 3
Addition (A + B):
[[ 2  3  4]
 [ 6  7  8]
 [10 11 12]]
Subtraction (A - B):
[[ 0  1  2]
 [ 2  3  4]
 [ 4  5  6]]
Element-wise Multiplication (A * B):
[[ 1  2  3]
 [ 8 10 12]
 [21 24 27]]
A dot B:
[[14 14 14]
 [32 32 32]
 [50 50 50]]
```

A dot B:

```
[[14 14 14]
 [32 32 32]
 [50 50 50]]
```

Transpose of A:

```
[[1 4 7]
 [2 5 8]
 [3 6 9]]
```

=== YOUR PROGRAM HAS ENDED ===

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

Horizontal Stacking: Stack the two matrices horizontally (side by side).

Vertical Stacking: Stack the two matrices vertically (one below the other).

Input Format:

The program should first prompt the user to input two 3x3 arrays.

Each array consists of 3 rows, and each row contains 3 space-separated integers.

The user will input the two arrays row by row.

Output Format:

The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.

The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

CODE:

```
import numpy as np
```

```
#Input matrices
```

```
print("Enter Array1:")
```

```
arr1 = np.array([list(map(int, input().split())) for i in range(3)])
```

```
print("Enter Array2:")
```

```
arr2 = np.array([list(map(int, input().split())) for i in range(3)])
```

```
# Perform horizontal stacking (hstack)
```

```
h_stack = np.hstack((arr1, arr2))
```

```
#Perform vertical stacking (vstack)
```

```
v_stack = np.vstack((arr1, arr2))
```

```
#Output results
```


```
print("Horizontal Stack:")
```

```
print(h_stack)
```

```
print("Vertical Stack:")
```

```
print(v_stack)
```

OUTPUT:



```
Enter Array1:
1 2 3
4 5 6
7 8 9
Enter Array2:
4 5 6
7 8 9
10 11 12
Horizontal Stack:
[[ 1  2  3  4  5  6]
 [ 4  5  6  7  8  9]
 [ 7  8  9 10 11 12]]
Vertical Stack:
[[ 1  2  3]
 [ 4  5  6]
 [ 7  8  9]
 [ 4  5  6]
 [ 7  8  9]
 [10 11 12]]
=== YOUR PROGRAM HAS ENDED ===
```

Write a Python program that takes the following inputs from the user:

Start value: The starting point of the sequence.

Stop value: The sequence should end before this value.

Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

The program should print the generated sequence based on the input values.

CODE:

```
import numpy as np
```

```
#Take user input for the start, stop, and step of the sequence
```

```
start = int(input())
```

```
stop = int(input())
```

```
step = int(input())
```



```
# Generate the sequence using np.arange()
```

```
sequence = np.arange(start, stop, step)
```

```
#Print the generated sequence
```

```
print(sequence)
```

OUTPUT:



```
3
10
2
[3 5 7 9]
==== YOUR PROGRAM HAS ENDED ====
```

The image shows a terminal window with a light blue border. The output of the code is displayed in a monospaced font. The first three lines are '3', '10', and '2'. The fourth line is '[3 5 7 9]'. Below this, a black bar with white text reads '==== YOUR PROGRAM HAS ENDED ===='. At the bottom of the terminal, there are two tabs: 'Terminal' and 'Test cases'.

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: A_i OR B_i).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

CODE:

```
import numpy as np
```

```
def array_operations(A, B):
```

```
    # Convert A and B to NumPy arrays
```

```
A = np.array(A)
```

```
B = np.array(B)
```

```
# Arithmetic Operations
```

```
sum_result = A + B
```

```
diff_result = A - B
```

```
prod_result = A * B
```

```
# Statistical Operations
```

```
mean_A = np.mean(A)
```

```
median_A = np.median(A)
```

```
std_dev_A = np.std(A)
```

```
# Bitwise Operations
```

```
and_result = A & B
```

```
or_result = A | B
```

```
xor_result = A ^ B
```

```
#Output results with one space between each element
```

```
print("Element-wise Sum:", ' '.join(map(str, sum_result)))
```

```
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
```

```
print("Element-wise Product:", ' '.join(map(str, prod_result)))
```

```
print(f"Mean of A: {mean_A}")
```

```
print(f"Median of A: {median_A}")
```

```
print(f"Standard Deviation of A: {std_dev_A}")
```

```
print("Bitwise AND:", ' '.join(map(str, and_result)))
```

```
print("Bitwise OR:", ' '.join(map(str, or_result)))
```

```
print("Bitwise XOR:", ' '.join(map(str, xor_result)))
```

```
A=list(map(int, input().split())) # Elements of array A
```

```
B=list(map(int, input().split())) # Elements of array B
```

```
array_operations(A, B)
```

OUTPUT:



```
1 2 3 4
5 6 7 8
Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32
Mean of A: 2.5
Median of A: 2.5
Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12
=== YOUR PROGRAM HAS ENDED ===
```

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

Creating a view of the original_array and assigning it to view_array.

Creating a copy of the original_array and assigning it to copy_array.

After completing these steps, observe how modifying the view affects the original_array, while modifying the copy does not.

Input Format:

A single line of space-separated integers.

Output Format:

After modifying the view:

Original array after modifying view: <original_array>

View array: <view_array>

After modifying the copy:

Original array after modifying copy: <original_array>

Copy array: <copy_array>

CODE:

```
import numpy as np
```

```
inputlist = list(map(int,input().split(" ")))
```

```
#Original array
```

```
original_array = np.array(inputlist)
```

Create a view

```
view_array = original_array.view()
```

#Create a copy

```
copy_array = original_array.copy()
```

#Modify the view

```
view_array[0] = 99
```

```
print("Original array after modifying view:", original_array)
```

```
print("View array:", view_array)
```

#Modify the copy

```
copy_array[1] = 88
```

```
print("Original array after modifying copy:", original_array)
```

```
print("Copy array:", copy_array)
```

OUTPUT:



```
10 20 30 40 50 60 70 80
Original array after modifying view: [99 20 30 40 50 60 70 80]
View array: [99 20 30 40 50 60 70 80]
Original array after modifying copy: [99 20 30 40 50 60 70 80]
Copy array: [10 88 30 40 50 60 70 80]
*** YOUR PROGRAM HAS ENDED ***
```

The given code in the editor takes a single array, `array1`, as space-separated integers as input from the user.

Additionally, it takes the following inputs:

`search_value`: The value to search for in the array.

`count_value`: The value to count its occurrences in the array.

`broadcast_value`: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

1. Searching: Find the indices where `search_value` appears in `array1` and print these indices.
2. Counting: Count how many times `count_value` appears in `array1` and print the count.
3. Broadcasting: Add `broadcast_value` to each element of `array1` using broadcasting, and print the resulting array.
4. Sorting: Sort `array1` in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing `array1`.
2. An integer `search_value` represents the value to search for in the array.
3. An integer `count_value` represents the value to count in the array.
4. An integer `broadcast_value` represents the value to add to each element of the array.

Output Format:

1. The indices where `search_value` occurs in `array1`.
2. The count of occurrences of `count_value` in `array1`.
3. The array after adding the `broadcast_value` to each element.
4. The sorted array.

CODE:

```
import numpy as np
```

```
#Input array from the user
```

```
array1 = np.array(list(map(int, input().split())))
```

```
#Searching
```

```
search_value = int(input("Value to search: "))
```

```
count_value = int(input("Value to count: "))
```

```
broadcast_value = int(input("Value to add: "))
```

```
#Find indices where value matches in array1
```

```
indices = np.where(array1 == search_value)[0]
```

```
print(indices)
```

```
#Count occurrences in array1
```

```
count = np.sum(array1 == count_value)
```

```
print(count)
```

```
#Broadcasting addition
```

```
broadcasted = array1 + broadcast_value
```

```
print(broadcasted)
```

```
# Sort the first array
```

```
sorted_array = np.sort(array1)
```

```
print(sorted_array)
```


OUTPUT:



```
1 1 1 2 2 2
Value to search: 1
Value to count: 2
Value to add: 2
[0 1 2]
3
[3 3 3 4 4 4]
[1 1 1 2 2 2]
=== YOUR PROGRAM HAS ENDED ===
```

The image shows a terminal window with a light blue header bar. The terminal content is as follows:

```
1 1 1 2 2 2
Value to search: 1
Value to count: 2
Value to add: 2
[0 1 2]
3
[3 3 3 4 4 4]
[1 1 1 2 2 2]
=== YOUR PROGRAM HAS ENDED ===
```

At the bottom of the terminal window, there is a dark blue bar with two buttons: "Terminal" (with a terminal icon) and "Test cases" (with a document icon).

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- ☐ Print all student details: Display the complete details of all students, including roll numbers and marks for all subjects.
- ☐ Find total students: Determine the total number of students in the dataset.
- ☐ Print all student roll numbers: Extract and print the roll numbers of all students.
- ☐ Print Subject 1 marks: Extract and print the marks of all students in Subject 1.
- ☐ Find minimum marks in Subject 2: Identify the lowest marks in Subject 2.
- ☐ Find maximum marks in Subject 3: Identify the highest marks in Subject 3.
- ☐ Print all subject marks: Display the marks of all students for each subject.
- ☐ Find total marks of students: Compute the total marks for each student across all subjects.
- ☐ Find the average marks of each student: Compute the average marks for each student.
- ☐ Find average marks of each subject: Compute the average marks for all students in each subject.
- ☐ Find average marks of Subject 1 and Subject 2: Compute the average marks for Subject 1 and Subject 2.
- ☐ Find average marks of Subject 1 and Subject 3: Compute the average marks for Subject 1 and Subject 3.
- ☐ Find the roll number of the student with maximum marks in Subject 3: Identify the student with the highest marks in Subject 3 and print their roll number.

- ❑ Find the roll number of the student with minimum marks in Subject 2:
Identify the student with the lowest marks in Subject 2 and print their roll number.
- ❑ Find the roll number of students who scored 24 marks in Subject 2:
Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- ❑ Find the count of students who got less than 40 marks in Subject 1:
Count the number of students who scored less than 40 marks in Subject 1.
- ❑ Find the count of students who got more than 90 marks in Subject 2:
Count the number of students who scored more than 90 marks in Subject 2.
- ❑ Find the count of students who scored ≥ 90 in each subject: Count the number of students who scored 90 or more marks in each subject.
- ❑ Find the count of subjects in which each student scored ≥ 90 :
Determine how many subjects each student scored 90 or more marks in.
- ❑ Print Subject 1 marks in ascending order: Sort and print the marks of students in Subject 1 in ascending order.
- ❑ Print students who scored between 50 and 90 in Subject 1: Display students who scored marks between 50 and 90 in Subject 1.
- ❑ Find index positions of students who scored 79 in Subject 1: Identify the index positions of students who scored exactly 79 marks in Subject 1.

CODE:

```
import numpy as np
```

```
a= np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
```

```
#1
```

```
print("All student Details:\n", a)
```

```
# 2
```

```
print("Total Students:", a.shape[0])

# 3
print("All Student Roll Nos", a[:, 0])

# 4
print("Subject 1 Marks", a[:, 1])

# 5
print("Min marks in Subject 2", np.min(a[:, 2]))

# 6
print("Max marks in Subject 3", np.max(a[:, 3]))

# 7
print("All subject marks:", a[:, 1:])

# 8
total = np.sum(a[:, 1:], axis=1)
print("Total Marks", total)

# 9 (no label in sample output)
print(np.round(np.mean(a[:, 1:], axis=1), 1))

# 10
print("Average Marks of each subject", np.round(np.mean(a[:, 1:],
axis=0), 1))

# 11
print("Average Marks of S1 and S2", np.round(np.mean(a[:, [1, 2]],
axis=0), 1))

# 12
print("Average Marks of S1 and S3", np.round(np.mean(a[:, [1, 3]],
axis=0), 1))

# 13
```

```

print("Roll no who got maximum marks in Subject 3", a[np.argmax(a[:,
3]), 0])

# 14

print("Roll no who got minimum marks in Subject 2", a[np.argmin(a[:,
2]), 0])

# 15

print("Roll no who got 24 marks in Subject 2", a[a[:, 2] == 24,
0].reshape(-1,1))

# 16

print("Count of students who got marks in Subject 1 < 40", np.sum(a[:, 1]
< 40))

# 17

print("Count of students who got marks in Subject 2 > 90:", np.sum(a[:,
2] > 90))

# 18

print("Count of students in each subject who got marks >= 90:",
np.sum(a[:, 1:] >= 90, axis=0))

# 19

print("Roll no:", a[:, 0])

print("Count of subjects in which student got marks >= 90:",
np.sum(a[:, 1:] >= 90, axis=1))

# 20

print(np.sort(a[:, 1]))

# 21 (print full rows like sample)

print(a[(a[:, 1] >= 50) & (a[:, 1] <= 90)])

print(a)

# 22 (exact output format)

print(np.where(a[:, 1] == 79))

```

OUTPUT:

```

all student Details:
[[301. 67. 77. 88.]
 [302. 78. 88. 77.]
 [303. 45. 56. 89.]
 [304. 88. 98. 45.]
 [305. 78. 88. 99.]
 [306. 68. 78. 36.]
 [307. 79. 12. 45.]
 [308. 46. 45. 77.]
 [309. 89. 32. 88.]
 [310. 79. 24. 33.]]
Total Students: 10
all Student Roll Nos [301. 302. 303. 304. 305. 306. 307. 308. 309. 310.]
Subject 1 Marks [67. 78. 45. 88. 78. 68. 79. 46. 89. 79.]
fin marks in Subject 2 12.0
fin marks in Subject 3 99.0
all subject marks: [[67. 77. 88.]
 [78. 88. 77.]
 [45. 56. 89.]
 [88. 98. 45.]
 [78. 88. 99.]
 [68. 78. 36.]
 [79. 12. 45.]
 [46. 45. 77.]
 [89. 32. 88.]
 [79. 24. 33.]]
Total Marks [232. 243. 190. 231. 265. 182. 136. 168. 209. 136.]
[77.3 81. 63.3 77. 88.3 60.7 45.3 56. 69.7 45.3]
Average Marks of each subject [71.7 59.8 67.7]
Average Marks of S1 and S2 [71.7 59.8]
Average Marks of S1 and S3 [71.7 67.7]
Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [[310.]]
Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90: 1
Count of students in each subject who got marks >= 90: [0 1 1]
Roll no: [301. 302. 303. 304. 305. 306. 307. 308. 309. 310.]
Count of subjects in which student got marks >= 90: [0 0 0 1 1 0 0 0 0 0]
Count of subjects in which students got marks >= 90:
[45. 46. 67. 68. 78. 78. 79. 79. 88. 89.]
[[301. 67. 77. 88.]
 [302. 78. 88. 77.]
 [304. 88. 98. 45.]
 [305. 78. 88. 99.]
 [306. 68. 78. 36.]
 [307. 79. 12. 45.]
 [309. 89. 32. 88.]
 [310. 79. 24. 33.]]
[[301. 67. 77. 88.]
 [302. 78. 88. 77.]
 [303. 45. 56. 89.]
 [304. 88. 98. 45.]
 [305. 78. 88. 99.]
 [306. 68. 78. 36.]
 [307. 79. 12. 45.]
 [308. 46. 45. 77.]
 [309. 89. 32. 88.]
 [310. 79. 24. 33.]]
(array([6, 9], dtype=int32),)
=== YOUR PROGRAM HAS ENDED ===

```

□



Terminal



Test cases