ASSIGNMENT 1 · TECHNICAL REPORT November 2026

2D Object Detection

Track A: Experimental Model Evaluation

Bhagyesh Rathi · SJSU ID 014764893

Zero-shot evaluation of seven COCO-pretrained detector configurations from five detector families on COCO val2017 and on the KITTI 2D object-detection benchmark, without any training or fine-tuning. The study measures accuracy (COCO-style mAP, AP50/75, AP by object scale, per-class AP, AR), speed (latency, FPS) and GPU memory, and analyses (1) cross-dataset generalisation (COCO → KITTI), (2) architecture differences (two-stage vs one-stage vs YOLO vs DETR), (3) closed-set vs open-vocabulary detection (YOLO11 vs YOLO-World) and (4) the speed–accuracy trade-off.

MODELS
7 COCO-pretrained configurations, 5 detector families

DATASETS
COCO val2017 (5,000 images) · KITTI val split (3,769 frames)

HARDWARE
NVIDIA GeForce RTX 5060 8 GB · PyTorch 2.11 (CUDA 12.8)

TRAINING
None — pure zero-shot / domain-transfer evaluation

Starting point: the course tutorial [15] https://github.com/lkk688/DeepDataMiningLearning/blob/main/DeepDataMiningLearning/ngdet/TUTORIAL.md (its `driving3` / `driving5` taxonomy presets and its "COCO-pretrained detector → driving dataset without retraining" experiment are reproduced here with an independent, minimal re-implementation in `src/`). All code, per-run metric files, figures and the original console logs of every run are published at https://github.com/bhagyeshrathi07/2d-object-detection-track-a (the logs are in `results/logs/`; see Appendix A and `README.md`). The 1.2 GB of cached raw detections is submitted separately because it exceeds GitHub's file-size limit.

1. Experimental setup

1.1 Hardware and software

Item	Value
GPU	NVIDIA GeForce RTX 5060, 8 GB (Blackwell, compute capability 12.0), driver 621.01
CPU	Intel Core Ultra 5 225F (10 cores)
OS	Windows 11 Home 10.0.26300
Python	3.12.10 (venv)
PyTorch / torchvision	2.11.0+cu128 / 0.26.0+cu128 (CUDA 12.8 build — required for sm_120)
Ultralytics	8.4.194
pycocotools	2.0.x (official COCO evaluation code)
Ultralytics CLIP fork	installed from GitHub archive (text encoder for YOLO-World prompts)

1.2 Models and checkpoints

#	Model	Family	Framework	Checkpoint	Params
1	Faster R-CNN ResNet50-FPN v2 [1, 2, 5]	two-stage, anchor-based	torchvision [13]	`FasterRCNN_ResNet50_FPN_V2_Weights.COCO_V1`	43.7 M
2	RetinaNet ResNet50-FPN v2 [3, 5]	one-stage, anchor-based, focal loss	torchvision	`RetinaNet_ResNet50_FPN_V2_Weights.COCO_V1`	38.2 M
3	FCOS ResNet50-FPN [4]	one-stage, anchor-free	torchvision	`FCOS_ResNet50_FPN_Weights.COCO_V1`	32.3 M
4	YOLO11n [6]	one-stage, anchor-free, CNN	Ultralytics [6]	`yolo11n.pt`	2.6 M
5	YOLO11m [6]	one-stage, anchor-free, CNN	Ultralytics	`yolo11m.pt`	20.1 M
6	RT-DETR-L [7, 16]	real-time DETR (transformer decoder, NMS-free)	Ultralytics	`rtdetr-l.pt`	33.0 M
7	YOLO-World v2-S [8, 9]	open-vocabulary YOLO (CLIP text embeddings)	Ultralytics	`yolov8s-worldv2.pt`	12.8 M

Parameter counts are measured (`sum(p.numel())`, §2.4), not copied from model cards.

Model 7 is run twice on KITTI: once with the 80 COCO class names as its vocabulary (closed-set baseline) and once prompted directly with KITTI's class names (`car, van, truck, pedestrian, cyclist, tram`), which is the open-vocabulary experiment.

1.3 Datasets and splits

Dataset	Split used	Images	Classes	Source
COCO 2017 [10]	`val2017` (full)	5,000	80	images.cocodataset.org
KITTI 2D object detection [11]	the standard 3,769-frame validation split of the 7,481-frame `training` set (Chen et al. [12] split, as shipped in OpenPCDet / MMDetection3D `ImageSets/val.txt`)	3,769	9 raw labels (Car, Van, Truck, Pedestrian, Person_sitting, Cyclist, Tram, Misc, DontCare)	s3.eu-central-1.amazonaws.com/avg-kitti

No model was trained or fine-tuned on either dataset, so the KITTI numbers are pure zero-shot / domain-transfer numbers. The val split was chosen (rather than all 7,481 frames) so that results are directly comparable with the split used by most KITTI papers, and because only those frames had to be fetched from the 12.5 GB archive (`src/fetch_kitti_subset.py` fetches individual members of the remote zip with HTTP range requests).

KITTI images are 1242×375 (a few frames are 1224×370 / 1238×374 / 1241×376); COCO images are ≈640×480. Both are evaluated with each model's native preprocessing (see 1.5).

1.4 Label / taxonomy mapping (KITTI ↔ COCO)

KITTI and COCO use different class definitions, so the KITTI ground truth and the detectors' COCO outputs are both mapped onto a shared taxonomy (`src/taxonomy.py`, `src/kitti_to_coco.py`). Two presets are used:

`driving3` (primary):

Unified class	KITTI labels	COCO classes (detector output)
vehicle	Car, Van, Truck, Tram	car, truck, bus, train
person	Pedestrian, Person_sitting	person
cyclist	Cyclist	bicycle, motorcycle
ignore region	Misc, DontCare	— (all other COCO classes are dropped)

`driving5` (finer):

Unified class	KITTI labels	COCO classes
car	Car, Van	car
truck	Truck	truck, bus
person	Pedestrian, Person_sitting	person
cyclist	Cyclist	bicycle, motorcycle
ignore region	Tram, Misc, DontCare	—

Implementation details that matter for the numbers:

- **Ignore regions.** KITTI `DontCare` boxes mark areas that were not labelled (e.g. distant or heavily occluded objects). They are converted to COCO `iscrowd=1` annotations, replicated once per unified class, so that any detection matched to such a box is neither a true nor a false positive and the box never counts towards recall. `Misc` (and `Tram` in `driving5`) is treated the same way.
- **Cyclist.** KITTI labels a bicycle *with its rider* as one `Cyclist` box. A COCO detector instead outputs a `bicycle` box and a separate `person` box. Following the tutorial, COCO `bicycle` is folded into `cyclist`; the rider's `person` box, however, is left as a `person` prediction and therefore counts as a false positive for the `person` class (no pedestrian GT covers it). This is a genuine taxonomy mismatch, not a detector failure, and is quantified in §3.1.
- **Van / Truck.** KITTI's `Van` is visually between COCO `car` and `truck`. In `driving3` the distinction disappears; `driving5` assigns Van to `car`, which is what COCO detectors overwhelmingly predict for KITTI vans.
- KITTI's `Person_sitting` is merged into `person`; COCO has no separate class.

1.5 Evaluation protocol

- Metrics: official `pycocotools` `COCOeval` (bbox) [14]. Reported: mAP@[.50:.95], AP50, AP75, AP_small/medium/large (COCO area thresholds 32^2 and 96^2 px), AR@100 and per-class AP (area = all, maxDets = 100).
- Score threshold: **0.001** for every model on every dataset (mAP integrates the full precision–recall curve; truncating it with a high threshold lowers AP). Max 100 detections/image for torchvision models (their default), 300 for Ultralytics models (their default for validation).
- NMS: torchvision models use their built-in class-wise NMS (IoU 0.5); Ultralytics YOLO models use IoU 0.7 (the Ultralytics validation default); RT-DETR is NMS-free (set prediction).
- Input resolution: torchvision models resize so that the shorter side is 800 px and the longer side ≤ 1333 px (aspect preserved; a 1242×375 KITTI frame becomes 1333×403). Ultralytics models letterbox the longer side to 640 px (a KITTI frame becomes 640×192 plus padding, i.e. objects are down-scaled by ~1.9×).

- Precision: fp32 for all accuracy runs. The latency benchmark (§2.4) runs both fp32 and fp16 (autocast for torchvision, `half=True` for Ultralytics).
- Batch size 1 everywhere (one image per forward pass), the deployment-relevant setting for a driving camera stream.
- Timing inside the accuracy runs (`results/metrics/*.json`) is per-image wall time of `predict()` with `torch.cuda.synchronize()`, including the model's own preprocessing/post-processing, after 5 warm-up images. Because the 0.001 threshold inflates NMS cost (tens of thousands of candidate boxes for Faster R-CNN), the **controlled** latency numbers in §2.4 are measured separately with a deployment-style confidence of 0.25, 20 warm-up and 100 timed iterations on a fixed image, with nothing else running on the GPU.

1.6 Exact commands

One command per model × dataset; the full environment set-up, data preparation and the job chains that produced every number are in `README.md` and `src/run_*.{ps1,sh}`. Representative lines:

```
python src/kitti_to_coco.py --root data/kitti --out data/kitti/annotations --split data/kitti/ImageSets/val.txt
python src/evaluate.py --model tv:fasterrcnn_resnet50_fpn_v2 --dataset coco
python src/evaluate.py --model ul:yolo11m.pt --dataset kitti              # scores driving3 + driving5
python src/evaluate.py --model ul:yolo11m.pt --dataset kitti --imgsz 1280
python src/evaluate.py --model ulkitti:yolov8s-worldv2.pt --dataset kitti # KITTI-name prompts
python src/latency.py --models tv:fasterrcnn_resnet50_fpn_v2 ... ul:yolov8s-worldv2.pt
python src/kitti_difficulty.py; python src/cyclist_fusion.py; python src/failure_examples.py; python src/make_report.py
```

Each run writes `results/metrics/<model>__<dataset>.json` with the model info, thresholds, resolution, hardware, library versions and its exact command line; raw detections are cached in `results/raw/` so every table can be re-scored on CPU (`--rescore-only`).

2. Results

All numbers below are copied from `results/summary.md`, `results/kitti_extra.md` and `results/cyclist_fusion.md`, which are generated from the per-run JSON files. "mAP" always means COCO mAP@[.50:.95].

2.1 COCO val2017 (in-domain sanity check)

Model	mAP	AP50	AP75	AP_S	AP_M	AP_L	AR_100	published mAP*
Faster R-CNN R50-FPN v2	**0.469**	0.679	0.513	0.309	0.507	0.604	0.630	46.7
RetinaNet R50-FPN v2	0.415	0.618	0.439	0.270	0.458	0.537	0.596	41.5
FCOS R50-FPN	0.392	0.583	0.420	0.222	0.424	0.513	0.571	39.2
YOLO11n	0.387	0.541	0.421	0.195	0.424	0.561	0.559	39.5
YOLO11m	0.506	0.673	0.550	0.335	0.560	0.664	0.661	51.5
RT-DETR-L	**0.528**	0.712	0.572	0.344	0.574	0.708	0.717	53.0
YOLO-World v2-S (COCO vocab)	0.368	0.513	0.399	0.206	0.406	0.489	0.569	37.7

* torchvision / Ultralytics model cards. The three torchvision models reproduce their published numbers to within 0.2 points, which validates the harness. The Ultralytics models are 0.2–0.9 points below their cards because the cards use `model.val()` with rectangular (minimal-padding) batches, while this study calls `predict()` with a square 640 letterbox, the same preprocessing a deployed single-image pipeline would use.

2.2 KITTI val split, zero-shot, `driving3` taxonomy (primary)

Model	mAP	AP50	AP75	AP_S	AP_M	AP_L	AP vehicle	AP person	AP cyclist	AP50 vehicle	AP50 person	AP50 cyclist
Faster R-CNN R50-FPN v2	0.237	0.453	0.226	0.160	0.216	0.305	0.496	**0.212**	0.002	0.847	0.501	0.011
RetinaNet R50-FPN v2	0.234	0.456	0.217	0.160	0.213	0.308	0.495	0.203	0.004	0.852	0.499	0.019
FCOS R50-FPN	0.230	0.443	0.218	0.159	0.205	0.302	0.491	0.192	0.006	0.848	0.460	0.022
YOLO11n @640	0.205	0.410	0.184	0.089	0.177	0.302	0.436	0.177	0.001	0.784	0.437	0.008
YOLO11m @640	0.232	0.448	0.222	0.152	0.211	0.301	0.497	0.200	0.001	0.849	0.488	0.005
RT-DETR-L @640	0.243	0.453	0.233	0.170	0.222	0.312	**0.522**	0.206	0.002	**0.861**	0.490	0.009
YOLO-World v2-S (COCO vocab)	0.223	0.422	0.213	0.129	0.199	0.312	0.484	0.182	0.003	0.818	0.430	0.017
YOLO-World v2-S (KITTI prompts, "pedestrian")	0.210	0.413	0.197	0.132	0.202	0.332	0.488	0.116	**0.027**	0.819	0.297	**0.123**
YOLO-World v2-S (KITTI prompts, "person")	0.225	0.423	0.216	0.131	0.200	0.322	0.487	0.183	0.006	0.819	0.423	0.025
YOLO11n @1280	0.235	0.452	0.223	0.156	0.220	0.299	0.498	0.204	0.001	0.842	0.506	0.007
YOLO11m @1280	0.242	0.464	0.231	0.178	0.223	0.300	0.511	0.212	0.002	0.855	0.525	0.013
RT-DETR-L @1280	**0.247**	0.450	0.241	**0.183**	0.232	0.328	0.520	0.217	0.005	0.818	0.499	0.032

GT instances in the val split: vehicle 16,895 · person 2,446 · cyclist 893 (+ 6,532 DontCare/Misc ignore regions).

2.3 KITTI val split, zero-shot, `driving5` taxonomy

Model	mAP	AP50	AP car	AP truck	AP person	AP cyclist	AP50 car	AP50 truck
Faster R-CNN R50-FPN v2	**0.246**	0.438	0.484	**0.285**	0.212	0.002	0.833	0.405
RetinaNet R50-FPN v2	0.227	0.418	0.487	0.214	0.204	0.004	0.842	0.311
FCOS R50-FPN	0.222	0.407	0.487	0.203	0.192	0.006	0.846	0.298
YOLO11n @640	0.168	0.332	0.431	0.064	0.178	0.001	0.779	0.103
YOLO11m @640	0.215	0.397	0.479	0.181	0.200	0.001	0.822	0.272
RT-DETR-L @640	0.222	0.401	**0.514**	0.168	0.206	0.002	**0.851**	0.252
YOLO-World v2-S (COCO vocab)	0.228	0.410	0.477	0.248	0.183	0.003	0.814	0.377
YOLO-World v2-S (KITTI prompts, "pedestrian")	0.230	0.421	0.490	0.287	0.117	0.027	0.826	0.435
YOLO-World v2-S (KITTI prompts, "person")	0.237	0.423	0.487	0.273	0.183	0.006	0.823	0.420
RT-DETR-L @1280	**0.261**	0.440	0.511	**0.311**	0.217	0.005	0.808	0.421

GT instances: car 16,002 · truck 606 · person 2,446 · cyclist 893.

2.4 Controlled latency, throughput and GPU memory (batch 1, RTX 5060)

Median of 100 timed iterations after 20 warm-up, confidence 0.25, `torch.cuda.synchronize()` around each call, nothing else on the GPU. KITTI frame 1242×375; COCO image 640×426.

Model	params	KITTI fp32 ms / FPS	KITTI fp16 ms / FPS	COCO fp32 ms	peak alloc MB (fp32 / fp16)	peak reserved MB fp32
Faster R-CNN R50-FPN v2	43.7 M	52.3 / 19.1	33.4 / 29.9	69.1	440 / 388	760
RetinaNet R50-FPN v2	38.2 M	37.5 / 26.7	25.5 / 39.2	51.7	349 / 233	494
FCOS R50-FPN	32.3 M	34.8 / 28.7	31.3 / 32.0	50.9	291 / 274	316
YOLO11n	2.6 M	**9.8 / 102**	10.6 / 94.7	8.7	**42 / 28**	72
YOLO11m	20.1 M	12.2 / 82.2	12.5 / 79.9	10.9	135 / 108	164
RT-DETR-L	33.0 M	25.2 / 39.6	22.7 / 44.1	24.7	213 / 207	258
YOLO-World v2-S	12.8 M	10.4 / 95.9	11.0 / 91.1	9.2	232 / 198	264

Per-image latency measured *inside* the accuracy runs (score threshold 0.001, same models, same GPU) is very different for the torchvision models: Faster R-CNN averaged **295 ms** per COCO image and 55 ms per KITTI frame, RetinaNet 166 / 40 ms, FCOS 76 / 37 ms, whereas the Ultralytics models were within 1–2 ms of the controlled benchmark. See §3.4.

2.5 KITTI difficulty levels (driving3, GT outside the level ignored)

Model	mAP all	Easy	Moderate	Hard	person AP50 E / M / H	vehicle AP50 E / M / H
Faster R-CNN R50-FPN v2	0.237	0.348	0.298	0.239	0.71 / 0.63 / 0.51	0.96 / 0.94 / 0.85
RetinaNet R50-FPN v2	0.234	0.345	0.295	0.240	0.67 / 0.63 / 0.51	0.98 / 0.95 / 0.86
FCOS R50-FPN	0.230	0.343	0.291	0.235	0.64 / 0.58 / 0.47	0.98 / 0.95 / 0.85
YOLO11n @640	0.205	0.326	0.260	0.212	0.63 / 0.55 / 0.45	0.97 / 0.89 / 0.80
YOLO11m @640	0.232	0.351	0.295	0.240	0.71 / 0.63 / 0.51	0.98 / 0.95 / 0.86
RT-DETR-L @640	0.243	**0.358**	0.304	0.248	0.72 / 0.63 / 0.50	0.98 / 0.96 / 0.87
YOLO11m @1280	0.242	0.357	**0.305**	0.247	**0.76 / 0.68 / 0.55**	0.97 / 0.95 / 0.86
RT-DETR-L @1280	0.247	0.337	0.299	**0.249**	0.67 / 0.61 / 0.51	0.88 / 0.88 / 0.81

2.6 The Cyclist class: box-definition mismatch and a post-hoc fix

Best IoU reached with each KITTI Cyclist GT box by any detection with score > 0.3 (median over the 893 cyclists), and driving3 scores after fusing overlapping person + bicycle detections into one cyclist box (`src/cyclist_fusion.py`):

Model	bicycle box median IoU (≥0.5)	person box median IoU (≥0.5)	fused box (≥0.5)	cyclist AP50 → fused	person AP → fused	mAP → fused
Faster R-CNN v2	0.21 (10 %)	0.51 (52 %)	0.52 (53 %)	0.011 → **0.172**	0.212 → 0.207	0.237 → **0.250**
RetinaNet v2	0.00 (14 %)	0.50 (48 %)	0.53 (54 %)	0.019 → 0.063	0.203 → 0.183	0.234 → 0.232
FCOS	0.29 (29 %)	0.53 (56 %)	0.55 (58 %)	0.022 → 0.061	0.192 → 0.172	0.230 → 0.226
YOLO11m @640	0.00 (4 %)	0.36 (31 %)	0.03 (35 %)	0.005 → 0.116	0.200 → 0.200	0.232 → 0.242

Model	bicycle box median IoU (≥0.5)	person box median IoU (≥0.5)	fused box (≥0.5)	cyclist AP50 → fused	person AP → fused	mAP → fused
YOLO11m @1280	0.00 (7 %)	0.44 (41 %)	0.51 (51 %)	0.013 → 0.150	0.212 → 0.206	0.242 → **0.253**
RT-DETR-L @640	0.00 (5 %)	0.45 (41 %)	0.52 (53 %)	0.009 → 0.105	0.206 → 0.160	0.243 → 0.237
RT-DETR-L @1280	0.22 (12 %)	0.54 (58 %)	0.60 (66 %)	0.032 → 0.141	0.217 → 0.191	0.247 → 0.253
YOLO-World v2-S (COCO vocab)	0.00 (4 %)	0.00 (26 %)	0.00 (35 %)	0.017 → 0.163	0.182 → 0.192	0.223 → 0.241

Rider-as-person effect (driving3, person class only; cyclist GT boxes additionally registered as *person* ignore regions): person AP rises by 0.03–0.04 and person AP50 by 0.06–0.11 for every model (e.g. Faster R-CNN 0.212 → 0.249, AP50 0.501 → 0.594; RetinaNet AP50 0.499 → 0.607).

2.7 Figures




Figure 1. In-domain COCO val2017 mAP versus zero-shot KITTI mAP (driving3 taxonomy) for each model. The 16-point spread on COCO compresses to 4 points on KITTI.




Figure 2. KITTI per-class AP@[.5:.95] under the driving3 taxonomy. Vehicles transfer well, persons lose most, cyclists collapse to ≈0 for every closed-set model.




Figure 3. AP by object scale (COCO area thresholds) on COCO and KITTI. Small-object AP is the weakest bucket everywhere and is dominated by input resolution on KITTI.




Figure 4. Speed–accuracy trade-off on the RTX 5060 at batch size 1 (circle = fp32, triangle = fp16, marker size ∝ peak GPU memory). Latency axis is logarithmic.

3. Technical analysis

3.1 Cross-dataset generalisation (COCO → KITTI): what degrades and why

The ranking compresses. On COCO the seven models span 16 mAP points (0.368–0.528); on KITTI they span 4 (0.205–0.243). COCO mAP is a weak predictor of zero-shot KITTI mAP: RT-DETR-L keeps first place, but YOLO11m (2nd on COCO) ties with RetinaNet and FCOS (5th/6th on COCO), and Faster R-CNN (4th on COCO) is 2nd on KITTI. Every model loses 15–29 mAP points. The absolute level (0.21–0.25) matches the 0.23–0.28 range reported in the course tutorial for the same experiment.

Per class, the degradation is extremely uneven (driving3 per-class AP):

- *Vehicle* generalises well. AP50 is 0.78–0.86 for every model and 0.96–0.98 on Easy vehicles, i.e. almost every clearly visible car is found. The mAP@[.5:.95] of ≈0.50 is a *localisation* ceiling, not a recall problem: KITTI boxes are drawn tightly around the visible part of truncated/occluded cars, COCO detectors were trained on amodal-ish looser boxes, and the IoU 0.75–0.95 thresholds punish that. AP75 ≈ 0.22 vs AP50 ≈ 0.45 confirms it.
- *Person* loses the most among "real" classes: COCO person AP 0.53–0.63 → KITTI 0.18–0.21. Three causes were isolated:
  1. **Scale.** KITTI pedestrians are small (many < 40 px high at 1242×375, and after a 640-px letterbox a 40-px person is ~20 px). AP_S is the lowest bucket for every model (0.09–0.18 vs AP_L ≈ 0.30), and the difficulty breakdown shows person AP50 falling from ≈0.71 (Easy: ≥40 px, unoccluded) to ≈0.51 (Hard: ≥25 px, heavy occlusion). Doubling the Ultralytics input to 1280 raises AP_S by +0.067 for YOLO11n and +0.026 for YOLO11m (§3.4).

2. **Label convention: riders.** KITTI never labels the rider of a bicycle as a pedestrian, but a COCO detector always emits a person box for them. Ignoring those boxes (§2.6) recovers +0.03–0.04 person AP and +0.06–0.11 AP50 for every model — about a tenth of the ≈0.4 COCO→KITTI person-AP gap is a taxonomy artefact rather than a detection failure.
3. **Occlusion / truncation.** Even on Easy pedestrians (≥40 px, unoccluded) AP50 only reaches ≈0.7; groups of pedestrians on sidewalks are heavily occluded, and KITTI's `Person_sitting` instances are rarely boxed as persons by COCO detectors.

- *Cyclist* collapses to AP ≈ 0.00 for every closed-vocabulary model, and this is purely a **box-definition mismatch**, not missed objects. §2.6 shows that the best COCO `bicycle` box reaches a median IoU of only 0.00–0.29 with the KITTI rider+bike box (the bike is the lower half of it), whereas the rider's `person` box already reaches IoU ≈ 0.5. A 15-line post-hoc fusion rule (merge an overlapping person + bicycle detection, consume the person box) raises cyclist AP50 from ≈0.01 to 0.06–0.17 and improves overall mAP for the stronger detectors (Faster R-CNN 0.237 → 0.250, YOLO11m@1280 0.242 → 0.253). It hurts FCOS/RetinaNet/RT-DETR@640 slightly, because their person boxes that get consumed were also matching real pedestrians near bikes. The lesson: with cross-dataset evaluation, a 0-AP class must be checked for *definition* mismatch before concluding the detector cannot see it.
- *Truck* (driving5) is where architectures differ most: Faster R-CNN 0.285 vs YOLO11n 0.064 and RT-DETR 0.168. KITTI trucks are rare (606 GT) and mostly large, flat-front European lorries, visually unlike COCO's pickups and US-style trucks; small models fold them into `car` / `bus`. The open-vocabulary model with an explicit "truck" prompt does best here (0.273–0.287), and RT-DETR at 1280 jumps to 0.311.

Which scales degrade most? On COCO, AP_S:AP_L ratios are ≈0.5; on KITTI they are ≈0.3–0.5 and the *absolute* AP_S of the 640-px YOLO/RT-DETR models (0.09–0.17) is below that of the 800-px torchvision models (0.16), despite YOLO11m/RT-DETR being far stronger on COCO small objects (0.335/0.344 vs 0.309). Input resolution, not architecture, dominates small-object transfer to the wide 1242×375 KITTI frame (§3.4).

3.2 Architecture comparison

Two-stage (Faster R-CNN) vs one-stage anchor-based (RetinaNet) vs one-stage anchor-free (FCOS), all ResNet50-FPN at 800 px:

- On COCO the ordering Faster R-CNN (0.469) > RetinaNet (0.415) > FCOS (0.392) is driven by AP75 (0.513 / 0.439 / 0.420): the second-stage box refinement of Faster R-CNN gives tighter boxes. On KITTI the three are within 0.007 mAP (0.237 / 0.234 / 0.230) and have identical vehicle AP (0.49–0.50) — the refinement advantage disappears when the box convention itself differs.
- Faster R-CNN retains the best *person* AP on both datasets (0.596 → 0.212), and RetinaNet's focal-loss one-stage head has the highest AR_100 on KITTI (0.394 vs 0.357) but lower precision, consistent with its denser, lower-confidence output (it also returns up to 300 detections/image vs 100).
- Cost: Faster R-CNN is 1.4–1.5× slower than RetinaNet/FCOS (52 vs 37/35 ms) and uses 1.3–1.5× the memory, for +5–8 mAP on COCO but only +0.3–0.7 on KITTI.

YOLO11 (CNN, anchor-free, NMS) vs RT-DETR-L (hybrid encoder + transformer decoder, NMS-free), both at 640 px in the same framework:

- RT-DETR-L beats YOLO11m by +2.2 mAP on COCO and +1.1 on KITTI with a similar parameter count (33 M vs 20 M) but 2.1× the latency (25 vs 12 ms) and 1.6× the memory. Its advantage is concentrated in AP_L (0.708 vs 0.664 on COCO) and AR_100 (0.717 vs 0.661): set-prediction with 300 queries recalls more crowded/large objects, and no NMS means overlapping vehicles in KITTI traffic queues are not suppressed (vehicle AP 0.522, the best of all models).
- YOLO11's cost structure is very different: YOLO11n → YOLO11m is 8× the params but only +2.4 ms, because at 640 px both are launch/post-processing-bound on this GPU (fp16 gives no speed-up at all, §3.4). RT-DETR scales worse with resolution: at 1280 it costs 60 ms (2.4×) for +0.4 driving3 mAP, while YOLO11m at 1280 costs 15.9 ms (+1.3×) for +1.0 mAP.
- Zero-shot robustness: YOLO11m loses 27.4 COCO→KITTI points, RT-DETR-L 28.5, Faster R-CNN 23.2 — the transformer is not intrinsically more robust to domain shift here; its KITTI lead is the same size as its COCO lead minus its weaker small-object transfer at 640 px.

3.3 Closed-set vs open-vocabulary (YOLO11 vs YOLO-World)

YOLO-World v2-S (12.8 M params, CLIP text head) was run three ways on KITTI:

vocabulary	driving3 mAP	vehicle	person (AP50)	cyclist (AP50)	driving5 truck
80 COCO names (closed-set behaviour)	0.223	0.484	0.182 (0.430)	0.003 (0.017)	0.248
KITTI names: car, van, truck, `pedestrian`, cyclist, tram	0.210	0.488	0.116 (0.297)	**0.027 (0.123)**	**0.287**
KITTI names with `person` instead of pedestrian	**0.225**	0.487	0.183 (0.423)	0.006 (0.025)	0.273

- With the COCO vocabulary YOLO-World behaves like a slightly weaker YOLOv8s (0.368 COCO mAP vs 0.387 for YOLO11n at 2.6 M params); on KITTI it transfers about as well as the closed-set YOLO11n/m (0.223 vs 0.205/0.232).
- Prompting with the target dataset's own names is **not automatically better**. "pedestrian" costs a third of the person AP (0.182 → 0.116) even though the two words are synonyms to a human: the CLIP text embedding of "pedestrian" is simply farther from what the detector's region features were aligned to during training on Objects365/GoldG/COCO captions, where "person" dominates.
- The "cyclist" prompt is the only way any model in this study produces KITTI-style rider+bike boxes directly (AP50 0.123, 5× the best closed-set model) — an open-vocabulary detector can *change the box definition* through language, which no closed-set model can. But prompts **compete**: as soon as "person" is in the vocabulary, the rider regions are claimed by "person" again and the cyclist

prompt collapses to AP50 0.025. The best vocabulary therefore depends on the downstream taxonomy, and prompt engineering changed mAP by ±0.015 — about the same as the gap between detector families on KITTI.

- The explicit "truck" prompt yields the best truck AP of any 640-px model (0.287 vs 0.181 for YOLO11m), and the model costs nothing extra at inference (10.4 ms, same as YOLO11n) because the text embeddings are computed once.

3.4 Speed–accuracy trade-off (latency, memory, accuracy)

- **Pareto front on COCO-mAP vs KITTI-frame latency** (fp32, §2.4): YOLO11n (9.8 ms, 0.387) → YOLO11m (12.2 ms, 0.506) → RT-DETR-L (25.2 ms, 0.528). Every torchvision model is dominated: Faster R-CNN v2 needs 52 ms for 0.469, RetinaNet/FCOS ≈ 35 ms for 0.39–0.42. On KITTI the front is YOLO11n@1280 (10.9 ms, 0.235) → YOLO11m@1280 (15.9 ms, 0.242) → RT-DETR-L@640 (25 ms, 0.243) → RT-DETR-L@1280 (60 ms, 0.247); the 800-px torchvision models again lie below it.
- **Resolution is the cheapest accuracy knob for the YOLO family on KITTI.** Going 640 → 1280 costs YOLO11n +1.4 ms per frame and gives +3.0 mAP / +6.7 AP_S; YOLO11m +3.5 ms for +1.0 mAP / +2.6 AP_S. The reason is that a 1242×375 frame letterboxed to 640 is only 640×193 of actual content — a 1.9× down-scale that pushes most pedestrians below 20 px. The torchvision models never had this problem (shorter side 800 ⇒ 1333×403, a 1.07× *up*-scale), which is why they keep up on KITTI despite much weaker COCO numbers.
- **fp16 helps only compute-bound models.** Faster R-CNN 52 → 33 ms (1.57×), RetinaNet 1.47×, RT-DETR-L 1.11×, FCOS 1.11×; YOLO11n/m and YOLO-World get *slower* by 0.3–0.8 ms because at ~10 ms per frame the time is in CPU-side letterboxing, kernel launches and NMS, not in GEMMs. Peak memory drops 3–35 %.
- **Low score thresholds are a hidden latency cost for NMS-based two-stage / dense detectors.** With the mAP-style threshold 0.001, Faster R-CNN spent 295 ms per COCO image (vs 69 ms at 0.25): up to 1000 proposals × 90 classes survive the threshold and go through class-wise NMS. On sparse KITTI frames the same model took 55 ms. RT-DETR (no NMS, fixed 300 queries) and YOLO (single-class-per-box NMS) were insensitive to the threshold. A deployment benchmark must therefore state its confidence threshold, as done in §2.4.
- **Memory** is not a constraint for any model at batch 1 on an 8 GB card (peak allocation 42–440 MB, reserved ≤ 760 MB); the ~6.8 GB reported by `nvidia-smi` during the runs was the caching allocator, not live tensors.

4. Failure analysis

The quantitative failures of §2–3 fall into five modes. Each was isolated by re-scoring the cached detections with one factor changed (§2.5, §2.6), so the size of every mode is measured, not guessed.

#	Failure mode	Where it shows	Root cause	Magnitude	Repair tried
F1	**Cyclist AP ≈ 0** for every closed-set model	§2.2 cyclist AP 0.001–0.006	*Box-definition mismatch*: KITTI boxes rider+bike as one object; COCO models emit `person` + `bicycle`, each with IoU ≈ 0.5 against the GT box and neither above it (Fig. 5a)	whole class lost (893 GT)	person+bicycle fusion (§2.6): AP50 0.01 → 0.06–0.17; "cyclist" text prompt in YOLO-World: AP50 0.12
F2	**Rider counted as a false-positive pedestrian**	§2.6 "rider ignored"	*Labelling convention*: KITTI never labels the rider as Pedestrian; every COCO model does (Fig. 5a, `person 0.91`)	−0.03 to −0.04 person AP, −0.06 to −0.11 person AP50 for every model	ignore-region re-scoring quantifies it; fusion consumes the box
F3	**Small pedestrians missed**	AP_S 0.09–0.18 vs AP_L ≈ 0.30; Easy→Hard person AP50 0.71 → 0.51	*Scale*: many KITTI pedestrians are < 40 px high; a 640-px letterbox halves that again (Fig. 5b)	largest single accuracy loss on KITTI	1280-px input: +6.7 AP_S for YOLO11n, +2.6 for YOLO11m (§3.4)
F4	**Occluded pedestrians in groups missed**	Easy AP50 only ≈ 0.7 even for ≥ 40 px, unoccluded	*Occlusion / crowding*: overlapping people on sidewalks produce merged or suppressed boxes (Fig. 5c: 7 of 17 missed at 158-px median height)	≈ 0.3 of person AP50 remains lost on Easy	none (would need training on crowded driving data); RT-DETR's NMS-free decoding does not help here (person AP50 0.49 vs 0.50 Faster R-CNN)
F5	**Van / Truck / Bus confusion**	driving5 truck AP 0.06–0.31 across models	*Taxonomy granularity*: KITTI has no Bus class (buses are labelled Truck) and Van sits between COCO `car` and `truck`; European flat-front lorries are unlike COCO trucks (Fig. 5c: Van → `truck 0.57`)	truck AP spread of 0.25 between models; invisible under driving3	map `bus` → truck and `Van` → car in driving5 (done); explicit "truck" prompt in YOLO-World gives the best 640-px truck AP (0.287)

Two further effects were observed but not quantified: **parked bicycles** (never labelled in KITTI, which only boxes *ridden* bikes as Cyclist) are detected as `bicycle` and therefore become cyclist false positives (Fig. 5c, blue boxes), and **tight KITTI boxes** on truncated/occluded vehicles cost localisation accuracy at the strict IoU thresholds (vehicle AP50 0.85 but AP75 ≈ 0.45, §3.1).



Figure 5 — qualitative failure examples (RT-DETR-L @640, score ≥ 0.3). (a) Frame 003367: two cyclists, each covered by a separate `person` and `bicycle` box (IoU 0.48 / 0.49 with the GT) — F1 and, for the `person 0.91` box, F2. (b) Frame 004215: four pedestrians 34–48 px high at the far left, two missed — F3. (c) Frame 002666: 17 pedestrians in a group, 7 missed; parked bicycles detected as `bicycle`; the KITTI `Van` detected as `truck` — F4, F5. Green = KITTI GT, dashed green = DontCare ignore region; red `person`, blue `bicycle`, yellow `car`, magenta `truck`. Generated by `src/failure_examples.py` from the cached detections.

What is a detector failure and what is not. Of the five modes only F3 and F4 are failures of the detectors in the usual sense (objects they cannot find); F1, F2 and F5 are mismatches between what COCO taught the model to draw and what KITTI's annotators drew. Had the study stopped at the per-class table, "cyclist AP = 0" would have been reported as a detection failure. The general lesson for zero-shot cross-dataset evaluation is to check box definitions and labelling conventions *before* attributing a 0-AP class to the model, and to report how much of a gap is recoverable by taxonomy work alone (here: ≈ 10 % of the person gap and most of the cyclist gap).

5. Conclusions

1. All seven COCO-pretrained detectors transfer to KITTI at a near-identical 0.21–0.25 mAP regardless of their 0.37–0.53 COCO mAP; in-domain accuracy is a poor proxy for zero-shot driving performance.
2. Vehicles transfer well (AP50 ≈ 0.85), pedestrians are limited by scale and occlusion, and the "cyclist" failure (AP ≈ 0) is a box-definition mismatch that a simple person+bicycle fusion partially repairs. About a tenth of the person-AP gap is also a labelling-convention artefact (riders).
3. Input resolution matters more than architecture for small objects on the wide KITTI frame: YOLO11n at 1280 px matches 800-px Faster R-CNN at 1/5 of the latency.
4. RT-DETR-L is the most accurate model on both datasets and has the best recall on crowded vehicles, but YOLO11m offers 95 % of its KITTI accuracy at half the latency and 60 % of the memory; the torchvision ResNet50-FPN models are Pareto-dominated on this GPU.
5. Open-vocabulary detection gives a new lever — the box definition and the class set can be set with words — but prompt wording changed mAP by as much as the choice of detector family, and prompts compete for the same regions.

Limitations

Single GPU, batch size 1, no TensorRT; Ultralytics numbers use square-letterbox `predict()` rather than rectangular `val()`; RetinaNet returns up to 300 detections per image versus 100 for the other torchvision models; only the 3,769-frame KITTI val split was evaluated; no fine-tuning was performed, so the fine-tuning analysis option was not pursued.

6. References

1. S. Ren, K. He, R. Girshick, J. Sun. *Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks.* NeurIPS 2015.
2. T.-Y. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, S. Belongie. *Feature Pyramid Networks for Object Detection.* CVPR 2017.
3. T.-Y. Lin, P. Goyal, R. Girshick, K. He, P. Dollár. *Focal Loss for Dense Object Detection.* ICCV 2017. (RetinaNet)
4. Z. Tian, C. Shen, H. Chen, T. He. *FCOS: Fully Convolutional One-Stage Object Detection.* ICCV 2019.
5. Y. Li, S. Xie, X. Chen, P. Dollár, K. He, R. Girshick. *Benchmarking Detection Transfer Learning with Vision Transformers.* arXiv:2111.11429, 2021. (training recipe of the torchvision "v2" detection weights)
6. G. Jocher, J. Qiu. *Ultralytics YOLO11*, 2024. https://github.com/ultralytics/ultralytics (YOLO11, and the RT-DETR / YOLO-World implementations and weights used here; version 8.4.194)
7. Y. Zhao, W. Lv, S. Xu, J. Wei, G. Wang, Q. Dang, Y. Liu, J. Chen. *DETRs Beat YOLOs on Real-time Object Detection.* CVPR 2024. (RT-DETR)

8. T. Cheng, L. Song, Y. Ge, W. Liu, X. Wang, Y. Shan. *YOLO-World: Real-Time Open-Vocabulary Object Detection.* CVPR 2024.
9. A. Radford et al. *Learning Transferable Visual Models From Natural Language Supervision.* ICML 2021. (CLIP text encoder used by YOLO-World)
10. T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, C. L. Zitnick. *Microsoft COCO: Common Objects in Context.* ECCV 2014.
11. A. Geiger, P. Lenz, R. Urtasun. *Are we ready for Autonomous Driving? The KITTI Vision Benchmark Suite.* CVPR 2012.
12. X. Chen, K. Kundu, Y. Zhu, A. Berneshawi, H. Ma, S. Fidler, R. Urtasun. *3D Object Proposals for Accurate Object Class Detection.* NeurIPS 2015. (origin of the 3,712 / 3,769 KITTI train/val split)
13. A. Paszke et al. *PyTorch: An Imperative Style, High-Performance Deep Learning Library.* NeurIPS 2019; TorchVision maintainers, *torchvision*, https://github.com/pytorch/vision (version 0.26.0).
14. COCO API / `pycocotools`. https://github.com/cocodataset/cocoapi
15. K. Liu. *DeepDataMiningLearning — ngdet tutorial* (course material). https://github.com/lkk688/DeepDataMiningLearning/blob/main/DeepDataMiningLearning/ngdet/TUTORIAL.md
16. N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, S. Zagoruyko. *End-to-End Object Detection with Transformers.* ECCV 2020. (DETR set prediction, NMS-free)

Appendix A — Evidence of execution

Everything in §2 was produced by the submitted code on the machine in §1.1. Three kinds of artefacts back the numbers. The first two are in the public GitHub repository https://github.com/bhagyeshrathi07/2d-object-detection-track-a together with the code and this report; the third is too large for GitHub and is submitted separately.

Artefact	Location	What it proves
Per-run metric files (19)	`results/metrics/<model>__<dataset>.json` (GitHub)	every metric in §2, plus model config, measured latency, peak GPU memory, hardware, library versions and the exact command of that run
Console logs of the job chains (unedited)	`results/logs/run_coco.log`, `run_rest.log`, `run_extra.log`, `fetch_kitti.log` (GitHub)	timestamps, per-500-image latency progress, `pycocotools` summary blocks, checkpoint downloads (progress bars stripped)
Cached raw detections (19 files, 1.2 GB)	`results/raw/` (separate archive)	every box the detectors produced; all KITTI tables can be regenerated on CPU with `evaluate.py --rescore-only`, `kitti_difficulty.py`, `cyclist_fusion.py`, `failure_examples.py`

A.1 Console excerpt — Faster R-CNN v2 on KITTI, from `results/logs/run_rest.log` (the COCO run of the same model, in `run_coco.log`, ends with `AP = 0.469`, the first row of §2.1):

```
===== tv:fasterrcnn_resnet50_fpn_v2  2026-10-30T22:11:43 =====
model: {
 "name": "fasterrcnn_resnet50_fpn_v2",
 "family": "Faster R-CNN (two-stage, anchor-based)",
 "framework": "torchvision 0.26.0+cu128 / torch 2.11.0+cu128",
 "checkpoint": "FasterRCNN_ResNet50_FPN_V2_Weights.COCO_V1",
 "input_resolution": "shorter side 800, longer side <= 1333 (aspect preserved)",
 "score_thr": 0.001, "nms_thr": 0.5, "max_det": 100, "precision": "fp32"
}
  500/3769  mean latency 54.9 ms
 1000/3769  mean latency 55.0 ms
 ...
 3500/3769  mean latency 55.2 ms
cached 374885 raw detections -> results\raw\fasterrcnn_resnet50_fpn_v2__kitti.json

=== fasterrcnn_resnet50_fpn_v2 on kitti [driving3] ===
Running per image evaluation...
Evaluate annotation type *bbox*
DONE (t=10.36s).
 Average Precision  (AP) @[ IoU=0.50:0.95 | area=   all | maxDets=100 ] = 0.237
 Average Precision  (AP) @[ IoU=0.50      | area=   all | maxDets=100 ] = 0.453
 Average Precision  (AP) @[ IoU=0.75      | area=   all | maxDets=100 ] = 0.226
 Average Precision  (AP) @[ IoU=0.50:0.95 | area= small | maxDets=100 ] = 0.160
 Average Precision  (AP) @[ IoU=0.50:0.95 | area=medium | maxDets=100 ] = 0.216
 Average Precision  (AP) @[ IoU=0.50:0.95 | area= large | maxDets=100 ] = 0.305
 Average Recall     (AR) @[ IoU=0.50:0.95 | area=   all | maxDets=100 ] = 0.357
```

A.2 Metric files. Each `results/metrics/<model>__<dataset>.json` on GitHub records, for one run, the model block shown above, the dataset and image count, mean / median / p90 latency, peak and reserved GPU memory, every metric of §2 per taxonomy with per-class AP and GT counts, the hardware and library versions, and the exact command line (e.g. `src/evaluate.py --model ul:rtdetr-l.pt --dataset kitti` yields the RT-DETR-L @640 rows of §2.2 / §2.3: mAP 0.2433, AP50 0.4534, vehicle AP 0.5225).

A.3 Independent check. The three torchvision models reproduce their published COCO mAP (46.7 / 41.5 / 39.2) to within 0.2 points (§2.1); a harness with a box-format, class-mapping or resizing bug would not do so.