Launchers - DBeaver - MariaDB

DBeaver For MariaDB

ProcessName: "C:\Program Files\DBeaver\dbeaver.exe"

Process Arguments: -con
"driver=mariadb|host=$SERVER|port=$PORT|user=$USERNAME|password=$PASSWORD"

PS: DBeaver application must be installed in the above directory.

Cagdas BARAK - Delinea

DBeaver_MariaDB

Overview   Audit

General settings

Launcher type ⑦	Process
Launcher name	DBeaver_MariaDB
State	Enabled
Use additional prompt	No
Track multiple windows	Yes
Record additional processes	—
Wrap custom parameters with quotation marks	Yes
Preserve SSH Client Process	No
Use SSH Tunneling with SSH Proxy	No

Windows settings

Configure the command that will run on Windows computers when this launcher is initiated
How do I process arguments ⬈

Process name	"C:\Program Files\DBeaver\dbeaver.exe"
Process arguments	-con "driver=mariadb|host=$SERVER|port=$PORT|user=$USERNAME|password=$PASSWORD"
Run process as secret credentials	No
Use Operating System Shell	No
Escape character	—
Characters to escape	—

Mac settings

Configure the command that will run on Mac computers when this launcher is initiated
How do I process arguments ⬈

Process name	—
Process arguments	—