

Testing classes series form the QA fox by the Arun motoori from videos-49 to 56

Interview questions for the Parallel execution:

1>Even though Multiple test tags, but only few test tags enabled for the parallel execution, how is it possible?

We are creating the parallel="classes" or "methods" thread-count="5" at the test level for which classes the parallel run needed to apply and in other test we don't use the concept of parallelization.

ex:

```
<test name="Test1" parallel="classes" thread-count="2">
<classes>

<class name="Testserialization.Register"/>
<class name="Testserialization.login"/>
</classes>
</test>
```

```
<test name="Test2">
<classes>

<class name="Testserialization.Search"/>
<class name="Testserialization.Search2"/>

</classes>
</test>
```

2>What happens when we provide parallel="none" thread-count="2" in the testing.xml?

When we provide the parallel="none" thread-count="2" at the test level or suite level then the parallelization will not occur which means we are running the threads in the sequential order(serialization).

3>What happens when we provide parallel="false" thread-count="2" in the testing.xml?

When we provide the parallel="false" thread-count="2" at the test level or suite level then the parallelization will not occur which means we are running the threads in the sequential order(serialization).

4>What happens when we provide parallel="tests" thread-count="1" in the testing.xml?

When we provide the parallel="tests" thread-count="1" at the test level or suite level then the parallelization will not occur which means we are running the threads in the sequential order(serialization).

5>What happens when we provide negative number in the thread count(parallel="tests" thread-count="-2")in the testing.xml?

The xml file will throw any error but while executing you will get the "IllegalArgumentException" will be displayed during run time.

6>What happens when there is more thread count and less number of tests(parallel="tests" thread-count="200") we have only 5 tests?

In this particular scenario the 5 threads will run for the existing 5 tests and remaining threads and will be ideal.

7>What happens when we provide parallel="classes" or parallel="methods" at the suite tag level in the testing.xml?

The test tags will be executed in the sequential manner.

New Threads will be created for every test tag for parallel execution of classes or methods.

ex:In the below examples the Test1 will execute first-->Operates on 2 threads-->1>Register
2>Login-->threads will be destroyed.

After that again 2 threads will be created for running the classes-->1>Search and 2>Search2-->threads will be destroyed.

```
<test name="Test1" parallel="classes" thread-count="2">
```

```
<classes>
```

```
<class name="Testserialization.Register"/>
```

```
<class name="Testserialization.Login"/>
```

```
</classes>
```

```
</test>
```

```
<test name="Test2">
```

```
<classes>
```

```
<class name="Testserialization.Search"/>
```

```
<class name="Testserialization.Search2"/>
```

`</classes>`

`</test>`

7>What happens when we provide parallel attribute only but not the thread-count in the testing.xml file.In this case what will be default thread-count?

5threads(Default thread-count=5) will be runned by defaultly if wont define any thread-count in the xml file means.