

# **Blind 75**

Bhanu Prasanna Koppolu

2023-11-04

# Table of contents

<b>Notations</b>	<b>3</b>
<b>Day - 9</b>	<b>4</b>
Contains Duplicate - 217 - LeetCode - Easy - Array & Hashing . . . . .	4
Approach - 1 . . . . .	4
Approach - 2 . . . . .	5
Approach - 3 . . . . .	6
Valid Anagram - 242 - LeetCode - Easy - Array & Hashing . . . . .	7
Approach - 1 . . . . .	7
Approach - 2 . . . . .	8
Two Sum - 1 - LeetCode - Easy - Array & Hashing . . . . .	9
Approach - 1 . . . . .	9
Approach - 2 . . . . .	10
<b>Day - 10</b>	<b>11</b>
Group Anagrams - 49 - LeetCode - Medium - Array & Hashing . . . . .	11
Approach - 1 . . . . .	11
Approach - 2 . . . . .	12

# Notations

- The first approach is the idea popped from my mind when I looked at the problem.

## Day - 9

After going through lot of things I have come across NeetCode. I have decided to solve all the 150 questions provided by [NeetCode](#).

### Contains Duplicate - 217 - LeetCode - Easy - Array & Hashing

#### Approach - 1

The First Approach that came to my mind was to write a Nested For Loop to check if it Contains Duplicate.

```
class Solution {
public:
    bool containsDuplicate(vector<int>& nums) {
        for (auto i = nums.begin(); i != nums.end(); i++) {
            for (auto j = i + 1; j != nums.end(); j++) {
                if (*i == *j) return true;
            }
        }

        return false;
    }
};
```

#### Output

The First Approach has Time Complexity of  $O(N^2)$  and Space Complexity of  $O(1)$ .

```
Time Limit Exceeded
70 / 75 testcases passed
```

## Approach - 2

Another Approach to this problem is using Sorting then Checking if it Contains Duplicate.

```
class Solution {
public:
    bool containsDuplicate(vector<int>& nums) {
        sort(nums.begin(), nums.end());

        for (int i = 0; i < nums.size() - 1; i++) {
            if (nums[i] == nums[i+1]) {
                return true;
            }
        }
        return false;
    }
};
```

## Output

The Second Approach has Time Complexity of  $O(N \log(N))$  and Space Complexity of  $O(1)$ .

Accepted

### Approach - 3

Using unordered\_set to check if it Contains Duplicate. The Time Complexity for Basic operations in unordered\_set is  $O(1)$  and for set it is  $O(\log(N))$ .

```
class Solution {
public:
    bool containsDuplicate(vector<int>& nums) {
        unordered_set<int> us;

        for (auto i = nums.begin(); i != nums.end(); i++) {
            if (us.find(*i) != us.end()) {
                return true;
            }
            us.insert(*i);
        }

        return false;
    }
};
```

### Output

The Third Approach has Time Complexity of  $O(N)$  and Space Complexity of  $O(N)$ . ***The optimal solution.***

Accepted

## Valid Anagram - 242 - LeetCode - Easy - Array & Hashing

### Approach - 1

Sort the characters of the string of **t** and **s** then check if both are same or not.

```
class Solution {
public:
    bool isAnagram(string s, string t) {
        sort(s.begin(), s.end());
        sort(t.begin(), t.end());

        if (s == t) {
            return true;
        }
        return false;
    }
};
```

### Output

The First Approach has Time Complexity of  $O(N \log(N))$  and Space Complexity of  $O(1)$ .

Accepted

## Approach - 2

Using unordered\_map which has principles derived from Hash Map. So basic operations are  $O(1)$ .

```
class Solution {
public:
    bool isAnagram(string s, string t) {

        if (s.size() != t.size()) {
            return false;
        }

        unordered_map<char, int> ums;
        unordered_map<char, int> umt;

        for (int i = 0; i < s.size(); i++) {
            ums[s[i]]++;
            umt[t[i]]++;
        }

        for (int i = 0; i < s.size(); i++) {
            if (ums[s[i]] != umt[s[i]]) {
                return false;
            }
        }

        return true;
    }
};
```

## Output

The Second Approach has Time Complexity of  $O(S + T)$  and Space Complexity of  $O(S + T)$ .

Accepted



## Two Sum - 1 - LeetCode - Easy - Array & Hashing

### Approach - 1

The general approach to this problem is Brute Force Approach.

```
class Solution {
public:
    vector<int> twoSum(vector<int>& nums, int target) {
        int l = nums.size();

        for (int i = 0; i < l; i++) {
            for (int j = 0; j < l && i != j; j++) {
                if (nums[i] + nums[j] == target) {
                    return {i, j};
                }
            }
        }

        return {};
    }
};
```

### Output

The First Approach has Time Complexity of  $O(N^2)$  and Space Complexity of  $O(1)$ .

Accepted

## Approach - 2

Using unordered\_map which has principles derived from Hash Map. So basic operations are  $O(1)$ .

```
class Solution {
public:
    vector<int> twoSum(vector<int>& nums, int target) {
        unordered_map<int, int> um;

        for (int i = 0; i < nums.size(); i++) {
            if (auto search = um.find(target - nums[i]); search != um.end()) {
                return {search->second, i};
            }

            um[nums[i]] = i;
        }

        return {};
    }
};
```

## Output

The Second Approach has Time Complexity of  $O(N)$  and Space Complexity of  $O(N)$ .

Accepted

# Day - 10

## Group Anagrams - 49 - LeetCode - Medium - Array & Hashing

### Approach - 1

Sorting and Matching Strings.

```
class Solution {
public:
    vector<vector<string>> groupAnagrams(vector<string>& strs) {
        vector<string> st = strs;
        vector<vector<string>> fs;
        unordered_set<int> us;

        for (int i = 0; i < st.size(); i++) {
            sort(st[i].begin(), st[i].end());
        }

        for (int i = 0; i < st.size(); i++) {
            vector<string> vs;

            for (int j = i; j < st.size(); j++) {
                if (us.find(j) == us.end()) {
                    if (st[i] == st[j]) {
                        vs.push_back(strs[j]);
                        us.insert(j);
                    }
                }
            }
            if (vs.size() != 0) {
                fs.push_back(vs);
            }
        }
    }
}
```

```

        return fs;
    }
};

```

## Output

The First Approach has Time Complexity of  $O(mn \log(n))$  and Space Complexity of  $O(n)$ .

Accepted

## Approach - 2

Used Hash Map to reduce the Time Complexity.

```

class Solution {
public:
    vector<vector<string>> groupAnagrams(vector<string>& strs) {
        unordered_map<string, vector<string>> m;

        for (int i = 0; i < strs.size(); i++) {
            string key = getKey(strs[i]);
            m[key].push_back(strs[i]);
        }

        vector<vector<string>> fs;

        for (auto i = m.begin(); i != m.end(); i++) {
            fs.push_back(i->second);
        }

        return fs;
    }
private:
    string getKey (string val) {
        string s = "";
        vector<int> c(26);

        for (int i = 0; i < val.size(); i++) {
            c[val[i] - 'a'] += 1;

```

```
    }  
  
    for (int i = 0; i < 26; i++) {  
        s = s + to_string(c[i]) + '#';  
    }  
  
    return s;  
}  
};
```

### Output

The Second Approach has Time Complexity of  $O(mn)$  and Space Complexity of  $O(mn)$ .

Accepted