

C++ Notes

Bhanu Prasanna Koppolu

2023-10-25

Table of contents

Day - 1	4
Time Complexity	4
Important Points	4
Akra-Bazzi Time Complexity Method	4
Asymptotic Notation	5
Big - O Notation (\leq Upper Bound)	5
Big - Ω Notation (\geq Lower Bound)	5
Big - Θ Notation (Average)	5
Little - o Notation ($<$ Upper Bound)	5
Little - ω Notation ($>$ Lower Bound)	6
Space Complexity	6
Linear Recurrence (Homogenous and Non-Homogenous)	6
Day - 2	7
Recursion	7
Important Points	7
Types of Recurrence Relations	7
How to understand & approach a problem?	7
Math for DSA	8
Day - 3	9
C++ Start	9
Day - 4	10
C++ from Book	10
Learning Language Tradition - Hello, World! Program	10
Day - 5	11
LeetCode Questions & Answers	11
Two Sum	11
Remove Duplicates from Sorted Array	12
Remove Element	12
Search Insert Position	13
Plus One	13

Day - 6	15
LeetCode Questions & Answers	15
Merge Sorted Array	15
Pascal's Triangle	16
Pascal's Triangle 2	16
Best Time to Buy and Sell Stock	17
Single Number	18
 Day - 7	 19
Single Linked List	19
Double Linked List	24
Circular Linked List	30

Day - 1

Time Complexity

Important Points

- **Definition** - Time Complexity is the relationship about how the time will grow as the input grows.
- Time Complexity \neq Total Time Taken by a Machine to execute.
- There are mainly 4 points for Time Complexity:
 1. Always look for the **Worst Case Time Complexity**.
 2. Always look at the **Complexity for Large Data**.
 3. Always **Ignore Constants**.
 4. Always **Ignore Less Dominant Terms**. *From Point 2*

Akra-Bazzi Time Complexity Method

If the recurrence become more complex then finding the time complexity will become harder. So, Akra-Bazzi method is the easy and simple method to find the Time Complexity.

The method goes as follows:

Let p be the unique real number for which

$$\sum_{i=1}^k a_i b_i^p = 1$$

Then,

$$T(x) = \Theta\left(x^p + x^p \int_1^x \frac{g(u)}{u^{p+1}} du\right)$$

Asymptotic Notation

The usage of Asymptotic Notation is for specifying and for the identification of the upper and lower bounds.

$$\lim_{x \rightarrow \infty} \frac{f(n)}{g(n)}$$

Below are the Asymptotic Notations:

Big - O Notation (\leq Upper Bound)

This is the Upper Bound and the complexity cannot go beyond this Upper Bound.

$$\lim_{x \rightarrow \infty} \frac{f(n)}{g(n)} < \infty$$

Big - Ω Notation (\geq Lower Bound)

This is the opposite of Big - O Notation. This is the Lower Bound and the function complexity will atleast require Lower Bound complexity.

$$\lim_{x \rightarrow \infty} \frac{f(n)}{g(n)} > 0$$

Big - Θ Notation (Average)

The Big - Θ Notation was created when a function lies in both Upper Bound (Big - O) and Lower Bound (Big - Ω).

$$0 < \lim_{x \rightarrow \infty} \frac{f(n)}{g(n)} < \infty$$

Little - o Notation ($<$ Upper Bound)

The Little - o is same as Big - O but it is slightly loose and strictly lesser than.

$$\lim_{x \rightarrow \infty} \frac{f(n)}{g(n)} = 0$$

Little - ω Notation (> Lower Bound)

The Little - ω is same as Big - Ω but it is slightly loose and strictly greater than.

$$\lim_{x \rightarrow \infty} \frac{f(n)}{g(n)} = \infty$$

Space Complexity

- Space Complexity is measured by combining the Input Space and the Auxiliary Space. The same Asymptotic Notations discussed above are the ones used for Space Complexity.

Linear Recurrence (Homogenous and Non-Homogenous)

- Resources Used:
 - [Click Here!](#)

This is the end of ***Day - 1***.

Day - 2

Recursion

Important Points

- Recursion helps in solving bigger/complex problems into smaller problems which can be solved in a simple way.
- You can convert a Recursion solution into Iterative and Vice Versa.
- Space Complexity is not constant due to Recursive Calls.

Types of Recurrence Relations

1. Linear Recurrence Relation
2. Divide & Conquer Recurrence Relation

How to understand & approach a problem?

- Identify if you can break down problem into smaller problems.
- Write the Recurrence Relations if needed.
- Draw the Recursive Tree.
- About the Tree:
 - See the flow of functions, how they are getting into the stack.
 - Identify and Focus on Left Tree Calls and Right Tree Calls.
 - Draw the tree and pointers using Pen & Paper for better understanding. *
 - Use a debugger to see the flow.
- See how the values and what type of values are returned at each step. See where the function will come out. In the end you will come out of the main function.
- Three Variables to concentrate on:
 - Arguments
 - Return Type
 - Body of Function
- Resources used:

- [Click Here!](#)

Math for DSA

- Resources used:
 - Math for DSA 1 - [Click Here!](#)
 - Math for DSA 2 - [Click Here!](#)

This is the end of ***Day - 2.***

Day - 3

C++ Start

- I have solved 18 Hackerrank Problems in the C++ section. - [Click Here!](#).

Day - 4

- I have solved total of 28 Hackerrank Problems in the C++ section. *I feel confident in C++.* - [Click Here!](#).

C++ from Book

- C++ developed by Bjarne Stroustrup at Bell Labs (1979).

Learning Language Tradition - Hello, World! Program

```
// Preprocessor Directive
#include <iostream>

// Start of the Program
int main() {
    // Tell the compiler what namespace to search in
    using namespace std;

    // Write to the screen using std::cout
    cout << "Hello, World!" << endl;

    // Return a value to the OS
    return 0;
}
```

Day - 5

- I have solved 5 LeetCode Questions using C++ in the Arrays Section. - [Click Here!](#).

LeetCode Questions & Answers

Two Sum

```
// Two_Sum.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    vector<int> twoSum(vector<int>& nums, int target) {
        int l = nums.size();

        for (int i = 0; i < l; i++) {
            for (int j = 0; j < l && i != j; j++) {
                if (nums[i] + nums[j] == target) {
                    return {i, j};
                }
            }
        }

        return {};
    }
};
```

Remove Duplicates from Sorted Array

```
// Remove_Duplicates_from_Sorted_Array.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    int removeDuplicates(vector<int>& v) {
        int j = 1;

        for (auto i = v.begin() + 1; i != v.end(); i++) {
            if (*i != *(i - 1)) {
                v[j] = *i;
                j++;
            }
        }

        return j;
    }
};
```

Remove Element

```
// Remove_Element.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    int removeElement(vector<int>& v, int val) {
        int j = 0;

        for (auto i = v.begin(); i != v.end(); i++) {
            if (*i != val) {
                v[j] = *i;
                j++;
            }
        }
    }
};
```

```

        return j;
    }
};

```

Search Insert Position

```

// Search_Insert_Position.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    int searchInsert(vector<int>& nums, int target) {
        auto x = std::lower_bound(nums.begin(), nums.end(), target);

        cout << (x - nums.begin()) << endl;

        return x - nums.begin();
    }
};

```

Plus One

```

// Plus_One.cpp
// LeetCode - C++
// Created by Bhanu Prasanna
// Not the Best Solution - Must Learn How to Optimize a Solution.

class Solution {
public:
    vector<int> plusOne(vector<int>& v) {
        int c = 0, l = v.size();

        for (int i = l-1; i >= 0; i--) {
            if (i == l-1) {
                if (v[i] == 9) {
                    v[i] = 0;
                    c = 1;
                }
            }
        }
    }
};

```

```

        } else {
            v[i] += 1;
            return v;
        }
    } else {
        if (v[i] == 9) {
            v[i] = 0;
            c = 1;
        } else {
            v[i] += c;
            return v;
        }
    }
}

if (*v.begin() == 0) {
    v.insert(v.begin(), 1);
}

return v;
}
};

```

Day - 6

- I have solved 5 LeetCode Questions using C++ in the Arrays Section. - [Click Here!](#).

LeetCode Questions & Answers

Merge Sorted Array

```
// Merge_Sorted_Array.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    void merge(vector<int>& nums1, int m, vector<int>& nums2, int n) {
        int i = m - 1;
        int j = n - 1;
        int k = m + n - 1;

        while (j >= 0) {
            if (i >= 0 && nums1[i] > nums2[j]) {
                nums1[k] = nums1[i];
                i--;
            } else {
                nums1[k] = nums2[j];
                j--;
            }
            k--;
        }
    }
};
```

Pascal's Triangle

```
// Pascal's_Triangle.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    vector<vector<int>> generate(int numRows) {
        vector<vector<int>> v;

        for (int i = 0; i < numRows; i++) {
            vector<int> x(i+1, 1);
            for (int j = 1; j < i; j++) {
                x[j] = v[i-1][j] + v[i-1][j-1];
            }
            v.push_back(x);
        }
        return v;
    }
};
```

Pascal's Triangle 2

```
// Pascal's_Triangle_2.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    vector<int> getRow(int rowIndex) {
        vector<vector<int>> v;
        vector<int> xv;

        for (int i = 0; i <= rowIndex; i++) {
            vector<int> x(i+1, 1);

            for (int j = 1; j < i; j++) {
                x[j] = v[i-1][j] + v[i-1][j-1];
            }
        }
    }
};
```



```

        if (i == rowIndex) {
            return x;
        }

        v.push_back(x);
    }

    return xv;
}
};

```

Best Time to Buy and Sell Stock

```

// Best_Time_to_Buy_and_Sell_Stock.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    int maxProfit(vector<int>& prices) {
        int lsf = INT_MAX;
        int op = 0;
        int pist = 0;

        for (int i = 0; i < prices.size(); i++) {
            if (prices[i] < lsf) {
                lsf = prices[i];
            }
            pist = prices[i] - lsf;
            if (pist > op) {
                op = pist;
            }
        }
        return op;
    }
};

```

Single Number

```
// Single_Number.cpp
// LeetCode - C++
// Created by Bhanu Prasanna

class Solution {
public:
    int singleNumber(vector<int>& nums) {
        int ans = 0;

        for (auto x:nums) {
            ans ^= x;
        }

        return ans;
    }
};
```

Day - 7

- I am going to implement Data Structures in C++.

Single Linked List

```
// Single_Linked_List.cpp
// DS - C++
// Created by Bhanu Prasanna

#include <iostream>
using namespace std;

class Node {
public:
    int data;
    Node* next;

    Node () {
        data = 0;
        next = nullptr;
    }

    Node (int d) {
        data = d;
        next = nullptr;
    }
};

class SLL : public Node {
    Node* head;

public:
    SLL () {
```

```

        head = nullptr;
    }

    // Insert Data at the Front of SLL
    void insert_front(int);

    // Insert Data at the Back of SLL
    void insert_back(int);

    // Insert Data in the Middle of SLL
    void insert(int, int);

    // Delete Data from the Front of SLL
    void delete_front();

    // Delete Data from the Back of SLL
    void delete_back();

    // Delete Data from the Middle of SLL
    void del(int);

    // Length of the SLL
    int length();

    // Print SLL
    void printll();

};

/* Delete Functions for Single Linked List */

void SLL::delete_front () {
    Node *t = head;

    if (t == nullptr) {
        cout << "There are no element in the SLL to delete!" << endl;
        return;
    }

    head = head->next;
}

```

```

void SLL::delete_back () {
    Node *t = head;

    if (t == nullptr) {
        cout << "There are no element in the SLL to delete!" << endl;
        return;
    }

    while (t->next->next != nullptr) {
        t = t->next;
    }
    t->next = nullptr;
}

void SLL::del(int pos) {
    Node *x = head;
    Node *y = head->next;

    if (x == nullptr) {
        cout << "There are no element in the SLL to delete!" << endl;
        return;
    }

    for (int i = 0; i < pos - 2; i++) {
        x = x->next;
        y = y->next;
    }
    x->next = y->next;
}

/* Insertion Functions for Single Linked List */

void SLL::insert_front (int d) {
    Node *t = new Node(d);

    if (head == nullptr) {
        head = t;
        return;
    }

    t->next = head;
}

```

```

        head = t;
    }

    void SLL::insert_back (int d) {
        Node *t = new Node(d);

        if (head == nullptr) {
            head = t;
            return;
        }

        Node *x = head;

        while (x->next != nullptr) {
            x = x->next;
        }
        x->next = t;
    }

    void SLL::insert (int d, int pos) {

        if (pos > SLL::length()) {
            SLL::insert_back(d);
            return;
        }

        if (pos == 1) {
            SLL::insert_front(d);
            return;
        }

        Node *t = new Node(d);
        Node *x = head;
        Node *y = head->next;

        for (int i = 0; i < pos - 2; i++) {
            x = x->next;
            y = y->next;
        }
    }

```

```

        t->next = y;
        x->next = t;
    }

/* Length of Single Linked List */

int SLL::length () {
    Node *t = head;
    int c = 0;

    while (t != nullptr) {
        t = t->next;
        c++;
    }

    return c;
}

/* Print Single Linked List */

void SLL::printll () {
    Node *t = head;

    if (t == nullptr) {
        cout << "Linked List is Empty" << endl;
        return;
    }

    while (t != nullptr) {
        if (t->next == nullptr) {
            cout << t->data << endl;
        } else {
            cout << t->data << " -> ";
        }
        t = t->next;
    }
}

int main () {
    SLL l;

```

```

        l.insert_front(10);
        l.insert_back(20);
        l.insert_back(40);
        l.insert_back(50);
        l.insert_back(60);

        l.insert(30, 3);

        l.insert(30,3);

        l.del(3);

        l.delete_back();
        l.delete_front();

        cout << "Elements of Linked List are:" << endl;

        l.printll();

        cout << endl << "Count: " << l.length() << endl;

        return 0;
}

```

Double Linked List

```

// Double_Linked_List.cpp
// DS - C++
// Created by Bhanu Prasanna

#include <iostream>
using namespace std;

class Node {
public:
    int data;
    Node* next;
    Node* prev;
}

```



```

Node () {
    data = 0;
    next = nullptr;
    prev = nullptr;
}

Node (int d) {
    data = d;
    next = nullptr;
    prev = nullptr;
}

};

class DLL : public Node {
    Node* head;

public:
    DLL () {
        head = nullptr;
    }

    // Insert Data at the Front of DLL
    void insert_front(int);

    // Insert Data at the Back of DLL
    void insert_back(int);

    // Insert Data in the Middle of DLL
    void insert(int, int);

    // Delete Data from the Front of DLL
    void delete_front();

    // Delete Data from the Back of DLL
    void delete_back();

    // Delete Data from the Middle of DLL
    void del(int);

    // Length of the DLL
    int length();

```

```

        // Print DLL
        void printll();

};

/* Delete Functions for Double Linked List */

void DLL::delete_front () {
    Node *t = head;

    if (t == nullptr) {
        cout << "There are no element in the DLL to delete!" << endl;
        return;
    }

    head = head->next;
    head->prev = nullptr;
}

void DLL::delete_back () {
    Node *t = head;

    if (t == nullptr) {
        cout << "There are no element in the DLL to delete!" << endl;
        return;
    }

    while (t->next->next != nullptr) {
        t = t->next;
    }
    t->next = nullptr;
}

void DLL::del(int pos) {
    Node *x = head;
    Node *y = head->next;

    if (x == nullptr) {
        cout << "There are no element in the DLL to delete!" << endl;
        return;
    }
}

```

```

        for (int i = 0; i < pos - 2; i++) {
            x = x->next;
            y = y->next;
        }
        y->next->prev = x;
        x->next = y->next;
    }

    /* Insertion Functions for Double Linked List */

    void DLL::insert_front (int d) {
        Node *t = new Node(d);

        if (head == nullptr) {
            head = t;
            return;
        }

        t->next = head;
        head->prev = t;

        head = t;
    }

    void DLL::insert_back (int d) {
        Node *t = new Node(d);

        if (head == nullptr) {
            head = t;
            return;
        }

        Node *x = head;

        while (x->next != nullptr) {
            x = x->next;
        }
        x->next = t;
        t->prev = x;
    }

```

```

void DLL::insert (int d, int pos) {

    if (pos > DLL::length()) {
        DLL::insert_back(d);
        return;
    }

    if (pos == 1) {
        DLL::insert_front(d);
        return;
    }

    Node *t = new Node(d);
    Node *x = head;
    Node *y = head->next;

    for (int i = 0; i < pos - 2; i++) {
        x = x->next;
        y = y->next;
    }

    t->next = y;
    y->prev = t;
    t->prev = x;
    x->next = t;
}

/* Length of Double Linked List */

int DLL::length () {
    Node *t = head;
    int c = 0;

    while (t != nullptr) {
        t = t->next;
        c++;
    }

    return c;
}

```

```

/* Print Double Linked List */

void DLL::printll () {
    Node *t = head;

    if (t == nullptr) {
        cout << "Linked List is Empty" << endl;
        return;
    }

    while (t != nullptr) {
        if (t->next == nullptr) {
            cout << t->data << endl;
        } else {
            cout << t->data << " -> ";
        }
        t = t->next;
    }
}

int main () {
    DLL l;

    l.insert_front(10);
    l.insert_back(20);
    l.insert_back(40);
    l.insert_back(50);
    l.insert_back(60);

    l.insert(30, 3);

    l.insert(30,3);

    l.del(3);

    l.delete_back();
    l.delete_front();

    cout << "Elements of Linked List are:" << endl;

    l.printll();
}

```

```

        cout << endl << "Count: " << l.length() << endl;

    return 0;
}

```

Circular Linked List

```

// Circular_Linked_List.cpp
// DS - C++
// Created by Bhanu Prasanna

#include <iostream>
using namespace std;

class Node {
public:
    int data;
    Node* next;

    Node () {
        data = 0;
        next = nullptr;
    }

    Node (int d) {
        data = d;
        next = nullptr;
    }
};

class CLL : public Node {
    Node* head;
    Node* last;

public:
    CLL () {
        head = nullptr;
        last = nullptr;
    }
}

```

```

// Insert Data at the Front of CLL
void insert_front(int);

// Insert Data at the Back of CLL
void insert_back(int);

// Insert Data in the Middle of CLL
void insert(int, int);

// Delete Data from the Front of CLL
void delete_front();

// Delete Data from the Back of CLL
void delete_back();

// Delete Data from the Middle of CLL
void del(int);

// Length of the CLL
int length();

// Print CLL
void printll();
};

/* Delete Functions for Circular Linked List */

void CLL::delete_front() {
    Node *t = head;

    if (t == nullptr) {
        cout << "There are no element in the CLL to delete!" << endl;
    }

    head = head->next;
    last->next = head;
}

void CLL::delete_back() {
    Node *t = head;

```

```

    if (t == nullptr) {
        cout << "There are no element in the CLL to delete!" << endl;
    }

    if (t->next == head) {
        head = nullptr;
        last = nullptr;
    }

    while (t->next->next != head) {
        t = t->next;
    }

    last = t;

    last->next = head;
}

void CLL::del(int pos) {
    Node *x = head;
    Node *y = head->next;

    if (x == nullptr) {
        cout << "There are no element in the CLL to delete!" << endl;
    }

    if (pos == CLL::length()) {
        CLL::delete_back();
    }

    for (int i = 0; i < pos - 2; i++) {
        x = x->next;
        y = y->next;
    }

    x->next = y->next;
}

/* Insertion Functions for Circular Linked List */

void CLL::insert_front(int d) {

```



```

Node *t = new Node(d);

if (head == nullptr) {
    head = t;
    last = t;
    last->next = head;
    return;
}

t->next = head;
head = t;
last->next = head;
}

void CLL::insert_back (int d) {
    Node *t = new Node(d);

    if (head == nullptr) {
        insert_front(d);
        return;
    }

    t->next = head;
    last->next = t;
    last = t;
}

void CLL::insert (int d, int pos) {
    if (pos > CLL::length()) {
        CLL::insert_back(d);
        return;
    }

    if (pos == 1) {
        CLL::insert_front(d);
        return;
    }

    Node *t = new Node(d);
    Node *x = head;
    Node *y = head->next;

```

```

        for (int i = 0; i < pos - 2; i++) {
            x = x->next;
            y = y->next;
        }

        t->next = y;
        x->next = t;
    }

    /* Length of Double Linked List */

    int CLL::length () {
        Node *t = head;
        int c = 0;

        if (t == nullptr) {
            return 0;
        }

        c++;
        t = t->next;

        while (t != head) {
            t = t->next;
            c++;
        }

        return c;
    }

    /* Print Double Linked List */

    void CLL::printll () {
        Node *t = head;

        if (t == nullptr) {
            cout << "Linked List is Empty" << endl;
            return;
        }

        cout << t->data << "-> ";
    }

```

```

        t = t->next;

    while (t != head) {
        if (t->next == head) {
            cout << t->data << endl;
        } else {
            cout << t->data << " -> ";
        }
        t = t->next;
    }
}

int main () {
    CLL l;

    l.insert_front(10);
    l.insert_back(20);
    l.insert_back(40);
    l.insert_back(50);
    l.insert_back(60);

    l.insert(30, 3);

    l.insert(30,3);

    l.del(3);

    l.delete_back();
    l.delete_front();

    cout << "Elements of Linked List are:" << endl;

    l.printll();

    cout << endl << "Count: " << l.length() << endl;

    return 0;
}

```