



Samrat FRP Traders

PRODUCT CATALOG

FRP RESINS &
COMPOSITE RAW MATERIALS

Trader & Supplier of FRP Resins
& Composite Raw Materials

Biratnagar, Nepal



SAMRAT FRP TRADERS

ABOUT US

About Samrat FRP Traders

Samrat FRP Traders is a trusted trader and supplier of FRP resins, composite raw materials, and allied industrial materials, based in Ward No. 2, Tinpani Chowk, Main Road, Biratnagar, Nepal. Our product range supports FRP fabrication, lamination, roofing, casting, and other industrial applications.



SAMRAT FRP TRADERS

INTRODUCTION

Our Product Range

◆ GP Resins	7
General-purpose orthophthalic resins for hand lay-up, spray-up and lamination.	
◆ Sheet Grade Resins	2
Sheet moulding and roofing grade systems.	
◆ GelCoat Resin	1
Surface-coating gelcoat for smooth, protective, high-gloss finish.	
◆ Fire Retardant Resins	2
Halogenated and halogen-free grades for fire-safety applications.	
◆ FRP Allied Products	2
Pigments and reinforcement materials for FRP fabrication.	
◆ Epoxy & Casting	4
Clear casting, art, UV-cure and hardener systems.	
◆ Industrial & Specialty Resins	6
Vinyl ester, bisphenol, PET, marble, fiberglass epoxy and moulding compound.	
◆ Hardeners	2
MEKP and Cobalt catalyst systems for resin curing.	

01 · GP RESINS

General-purpose orthophthalic resins for hand lay-up, spray-up and lamination

5 Featured Products

GCR

GP Clear Resin

General-purpose orthophthalic resin for crystal-clear, high-gloss FRP applications

Resin Type	Orthophthalic UPR
Viscosity	350–450 cPs
Gel Time	<8 min
Specific Gravity	1.20 g/cm ³

Water Tanks · Panel Lamination · Hand Lay-Up

LR

Lamination Resin

High-gloss orthophthalic resin for premium lamination applications

Resin Type	Orthophthalic UPR
Viscosity	400 cPs
Gel Time	5 min
Specific Gravity	1.20 g/cm ³

Door Lamination · Photo Lamination · Furniture & Woodwork

GQR

GP Quartz Resin

Specialized resin for engineered stone and quartz surface production

Resin Type	Orthophthalic UPR
Viscosity	350–650 cPs
Gel Time	7–10 min
Specific Gravity	2.45 g/cm ³

Engineered Stone · Quartz Countertops · Decorative Slabs

BGR

Button Grade Resin

Specialized resin for button moulding and decorative components

Resin Type	Orthophthalic UPR
Viscosity	1,000–3,000 cPs
Gel Time	5–9 min
Specific Gravity	1.05–1.20 g/cm ³

Garment Fasteners · Decorative Accessories · Resistant Finish

GYR

GP Yellow Resin

General-purpose orthophthalic resin for high-gloss yellow FRP applications

Resin Type	Viscosity	Gel Time	Specific Gravity
Orthophthalic UPR	450–650 cPs	8–12 min	1.25 g/cm ³

FRP Components · Decorative Mouldings · General Purpose Lamination

02 · SHEET GRADE RESINS

2 Products

Sheet moulding and roofing grade systems

SGY

Sheet Grade Yellow

Low-viscosity resin for general-purpose FRP sheet manufacturing

Resin Type	Orthophthalic UPR
Viscosity	280 cPs
Gel Time	5.5 min
Specific Gravity	1.9–2.2 g/cm ³

FRP sheet manufacturing · General purpose

RLS

Roof Light Sheet

UV-stabilised resin for rooflight sheet manufacturing

Resin Type	Orthophthalic UPR
Viscosity	280 cPs
Gel Time	5.5 min
Specific Gravity	1.10 g/cm ³

Rooflight sheets · UV-stable roofing

03 · GELCOAT RESIN

1 Product

Surface-coating gelcoat for smooth, protective, high-gloss finish

GGR

GP Gelcoat Resin

High-coverage, high-gloss surface finishing resin

Resin Type	Viscosity	Gel Time	Specific Gravity
Isophthalic (ISO)	11,000 cPs	8.5 min	1.10–1.30 g/cm ³

Automotive slides · FRP doors · Metro / rail coaches

04 · FIRE RETARDANT RESINS

2 Products

Ortho and iso based fire-resistant systems

FRR

Fire Retardant Resin

Orthophthalic base resin for fire-resistant FRP applications

Resin Type	Orthophthalic (Ortho)
Viscosity	400 cPs
Gel Time	5.5 min
Specific Gravity	1.10–1.75 g/cm ³

Railways · Automobile · Fire retardant parts

IFR

ISO Fire Retardant

Isophthalic base resin for fire and chemical resistant applications

Resin Type	Isophthalic (ISO)
Viscosity	350–1,000 cPs
Gel Time	8–12 min
Specific Gravity	1.10–1.40 g/cm ³

High-rise buildings · Metro coaches · Laminates

05 · FRP ALLIED PRODUCTS

2 Products

Pigments and reinforcement materials for FRP fabrication

FPP

PIGMENT ADDITIVE

FRP Polyester Pigment

Colour concentrate paste for polyester resin systems

Form	Paste
Colour Range	White, Black, Red, Blue, Green & Yellow
Dosage	2–5% by weight
Compatibility	Compatible with Unsaturated Polyester Resins, Vinyl Ester Resins and Gelcoats

Colour matching · Gelcoat tinting

GFM

REINFORCEMENT MATERIAL

Glass Fiber CSM

E-glass chopped strand mat for hand lay-up and spray-up

Fiber Type	Chopped Strand Mat
Areal Weight	300 GSM & 450 GSM
Roll Width	1040 mm
Binder Type	Emulsion Binder

Hand lay-up · Structural laminates

06 · EPOXY & CASTING

Clear casting, art, UV-cure and hardener systems

4 Products

ECCR

Epoxy Clear Casting Resin

Crystal-clear epoxy resin system for decorative casting

Resin Type	Two-part Epoxy-Polyamine Thermosetting Polymer System
Viscosity	400 cPs
Gel Time	2–6 hours
Specific Gravity	1.08–1.14 g/cm ³

Resin art · Tabletop casting

EAR

Epoxy Art Resin

Two-part epoxy system for artistic resin work

Resin Type	Epoxy-Based Two-Part Epoxy Resin & Amine Hardener System
Viscosity	500–1,200 cPs
Gel Time	2–6 hours
Specific Gravity	1.05–1.15 g/cm ³

Resin art · Jewelry · Tabletop coating

UVR

UV-CURE SYSTEM

UV Resin

UV-curable resin for rapid light-cured finishing

Resin Type	Acrylate / Methacrylate UV-Curable Resin System
Viscosity	1,500–3,000 cPs
Cure Time (UV)	60–90 sec
Specific Gravity	1.05–1.25 g/cm ³

UV coatings · Rapid prototyping

EPH

CURING AGENT

Epoxy Hardener

Curing agent for epoxy resin systems

Chemical Type	Aliphatic Amines
Viscosity	100–2,000 cPs
Mixing Ratio	2:1
Specific Gravity	0.93–1.15 g/cm ³

Epoxy curing · Two-part systems

07 · INDUSTRIAL & SPECIALTY RESINS

6 Products

Vinyl ester, bisphenol, PET, marble, fiberglass epoxy and moulding compound

DMC

DMC / SMC Resin

High-filler-loading resin for moulding compounds

Resin Type	Orthophthalic Unsaturated Polyester Resin
Viscosity	550 cPs
Gel Time	10 min
Specific Gravity	1.13 g/cm³

Compression moulding · Electrical components

VER

Vinyl Ester Resin

High-performance system for chemical and corrosion resistance

Resin Type	Bisphenol-A Epoxy Vinyl Ester Resin
Viscosity	350 cPs
Gel Time	18 min
Specific Gravity	1.05 g/cm³

Chemical tanks · FRP linings

BPR

Bisphenol Resin

Bisphenol-based vinyl ester for advanced corrosion resistance

Resin Type	Bisphenol-A Epoxy Vinyl Ester Resin
Viscosity	400 cPs
Gel Time	20 min
Specific Gravity	1.06 g/cm³

Chemical processing · Marine

MBR

Marble Resin

Filled resin for cultured marble and onyx production

Resin Type	Orthophthalic Unsaturated Polyester Resin
Viscosity	300 cPs
Gel Time	15 min
Specific Gravity	1.12 g/cm³

Cultured marble · Decorative panels

FER

Fiberglass Epoxy Resin

Epoxy system for structural fiberglass laminating

Resin Type	Bisphenol-A Epoxy Resin
Viscosity	900 cPs
Gel Time / Pot Life	35 min
Specific Gravity	1.16 g/cm³

Structural laminates · Filament winding

PET

SHEET GRADE

PET Resin / Polyester Putty Resin

PET-modified liquid unsaturated polyester resin for sheet, laminate and panel applications.

Resin Type	PET-Modified Unsaturated Polyester Resin (Liquid)
Viscosity	450–650 cPs at 25°C
Gel Time	5–12 min at 25°C
Specific Gravity	1.05–1.12 g/cm³ at 25°C

Fibre Sheets · PET Sheets ·
FRP Sheet Lamination · Panel Manufacturing

08 · HARDENERS

MEKP and cobalt octoate curing systems for resin polymerization

2 Products

MEKP

MEKP Hardener

Peroxide catalyst for room-temperature resin curing

Active Oxygen	9.0%
Viscosity	25 cPs
Recommended Dosage	1.0–2.0%
Specific Gravity	1.17 g/cm ³

Used across all standard polyester systems

COB

Cobalt Octoate

Accelerator for room-temperature peroxide curing

Cobalt Content	6%
Viscosity	15 cPs
Recommended Dosage	0.2–0.5%
Specific Gravity	0.95 g/cm ³

Used alongside MEKP in standard cure systems

⚠ HANDLING NOTE

MEKP and cobalt octoate must never be mixed directly with each other. Add each separately into the resin — direct contact between the two can react violently.



SAMRAT FRP TRADERS

FRP & Composite Materials. For Industrial Applications.

For product, grade and bulk-order enquiries -
reach out to our team directly.

LOCATION

Ward No. 2, Tinpani Chowk, Main Road
Biratnagar, Nepal

CONTACT

+91-7463881652
+977-9805526904

EMAIL

samratfrptraders@gmail.com

REGISTRATION DETAILS

PAN	623071827
VAT NO.	623071827
EXIM CODE	6230718270114NP

