



SAMRAT POLY RESINS

Manufacturer of Coating & Composite Resins · Doraha, Ludhiana, Punjab, India

TECHNICAL DATA SHEET

Doc. Ref: SPR-TDS-UVR · Rev. 01 · July 2026

UV RESIN

UV/LED-Curable Epoxy Acrylate · Crystal-Clear, Low Viscosity · Coatings, Adhesives & Craft

PRODUCT DESCRIPTION

UV Resin is an epoxy-acrylate resin that cures rapidly under UV/LED light to a crystal-clear, high-gloss finish. Low-viscosity and fast-curing, it offers excellent scratch resistance, low shrinkage and outstanding surface hardness for detailed decorative work, with strong adhesion across multiple surfaces.

KEY FEATURES

- Fast UV/LED curing — cures in seconds under lamp
- Low viscosity, self-levelling clear finish
- Excellent scratch resistance, low shrinkage
- Strong adhesion on multiple surfaces
- Chemical resistant, durable cured surface

RECOMMENDED APPLICATIONS

- Jewellery making and resin art
- Encapsulation, doming and electronics
- Adhesive, label, metal and wood coating
- Crafts, coatings and miniature models

TYPICAL TECHNICAL PROPERTIES

Resin Chemistry	Epoxy acrylate
Curing Type	UV / LED cure
Colour / Appearance	Clear (crystal-clear cured finish)
Viscosity	450 cPs (25 °C)
Cured Hardness	Shore D 80
Surface Properties	Excellent scratch resistance, low shrinkage
Cure Wavelength / Energy	365–405 nm
Cure Time (under lamp)	30–60 seconds
Specific Gravity / Density	1.10 g/cm ³
Shelf Life	12 months (unopened)
Storage Conditions	Store in a cool, dry place (15–25 °C), protected from direct sunlight and UV exposure
Packaging	200 kg pack
Minimum Order Quantity	1,000 kg

SAFETY & HANDLING

Follow standard industrial safety practices when handling this product, including appropriate personal protective equipment and adequate ventilation. Refer to the applicable Safety Data Sheet (SDS) where available.

Disclaimer: The information above is based on data published by the manufacturer at the time of issue and is believed accurate. Values shown are typical and are not to be interpreted as guaranteed specifications; properties may vary within normal manufacturing tolerances between batches. Users are responsible for determining suitability for their intended application and should confirm current specifications directly with Samrat Poly Resins prior to use.